CAC

CAUTION: THE INFORMATION IN THIS PUBLICATION MAY BE SUPERSEDED BY NOTAM OR AIP SUPPLEMENT

ATTENTION : LE CONTENU DE LA PRÉSENTE PUBLICATION PEUT ÊTRE REMPLACÉ PAR NOTAM OU SUPPLÉMENT D'AIP

EFFECTIVE | EN VIGUEUR

0901Z **5 OCTOBER | OCTOBRE 2023**

TO | AU

0901Z 30 NOVEMBER | NOVEMBRE 2023

CANADIAN AIRPORT CHARTS

CARTES DES AÉROPORTS CANADIENS

Serving a world in motion
Au service d'un monde en mouvement
navcanada.ca

NAV CANADA

CANADIAN AIRPORT CHARTS
CARTES DES AÉROPORTS CANADIENS



The information in the Canadian Airport Charts provides pictorial displays of Canadian airport manoeuvring areas found in the Canada Air Pilot or the military GPH 200, and may be reproduced for the sole purpose of assisting pilots during aircraft ground movement operations. Up-to-date information on flight planning procedures and airport services, including fuel, lighting, and local prohibitions or procedures is found in the Canada Flight Supplement.

L'information qui se trouve dans les Cartes des aéroports canadiens contient des indicateurs topographiques des aires de manœuvre des aéroports canadiens provenant du Canada Air Pilot ou du GPH 200 militaire et peut être reproduite à seule fin d'aider les pilotes durant les mouvements d'aéronefs au sol. De l'information à jour sur les procédures de préparation de plans de vol et les services d'aéroport, y compris le carburant, le balisage, ainsi que les interdictions et les procédures locales, se trouve dans le Supplément de vol Canada.

Published by NAV CANADA in accordance with ICAO Annexes 4 and 15 of the Convention on International Civil Aviation

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Source of Canadian Military Aeronautical Data:
His Majesty the King in Right of Canada Department of National Defence

Publié par NAV CANADA en vertu des Annexes 4 et 15 de la Convention relative à l'aviation civile internationale de l'OACI

Source des données aéronautiques civiles canadiennes : © 2023 NAV CANADA Tous droits réservés

Source des données aéronautiques militaires canadiennes :
Ministère de la Défense Nationale de Sa Majesté le Roi aux droits du Canada

Preface

NAV CANADA, as the office responsible for the publication and distribution of aeronautical information, has decided to make aerodrome diagrams readily available to general aviation pilots through its website. This move will contribute to enhance aviation safety and will help to mitigate some of the risks associated with runway incursions.

Hot Spot: A location on an aerodrome movement area with a high risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.

Hot Spots are found on applicable Canadian Aerodrome Charts.


Préface

NAV CANADA, en tant que responsable de la publication et de la distribution de l'information aéronautique, a décidé de mettre les schémas d'aérodrome à la disponibilité des pilotes d'aviation générale par l'intermédiaire de son site Web. Cette décision contribuera à accroître la sécurité aérienne et aidera à atténuer certains des risques associés aux incursions sur piste.

Point chaud : Endroit sur l'aire de mouvement d'un aérodrome où il y a un risque accru de collision ou d'incursion sur piste et où une attention soutenue de la part du pilote/conducteur est requise.

Les points chauds se trouvent sur les cartes d'aérodrome canadiennes applicables.

All graphics presented here are for explanatory purposes only and are not intended to be used for navigation.




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Aerodrome Chart Legend

1. Declared Distance Night
2. Take Off Run Available
3. Take Off Distance Available
4. Accelerate Stop Distance Available
5. Landing Distance Available
6. Landing Distance Available Table
7. Magnetic Variation
8. Latitude Coordinate
9. Threshold Displacement Note
10. Visual Glide Slope Indicator
11. Displaced Runway Threshold
12. Turnaround Bay
13. Centreline Light
14. Runway Bearing
15. RVR Sensor
16. Approach Lighting
17. Wind Direction Indicator
18. Taxiway
19. Taxiway Identification
20. Aerodrome Reference Point
21. Runway Dimensions
22. Obstruction
23. Building
24. Threshold Elevation
25. Runway Number
26. CAT I Holding Bar
27. Apron Identification
28. Runway
29. Departure Procedure
30. Runway Slope Gradient
31. NAVAID within AD Limit
32. Operational Notes
33. Control Tower
34. Longitude Coordinate
35. Construction Area
36. Departure Climb Rate Table
37. Reduced Visibility Operation Table
38. Low Visibility Operation Table
39. Take-off Minima Box
40. Scale Bar
41. Geographic Grid
42. Hot Spot

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Toute illustration n'est présentée ici qu'à titre indicatif et ne doit pas être utilisée pour la navigation.



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Légende des cartes d'aerodrome

1. Distance déclarée (nuit)
2. Longueur de roulement utilisable au décollage
3. Distance de décollage utilisable
4. Distance utilisable pour l'accélération-arrêt
5. Distance d'atterrissage utilisable
6. Tableau des distances d'atterrissage utilisables
7. Déclinaison magnétique
8. Coordonnée de latitude
9. Note sur le décalage du seuil
10. Indicateur visuel de pente d'approche
11. Seuil de piste décalé
12. Aire de demi-tour
13. Feux de l'axe de piste
14. Relèvement de la piste
15. Capteur RVR
16. Balisage lumineux d'approche
17. Indicateur de direction du vent
18. Voie de circulation

    Indicatif de voie de circulation
20. Point de référence d'aérodrome
21. Dimensions de la piste
22. Obstruction
23. Bâtisse
24. Altitude du seuil
25. Numéro de piste
26. Barre d'attente d'ILS CAT I
27. Identification de l'aire de trafic
28. Piste
29. Procédure de départ
30. Pente de la piste
31. NAVAID sur l'aérodrome
32. Notes opérationnelles
33. Tour de contrôle
34. Coordonnée de longitude
35. Zone de construction
36. Tableau des taux de montée de départ
37. Tableau des opérations par visibilité réduite
38. Tableau des opérations par faible visibilité
39. Case des minimums de décollage
40. Barre d'échelle
41. Grille géographique
42. Point chaud

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


AKLAVIK/FREDDIE CARMICHAEL, NT

AERODROME CHART — CYKD

CTR Edmonton – **132.4**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	13	31
TORA	3002	3002
TODA	3199	3199
ASDA	3002	3002
LDA	3002	3002



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13, 31: *	500 0 500

AERODROME CHART — CYKD

EFF 7 OCT 21

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


ALERT, NU

AERODROME CHART (DND)

CYLT

TFC – **126.7** ATF

DECL DISTS	05	23
TORA	5500	5500
TODA	5500	5500
ASDA	5500	5500
LDA	5500	5500



TAKE-OFF MINIMA
Rwys 05; 23: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


ARCTIC BAY, NU

AERODROME CHART — CYAB

LWIS – **128.7**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	13	31
TORA	3935	3935
TODA	4919	4919
ASDA	3935	3935
LDA	3935	3935



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAB


EFF 10 AUG 23

ARVIAT, NU

AERODROME CHART — CYEK

AWOS – **128.7**				APRT RADIO – **122.1** TFC – **122.1**		MF		

DECL DISTS	15	33
TORA	4000	4000
TODA	4984	4500
ASDA	4000	4000
LDA	4000	4000



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEK


EFF 8 SEP 22

BAKER LAKE, NU

AERODROME CHART — CYBK

		APRT RADIO – **122.1** MF	RADIO Edmonton – **122.37** **5680**

DECL DISTS	16	34
TORA	4195	4195
TODA	5179	4195
ASDA	4195	4195
LDA	4195	4195



TAKE-OFF MINIMA
Rwy 16: ½
Rwy 34: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BEAVER CREEK, YT

AERODROME CHART — CYXQ

			APRT RADIO – **122.1** TFC – **122.1** MF				RADIO Whitehorse – **123.47**	

DECL DISTS	14	32						
TORA	3600	3745						
TODA	3600	3945						
ASDA	3745	3745						
LDA	3745	3404						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14, 32: *	1000 500 0 500 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYXQ


EFF 14 JUL 22

BURWASH, YT

AERODROME CHART — CYDB

◕ AWOS – 128.7			◕ APRT RADIO – **122.1** ◕ TFC – **122.1** MF					

DECL DISTS	11	29						
TORA	5006	5006						
TODA	5203	5203						
ASDA	5006	5006						
LDA	5006	5006						



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYDB


EFF 5 OCT 23

CAMBRIDGE BAY, NU

AERODROME CHART — CYCB

			APRT RADIO – **122.1** MF	RADIO Edmonton – **123.25**

DECL DISTS	13	31
TORA	5076	5076
TODA	6060	6060
ASDA	5076	5076
LDA	5076	5076



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 13; 31: ½	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYCB


EFF 29 DEC 22

CHESTERFIELD INLET, NU

AERODROME CHART — CYCS

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	12	30
TORA	3600	3600
TODA	4584	4584
ASDA	3600	3600
LDA	3600	3600



* DEPARTURE PROCEDURE

Rwy 12 - ½
Note: Power lines to 86 ASL aprx 1000' past departure end of rwy, 400' RIGHT of rwy centreline.
Tower to 119 ASL aprx 0.3 NM past departure end of rwy, 600' LEFT of rwy centreline..

Rwy 30 - ½
Note: Terrain to 40 ASL aprx 1000' past departure end of rwy, 450' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 12; 30: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYCS
EFF 8 SEP 22


CLYDE RIVER, NU

AERODROME CHART — CYCY

AWOS – **124.6**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	02	20
TORA	3501	3501
TODA	4485	4485
ASDA	3501	3501
LDA	3501	3501



✱DEPARTURE PROCEDURE

Rwy 02 - ½ - (CAT A, B and C only) Climb hdg **018°T** to **1900** BPOC.

Rwy 20 - ½ - (CAT A, B and C only) Requires a minimum climb gradient of **430** ft/NM to **1500**. Climb hdg **198°T** to **2800** BPOC.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2300** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150

TAKE-OFF MINIMA
Rwys 02; 20: ✱

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


COLVILLE LAKE/TOMMY KOCHON, NT

AERODROME CHART — CYVL

AWOS – **128.6**

TFC – **123.2** ATF

DECL DISTS	17	35
TORA	3935	3935
TODA	4919	4919
ASDA	3935	3935
LDA	3935	3935



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17; 35: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CORAL HARBOUR, NU

AERODROME CHART — CYZS

		APRT RADIO – **122.1** MF	RADIO Edmonton – **123.27**

DECL DISTS	16	34
TORA	5006	5006
TODA	5990	5990
ASDA	5006	5006
LDA	5006	5006



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16; 34: ½	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZS


EFF 23 FEB 23

DAWSON CITY, YT

AERODROME CHART — CYDA

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF

DECL DISTS	03	21						
TORA	5003	5003						
TODA	5203	5203						
ASDA	5003	5003						
LDA	5003	5003						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03, 21: *	1000 0 1000

AERODROME CHART — CYDA

EFF 23 FEB 23

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


DÉLINE, NT

AERODROME CHART

CYWJ

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	08	26
TORA	3933	3933
TODA	4917	4917
ASDA	3933	3933
LDA	3933	3933



TAKE-OFF MINIMA
Rwys 08; 26 : *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CYWJ

EFF 2 DEC 21


DIAVIK, NT

AERODROME CHART — CDK2

UNICOM – **122.7** (AU)

ATF* CYOA

DECL DISTS	10	28
TORA	5234	5234
TODA	5234	5234
ASDA	5234	5234
LDA	5234	5234



TAKE-OFF MINIMA
Rwy 10: *
Rwy 28: ½

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CDK2


EFF 31 DEC 20

EKATI, NT

AERODROME CHART — CYOA

AUTO – **122.17**		UNICOM – **122.7** (AU) ATF*	CTR Edmonton – **135.17** RADIO Edmonton – **123.27**

DECL DISTS	02	20
TORA	6411	6411
TODA	6411	6411
ASDA	6411	6411
LDA	6411	6411



* DEPARTURE PROCEDURE

Rwy 02 - ½ - Requires a minimum climb gradient of **220** ft/NM to **1800**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2000** BPOC.
Note: Powerline to 1593 ASL aprx 0.1 NM past departure end of rwy 510' RIGHT of rwy centreline.

Rwy 20 - ½
Note: Terrain to 1542 ASL at departure end of rwy, 320' RIGHT of rwy centreline.

NOTE:
Departure procedure not auth when any blasting areas are active.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
220 FT/NM	330	440	520	590	660	740	920	1100

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02; 20: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYOA

EFF 31 DEC 20


EUREKA, NU

AERODROME CHART — CYEU

UNICOM – **122.8** (AU)

ATF

DECL DISTS	10	28
TORA	4802	4802
TODA	4802	4802
ASDA	4802	4802
LDA	4802	4802



Rwy strength & cond subject to seasonal & climatic var. Acft 65,000 lbs and over PPR.

***** DEPARTURE PROCEDURE

Rwy 10 - ½ **-** Requires a minimum climb gradient of **380** ft/NM to **1700**. Climb between hdg **160°T** CW to **284°T** to **4900** BPOC.

or

SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **3000** BPOC.

Rwy 28 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **3000** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
380 FT/NM	570	760	890	1020	1140	1270	1590	1900

TAKE-OFF MINIMA

Rwys 10; 28: *****

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEU


EFF 5 OCT 23

FARO, YT

AERODROME CHART — CZFA

			APRT RADIO – **122.1** TFC – **122.1** MF				RADIO Whitehorse – **123.55**	

DECL DISTS	09	27						
TORA	3996	3996						
TODA	4196	4196						
ASDA	3996	3996						
LDA	3996	3996						



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
480 FT/NM	720	960	1120	1280	1440	1600	2000	2400

***** DEPARTURE PROCEDURE

Rwy 09 - ½ - Requires a minimum climb gradient of **480** ft/NM to **7800**.
Climb hdg **093°** to **6000**.
Note: Trees to 2395 ASL abeam departure end of rwy, 230° LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **6700** BPOC.

Rwy 27 -½ - Requires a minimum climb gradient of **480** ft/NM to **7700**.
Climb hdg **273°** to **5000**. Climb between hdg **252°** CCW to hdg **093°**.
Note: Trees to 2385 ASL abeam departure end of rwy, 230° LEFT of rwy centreline.
COMM towers to 2382 ASL abeam departure end of rwy, 230° RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **6700** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *****	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


FORT GOOD HOPE, NT

AERODROME CHART

CYGH

		◕ APRT RADIO – **122.1** ◕ TFC – **122.1** MF				RADIO Edmonton – **123.55**		

DECL DISTS	07	25						
TORA	4434	4434						
TODA	4631	4631						
ASDA	4434	4434						
LDA	4434	4434						



* DEPARTURE PROCEDURE

Rwy 07 - ½

Note: Trees to 312 ASL aprx 200' past departure end of rwy, 150' LEFT and 400' RIGHT of rwy centreline.

Rwy 25 - ½

Note: Trees to 285 ASL aprx 200' past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07; 25: *	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


FORT LIARD, NT

AERODROME CHART — CYJF

APRT RADIO – **121.1**
TFC – **122.1**
MF

CTR Edmonton – **132.87**

DECL DISTS	03	21
TORA	2946	2946
TODA	3143	3143
ASDA	2946	2946
LDA	2946	2946



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03; 21: *	1000 — 0

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYJF

EFF 14 JUL 22


FORT MCPHERSON, NT

AERODROME CHART — CZFM

CTR Edmonton – **132.4**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	12	30
TORA	3934	3934
TODA	4525	4918
ASDA	3934	3934
LDA	3934	3934



* DEPARTURE PROCEDURE

Rwy 12 - ½ - Climb hdg **122°** to **1100** BPOC.
Note: Trees to 151 ASL aprx 0.1 NM past departure end of rwy.

Rwy 30 - ½ - Requires a minimum climb gradient of **230** ft/NM to **5900**.
Note: Trees to 148 ASL aprx 0.2 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

TAKE-OFF MINIMA
Rwys 12; 30: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT PROVIDENCE, NT

AERODROME CHART — CYJP

TFC – **123.2** ATF*

DECL DISTS	14	32
TORA	2999	2999
TODA	3983	3983
ASDA	2999	2999
LDA	2999	2999



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYJP

EFF 12 AUG 21


FORT RESOLUTION, NT

AERODROME CHART — CYFR

CTR Edmonton – **133.85**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	13	31
TORA	4001	4001
TODA	4854	4985
ASDA	4001	4001
LDA	4001	3346



TAKE-OFF MINIMA

Rwys 13, 31: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


AERODROME CHART — CYFR

EFF 7 OCT 21

FORT SIMPSON, NT

AERODROME CHART — CYFS

			APRT RADIO – **122.2** MF*				CTR Edmonton – **135.4** RADIO Edmonton – **123.47**	
DECL DISTS	**14**	**32**						
TORA	6000	6000						
TODA	6200	6984						
ASDA	6000	6000						
LDA	6000	6000						



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 14: ½ Rwy 32: *	2000 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYFS


EFF 29 DEC 22

FORT SMITH, NT

AERODROME CHART — CYSM

		APRT RADIO – **122.2** MF	RADIO Edmonton – **123.55 239.8**

DECL DISTS	03	21	12	30				
TORA	1797	1797	6001	6001				
TODA	2781	2781	6985	6985				
ASDA	1797	1797	6001	6001				
LDA	1797	1797	6001	6001				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03: 21: NOT ASSESSED Rwys 12: 30: *	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSM

EFF 10 AUG 23


GAHCHO KUE, NT

AERODROME CHART

CGK2

AWOS – **122.55**		UNICOM – **123.35** (AU) ATF	

DECL DISTS	06	24
TORA	5311	5311
TODA	6295	6295
ASDA	5311	5311
LDA	5311	5311



* DEPARTURE PROCEDURE

Rwy 06 - ½

Note: Terrain to 1474 ASL aprx 250' past departure end of rwy, 490' RIGHT of rwy centerline.

Rwy 24 - ½ - Requires a minimum climb gradient of **280** ft/NM to **2000**.

Note: Terrain to 1474 ASL aprx 0.4 NM past departure end of rwy, 210' LEFT of rwy centerline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **2100** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
280 FT/NM	420	560	660	750	840	940	1170	1400

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06, 24: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GAMÈTÌ/RAE LAKES, NT

AERODROME CHART — CYRA

◕ APRT RADIO – **122.1**
◕ TFC – **122.1** MF

DECL DISTS	14	32
TORA	3000	3000
TODA	3197	3197
ASDA	3000	3000
LDA	3000	3000



* DEPARTURE PROCEDURE
Rwy 14 - ½ - Requires a minimum climb gradient of **350** ft/NM to **1800**.
Note: Trees to 755 ASL aprx 200' past departure end of rwy, 100' LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700** BPOC.

Rwy 32 - ½ - NO LEFT turn below **1700** BPOC.
Note: Trees to 755 ASL aprx 200' past departure end of rwy, 100' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32 :*	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


GJOA HAVEN, NU

AERODROME CHART — CYHK

MET – **128.7**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	13	31
TORA	4400	4400
TODA	5384	5384
ASDA	4400	4400
LDA	4400	4400



TAKE-OFF MINIMA

Rwy 13; 31: ½

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHK


EFF 3 NOV 22

HAY RIVER/MERLYN CARTER AIRPORT, NT

AERODROME CHART — CYHY

		APRT RADIO – **122.3** MF	CTR Edmonton – **133.85** RADIO Edmonton – **123.27**

DECL DISTS	14	32	05	23				
TORA	6000	6000	4001	4001				
TODA	6984	6984	4985	4985				
ASDA	6000	6000	4001	4001				
LDA	6000	6000	4001	4001				



* DEPARTURE PROCEDURE

Rwy 05 - ½
Note:Trees to 597 ASL aprx 0.2NM past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.
Tower to 636 ASL aprx 0.7NM past departure end of rwy, 450' LEFT of rwy centreline.

Rwy 14 - ½
Note:Trees to 623 ASL aprx 0.2NM past departure end of rwy, 100' LEFT of rwy centreline.

Rwy 23 - ½
Note:Trees to 610 ASL aprx 0.2NM past departure end of rwy, 500' LEFT and RIGHT of rwy centreline.

Rwy 32 - ½
Note:Trees to 548 ASL aprx 0.2NM past departure end of rwy, 400' LEFT of rwy centreline.
Trees to 614 ASL aprx 0.4NM past departure end of rwy, 900' LEFT of rwy centreline.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHY


EFF 10 AUG 23

IGLOOLIK, NU

AERODROME CHART — CYGT

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	15	33
TORA	4095	4095
TODA	5079	4423
ASDA	4095	4095
LDA	4095	4095



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGT


EFF 5 OCT 23

INUVIK (MIKE ZUBKO), NT

AERODROME CHART — CYEV

ATIS – **128.5**		RADIO – **122.3 262.7**	CTR Edmonton – **132.4** RADIO Edmonton – **123.37 5680**
		MF	

DECL DISTS	06	24
TORA	6006	6006
TODA	6006	6006
ASDA	6006	6006
LDA	6006	6006



* DEPARTURE PROCEDURE

Rwy 06 - ½ - NO LEFT turn until reaching **1200** BPOC.

Rwy 24 - ½ - NO RIGHT turn until reaching **1000** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	1000 0 1000 2000

AERODROME CHART — CYEV

EFF 5 OCT 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

IQALUIT, NU

AERODROME CHART — CYFB

		RADIO – **122.2 296.2**	CTR Montreal – **134.55** RADIO Quebec – **123.27 5680** **MF**

DECL DISTS	16	34
TORA	8605	8605
TODA	9589	9589
ASDA	8605	8605
LDA	8605	8605



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 34: RVR 1200 RWY 16: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16; 34: *	2000 1000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYFB

EFF 5 OCT 23

JEAN MARIE RIVER, NT


AERODROME CHART — CET9

CTR Edmonton – **135.4**

TFC – **123.2**

ATF

DECL DISTS	11	29
TORA	2512	2512
TODA	3496	3496
ASDA	2512	2512
LDA	2512	2512



* DEPARTURE PROCEDURE

Rwy 11 - ½

Note: Trees to 538 ASL aprx 0.2 NM past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.

Rwy 29 - ½

Note: Trees to 545 ASL aprx 0.2 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


KIMMIRUT, NU

AERODROME CHART — CYLC

APRT RADIO – **122.1**
TFC – **122.1**
MF

CTR Montreal – **134.55**

DECL DISTS	15	33
TORA	1899	1899
TODA	2719	1899
ASDA	1899	1899
LDA	1899	1899



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15, 33: *	500 0 500


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KINNGAIT AIRPORT, NU

AERODROME CHART — CYTE

AWOS – **128.7**	APRT RADIO – **122.1** TFC – **122.1** MF	RADIO Quebec – **123.37**

DECL DISTS	13	31
TORA	3988	3988
TODA	4644	4972
ASDA	3988	3988
LDA	3988	3988



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYTE


EFF 10 AUG 23

KUGAARUK, NU

AERODROME CHART — CYBB

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF

DECL DISTS	05	23
TORA	5000	5000
TODA	5295	5459
ASDA	5000	5000
LDA	5000	5000



* DEPARTURE PROCEDURE

Rwy 05 - ½ - Climb hdg **049°T** to **700** BPOC.
Note: Road to 40 ASL aprx 0.1 NM past departure end of rwy.
Terrain to 138 ASL aprx 0.4 NM past departure end of rwy,
950' LEFT of rwy centreline.

Rwy 23 - ½ - Climb hdg **229°T** to **900** BPOC.
Note: Line of power poles to 95 ASL abeam departure end of rwy,
450' RIGHT of rwy centreline and aprx 0.2 NM past departure end of rwy.
Terrain to 96 ASL aprx 0.3 NM past departure end of rwy,
850' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 05; 23: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


AERODROME CHART — CYBB
EFF 29 DEC 22

KUGLUKTUK, NU

AERODROME CHART — CYCO

		APRT RADIO – **122.1**	CTR Edmonton – **124.25** RADIO Edmonton – **123.15** MF

DECL DISTS	12	30						
TORA	5502	5502						
TODA	6486	6486						
ASDA	5502	5502						
LDA	5502	5502						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12; 30: ½	1000 0 1000

AERODROME CHART — CYCO

EFF 31 DEC 20


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LUTSELK'E, NT

AERODROME CHART — CYLK

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF

DECL DISTS	08	26
TORA	3003	3003
TODA	3200	3200
ASDA	3003	3003
LDA	3003	3003



* DEPARTURE PROCEDURE

Rwy 08 - ½ - Requires a minimum climb gradient of **500** ft/NM to **1500**.
Note: Trees to 607 ASL aprx 200' past departure end of rwy, 200' LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

Rwy 26 - ½ - Requires a minimum climb gradient of **400** ft/NM to **1500**.
Note: Trees to 610 ASL aprx 200' past departure end of rwy, 100' LEFT and 300' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

TAKE-OFF MINIMA

Rwys 08; 26: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MARY RIVER, NU


AERODROME CHART — CMR2

AWOS – **122.35**

UNICOM – **123.35** (AU)

ATF

DECL DISTS	12	30
TORA	6505	6505
TODA	6505	6505
ASDA	6505	6505
LDA	6505	6505



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
360 FT/NM	540	720	840	960	1080	1200	1500	1800
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150

✱ DEPARTURE PROCEDURE

Rwy 12 - ½ - Requires a minimum climb gradient of **430** ft/NM to **2700**. NO LEFT turn below **2700**.

or

SPEC VIS - Climb in visual conditions to cross arpt at or above **2700** BPOC.

Note: Departure procedure not auth when blasting areas active. See CFS CAUTION.

Rwy 30 - ½ - Requires a minimum climb gradient of **360** ft/NM to **2000**. NO RIGHT turn below **2400**.

or

SPEC VIS - Climb in visual conditions to cross arpt at or above **2700** BPOC.

Note: Departure procedure not auth when blasting areas active. See CFS CAUTION.

TAKE-OFF MINIMA

Rwys 12, 30: ✱

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MAYO, YT

AERODROME CHART — CYMA

		APRT RADIO – **122.1** MF	RADIO Whitehorse – **122.37**

DECL DISTS	07	25
TORA	4843	4843
TODA	5040	5040
ASDA	4843	4843
LDA	4843	4843



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850

* DEPARTURE PROCEDURE

Rwy 07 - ½ - Requires a minimum climb gradient of **370** ft/NM to **5900**.
Climb hdg **071°** to **5200** BPOC.
Note: Trees to 1696 ASL aprx 200' past departure end of rwy, 130' LEFT and 150' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **4900** BPOC.

Rwy 25 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **4900** BPOC.

TAKE-OFF MINIMA

Rwys 07; 25: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


NAHANNI BUTTE, NT

AERODROME CHART

CBD6

TFC – **123.2** ATF

DECL DISTS	16	34
TORA	2554	2554
TODA	2554	2554
ASDA	2554	2554
LDA	2554	2554



TAKE-OFF MINIMA

Rwys 16, 34: *


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

NAUJAAT, NU

AERODROME CHART — CYUT

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	16	34
TORA	3400	3400
TODA	4384	3905
ASDA	3400	3400
LDA	3400	3400



TAKE-OFF MINIMA
Rwy 16: ½
Rwy 34: ★

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYUT


EFF 20 APR 23

NORMAN WELLS, NT

AERODROME CHART — CYVQ

		RADIO – **122.2 282.3** MF	CTR Edmonton – **134.82** RADIO Edmonton – **123.27**

DECL DISTS	10	28
TORA	5998	5998
TODA	6982	6982
ASDA	5998	5998
LDA	5998	5998



TAKE-OFF MINIMA
Rwys 10; 28: *

SCALE IN FEET
1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OLD CROW, YT

AERODROME CHART — CYOC

			APRT RADIO – **122.1** TFC – **122.1** MF			RADIO Whitehorse – **123.47** DRCO		

DECL DISTS	04	22
TORA	5010	4913
TODA	5010	4913
ASDA	5020	5020
LDA	4716	4813



* DEPARTURE PROCEDURE

Rwy 04 - ½ **-** Requires a minimum climb gradient of **480** ft/NM to **2900**.
Climb hdg **043°** to **4000** BPOC.
Note: Trees to 850 ASL past departure end of rwy, 300' RIGHT and 400' LEFT of rwy centreline.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **4100** BPOC.

Rwy 22 - ½ **-** Requires a minimum climb gradient of **450** ft/NM to **4100**.
Climb hdg **223°** to **4600** BPOC.
Note: Trees to 853 ASL past departure end of rwy, 200' RIGHT of rwy centreline.
Road to 819 ASL past departure end of rwy, 200' LEFT of rwy centreline.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **4100** BPOC.

TAKE-OFF MINIMA
Rwys 04; 22: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


PANGNIRTUNG, NU

AERODROME CHART — CYXP

LWIS – **125.1**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	06	24
TORA	2920	2920
TODA	3301	3904
ASDA	2920	2920
LDA	2920	2920



TAKE-OFF MINIMA

Rwys 06; 24: *

SCALE IN FEET
500 0 500


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PAULATUK (NORA ALIQATCHIALUK RUBEN), NT

AERODROME CHART — CYPC

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF

DECL DISTS	02	20
TORA	4003	4003
TODA	4200	4200
ASDA	4003	4003
LDA	4003	4003



TAKE-OFF MINIMA
Rwy 02: ½
Rwy 20: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPC

EFF 7 OCT 21

POND INLET, NU

AERODROME CHART — CYIO

MET – **128.3**

APRT RADIO – **122.1**
TFC – **122.1**
MF

RADIO Quebec – **123.27**

DECL DISTS	02	20
TORA	4006	4006
TODA	4990	4006
ASDA	4006	4006
LDA	4006	4006

77 58.8 77 57.6

* DEPARTURE PROCEDURE
Rwy 02 - ½ - Climb between hdg **285° T** CCW to **202° T**.

Rwy 20 - ½ - Requires a minimum climb gradient of **350** ft/NM to **3700**. No turn below **3700**.
Note: Hill to 258' abeam the departure end of rwy, 150' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross arpt at or above **3700** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 FT/NM	530	700	820	940	1050	1170	1460	1750

ELEV 189

AS 20

202°T

Up 0.32%

366

72 41.5

4006 x 98

gravel

CYIO
N72 41.37
W77 58.14

72 41.2

022°T

AS 02

ELEV 202

VAR 32° W 2023

ANNUAL RATE OF CHANGE 51' E

77 58.8 77 57.6

TAKE-OFF MINIMA

Rwys 02; 20: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYIO


EFF 10 AUG 23

QIKIQTARJUAQ, NU

AERODROME CHART — CYVM

AUTO– **122.55**		APRT RADIO Broughton – **122.1** TFC – **122.1** **MF**	

DECL DISTS	03	21
TORA	3803	3803
TODA	4787	4787
ASDA	3803	3803
LDA	3803	3803



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03; 21: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVM


EFF 29 DEC 22

RANKIN INLET, NU

AERODROME CHART — CYRT

			RADIO Rankin – **122.2** MF	RADIO Edmonton – **123.55**

DECL DISTS	13	31
TORA	6000	6000
TODA	6984	6984
ASDA	6000	6000
LDA	6000	6000



TAKE-OFF MINIMA
Rwy 13: *
Rwy 31: ½

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRT


EFF 29 DEC 22

RESOLUTE BAY, NU

AERODROME CHART — CYRB

		APRT RADIO – **122.1** MF*	RADIO Edmonton – **126.7 5680**

DECL DISTS	17	35
TORA	6504	6504
TODA	7488	7488
ASDA	6504	6504
LDA	6504	6504



TAKE-OFF MINIMA
Rwy 17: ½ Rwy 35: *

SCALE IN FEET
1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SACHS HARBOUR (DAVID NASOGALUAK JR. SAARYUAQ), NT

AERODROME CHART — CYSY

			◕ APRT RADIO – **122.1** ◕ TFC – **122.1** MF			RADIO Edmonton – **123.55**		

DECL DISTS	08	26						
TORA	4002	4002						
TODA	4202	4202						
ASDA	4002	4002						
LDA	4002	4002						



TAKE-OFF MINIMA
Rwy 08: *
Rwy 26: ½

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSY

EFF 7 OCT 21


SAMBAA K'E, NT

AERODROME CHART — CEU9

CTR Edmonton – **135.4**

TFC – **123.2**

DECL DISTS	04	22
TORA	3501	3501
TODA	3501	3501
ASDA	3501	3501
LDA	3501	3501



TAKE-OFF MINIMA
Rwys 04; 22: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CEU9


EFF 2 DEC 21

SANIKILUAQ, NU

AERODROME CHART — CYSK

◕ APRT RADIO – **122.1**
◕ TFC – **122.1** MF

DECL DISTS	09	27
TORA	3807	3807
TODA	4791	4791
ASDA	3807	3807
LDA	3807	3807



* DEPARTURE PROCEDURE

Rwy 09 - ½
Note: Tower to 238 ASL aprx 0.9 NM past departure end of rwy, 1000' RIGHT of rwy centreline.

Rwy 27 - ½
Note: Terrain to 208 ASL aprx 0.4 NM from departure end of rwy, 800' LEFT and 550' RIGHT of rwy centreline.

TAKE-OFF MINIMA
Rwys 09; 27: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSK


EFF 15 JUN 23

SANIRAJAK AIRPORT, NU

AERODROME CHART — CYUX

AWOS – **128.7**	◕ APRT RADIO – **122.2** ◕ TFC – **122.2** MF	RADIO Edmonton – **123.27**

DECL DISTS	12	30
TORA	5410	5410
TODA	5610	6394
ASDA	5410	5410
LDA	5410	5218



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12: * Rwys 30: ½	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYUX

EFF 29 DEC 22


SNAP LAKE, NT

AERODROME CHART — CSK6

UNICOM – **123.5** (AU)

ATF

DECL DISTS	09	27
TORA	5282	5282
TODA	6266	6266
ASDA	5282	5282
LDA	5282	5282



TAKE-OFF MINIMA

Rwys 09, 27: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TALOYOAK, NU

AERODROME CHART — CYYH

		APRT RADIO – **122.1** MF	RADIO Edmonton – **123.55**

DECL DISTS	15	33
TORA	4009	4009
TODA	4993	4993
ASDA	4009	4009
LDA	4009	4009



TAKE-OFF MINIMA
Rwy 15: *
Rwy 33: ½

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYH

EFF 10 AUG 23


TESLIN, YT

AERODROME CHART — CYZW

APRT RADIO – **122.1**
TFC – **122.1**
MF

CTR Edmonton – **134.15**

DECL DISTS	09	27
TORA	5028	5028
TODA	5225	5225
ASDA	5028	5028
LDA	5028	5028



GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

* DEPARTURE PROCEDURE

Rwy 09 - ½ **-** Requires a minimum climb gradient of **500** ft/NM to **5800**. Climb hdg **086°** to **6400** BPOC.
Note: Trees to 2362 ASL aprx 200' past departure end of rwy, 400' RIGHT and 500' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **5600** BPOC.

Rwy 27 - ½ - Requires a minimum climb gradient of **370** ft/NM to **7600**. Climb hdg **266°** to **5800** BPOC.
Note: Trees to 2306 ASL aprx 200' past departure end of rwy, 400' LEFT and 350' RIGHT of rwy centreline.
Trees to 2421 ASL aprx 0.3 NM past departure end of rwy, 400' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **5600** BPOC.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


TUKTOYAKTUK/JAMES GRUBEN, NT

AERODROME CHART — CYUB

CTR Edmonton – **132.4**

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	10	28
TORA	4600	4600
TODA	4800	4800
ASDA	4600	4600
LDA	4600	4600



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 26 ASL aprx 200' past departure end of rwy, 150' LEFT and 200' RIGHT of rwy centreline. Powerline to 72 ASL aprx 0.3 NM past departure end of rwy, 950' LEFT of rwy centreline.

TAKE-OFF MINIMA

Rwy 10: *
Rwy 28: ½

SCALE IN FEET
1000 0 500 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TULITA, NT

AERODROME CHART — CZFN

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	07	25
TORA	3935	3935
TODA	4135	4135
ASDA	3935	3935
LDA	3935	3935



* DEPARTURE PROCEDURE
Rwy 07 - ½ - Climb hdg **065°** to **1300** BPOC.
Note: Trees to 392 ASL aprx 200' past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.

Rwy 25 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1800** BPOC.

TAKE-OFF MINIMA
Rwys 07, 25: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ULUKHAKTOK, NT

AERODROME CHART — CYHI

			APRT RADIO – **122.1** TFC – **122.1** MF				RADIO Edmonton – **123.47**	

DECL DISTS	06	24						
TORA	4300	4300						
TODA	5284	5284						
ASDA	4300	4300						
LDA	4300	4300						



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850

* DEPARTURE PROCEDURE

Rwy 06 - ½ - Requires a minimum climb gradient of **370** ft/NM on track **057°T** from "HI" NDB to **900** BPOC

or

SPEC VIS - Climb in visual conditions to cross the airport at or above **1100** BPOC.

TAKE-OFF MINIMA	
Rwy 06:	*
Rwy 24:	½

SCALE IN FEET

1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHI


EFF 15 JUN 23

WATSON LAKE, YT

AERODROME CHART — CYQH

		APRT RADIO – **122.1** MF	RADIO Whitehorse – **123.37**

DECL DISTS	09	27
TORA	5504	5504
TODA	5704	5804
ASDA	5504	5504
LDA	5504	5504



* DEPARTURE PROCEDURE

Rwy 09 - ½ - Requires a minimum climb gradient of **340** ft/NM to **4100**. NO LEFT turn below **4100**.
Note: Road to 2262 ASL aprx 200' past departure end of rwy, 200' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **4000** BPOC.

Rwy 27 - ½ - Climb hdg **270°** to **3500** BPOC.
Note: Road to 2262 ASL aprx 300' past departure end of rwy, 250' LEFT of rwy centreline.
Trees to 2303 ASL aprx 500' past departure end of rwy, 500' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
340 FT/NM	510	680	800	910	1020	1140	1420	1700

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQH

EFF 7 OCT 21


WEKWEETI, NT

AERODROME CHART — CYWE

AWOS – **128.7**

TFC – **123.2** ATF

DECL DISTS	13	31
TORA	2999	2999
TODA	3196	3196
ASDA	2999	2999
LDA	2999	2999



* DEPARTURE PROCEDURE

Rwy 13 - ½

Note: Trees to 1253 ASL, 200' past the departure end of rwy, aprx 100' LEFT of rwy centreline.

Rwy 31 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.

TAKE-OFF MINIMA
Rwys 13; 31: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WHALE COVE, NU

AERODROME CHART — CYXN

APRT RADIO – **122.1**
TFC – **122.1**
MF

DECL DISTS	15	33
TORA	3937	3937
TODA	3937	3937
ASDA	3937	3937
LDA	3937	3937



TAKE-OFF MINIMA
Rwy 15; 33: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYXN


EFF 3 NOV 22

WHATÌ, NT

AERODROME CHART — CEM3

TFC – **123.2** ATF

DECL DISTS	10	28						
TORA	2991	2991						
TODA	3188	3188						
ASDA	2991	2991						
LDA	2991	2991						



* DEPARTURE PROCEDURE

Rwy 10 -½ **-** Requires a minimum climb gradient of **500** ft/NM to **1100**.
Note: Trees to 935 ASL aprx 0.2NM past departure end of rwy, 590' RIGHT of rwy centreline.
Trees to 925 ASL aprx 320' past departure end of runway 430' LEFT of centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

Rwy 28 -½
Note: Tower to 1016 ASL aprx 0.8NM past departure end of rwy, 0.3NM RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

TAKE-OFF MINIMA	
Rwys 10, 28: *	SCALE IN FEET 1000 0 1000

AERODROME CHART — CEM3

EFF 15 JUN 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WHITEHORSE/ERIK NIELSEN INTL, YT

AERODROME CHART — CYXY

ATIS – **125.25**	GND – **121.9**	TWR – **118.3 236.6** RADIO – **118.3** MF	CTR Edmonton – **134.15**

DECL DISTS	02	20	14R	32L	14L	32R		
TORA	1798	nu	9500	9500	6597	6597		
TODA	1798	nu	10484	10484	9877	6597		
ASDA	1798	nu	9500	9500	6597	6597		
LDA	nu	1798	8657	8098	6597	6597		



* DEPARTURE PROCEDURE
Rwys 14L, 14R, 32L, 32R - SPEC VIS - Climb in visual conditions to cross the aprt at or above **6400** BPOC.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 32L: RVR 1200 RWY 14R: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14L; 14R; 32L; 32R: * Rwys 02; 20: NOT ASSESSED	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


WRIGLEY, NT

AERODROME CHART

CYWY

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF

DECL DISTS	11	29
TORA	3500	3500
TODA	3697	3697
ASDA	3500	3500
LDA	3005	3500



* DEPARTURE PROCEDURE

Rwy 11 - ½ - Requires a minimum climb gradient of **300** ft/NM to **3400**.
Climb between hdg **135°** CW to **293°** to **4600** BPOC.
Note: Trees to 573 ASL aprx 200' past departure end of rwy, 300' LEFT and RIGHT of rwy centreline.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **4200** BPOC.

Rwy 29 - ½ **-** Requires a minimum climb gradient of **340** ft/NM to **3500**.
Climb between hdg **294°** CCW to **114°** to **5200** BPOC.
Note: Trees to 522 ASL aprx 200' past departure end of rwy, 300' LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **4200** BPOC.

TAKE-OFF MINIMA

Rwys 11, 29: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

YELLOWKNIFE, NT

AERODROME CHART — CYZF

ATIS – **128.4**	◔ GND – **121.9**	◔ TWR – **118.5 340.8** ◔ RADIO – **118.5** ◔MF	CTR Edmonton – **135.8** RADIO Edmonton – **123.37 5680**

DECL DISTS	10	28	16	34				
TORA	5001	5001	7503	7503				
TODA	5985	5985	8487	8487				
ASDA	5001	5001	7503	7503				
LDA	5001	5001	7503	7503				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 34: RVR 1200 RWY 16: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 34: ½ Rwys 10; 16; 28: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZF


EFF 10 AUG 23

ABBOTSFORD, BC

AERODROME CHART — CYXX

ATIS – **119.8**	GND – **121.8**	TWR – **119.4 295.0** RADIO Cranbrook – **119.4 295.0** MF*	TML Victoria – **132.7**

DECL DISTS	01	19	07	25				
TORA	5328	5328	9597	9597				
TODA	6178	5854	10101	10581				
ASDA	5328	5328	9597	9597				
LDA	5328	5328	9597	9302				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07: RVR 1200 RWY 25: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwy 01: Not Assessed Rwys 07; 19; 25: *	SCALE IN FEET 1000 0 1000 2000 3000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


ANAHIM LAKE, BC

AERODROME CHART — CAJ4

UNICOM – **122.8** (AU)

ATF

DECL DISTS	13	31
TORA	4642	4642
TODA	4839	4839
ASDA	4642	4642
LDA	4642	4642



TAKE-OFF MINIMA
Rwys 13; 31: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BELLA BELLA (CAMPBELL ISLAND), BC

AERODROME CHART — CBBC

AWOS – **128.7**		TFC – **122.8** ATF	CTR Vancouver – **132.2** RADIO Pacific – **123.47**

DECL DISTS	13	31
TORA	3702	3702
TODA	4686	4686
ASDA	3702	3702
LDA	3702	3702



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450

*DEPARTURE PROCEDURE

Rwy 13 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **3000** BPOC. When CYR157 is active, climb between hdg **148°** CW to **075°** to remain clear of CYR157.

Rwy 31 - ½ - Requires a minimum climb gradient of **290** ft/NM to **3200**. Climb hdg **314°** to **3200** BPOC. When CYR157 is active, climb between hdg **148°** CW to **075°** to remain clear of CYR157.
Note: Trees to 290 ASL past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **3000** BPOC. When CYR157 is active, climb between hdg **148°** CW to **075°** to remain clear of CYR157.

TAKE-OFF MINIMA
Rwys 13, 31: *

SCALE IN FEET
1000 500 0 500 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CAMPBELL RIVER, BC

AERODROME CHART — CYBL

ATIS – **128.55**		RADIO – **122.0** TFC – **122.0** MF*	TML Comox – **123.7 227.6** RADIO Pacific – **123.55**

DECL DISTS	12	30
TORA	6499	6499
TODA	7483	7483
ASDA	6499	6499
LDA	6499	6499



★ DEPARTURE PROCEDURE
Refer to DEPARTURE PROCEDURE (RNAV)
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700**. Then climb INBD track **297°** to "YBL" NDB to **2800**. As required shuttle climb. Shuttle climb to **6200** BPOC (max **200** kt).

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 12: RVR 1200 Day only RWY 30: (¼sm) Day only	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 12; 30: ★	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CASTLEGAR/WEST KOOTENAY REGIONAL, BC

AERODROME CHART — CYCG


RADIO – **122.1**

TFC – **122.1**

CTR Vancouver – **134.2 227.3**

MF*

DECL DISTS	15	33
TORA	5299	5299
TODA	5299	5619
ASDA	5299	5299
LDA	5299	5299



* DEPARTURE PROCEDURE

Rwy 15 - SPEC VIS **-** Do not exceed **210** kt below **6100**. Climb in visual conditions to cross the aprt at or above **6100**. Then climb hdg **157°** to **8100** BPOC

Rwy 33 - SPEC VIS - Do not exceed **210** kt below **6100**. Climb in visual conditions to cross the aprt at or above **6100**. Then climb hdg **157°** to **8100** BPOC

TAKE-OFF MINIMA
Rwys 15; 33: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYCG


EFF 17 JUN 21

CHETWYND, BC

AERODROME CHART — CYCQ

LWIS – **122.55**		TFC – **123.2** ATF	CTR – Edmonton **132.6**

DECL DISTS	05	23
TORA	4481	4481
TODA	4481	4481
ASDA	4481	4481
LDA	4481	4481



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 23: *	1000 0 1000

AERODROME CHART — CYCQ

EFF 25 APR 19


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

COMOX, BC

AERODROME CHART (DND) CYQQ

ATIS – **118.6 282.2**	CLNC DEL – **127.0 227.6** GND – **119.75 250.3**	TWR – **126.2 358.1**	DEP – **123.7 227.6**

DECL DISTS	12	30	18	36				
TORA	9960	9960	4970	4970				
TODA	9960	9960	4970	4970				
ASDA	9960	9960	4970	4970				
LDA	9960	9960	4970	4970				



LDA FOR LAND AND HOLD SHORT OPERATIONS		
FROM	TO	LDA in ft
Thld rwy 30	Short of Rwy 18-36	7450
Thld rwy 36	Short of Rwy 12-30	3150

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 12, 30: RVR 1200	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 12; 30; 36: * Rwy 18: NOT ASSESSED	SCALE IN FEET 2000 1000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART (DND) CYQQ

EFF 5 OCT 23

CRANBROOK/CANADIAN ROCKIES INTL, BC

AERODROME CHART — CYXC

RADIO – **122.3 262.7** MF

CTR Vancouver – **133.6**

DECL DISTS	16	34
TORA	8000	8000
TODA	8984	8800
ASDA	8000	8000
LDA	7220	8000

* DEPARTURE PROCEDURE

Fl. R hazard beacon southeast of airport must be operating for night take-off Rwy 16.

Rwy 16 -½-

CAT A & B - Requires a minimum climb gradient of **410** ft/NM to **7400**. Climb hdg **164°** to **5700**. Then climbing LEFT turn to **9400** direct to "XC" NDB. As required, shuttle climb INBD track **345°**, all turns LEFT (max 200kt) BPOC.

CAT C & D - Requires a minimum climb gradient of **440** ft/NM to **9400**. Climb hdg **164°** to **7300**. Then climbing LEFT turn to **9400** direct to "XC" NDB. As required, shuttle climb INBD track **345°**, all turns LEFT (max 200kt) BPOC.


Note: Trees to 3160 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT of rwy centreline.
or
SPEC VIS - Climb visual over aprt to **6300**. Continue climb INBD track **345°** to "XC" NDB. Then shuttle climb INBD track **345°** (max 200kt), all turns LEFT to **9400** BPOC.

Rwy 34 -½ - Requires a minimum climb gradient of **290** ft/NM to "SX" NDB. Climb track **344°** to "SX" NDB. As required, shuttle climb INBD track **164°** to **10,500** (max 200kt) BPOC.

Note: Trees to **3082** aprx 0.1 NM past departure end of rwy.
or
SPEC VIS - Climb visual over aprt to **5100**. Continue climb track **344°** to "SX" NDB. As required, shuttle climb INBD track **164°** to **10,500** (max 200kt) BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450
410 FT/NM	620	820	960	1100	1230	1370	1710	2050
420 FT/NM	630	840	980	1120	1260	1400	1750	2100
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200



RUNWAY LEVEL OF SERVICE

RVO	LVO
RWY 16, 34: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16, 34: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CRESTON, BC

AERODROME CHART — CAJ3

LWIS – **129.17**		UNICOM – **122.8** ATF	CTR Vancouver – **133.6**

DECL DISTS	15	33
TORA	3944	3944
TODA	3944	3944
ASDA	3944	3944
LDA	3944	3944



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CAJ3


EFF 20 APR 23

DAWSON CREEK, BC

AERODROME CHART — CYDQ

AWOS – **128.55**		◕ RADIO Peace River – **122.2** ◕ TFC – **122.2** MF	◕ RADIO Peace River – **122.2**

DECL DISTS	07	25
TORA	5001	5001
TODA	5985	5785
ASDA	5001	5001
LDA	5001	5001



* DEPARTURE PROCEDURE

Rwy 07 - ½ - Requires a minimum climb gradient of **440** ft/NM to **3200**.
Note: Trees to 2279 ASL aprx 0.2 NM past departure end of rwy, 500' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **3400** BPOC.

Rwy 25 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **3400** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07; 25: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT NELSON, BC

AERODROME CHART — CYYE

ATIS – **125.65**		RADIO – **122.5** MF	CTR Edmonton – **132.87 290.6** RADIO Edmonton – **123.55**

DECL DISTS	04	22	08	26				
TORA	6402	6402	3575	3575				
TODA	7386	7386	4075	3775				
ASDA	6402	6402	3575	3575				
LDA	6402	6402	3575	3575				



* DEPARTURE PROCEDURE

Rwy 04 - ½

Note: Trees to 1337 ASL aprx 0.2 NM past departure end of rwy, 100' LEFT of rwy centreline.

Rwy 22 - ½ - Requires a minimum climb gradient of **290** ft/NM to **2200**. Climb hdg **219°** to **2400** BPOC.

Note: Trees to 1339 ASL aprx 0.3 NM past departure end of rwy, 800' LEFT and 1000' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04; 22: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT ST. JOHN, BC

AERODROME CHART — CYXJ

ATIS – **128.5**	CLNC DEL – **121.9**	RADIO – **118.5** MF	CTR Edmonton – **132.6 285.4** RADIO Edmonton – **123.55**

DECL DISTS	03	21	12	30				
TORA	6698	6698	6909	6909				
TODA	7508	7518	7734	7893				
ASDA	6698	6698	6909	6909				
LDA	6698	6502	6909	6909				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 30: RVR 1200 RWY 12: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: ½	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYXJ

EFF 8 SEP 22


GOLDEN, BC

AERODROME CHART — CYGE

CTR Vancouver – **132.35**
RADIO Pacific – **122.37**

TFC – **122.8** MF

DECL DISTS	14	32						
TORA	4528	4528						
TODA	4528	4528						
ASDA	4528	4528						
LDA	4528	4528						



TAKE-OFF MINIMA
Rwy 14; 32: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGE

EFF 27 JAN 22

GRAND FORKS, BC


AERODROME CHART — CZGF

AUTO – **122.55**

TFC – **123.2** ATF

CTR Vancouver – **134.2**
RADIO Pacific – **125.85**

DECL DISTS	07	25
TORA	4311	4311
TODA	4700	4790
ASDA	4311	4311
LDA	4311	4311



TAKE-OFF MINIMA

Rwys 07; 25: NOT ASSESSED

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KAMLOOPS, BC

AERODROME CHART — CYKA

CLNC DEL – **121.9**	RADIO – **125.7**	CTR Vancouver – **132.35**
	MF	

DECL DISTS	09	27	04	22				
TORA	8000	8000	2780	2780				
TODA	8984	8984	2780	2780				
ASDA	8000	8000	2780	2780				
LDA	8000	8000	2091	2780				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKA

EFF 8 SEP 22

KAMLOOPS, BC

PARKING AREAS

CYKA

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYKA

EFF 10 SEP 20

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	504218.39N 1202625.48W	4A	504216.53N 1202630.20W
2	504217.50N 1202627.71W	5	504215.62N 1202633.07W
3	504216.91N 1202629.39W	6	504215.03N 1202634.55W
4	504216.14N 1202631.59W		


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KELOWNA, BC

AERODROME CHART — CYLW

ATIS – **127.5** AWOS – **127.5**	GND – **121.7**	TWR – **119.6 292.2** RADIO Penticton – **119.6** MF*	CTR Vancouver – **133.5**

DECL DISTS	16	34
TORA	8900	8900
TODA	9320	9251
ASDA	8900	8900
LDA	7700	8500



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 16, 34: (¼ sm)	NOT AUTHORIZED


TAKE-OFF MINIMA	
Rwys 16; 34: *	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KELOWNA, BC

PARKING AREAS (APRON I)

CYLW



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

CYLW

EFF 10 OCT 19

KELOWNA, BC

PARKING AREAS (APRON III)

CYLW


ATIS – **127.5**
AWOS – **127.5**

GND – **121.7**

Note:
Apron III: Parking for commercial operators and aircraft over 12,500 lb 3 hr PPR.
Contact OPR 250-807-4350.
Ground handling/marshalling mandatory.
Towing/push back may be required.
Pilots cautioned to minimize thrust as potential jetblast damage to adjacent acft and property.

Multilateration:
Keep transponders off or in standby mode on aprons and while taxiing.

Apron III: Heli prkg not auth.
Shell Aerocentre Apron:Heli prkg PPR



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON III)

CYLW


EFF 15 JUN 23

LANGLEY REGIONAL, BC

AERODROME CHART — CYNJ

ATIS – **124.5**	GND – **121.9**	TWR – **119.0**	TML Victoria – **132.7**
		TFC – **119.0** MF*	

DECL DISTS	01	19	07	25				
TORA	2100	2100	2743	2743				
TODA	2200	2200	2743	2743				
ASDA	2100	2100	2743	2743				
LDA	1996	2004	2089	2400				



* DEPARTURE PROCEDURE
Rwy 01, 19 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **800** (CATS A, B & C). Then intercept INBD **R-328** to 'HUH' VORTAC. Maintain **2000** or as assigned. Shuttle climb INBD **R-270** at 'HUH' VORTAC to **MEA** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 01;19: *	1000 500 0 500
Rwys 07;25: NOT ASSESSED	

AERODROME CHART — CYNJ


EFF 8 SEP 22

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LANGLEY REGIONAL, BC

TAXI CHART CYNJ

ATIS – **124.5**		TWR – **119.0**
	GND – **121.9**	TFC – **119.0** MF*



HOT SPOTS

HS 1- Rwy 19 & 25 intersection can be confusing.

HS 1- Do not exit onto Rwy 01/19 or Twy "H" when landing Rwy 07 w/o prior ATC auth.

NOTES:

1 - No aircraft/vehicle control on aprons. Maneuvering at pilot's discretion.

2 - Run up to be completed prior to contacting gnd on 121.9 when possible. Advise gnd run up complete.

3 - DEP/ARR AC provide TYPE/IDENT/POSITION/INTENTIONS on initial call.

4 - Caution on Apron 1 & 2 due frequent heli ARR/DEP.

5 - Airport restricted to a maximum weight of 12,500 lbs except with airport operator's authorization.

SCALE IN FEET

1000 500 0 500


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MACKENZIE, BC

AERODROME CHART — CYZY

AWOS – **127.7**		TFC – **123.5** MF	RADIO Pacific – **123.47**

DECL DISTS	17	35
TORA	5033	5033
TODA	6017	5033
ASDA	5233	5233
LDA	5033	5033



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17, 35: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZY

EFF 30 JAN 20

MASSET, BC


AERODROME CHART — CZMT

UNICOM – **122.7**

CTR Vancouver – **133.67**

MF

DECL DISTS	13	31
TORA	4924	4924
TODA	4924	4924
ASDA	4924	4924
LDA	4924	4674



★ DEPARTURE PROCEDURE

Rwy 13 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **900** BPOC.

Rwy 31 - ½ **-** Climb hdg **309°** to **500** BPOC.

Note: Trees to 78 ASL aprx 500' past departure end of rwy, 350' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 13; 31: ★

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZMT


EFF 12 AUG 21

NANAIMO, BC

AERODROME CHART — CYCD

ATIS – **128.42** LWIS – **128.42**	GND – **122.6**	RADIO – **122.1 291.8** TFC – **122.1** MF*	TML Victoria – **121.07 252.3** RADIO Pacific – **126.0**

DECL DISTS	16	34
TORA	6602	6602
TODA	7094	7192
ASDA	6602	6602
LDA	6405	5600



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

* DEPARTURE PROCEDURE

Rwy 16 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

Rwy 34 - ½ **-** Requires a minimum climb gradient of **400** ft/NM to **1600**. Climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.
Note: Trees to 156 ASL aprx 200' past departure end of rwy, 300' LEFT of rwy centreline. Pole to 149 ASL aprx 0.1 NM past departure end of rwy, 650' RIGHT of rwy centreline. Trees to 208 ASL aprx 0.3 NM past departure end of rwy.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 34: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 16; 34: *	SCALE IN FEET 1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

NANAIMO/NANAIMO HARBOUR HELIPORT, BC

HELIPORT CHART CDH5

			TML Victoria – **121.07 252.3**
		TFC Nanaimo Harbour – **122.9** ATF	

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
HRP *	400 0 400

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HELIPORT CHART CDH5


EFF 5 OCT 23

PENTICTON, BC

AERODROME CHART — CYYF

	GND ADV – **121.9**	RADIO – **118.5** MF	CTR Vancouver – **133.5 351.3**

DECL DISTS	16	34
TORA	6000	6000
TODA	6600	6984
ASDA	6000	6000
LDA	6000	5700



TAKE-OFF MINIMA

Rwys 16; 34: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYF


EFF 15 JUN 23

PITT MEADOWS, BC

AERODROME CHART — CYPK

ATIS – **125.0**	GND – **123.8**	TWR – **126.3** TFC – **126.3** MF*	DEP Vancouver – **132.3 363.8**

DECL DISTS	08R	26L	08L	26R	18	36		
TORA	5003	5003	2485	2485	2484	2484		
TODA	5495	5495	2585	2585	2584	2584		
ASDA	5003	5003	2485	2485	2484	2484		
LDA	4806	4839	2485	2485	2484	2484		



* DEPARTURE PROCEDURE

All Rwys - SPEC VIS - Climb in visual conditions to cross the aprt at or above **700**. Then climb OBD **R-169** from "YPK" VOR to KEPVI (YPK **R-169**/YVR **R-089**) to **1900**. Shuttle climb to **6700** BPOC. Do not exceed **230** kt.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPK

EFF 5 OCT 23

PORT ALBERNI (ALBERNI VALLEY REGIONAL), BC


AERODROME CHART — CBS8

TML Comox – **123.7**

TFC – **123.0**

ATF

DECL DISTS	12	30						
TORA	5003	5003						
TODA	5003	5003						
ASDA	5003	5003						
LDA	5003	5003						



TAKE-OFF MINIMA

Rwys 12; 30: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PORT HARDY, BC

AERODROME CHART — CYZT

		RADIO Hardy – **122.2**	CTR Vancouver – **132.2 266.3**
		MF*	

DECL DISTS	08	26	11	29	16	34		
TORA	4000	4000	4999	4999	3984	3984		
TODA	4902	4000	5983	5819	3984	4476		
ASDA	4000	4000	4999	4999	3984	3984		
LDA	4000	4000	4999	4999	3984	2493		



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 29: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 08, 34: NOT ASSESSED Rwys 11, 16, 26, 29: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZT

EFF 29 DEC 22


POWELL RIVER, BC

AERODROME CHART — CYPW

TML Comox – **123.7 227.6**

TFC – **123.0** **MF**

DECL DISTS	09	27	09	27				
TORA	3621	3621	3621	3621				
TODA	4326	3965	4326	3965				
ASDA	3795	3728	3621	3621				
LDA	3621	3621	3621	3621				



***** DEPARTURE PROCEDURE
Rwys 09, 27 - Departure NOT auth when CYA124(M) active above **1000**.
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2200**, then climb between hdg **127°** CW to **279°** to **MEA** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *****	1000 0 1000

AERODROME CHART — CYPW

EFF 15 JUN 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PRINCE GEORGE, BC

AERODROME CHART — CYXS

ATIS – **128.72** AWOS – **128.72**	GND – **121.9**	TWR – **118.3** RADIO Williams Lake – **118.3** MF*	CTR Vancouver – **133.8**

DECL DISTS	06	24	15	33	01	19		
TORA	5624	5624	11450	11450	3769	3769		
TODA	6424	6608	12385	12250	4404	3769		
ASDA	5624	5624	11450	11450	3769	3769		
LDA	5624	5223	11450	10950	2785	3396		



GROUND SPEED	90	120	140	160	180	200	250	300
320 FT/NM	480	640	750	860	960	1070	1340	1600
370 FT/NM	560	740	870	990	1110	1240	1550	1850
410 FT/NM	620	820	960	1100	1230	1370	1710	2050

* DEPARTURE PROCEDURE

Rwy 06 - ½ - Requires a minimum climb gradient of **370** ft/NM to **4900**. Climb INBD **R-249** to "YXS" VOR. Then shuttle INBD **R-249** to MEA BPOC.
Note: Road to 2254 ASL aprx 0.1 NM past departure end of rwy, LEFT and RIGHT of rwy centreline.
Rwy 15 - ½ - Requires a minimum climb gradient of **410** ft/NM to **5400**.
Note: Trees to 2332 ASL aprx 0.4 NM past departure end of rwy, 900' LEFT of rwy centreline.
Rwy 33 - ½ - Requires a minimum climb gradient of **320** ft/NM to **4900**.
Note: Trees to 2376 ASL aprx 0.5 NM past departure end of rwy, 900' LEFT of rwy centreline.
or
Rwy 06, 15, 24, 33 - SPEC VIS - Climb visual over aprt to **4100** BPOC.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 15: RVR 1200 RWY 33: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 01,19: Not assessed Rwys 15, 33, 06, 24: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYXS


EFF 23 FEB 23

PRINCE RUPERT, BC

AERODROME CHART — CYPR

AWOS – **128.57**		TFC – **122.5** MF*	CTR Vancouver – **133.67**

DECL DISTS	13	31
TORA	6000	6000
TODA	6853	6984
ASDA	6000	6000
LDA	6000	6000



* DEPARTURE PROCEDURE

Rwy 13 - ½- CLB between trk **198°** CW to **312°** from "PR" NDB to **3600** BPOC.
Note: Trees to 171 ASL beyond departure end of rwy, both LEFT and RIGHT of centreline.
Trees to 189 ASL aprx 630' from departure end of rwy, 650' LEFT of centreline.

Rwy 31 - ½- CLB between trk **312°** CCW to **198°** from "PR" NDB to **3700** BPOC.
Note: Trees to 139 ASL beyond departure end of rwy, both LEFT and RIGHT of centreline.
Trees to 203 ASL aprx 0.5 NM from departure end of rwy, both LEFT and RIGHT of centreline.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 13: RVR 1200 RWY 31: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 13, 31: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPR


PRINCETON, BC

AERODROME CHART — CYDC

CTR Vancouver – **135.0 351.3**

TFC – **123.2** **ATF**

DECL DISTS	04	22
TORA	3932	3932
TODA	4916	4732
ASDA	3932	3932
LDA	3932	3932



* DEPARTURE PROCEDURE
Rwys 04, 22 - SPEC VIS - Climb in visual conditions over aprt to **4700**. Then climb outbound on track **350°** from "DC" NDB to **5900** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04; 22: *	1000 0 1000

AERODROME CHART — CYDC

EFF 10 AUG 23

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


QUALICUM BEACH, BC

AERODROME CHART — CAT4

TML Comox – **123.7 227.6**

TFC – **122.8** **MF**

DECL DISTS	11	29						
TORA	3564	3564						
TODA	3564	3564						
ASDA	3564	3564						
LDA	3079	3364						



* DEPARTURE PROCEDURE

Rwy 11, 29 - SPEC VIS -Climb in visual conditions to cross the aprt at or above **1900** (CAT A, B & C). Continue climb hdg **044°** to intercept T719 to **MEA** BPOC.

Note: Departure procedure not authorized when CYR107 or CYA124(M) active above **1000**.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *	1000 500 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

QUESNEL, BC

AERODROME CHART — CYQZ

AWOS – **124.4**		RADIO Williams Lake – **122.2** TFC – **122.2** MF	CTR Vancouver – **134.0 381.4**

DECL DISTS	13	31
TORA	5501	5501
TODA	6485	6041
ASDA	5501	5501
LDA	5501	5501



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQZ


EFF 20 APR 23

SALMON ARM, BC

AERODROME CHART — CZAM

LWIS – **122.55**		UNICOM – **122.9** MF	CTR Vancouver – **133.5** **294.0** RADIO Pacific – **122.37**

DECL DISTS	14	32
TORA	4261	4261
TODA	4261	4261
ASDA	4261	4261
LDA	4261	4261



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZAM


EFF 8 SEP 22

SANDSPIT, BC

AERODROME CHART — CYZP

AWOS – **128.75**		RADIO Terrace – **122.3 296.2** MF	CTR Vancouver – **133.67 227.2**

DECL DISTS	13	31
TORA	5112	5112
TODA	5112	5112
ASDA	5112	5112
LDA	5112	5112



★ DEPARTURE PROCEDURE
Rwy 13 - ½ - Climb hdg **125°** to **3600** BPOC.
Rwy 31 - ½ - Climb hdg **305°** to **2800** BPOC.
Note: Trees to 29 ASL aprx 0.1 NM past departure end of rwy, 200' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13, 31: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZP


EFF 23 FEB 23

SMITHERS, BC

AERODROME CHART — CYYD

AWOS – **128.65**		RADIO – **122.3** TFC – **122.3** **MF**	CTR Vancouver – **132.52** RADIO Pacific – **123.37**

DECL DISTS	15	33
TORA	7545	7545
TODA	8300	8165
ASDA	7545	7545
LDA	7286	7283



TAKE-OFF MINIMA
Rwys 15, 33: *

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYD

EFF 20 APR 23

SONORA RESORT, BC

HELIPORT CHART


CSR6

TML Comox – **123.7**

TFC – **123.2**

ATF

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HELIPORT CHART CSR6


EFF 7 OCT 21

SOUTH CARIBOO/108 MILE, BC

AERODROME CHART — CZML

LWIS – **122.55**		TFC – **123.2** ATF	CTR Vancouver – **134.0 381.4**

DECL DISTS	15	33
TORA	5292	5292
TODA	5292	5292
ASDA	5292	5292
LDA	4877	5292



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15; 33: *	1000 0 1000

AERODROME CHART — CZML

EFF 29 DEC 22

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


SPARWOOD/ELK VALLEY, BC

AERODROME CHART — CYSW

TFC – **123.2** ATF

Pacific Radio – **126.7** DRCO

DECL DISTS	17	35						
TORA	3963	3963						
TODA	3963	3963						
ASDA	3963	3963						
LDA	3963	3963						



TAKE-OFF MINIMA

Rwys 17; 35: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSW


EFF 5 OCT 23

TERRACE, BC

AERODROME CHART — CYXT

		RADIO – **122.0** MF	CTR Vancouver – **128.4 269.1**

DECL DISTS	15	33	03	21				
TORA	7497	7497	5371	5371				
TODA	8481	8481	6355	6355				
ASDA	7497	7497	5371	5371				
LDA	7497	7497	5371	5371				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 15, 33: (¼ sm) Day only	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 03, 21: NOT ASSESSED Rwys 15, 33: *	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYXT


EFF 5 OCT 23

TOFINO/LONG BEACH, BC

AERODROME CHART — CYAZ

		RADIO Hardy – **123.25** TFC – **123.25** MF	CTR Vancouver – **132.9** RADIO Pacific – **125.85**

DECL DISTS	07	25	11	29	16	34		
TORA	5000	5000	5000	5000	5000	5000		
TODA	5000	5000	5000	5000	5000	5000		
ASDA	5000	5000	5000	5000	5000	5000		
LDA	4265	4642	4500	5000	4792	4113		



* DEPARTURE PROCEDURE

Rwy 11 - ½ **-** Climb direct to "YAZ" NDB. Climbing RIGHT turn OBD track **136°** to **4300**. Then climb between track **197°** CCW to **302°** from "YAZ" NDB to remain clear of CYD106.
Note: Trees to 215 ASL aprx 350' past departure end of rwy, 100' RIGHT of rwy centreline and aprx 0.3 NM past departure end of rwy, LEFT of rwy centreline.

Rwy 16 - ½ **-** Climb hdg **158°** to **3700**. Then climb between hdg **183°** CCW to **312°** to remain clear of CYD106.
Note: Trees to 197 ASL aprx 450' past departure end of rwy, 450' RIGHT of rwy centreline and aprx 0.1 NM past departure end of rwy.

Rwys 07, 25, 29, 34 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **1300**. Continue climbing hdg **180°** to **4100** (Cat A), **4200** (Cat B & C), **4300** (Cat D). Then climb between hdg **183°** CCW to **312°** to remain clear of CYD106.

Threshold Rwy 07 displaced 735'.
Threshold Rwy 11 displaced 500'.
Threshold Rwy 16 displaced 208'.
Threshold Rwy 25 displaced 358'.
Threshold Rwy 34 displaced 887'.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TRAIL, BC

AERODROME CHART

CAD4


AUTO – **122.17**

TFC – **123.2**

MF

CTR Vancouver – **134.2 227.3**

DECL DISTS	16	34
TORA	4001	4001
TODA	4765	4505
ASDA	4574	4479
LDA	4001	4001



TAKE-OFF MINIMA
Rwys 16, 34: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VANCOUVER INTL, BC

AERODROME CHART — CYVR

ATIS – **124.6**	CLNC DEL – **121.4** GND – **121.7** (S) **127.15** (N) **275.8**	TWR – **118.7** (S) **119.55** (N) **226.5**	DEP – **126.12** (N) **132.3** (S) **363.8**

DECL DISTS	08R	26L	08L	26R	13	31		
TORA	11500	11500	9941	9941	7300	7300		
TODA	12484	17250	11417	14911	8284	8284		
ASDA	11500	11500	9941	9941	7300	7300		
LDA	10803	10803	9941	9941	7300	7300		



TORA FOR INTERSECTION DEPARTURES

RWY	INTXN	TORA in ft	RWY	INTXN	TORA in ft	RWY	INTXN	TORA in ft	RWY	INTXN	TORA in ft
08L	M8	9612	26R	M7/N7	9612	08R	A6	8800	26L	D7	10803
	M6	7828		M5	7828		L2	8665		D5/C	10407
	M4	6099		M3	6103		A4	6801		B	8806
							H	5290		D3	7064
							E	5104		H	5580
							L4/A	10803		E	5775

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08L, 08R, 26L, 26R: RVR 1200	RWY 08L, 08R, 26L, 26R: RVR 600
TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

Widebody Aircraft

A380*/B747-8/AN124 AVAILABLE TAXIWAYS: D, DT, D3, D5, D7, D9, H (north of rwy 08R/26L), J (north of parking position W2), JA, K (west of R), L (west of 13/31), L4, L6, M, M5, M6, M7, M9, M10, P, R & V.
*A380: When A380 is on Twy M between Twy J and Twy T, the Taxilane between Gate 66 & Twy T is restricted to B757 & smaller (& vice versa). Discretionary oversteer is required at every intersection.

A340-600/B777-300/A350-900/A350-1000/B787-10 AVAILABLE TAXIWAYS: D, D3, D5, D7, D9, DT, DY, E (south of rwy 08R/26L), H (north of rwy 08R/26L), J, JA, JB, JC, K, L (West of J), L2, L4, L6, M, M4, M5, M6, M7, M8, M9, M10, P, T, R & V. Discretionary oversteer is required at every intersection.

Rwy 08L Arrivals
Use of reverse thrust is to be avoided or reduced when conditions permit.

Rwy 08R Arrivals
Acft exiting onto D1, turn north on E. Do not stop in rwy area. See HOT SPOT 2.

Rwy 13 Departures
Not authorized for A340-600/B777-300/A350-900/A350-1000/B787-10 & larger.

Rwy 26R Arrivals
Use of reverse thrust is to be avoided or reduced when conditions permit.

Rwy 26L Arrivals
Turns onto Rwy 31 NOT AUTHORIZED without clearance. Acft exiting onto Rwy 13/31: RH turns onto D rstd to B767/A310 & smaller, discretionary oversteer is required. Acft exiting onto H, hold short of D. Do not stop in rwy area. See HOT SPOT 2.

Rwy 31 Arrivals
Not authorized for A340-600/B777-300/A350-900/A350-1000/B787-10 & larger.

Taxiways

A (east of E): Rstd to B767/A310 & smaller.

A Compass Rose: Not avbl SS-SR.

A2: Rstd to Lear 60/DH8-300 & smaller.

B: Rstd to B767/A310 & smaller.

C (south of F): Rstd to B737/A321 & smaller.

C (north of F): Rstd to B767/A310 & smaller.

D: CAUTION: Acft cannot safely taxi via Twy D East or West past acft at the Twy D5 or Twy D7 hold lines.

D (eastbound): No left turns onto H by A321/B737-900 & larger.

D (westbound): No left turns onto H. No left turns onto D7. Right hand turns onto Twy DR - discretionary oversteer required.

D2: Rstd to CRJ-900 & smaller.

D3 (rapid exit): Design speed in wet conditions is 50 kt (95 km/h)

D7: No RH turns onto D.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

DR, DS: Rstd to B767/A310 & smaller.

DW: Rstd to B757 & smaller.

E (north of D): Rstd to A330/B787-10 & smaller.

F (west of C): Rstd to B767/A310 & smaller.

F (east of C): Rstd to CRJ-900 & smaller. Follow me required below RVR 1200, ctc Aprt Ops.

G: Rstd to A310/B767 & smaller.

H (southbound): No right turns onto A, L, or H4, no right turns onto D by B737-900/A321 & larger. No left turns onto D1.

H (northbound): No left turns onto V. No right turns onto D. No right turns onto L for B767/A310 & larger.

H (south of rwy 08R/26L): Rstd to B767/A310 & smaller.

H2: Avbl to B767, A310 & smaller.

J (southbound): B747/A340 not auth S of Twy K. All acft use min thrust when turning due jet blast.

J (northbound): No left turns onto K by B767/A310 & larger.

L: Entry & exit at Apron VI rstd to B737/A321 & smaller. No right turns onto V.

L2 (rapid exit): Design speed in wet conditions is 50kt (95 km/h).

M1-M6 (rapid exit): Design speed in wet conditions is 50 kt (95 km/h).

M3: Not avbl to A340-600/B777-300/A350-900/A350-1000/B787-10 & larger.

M4: No left or right turns onto M for A340-600/B777-300/A350-900/A350-1000/B787-10 & larger.

P: Right turn onto M rstd to B767/A310 & smaller.

Q: Follow me required below RVR 1200, ctc Aprt Ops.

S: Rstd to B767/A310 & smaller.

V: No left turns onto L.

Uncontrolled Taxiways

C (south of F), F, J (btwn K & L), Q, DR, DS, DT, DU, DV & DW.

Uncontrolled Vehicle Crossings

DS, DT, DU, DV, DY, F, H (north of H4), J, JA, JB, JC, K, N7, P, Q, R, S, T, V.

APU Shutdown Procedure

Acft Auxiliary Power Unit (APU) use shall be limited to 15 min or less in total between on-block time and departure of acft from stands supplied with Ground Power Unit (GPU) and/or preconditioned air, for environmental reasons, if the outside air temperature is between 0 degrees and 20 degrees Celsius.

Acft shall not need to comply with the above limitations on stands not equipped with serviceable GPU and/or preconditioned air or if there are overriding health & safety considerations.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

Apron

Advise ATC if ground crew not present at gate.

Apron I: Rstd to CRJ-900/SF34 and smaller.

Apron III: Jets tow in & out.

Apron IV: Rstd to B757 & smaller. Acft stand taxilane east of DW rstd to Convair CV-580 & smaller.

Apron I, II, III, IV, V, VI, VIII: PPR Airport Ops is required.

Apron VI (East) bypass restricted to B737 and smaller.

Apron VI (East) bypass (taxilane centerline amber lighting): Simultaneous use of dual taxilanes restricted to narrow body acft.

Apron VI (East) Pushbacks from remote parking positions E1-E3 to west taxilane.

Apron VI (East) Pushbacks from remote parking positions E10-E19 to south taxilane.

Apron VI (horseshoe): Taxilanes restricted to B737/A321 & smaller.

Apron VI: Travelling eastbound, turns onto P restricted to B767/A310 & smaller.

Apron VIII: Rstd to B767/A310 & smaller.

PPR for all engine airstarts or crossbleed starts on aprons I, II, III, IV, V, VI, VIII.

Between FedEx & Purolator aprons: Rstd to Fairchild Swearingen Metroliner & smaller.

Hot Spots

HS 1 - Twy V holdline for Rwy 13-31 is 30 m (100 ft) back due to intersection geometry.

HS 2 - Acft taxiing H, southbound, holdline is located 30 m (100 ft) back from the standard rwy hold position. Acft exiting onto D1, turn north on E. Do not stop in rwy area.

HS 3 - Twy N7 holdline for Rwy 26R 08L at intersection Twy N7 and Apron IX. 214 m from rwy edge.

HS 4 - Acft cannot safely taxi via Twy D East or West past acft at the Twy D5 or D7 hold lines. Twy D9 commences beyond the runway holdshort line for Rwy 08R/26L on Twy D and Twy DY.

HS 5 - Multiple taxilanes converge.

HS 6 - Taxiing to Rwy 08R/26L, acft fail to hold short and incur on Rwy 13/31 on Twy A.


HS 7 - Taxiing across Rwy 08R/26L, acft fail to hold short and incur on Rwy 13/31 on Twy E.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VANCOUVER INTL, BC

TAXI CHART — CYVR

ATIS – **124.6**	CLNC DEL – **121.4** GND – **121.7** (S) **127.15** (N) **275.8**	TWR – **118.7** (S) **119.55** (N) **226.5**



Multilateration: Keep transponder on at all times when taxiing. No code, squawk 1000.
Note: Not all taxiways are available in conditions of less than 1200 RVR. Acft pushing back from gates 40 thru 43 ctc 127.15 (North).

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAXI CHART — CYVR

EFF 5 OCT 23

Read Back: "Code Route (code) and Assigned Runway"

Monitor tower frequency approaching the hold line of the assigned runway, unless otherwise instructed by ATC.

Rwy 08R/26L – TWR 118.7 Rwy 08L/26R – TWR 119.55

Code	Taxi Route
Echo	Rwy 08R – E, D, H, L, hold short L6. Rwy 08L – E, D, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – E, D, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – E, D.
Golf	Rwy 08R – G, H, L, hold short L6. Rwy 08L – G, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – G, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – G, H, D.
Juliet-Alfa*	Rwy 08R – JA, J, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JA, J, M, M10. Rwy 26R – JA, J, M, M9. Rwy 26L – JA, J, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Juliet-Bravo*	Rwy 08R – JB, J, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JB, J, M, M10. Rwy 26R – JB, J, M, M9. Rwy 26L – JB, J, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Juliet-Charlie*	Rwy 08R – JC, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JC, J, M, M10. Rwy 26R – JC, J, M, M9. Rwy 26L – JC, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Lima	Rwy 08L – L, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – L, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – L, J, H, D.
Papa*	Rwy 08R – P, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – P, M, M10. Rwy 26R – P, M, M9. Rwy 26L – P, M, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Sierra	Rwy 08R – S, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – S, M, M10. Rwy 26R – S, M, M9. Rwy 26L – S, M, V, hold short H, contact ground 121.7 (expect taxi H, D).
Tango*	Rwy 08R – T, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – T, M, M10. Rwy 26R – T, M, M9 Rwy 26L – T, M, V, hold short H, contact ground 121.7 (expect taxi via H, D).

*A340-600/B777-300/A350-900/A350-1000 Taxi Routes

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Low Visibility Procedures (RVR less than 1200 to 600 ft)

Application

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast: “Low visibility procedures in effect for <name of applicable runway>”.

General

Taxi Routes

Low Visibility Taxi Routes are equipped with green inset centerline lighting. Some taxiway/taxiway intersections have been identified with three inset yellow centerline lights. Midfield crossings of 08R/26L are not permitted during low visibility operations.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area. In the event of an ASDE failure, ATC may suspend, restrict or terminate low visibility operations.

Departures

The primary runways for departure are 08R/26L. Yellow flashing runway guard lights (wig-wags) and stop bars are installed abeam each hold line. Intersection take-offs are not permitted.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

SMGCS Rwy 08L/26R and 08R/26L

Runway/taxiway intersections are equipped with yellow flashing runway guard lights and stop bars consisting of red in-set lights and red elevated lights located at the taxi hold position.

At runway entry points, M10, M8, M7, M9, N7, L4, L6, D, D5, D7, DY, C and A, when the red stop bar lights are illuminated, green lead-on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead-on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.

“AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR”

Arrivals

The primary runways for arrival are 08L/26R.

Plan to exit on the centerline lighted rapid exit taxiways and proceed beyond the alternating green and yellow centerline lights to the taxi intersection lights to ensure the aircraft is clear of the runway and the ILS sensitive area.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LOW VISIBILITY TAXI CHART

LAND RWY 08L/08R, DEPART RWY 08L/08R (RVR LESS THAN 1200 TO 600 FT)

VANCOUVER INTL, BC
CYVR

ATIS – **124.6**	CLNC DEL – **121.4** GND – **121.7** (S) **127.15** (N) **275.8**	TWR – **118.7** (S) **119.55** (N) **226.5**




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LOW VISIBILITY TAXI CHART

LAND RWY 26L/26R, DEPART RWY 26L/26R (RVR LESS THAN 1200 TO 600 FT)

VANCOUVER INTL, BC
CYVR

ATIS – **124.6**	CLNC DEL – **121.4** GND – **121.7** (S) **127.15** (N) **275.8**	TWR – **118.7** (S) **119.55** (N) **226.5**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

1. De-icing at gates permitted for frost removal only, contact “VANCOUVER DE-ICE” on 129.95.
2. De-icing pads West are positively controlled when de-icing OPS are in effect, PAD CONTROL is providing control of all aircraft and vehicle movements on these surfaces.
3. 30 min prior to pushback or taxi, advise “VANCOUVER DE-ICE” on 129.95 that de-icing is required, the type(s) of fluids required and the aircraft type. VANCOUVER DE-ICE will designate de-ice pad.
4. When requesting pushback or taxi clearance, advise ATC that de-icing is required and designated de-ice pad.
5. When advised by ATC, contact “PAD CONTROL” on 131.975 for instructions in the de-icing center and assignment to a de-icing bay.
6. Follow PAD CONTROL instructions to de-icing bay.
7. When advised by PAD CONTROL, contact ICEMAN on 130.7 and confirm brakes set, aircraft configured, engines at idle, de icing fluid requirements and any special de-icing instructions.
8. After de-icing is completed and the aircraft has been inspected, ICEMAN will confirm aircraft is clean, start time for HOLDOVER and types of fluids applied.
9. When advised by ICEMAN, contact PAD CONTROL on 131.975 for instructions.

UNDER NO CIRCUMSTANCES MAY THE AIRCRAFT BE MOVED BEFORE PAD CONTROL ADVISES THAT THE AIRCRAFT IS CLEARED TO TAXI OUT OF THE BAY.

West Pad

1. Aircraft queuing is on Twy V at Twy K and on Twy M.
2. Narrow-body aircraft will use positions W1, W3, W4, W6, W7, W9, W17 and W19, indicated by yellow inset guidance lights.
3. When transferred from ATC, follow PAD CONTROL instructions to de-icing bays.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Ground Run-up Enclosure (GRE)

Operators must receive an orientation for the GRE facility prior to use.

Crews may contact the Icehouse to schedule de-icing up to 120 minutes prior to departure. Information required: aircraft type, flight number/call sign, and the type(s) of fluids required. Parking position 2A, on Apron 1, is the only staging position for the facility. Aircraft waiting to use the GRE must remain on their aprons until 2A becomes available.

Propeller aircraft, and jet aircraft with a wing span of 71 ft or less (Dassault Falcon 900 and smaller) may power in/out of the facility.

ICEMAN will advise if engines should be running during de-icing.

Entry Procedure

1. Before contacting ATC for taxi, contact ICEMAN 130.92 for position in de-icing queue.
2. When ICEMAN approves access to either the staging position (2A) or GRE, contact ATC 121.7 for taxi.
3. Proceed as instructed by ICEMAN. CAUTION: DO NOT enter GRE until instructed by ICEMAN.
4. Advise ICEMAN 130.92 when stopped in the GRE.

De-Icing Procedure

5. Contact ICEMAN 130.92 to confirm brakes set, aircraft configured, engines idle, and provide fluid requirements.
6. After de-icing is complete and the aircraft has been inspected, ICEMAN will confirm aircraft is clean, start time for HOLDOVER and types of fluids applied.


Exit Procedure

7. When ready to taxi contact ICEMAN 130.92 for instructions.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY CYVR

ATIS – **124.6**	DE-ICE – **129.95** GND – **121.7** (S) **127.15** (N) PAD CTL – **131.97** ICEMAN – **130.7**




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VANCOUVER INTL, BC

SOUTH DE-ICING FACILITY

CYVR




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SOUTH DE-ICING FACILITY

CYVR

EFF 17 JUN 21




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VANCOUVER INTL, BC

START BOXES

CYVR



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

START BOXES

CYVR

EFF 10 AUG 23

PARKING AREAS (COMMON USE CARGO)

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (COMMON USE CARGO)

CYVR

EFF 23 FEB 23

VANCOUVER INTL, BC

PARKING AREAS (SOUTH TERMINAL) CYVR

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (SOUTH TERMINAL) CYVR

EFF 20 APR 23

VANCOUVER/BOUNDARY BAY, BC

AERODROME CHART — CZBB

ATIS – **125.5**	GND – **124.3**	TWR – **127.6** **118.1** TFC – **118.1** MF*	DEP Vancouver – **132.3** (S) **363.8**


DECL DISTS	07	25	13	31
TORA	5606	5606	5605	5605
TODA	5606	6590	5605	5933
ASDA	5606	5606	5605	5605
LDA	5606	5006	4949	5605

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
240 FT/NM	360	480	560	640	720	800	1000	1200

LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)

FROM	TO	LDA in ft
Thld rwy 25	Short of Rwy 13-31	4582
Thld rwy 31	Short of Rwy 07-25	4505



* DEPARTURE PROCEDURE

Rwy 07 - ½ - Climb between hdg **073°** CW to **253°**.
Note: Terrain to 14 ASL within 650' of departure end of rwy.
Rwy 13 - ½ - Climb between hdg **073°** CW to **253°**.
Note: Trees to 20 ASL within 800' of departure end of rwy. Building to 17 ASL abeam departure end of rwy, 500' LEFT of rwy centreline.
Rwy 25 - ½ - Requires a minimum climb gradient of **240** ft/NM to **300**. Climb between hdg **253°** CCW to **073°**.
Note: Trees to 40 ASL 0.2 NM past departure end of rwy.
or
SPEC VIS - Do not exceed **230** kts. Climb in visual conditions to cross the aprt at or above **700**. Then climb OBD **R-089** from "YVR" VOR to KEPVI (YVR **R-089**/YPK **R-169**). Shuttle to **6900** BPOC.
Rwy 31: Not Authorized.

TAKE-OFF MINIMA
All Rwys: *

SCALE IN FEET
2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


VANCOUVER/HARBOUR (PUBLIC), BC

HELIPORT CHART

CBC7

ATIS – **126.8**	CLNC DEL – **125.35**	TWR Harbour – **118.4** TFC – **118.4** ATF*	DEP Vancouver – **126.12**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HELIPORT CHART CBC7

EFF 24 MAR 22

VANDERHOOF, BC


AERODROME CHART — CAU4

AWOS – **122.55**

TFC – **122.8** ATF

CTR Vancouver – **133.8**

DECL DISTS	03	21	07	25	16	34		
TORA	4496	4496	5019	5019	3331	3331		
TODA	4496	4496	5019	5019	3331	3331		
ASDA	4496	4496	5019	5019	3331	3331		
LDA	4496	4496	5019	4796	3331	3331		



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CAU4


EFF 23 FEB 23

VERNON, BC

AERODROME CHART — CYVK

LWIS – **123.17**		◕ UNICOM – **122.8** MF	CTR Vancouver – **133.5**

DECL DISTS	05	23
TORA	3517	3517
TODA	3517	3517
ASDA	3517	3517
LDA	3517	3061



* DEPARTURE PROCEDURE
Rwys 05, 23 - SPEC VIS -
Climb in visual conditions to cross the aprt at or above **3200**. Continue climb INBD track **007°** to "6K" NDB. Then OBD track **351°** from "6K" NDB to **6700** BPOC.

TAKE-OFF MINIMA
Rwys 05; 23: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VICTORIA HARBOUR (CAMEL POINT), BC

HELIPORT CHART — CBF7

ATIS – **120.0**		RADIO Victoria Harbour – **122.2**	TML Victoria – **125.95**
		TFC – **122.2** MF*	

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VICTORIA INTL, BC

AERODROME CHART — CYYJ

ATIS – **118.8** LWIS – **118.8**	CLNC DEL – **126.4** GND – **121.9 361.4**	TWR – **119.7 239.6** RADIO Kamloops – **119.7** MF*	DEP – **125.95**

DECL DISTS	03	21	09	27	14	32		
TORA	4141	3622	6998	6998	5001	4574		
TODA	4141	3622	7982	7982	5001	4574		
ASDA	5027	5027	6998	6998	5001	5001		
LDA	3622	4141	6998	6998	4574	5001		



* DEPARTURE PROCEDURE
Refer to SID
or
Rwys 03, 14, 27, 32 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1500**, then climb INBD track **004°** to "AP" NDB BPOC.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 09, 27: RVR 1200	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 03; 09; 14; 27; 32:* Rwy 21: NOT ASSESSED	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

Widebody Aircraft

Rwy 09 Departures: Twy B, Rwy 03/21, Twy G, Twy E.

Rwy 09 Arrivals: Twy E westbound, Twy S, Twy A.

Rwy 27 Departures: Twy A, Twy S, Twy E eastbound.

Rwy 27 Arrivals: Twy E, Twy G, Rwy 03/21, Twy B.

Taxiways

Taxiway C restricted to 50,000 lbs.

Taxiway M restricted to 12,500 lbs.

Aprons

Apron II restricted to 50,000 lbs.

Apron IV restricted to scheduled commercial traffic only.
Exceptions require prior approval of airport operator.

Rwy 03-21 Operations

Aircraft restricted to max 65,000 lbs for take-off and landing.

No weight restriction for taxiing aircraft rwy 03/21 south of rwy 14/32.

Rwy 27 Arrivals

Aircraft exiting on rwy 14, HOLD SHORT rwy 03, see Hot Spot 3.

Rwy 09 Arrivals

Aircraft exiting on rwy 21, HOLD SHORT rwy 14, see Hot Spot 3.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VICTORIA INTL, BC

TAXI CHART

CYYJ

ATIS – **118.8**	CLNC DEL – **126.4**	TWR – **119.7 239.6**
LWIS – **118.8**	GND – **121.9 361.4**	RADIO Kamloops – **119.7**
		MF*



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DE-ICING PROCEDURES

GENERAL

1. De-icing at gates is not permitted without authorization from airport operator.
2. North de-icing pad access is controlled by DE-ICE CONTROL. ALL Aircraft must have an approved assignment time prior to pushback or taxi.
3. Assignment times will be provided to de-icing providers only and are provided at 20-minute intervals. De-icing provider contact information and times are detailed in the Services section.
4. ATC does not have oversight of de-icing assignments; all inquires must be directed to de-icing providers or Snow Desk when open (250-953-7595). If the Snow Desk is not open, all inquiries should be directed to de-icing providers or Airport Operations, Manager, Integrated Operations Centre.

SCHEDULED COMMERCIAL AIRCRAFT

1. De-icing assignments will be communicated to commercial aircraft via de-icing providers and individual company processes.
2. **NO de-icing will occur until an assignment has been issued**.

NON-SCHEDULED AIRCRAFT

1. Aircraft requiring an assignment shall contact a de-icing provider, who will request the assignment.
2. De-ice control will issue the assignment between scheduled commercial movements and notify the de-icing provider. The de-icing provider will provide the assignment to the aircraft.
3. If the non-scheduled aircraft misses their assignment, a new assignment must be obtained.
4. **NO de-icing will occur until an assignment has been issued**.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VICTORIA INTL, BC

PARKING AREAS

CYYJ

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYYJ


EFF 5 OCT 23

WILLIAMS LAKE, BC

AERODROME CHART — CYWL

		RADIO – **122.3** MF	CTR Vancouver – **134.0 381.4**

DECL DISTS	12	30
TORA	6966	6966
TODA	7668	7767
ASDA	6966	6966
LDA	6966	6966



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 12, 30: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYWL

EFF 23 FEB 23

ATHABASCA, AB


AERODROME CHART — CYWM

DEP Edmonton – **134.7**

TFC – **123.2**

ATF

DECL DISTS	17	35
TORA	4003	4003
TODA	4003	4003
ASDA	4003	4003
LDA	4003	4003



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17; 35: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BERENS RIVER, MB

AERODROME CHART — CYBV

			UNICOM – **122.8** (AU)			RADIO Edmonton – **123.47** ATF		

DECL DISTS	09	27						
TORA	2888	2888						
TODA	3872	3534						
ASDA	2888	2888						
LDA	2888	2888						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *	1000 0 1000

AERODROME CHART — CYBV

EFF 23 FEB 23

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


BLOODVEIN RIVER, MB

AERODROME CHART — CZTA

UNICOM – **122.8** (AU)

ATF

DECL DISTS	18	36						
TORA	2994	2994						
TODA	3978	3978						
ASDA	2994	2994						
LDA	2994	2994						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18; 36: *	1000 0 1000

AERODROME CHART — CZTA

EFF 2 DEC 21


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BONNYVILLE, AB

AERODROME CHART — CYBF

AUTO – **122.97**	TFC – **123.2** ATF	TML Cold Lake – **124.5**

DECL DISTS	08	26
TORA	4434	4434
TODA	4434	4434
ASDA	4434	4434
LDA	4434	3921



* DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Road and trees to 1904 ASL aprx 0.1 NM past departure end of rwy.

Rwy 26 - ½

Note: Apron and hangars north of rwy.
Road and trees to 1926 ASL aprx 0.3 NM past departure end of rwy, 300' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BRANDON MUNICIPALITY, MB

AERODROME CHART — CYBR

		RADIO – **122.1**	CTR Winnipeg – **132.25** RADIO Edmonton – **123.27**
		MF*	

DECL DISTS	08	26	14	32				
TORA	6510	6510	3068	3068				
TODA	7310	7110	3568	3568				
ASDA	6510	6510	3068	3068				
LDA	6510	6510	3068	3068				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBR

EFF 24 MAR 22

BROCHET, MB


AERODROME CHART — CYBT

UNICOM – **122.8** (AU)

CTR Winnipeg – **135.05**

ATF

DECL DISTS	03	21						
TORA	3500	3500						
TODA	4484	4484						
ASDA	3500	3500						
LDA	3500	3500						



✱DEPARTURE PROCEDURE

Rwy 03 - ½

Note: Trees to 1145 ASL 400' past departure end of runway.

Rwy 21 - ½

Note: Road to 1159 ASL aprx. 0.1NM past departure end of rwy, 300' LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03, 21: ✱	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BROOKS REGIONAL, AB

AERODROME CHART — CYBP

		UNICOM – **122.8**	CTR Edmonton – **132.65 229.3** ATF

DECL DISTS	12	30						
TORA	3216	3216						
TODA	3216	3216						
ASDA	3216	3216						
LDA	3216	3216						



* DEPARTURE PROCEDURE

Rwy 12 - ½ - Climb between hdg **146°** CW **306°** to remain clear of CYR229, CYR230 and CYR231.
Note: Vehicles on road to 2506 ASL aprx 170' past departure end of rwy.

Rwy 30 - ½ - Climb between hdg **135°** CW **047°** to remain clear of CYR229, CYR230 and CYR231.
Note: Powerlines to 2573 ASL aprx 0.45 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02; 20: NOT ASSESSED Rwys 12; 30: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBP


EFF 27 JAN 22

BUFFALO NARROWS, SK

AERODROME CHART — CYVT

AWOS – **128.6**		RADIO Regina – **118.65** TFC – **118.65** MF	RADIO Edmonton – **123.27**

DECL DISTS	06	24	12	30				
TORA	2297	2297	5006	5006				
TODA	2297	2297	5990	5990				
ASDA	2297	2297	5006	5006				
LDA	2297	2297	5006	5006				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CALGARY/SPRINGBANK, AB

AERODROME CHART — CYBW

ATIS – **127.9** AWOS – **127.9**	GND – **121.8**	TWR – **118.2 120.7** TFC – **118.2** MF*	DEP – **124.52 255.1** RADIO Edmonton – **123.37**

DECL DISTS	08	26	17	35				
TORA	3423	3423	5000	5000				
TODA	3863	4423	5840	5720				
ASDA	3423	3423	5000	5000				
LDA	3423	3423	5000	5000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 35: RVR 1200 Day only RWY 17: (¼sm) Day only	NOT AUTHORIZED

TAKE-OFF MINIMA	
All Rwys: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBW

EFF 7 OCT 21

Visibility Procedures (RVR less than 2600 to 1200 ft)

Reduced Visibility Taxi Routes

Taxi routes will be coordinated by ATC. All taxiways and runways are available except for rwy 08/26, taxiway D north of taxiway C, and taxiway C east of taxiway E. Uncontrolled taxiways may be used at the discretion of the pilot. Vehicles responding to an emergency are not required to follow the routes.

Departures

Rwy 17/35 will be used for departures.

Sequencing of Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-off as described in CAP GEN Operating Minima.

Surface Movement Guidance Control System

All taxiway intersections are equipped with rwy guard lights.

AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR.

Arrivals

Taxi routes will be coordinated by ATC.

Airport Services and Equipment Available under Reduced Visibility Operations

All taxiway intersections are equipped with rwy guard lights.

Runway Level of Service


Runway	Certification
17	¼ sm Day only
35	RVR 1200 Day only

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

REDUCED VISIBILITY TAXI CHART
(RVR LESS THAN 2600 TO 1200 FT)

CALGARY/SPRINGBANK, AB
CYBW

ATIS – **127.9** AWOS – **127.9**	GND – **121.8**	TWR – **118.2 120.7** TFC – **118.2** MF*




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CALGARY/YYC CALGARY INTL, AB

AERODROME CHART — CYYC

ATIS – **128.22**	CLNC DEL – **120.82** ◒ APRON – **121.3** (I) GND – **121.9** (W) **125.35** (E) **275.8**	TWR – **118.4** (W) **118.7** (E) **236.6**	DEP – **124.52** (W) **119.8** (E) **255.1**

DECL DISTS	08	26	11	29	17R	17L	35L	35R
TORA	6200	6200	8000	8000	12675	14000	12675	14000
TODA	6500	7184	8719	8984	13659	14984	13659	14984
ASDA	6200	6200	8000	8000	12675	14000	12675	14000
LDA	6200	6200	8000	8000	12675	14000	12675	14000



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 11, 17R, 17L, 29, 35L, 35R: RVR 1200	RWY 17L, 35R: RVR 600

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LDA for High Intensity Runway Operations				
From threshold rwy:	To exit point	LDA in ft	Preferred exit for med/heavy jet transport	Preferred exit for prop/ turboprop transport
11	A C G F1 F/U	3373 5000 5165 6000 8000	 F/U	 F1
17L	D1 D3 D5 S Q B	4154 6549 8261 11,979 13,475 13,795	 D3 D5 	 D3
17R	A1 C2 C1 A3 C3 C/A	3976 5840 6415 7489 8516 12,675	 C1 A3 C3 	 C1 A3
29	C A J2 W/J	3200 4853 6606 8000	 J2 J	 J2
35L	C3 A3 C1 C2 A1 C4 C6 A/C	4154 5181 6255 6830 8684 9369 10,984 12,675	 C2 C4 	 C2
35R	D2 D4 D6 Z V D	4156 6462 8265 10,205 13,475 13,795	 D4 D6 	D2 D4

Pilots may plan their arrivals using the above table of threshold-to-exit-point distances. The distances are measured from the landing threshold to the point of the intersection of the runway centreline and the extended exit taxiway centreline.

During HIRO operations, the Control Tower may nominate the rwy exit. Compliance with ATC nomination of rwy exit is at the pilot's discretion and should be acknowledged.

REMARK: For detailed information on High Intensity Runway Operations, pilots may refer to AIP RAC 4.4.10

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Reduced Take-Off Runs

When authorized by ATC, intersection departures are available as follows:

RUNWAY	INTERSECTION	RUNWAY REMAINING
17L	V Z	13680 10450
35R	Q S	13680 12200

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

Widebody Aircraft

***A380/*B747-8/*AN124 Available Taxiways:** B, BC, D, E, EA, J (east of JV), JS, JQ, JR, S, V, Q, Z, Apron IX and Apron IX De-Ice Pad.

*Twy H and C (north of J) restricted from simultaneous use by aircraft larger than B767/A300.

A340-600/777-300: Discretionary oversteer required at all intersections.

Taxiways

P, GB, GD: Uncontrolled.

W, N & M: Restricted to aircraft with wingspan of 170' or less.

AB, P, GB, JT, WB, YD & YE: Restricted to aircraft with wingspan of 118' or less.

C: Right turn on YB restricted to aircraft with wingspan of 118' or less.

F: Left turn on G restricted to aircraft with wingspan of 118' or less.

F: Left turn on F1 restricted to aircraft with wingspan of 79' or less.

F1: Right turn on F restricted to aircraft with wingspan of 79' or less.

G: Right turn on F restricted to aircraft with wingspan of 118' or less.

GB & GD: Restricted to one-way westbound.

J eastbound: Right turn on J2 restricted to aircraft with wingspan of 79' or less.

J2: Left turn on J restricted to aircraft with wingspan of 79' or less.

Y: Right turn on YB restricted to aircraft with wingspan of 118' or less.

YB: Left turn on C restricted to aircraft with wingspan of 118' or less. Left turn on Y restricted to aircraft with wingspan of 118' or less.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CALGARY/YYC CALGARY INTL, AB

TAXI CHART

CYYC

ATIS – **128.22**	CLNC DEL – **120.82** APRON – **121.3** (I) GND – **121.9** (W) **125.35** (E) **275.8**	TWR – **118.4** (W) **118.7** (E) **236.6**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAXI CHART

CYYC

EFF 29 DEC 22

Low Visibility Procedures (RVR less than 1200 to 600 ft) and Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

Low/Reduced Visibility Taxi Routes

Anticipated taxi routes will be identified, and should portions thereof be unavailable, alternate routes will be identified.

In the event that an aircraft must taxi across the airfield for departure, the RVR values along the taxi route must be used to determine visibility limitations.

Once an aircraft has commenced taxi for takeoff, or taxi after landing, and the visibility falls below the published level of service on the given taxiway, the aircraft may continue to taxi.

Rwy 08/26 may be used as a taxiway.

Aircraft requiring imminent departure are permitted to tow during RVO but must obtain taxi routing clearances and follow all applicable airside traffic directives guidelines. Tow operations below 1200 RVR are not authorized on manoeuvring areas.

Engine run ups will not be allowed.

Departures

Departures during LVO will be on rwy 17L/35R. During RVO, rwy 17R/35L will be the preferential runway. The departure runway will be identified.

Runways 17L/35R, 17R/35L and 11/29 are equipped with high intensity edge lights and threshold/end lights. Rwy 17L/35R is equipped with centreline lights.

Departure taxi routes will be the most direct route to the threshold. Intersection departures are not permitted. If the primary route is unavailable, Calgary Tower may recommend a secondary route.

Exceptions for departures:

- Taxi to Rwy 11 may be approved from Apron VII and IX when RVR 11 is 1200 or greater
- Taxi to Rwy 11 may be approved from Apron I, East Deice and West Deice when RVR 11 AND 17R are 1200 or greater
- Taxi to Rwy 17R may be approved from Apron I, IX, East Deice and West Deice when RVR 17R is 1200 or greater
- Taxi to Rwy 17R may be approved from Apron VII when RVR 11 AND 17R are 1200 or greater.
- Taxi to Rwy 35L may be approved from Aprons III, IV, V, VI and VIII when RVR 35L is 1200 or greater
- Taxi to Rwy 29 may be approved from Apron I & II and IX when RVR 17R and RVR 29 are 1200 or greater.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Sequencing of Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-off as described in CAP GEN Operating Minima.

Surface Movement Ground Control System

All taxi hold positions on taxiways leading to Runway 17L/35R are equipped with stop bars.

Prior to manoeuvring on aprons, aircraft are recommended to contact Apron Advisory Service.

AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR

Arrivals

Arrivals during LVO will be on rwy 17L/35R. During RVO, rwy 17L/35R will be the preferential runway. ATC will designate the arrival runway.

Calgary Tower will direct arrival taxi routes in order to ensure the aircraft exits the runway at the first available exit, and will provide instruction from the runway to the Apron.

Airport Services And Equipment Available Under Low Or Reduced Visibility Operations

Airport Surface Detection Equipment (ASDE)

Upon request “follow-me” service can be provided to aircraft. Requests should be made with as much notice as possible.

Runway Level of Service

Rwy	Certification
11	RVR 1200
29	RVR 1200
17L	RVR 600
35R	RVR 600
17R	RVR 1200
35L	RVR 1200

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART

LAND RWY 17L, DEPART RWY 17L (RVR LESS THAN 1200 TO 600 FT)

CALGARY/YYC CALGARY INTL, AB

CYYC

ATIS – **128.22**	CLNC DEL – **120.82** APRON – **121.3** (I) GND – **121.9** (W) **125.35** (E) **275.8**	TWR – **118.4** (W) **118.7** (E) **236.6**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART

LAND RWY 35R, DEPART RWY 35R (RVR LESS THAN 1200 TO 600 FT)

CALGARY/YYC CALGARY INTL, AB

CYYC

ATIS – **128.22**	CLNC DEL – **120.82** APRON – **121.3** (I) GND – **121.9** (W) **125.35** (E) **275.8**	TWR – **118.4** (W) **118.7** (E) **236.6**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

De-icing Procedures

1. Contact CALGARY DE-ICE on 129.5 thirty (30) min prior to push-back with aircraft type and estimated push-back time.
2. Contact CALGARY DE-ICE on 129.5 five (5) min prior to push-back to confirm treatment type and DE-ICE pad assignment.
3. Follow normal pushback procedures and advise Apron Advisory EAST or WEST DE-ICE pad has been assigned.
4. East Pad - Enter from Twy J at Twy JQ. When instructed by GROUND CONTROL, contact PAD CONTROL on 129.12 prior to entering pad.
5. West Pad - Enter from Twy J at Twy JV. When instructed by GROUND CONTROL, contact PAD CONTROL on 122.35 prior to entering pad.
6. Follow PAD CONTROL instructions, signboards and guidance lines to the assigned staging position or de-icing bay and confirm "BRAKES SET" when in position with nosewheel on stopbar.
   CAUTION: The wingtip to tail clearance for aircraft taxiing in the EAST pad from JQ behind staged aircraft is only assured when the staged aircraft nosewheel is on the stopbar.
7. If assigned a staging bay, monitor PAD CONTROL until further instructed.
8. When directed by PAD CONTROL, contact ICEMAN (East 123.35, West 122.72) and confirm "BRAKES SET, AIRCRAFT CONFIGURED FOR DE-ICE."
9. When de-ice is complete, do not move aircraft. When directed by ICEMAN, contact PAD CONTROL on assigned frequency.
10. Advise PAD CONTROL when ready to taxi. PAD CONTROL will assign appropriate GROUND CONTROL frequency to obtain taxi clearance.
11. Queuing is not permitted on Twy J, staging positions are provided on both EAST and WEST pads, reference DE-ICE Facility diagram.

CAUTION:


During the de-icing process, thrust setting must not exceed ground idle and/or propellers must remain feathered at all times.

Engine run-ups will only be approved by PAD CONTROL or ICEMAN when operations permit and when it is safe to do so. Engine fan blade ice shedding run-ups are prohibited on the de-ice pads.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ATIS – **128.22**	DE-ICE – **129.5** GND – **121.9** (W) **125.35** (E) **275.8** PAD CTL – **122.35** (W) **129.12** (E) ICEMAN – **122.72** (W) **123.35** (E)

WEST DE-ICE






ANNUAL RATE OF CHANGE 12' W

S1, S2 & S3 are staging for narrow-body aircraft only.

S4 is for staging wide-body or narrow-body as directed by ICEMAN WEST DE-ICE

CALGARY DEICE (Initial contact)	**129.5**
PAD CONTROL WEST DE-ICE	**122.35**
ICEMAN WEST DE-ICE	**122.725**

EAST DE-ICE





ANNUAL RATE OF CHANGE 12' W

Apron taxilane up to Bay 5 will accomodate aircraft with wingspans of 213' (65m) and smaller.

Apron taxilane Bay 6 to Bay 9 will accomodate aircraft with wingspans of 118' (36m) and smaller.

Aircraft in staging positions must place nosewheel on stopbar to ensure clearance to taxilane.

Aircraft must contact E GND prior to exiting EAST DE-ICE for access onto Twy Bravo.


Delimitation Area Marking

De-icing pad aircraft exit to Twy Bravo.

CALGARY DEICE (Initial contact)	**129.5**
PAD CONTROL EAST DE-ICE	**129.125**
ICEMAN EAST DE-ICE	**123.35**

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ATIS – **128.22**	CLNC DEL – **120.82** APRON – **121.3** (I) GND – **121.9** (W) **125.35** (E) **275.8**



Apron 1 Exit Routing Procedure and Restrictions (see chart below)

Routing
Apron I Advisory (121.3 - limited hours) will normally direct departing acft to a taxi position fix dependent upon active runways.
Twy JT restricted to aircraft with wingspan of 118' or less.
Twy GB is restricted to one-way westbound and to aircraft with wingspan of 118' or less.
Twy GD restricted to one-way westbound

Multilateration: Acft transponders must be kept on at all times when manoeuvring on runways, taxiways and all aprons.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CAMROSE, AB


AERODROME CHART — CEQ3

TML Edmonton – **119.5**

◕ UNICOM – **122.8**

ATF

DECL DISTS	14	32						
TORA	4512	4512						
TODA	4712	4512						
ASDA	4512	4512						
LDA	4315	4512						



TAKE-OFF MINIMA
Rwys 14, 32: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CHURCHILL, MB

AERODROME CHART — CYYQ

		RADIO – **126.9**	CTR Winnipeg – **134.6** RADIO Edmonton – **123.27**
		MF	

DECL DISTS	15	33	07	25				
TORA	9195	9195	4000	4000				
TODA	10179	10179	4700	4984				
ASDA	9195	9195	4000	4000				
LDA	9195	9195	4000	4000				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: ½	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CIGAR LAKE, SK


AERODROME CHART — CJW7

AUTO – **122.97**

UNICOM – **123.3** (AU)

ATF

DECL DISTS	17	35						
TORA	5240	5240						
TODA	5869	5869						
ASDA	5240	5240						
LDA	5240	5240						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17; 35: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

COLD LAKE REGIONAL, AB

AERODROME CHART — CEN5

ATIS Cold Lake – **118.25**		TFC – **122.8** ATF	TML Cold Lake – **124.5**

DECL DISTS	08	26
TORA	3005	3005
TODA	3005	3005
ASDA	3005	3005
LDA	3005	3005



* DEPARTURE PROCEDURE

Rwy 08 - ½
Note: Trees to 1893 ASL 0.3 NM past departure end of rwy, 760' RIGHT of extended rwy centreline.

Rwy 26 - ½
Note: Trees to 1860 ASL 0.3 NM past departure end of rwy.

TAKE-OFF MINIMA
Rwys 08, 26: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

COLD LAKE/GROUP CAPTAIN R.W. MCNAIR, AB

AERODROME CHART (DND) CYOD

ATIS – **118.25 260.0**	CLNC DEL –**120.6 230.6** GND – **121.9 275.8**	TWR – **126.2 226.5 236.6 255.7** (E) ADVSY Cold Lake – **126.2** (E)	TML – **124.5 322.8**

DECL DISTS	04	22	13L	31R	13R	31L		
TORA	8273	8273	12599	12599	9999	9999		
TODA	8273	8273	12599	12599	9999	9999		
ASDA	8273	8273	12599	12599	9999	9999		
LDA	8273	8273	12599	12599	9999	9999		



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAKE-OFF MINIMA

All Rwys: ½

SCALE IN FEET

2000 0 2000 4000

COLLINS BAY, SK


AERODROME CHART — CYKC

AUTO – **122.35**

UNICOM – **123.3** (AU)

ATF

DECL DISTS	02	20
TORA	5191	5191
TODA	5863	6175
ASDA	5191	5191
LDA	5191	5191



★ DEPARTURE PROCEDURE

Rwy 02 - ½ -
Note: Powerline to 1342 ASL aprx 0.1 NM past departure end of rwy, 120' LEFT of rwy centreline, vehicles to 1333 ASL aprx 0.1 NM past departure end of rwy, 50' RIGHT of rwy centreline.

Rwy 20 - ½ - Requires a minimum climb gradient of **280** ft/NM to **2300.** Climb hdg **204°** to **2000** BPOC.
Note: Trees to 1365 ASL aprx 0.3 NM past departure end of rwy, 90' LEFT of rwy centreline, trees to 1415 ASL aprx 0.6 NM past departure end of rwy, 740' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross aprt at or above **2300** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
280 FT/NM	420	560	660	750	840	940	1170	1400

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02, 20: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKC

EFF 5 OCT 23

CONKLIN (LEISMER), AB

AERODROME CHART — CET2


AUTO – **123.17**

◒ UNICOM – **122.8** (AU)

ATF

CTR Edmonton – **133.72**

DECL DISTS	09	27
TORA	5251	5251
TODA	6235	6235
ASDA	5251	5251
LDA	5251	5251



DEPARTURE PROCEDURE

Rwy 09 - ½

Note: Powerline and trees to 1951 ASL 0.3 NM past departure end of rwy, 730' LEFT of rwy centreline.

Rwy 27 - ½

Note: Trees to 1934 ASL at departure end of rwy, 280' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: ✱	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CROSS LAKE (CHARLIE SINCLAIR MEMORIAL), MB


AERODROME CHART — CYCR

CTR Winnipeg – **135.1**

◕ UNICOM – **122.8** (AU)

ATF

DECL DISTS	05	23
TORA	3991	3991
TODA	4975	4975
ASDA	3991	3991
LDA	3991	3991



TAKE-OFF MINIMA
Rwys 05, 23: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


CUMBERLAND HOUSE, SK

AERODROME CHART — CJT4

CTR Winnipeg – **135.62**

TFC – **123.2** ATF

DECL DISTS	10	28
TORA	2944	2944
TODA	2944	2944
ASDA	2944	2944
LDA	2944	2944



TAKE-OFF MINIMA

Rwy 10: *
Rwy 28: ½

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DAUPHIN (LT. COL W.G.(BILLY) BARKER, VC), MB

AERODROME CHART — CYDN

AWOS – **128.6**		RADIO Brandon – **122.3** TFC – **122.3** MF	RADIO Edmonton – **123.37**

DECL DISTS	08	26	14	32	02	20		
TORA	2703	2703	5002	5002	2110	2110		
TODA	3687	3523	5986	5986	2110	2110		
ASDA	2703	2703	5002	5002	2110	2110		
LDA	2703	2703	5002	5002	2110	2110		



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYDN

EFF 10 AUG 23

DELORAINE, MB

AERODROME CHART


CJJ4

CTR Winnipeg – **132.25**

TFC – **122.8**

ATF

DECL DISTS	08	26	17	35				
TORA	3981	3981	2218	2218				
TODA	3981	3981	2218	2218				
ASDA	3981	3981	2218	2218				
LDA	3981	3981	2218	2218				



* DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Building to 1726 ASL abeam departure end of rwy, 330' LEFT of rwy centreline. Trees to 1716 ASL aprx 0.2 NM past departure end of rwy.

Rwy 26 - ½

Note: Terrain to 1687 ASL abeam departure end of rwy, 160' LEFT of rwy centreline.

TAKE-OFF MINIMA

Rwys 08; 26: *
Rwys 17; 35: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DONNELLY, AB


AERODROME CHART — CFM4

CTR Edmonton – **135.27**

TFC – **123.2**

ATF

DECL DISTS	07	25
TORA	3182	3182
TODA	3182	3182
ASDA	3182	3182
LDA	3182	2980



TAKE-OFF MINIMA
Rwys 07, 25: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DRAYTON VALLEY(HEALTH CENTRE), AB

HELIPORT CHART — CFV9

			UNICOM – **122.8** (AU) ATF CER3	CTR Edmonton – **132.05**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DRAYTON VALLEY INDUSTRIAL, AB


AERODROME CHART — CER3

UNICOM – **122.8**

CTR Edmonton – **132.05**

ATF

DECL DISTS	14	32
TORA	5065	5065
TODA	5065	5065
ASDA	5065	5065
LDA	3573	5065



***DEPARTURE PROCEDURES**

Rwy 14 - ½
Note: Road to 2764 ASL 0.1 NM past departure end of rwy, 600' LEFT of rwy centreline. Buildings to 2772 ASL 0.1 NM past departure end of rwy, 400' RIGHT of rwy centreline.

Rwy 32 - ½
Note: Trees to 2810 ASL, 50' past departure end of rwy, 150' LEFT and 450' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14, 32: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CER3


EFF 3 NOV 22

DRUMHELLER MUNICIPALITY, AB

AERODROME CHART — CEG4

AUTO – **122.17**		UNICOM – **122.8** ATF	CTR Edmonton – **124.45 132.85**

DECL DISTS	17	35						
TORA	3505	3505						
TODA	3505	3505						
ASDA	3505	3505						
LDA	3505	3505						



TAKE-OFF MINIMA
Rwys 17; 35: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDMONTON/COOKING LAKE, AB


AERODROME CHART — CEZ3

TFC – **123.35**

TML Edmonton – **119.5**

MF*

DECL DISTS	10	28						
TORA	2952	2952						
TODA	2952	2952						
ASDA	2952	2952						
LDA	2952	2952						



***DEPARTURE PROCEDURE**

Rwy 10 - ½

Note: Trees to 2538 ASL aprx 0.3 NM past departure end of rwy, 970' LEFT of rwy centreline.

Rwy 28 - ½ - Requires a minimum climb gradient of **240** ft/NM to **3800**.

Note: Trees to 2538 ASL aprx 0.3 NM past departure end of rwy, 500' LEFT of rwy centreline.

or

SPEC VIS - Climb visual over aprt to **3800** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
240 FT/NM	360	480	560	640	720	800	1000	1200

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28:*	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDMONTON INTL, AB

AERODROME CHART — CYEG

ATIS – **128.0**	CLNC DEL – **124.1** GND – **121.7 275.6**	TWR – **118.3 381.2**	DEP – **133.65 363.8** RADIO Edmonton – **122.37**

DECL DISTS	02	20	12	30				
TORA	10995	10995	10200	10200				
TODA	11979	11979	11184	11184				
ASDA	10995	10995	10200	10200				
LDA	10995	10995	10200	10200				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 02, 12, 30: RVR 1200 RWY 20: (1/4sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02; 12; 20: ½ Rwy 30: *	2000 0 2000 4000 6000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEG

EFF 5 OCT 23

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

If any portion of the airport drops below ½ SM or 2600 RVR but is at or above ¼ SM or 1200 RVR, the airport is considered to be operating in RVOP with no restrictions to aircraft or vehicles.

If any portion of the airport drops below ¼ SM or 1200 RVR, provided the runway of intended use is at or above ¼ SM or 1200 RVR, the following procedures shall be implemented:

- Any runway that is below ¼ SM or 1200 RVR will not be used for arrivals or departures.
- Restrictions apply to vehicles and aircraft on the manoeuvring area. Only one aircraft, helicopter or vehicle will be given permission to operate on the manoeuvring area at any given time (except as permitted below under Vehicle Exceptions).
- Towing of aircraft on the manoeuvring area is not permitted.

Departures

An aircraft may be taxied for departure if the runway of intended use is at or above ¼ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility drops below ¼ SM or 1200 RVR after taxi clearance was issued, the aircraft may continue to taxi.

An aircraft may depart during RVOP operations provided the RVR serving the departure runway is at or above ¼ SM or 1200 RVR.

Arrivals

An aircraft may land and taxi if the runway of intended use is at or above ¼ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

Arrivals will be in accordance with applicable approach minima or approach ban considerations. After landing, the aircraft may taxi provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility for the runway of intended use drops below ¼ SM or 1200 RVR after an arriving aircraft crosses the final approach fix (FAF), the aircraft may land and taxi in.

Vehicle Exceptions

A group of vehicles may be considered one movement provided they are traveling together and use a single call sign.

Vehicles are permitted to operate on an inactive runway. Once vehicles are established and restricted to remain on the inactive runway, RVOP may resume on the remaining manoeuvring area.

Emergency vehicles responding to emergency situations are exempt.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

De-icing Procedures


1. When de-icing is required, ctc EDMONTON DE-ICE on 122.850 30 min prior or as soon as possible with de-icing requirements. AEROMAG will assign the expected de-icing pad or holding area according to de-icing flow.
2. Prior to pushback and for taxi clearance ctc GROUND CONTROL on 121.700 with de-icing pad assignment.
3. On the Main Apron, hold short of the assigned de-icing pad and ctc AEROMAG PAD CONTROL on 122.775.
4. Follow AEROMAG PAD CONTROL instructions and guidance lines to the assigned de-icing bay or staging bay and confirm "BRAKES SET" when in position. Monitor GROUND CONTROL on 121.700 at all times.
5. When directed by AEROMAG PAD CONTROL, ctc ICEMAN on 130.125 (136.535 backup frequency) and confirm "BRAKES SET, AIRCRAFT CONFIGURED and ENGINES IDLE FOR DE-ICE."
6. When de-ice is complete, do not move aircraft. When directed by ICEMAN, ctc AEROMAG PAD CONTROL on 122.775 to obtain taxi instructions.
7. Follow AEROMAG PAD CONTROL instructions to exit de-icing. Hold short of Twy ALPHA and ctc GROUND on 121.700 to obtain clearance. Holding short of Twy ALPHA is only relevant to DF1 and DF2. DF3 aircraft exit onto Apron I.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDMONTON INTL, AB

PARKING AREAS (APRON 1)

CYEG



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON 1)

CYEG

EFF 10 SEP 20

EDMONTON/JOSEPHBURG, AB

AERODROME CHART — CFB6


AWOS – **122.35**

TFC – **123.5**

ATF

TML – **119.5**

DECL DISTS	08	26
TORA	4560	4560
TODA	4796	4826
ASDA	4560	4560
LDA	4166	4313



✱ DEPARTURE PROCEDURE

Rwy 08 - ½ **-** Procedure not authorised when CYA202(S) is active. Climb hdg **085°** to **2600** BPOC. Do not climb between hdg **220°** CW to **275°** until clear of CYA209(T) and CYA218(P).
Note: Trees to 2138 ASL abeam departure end of rwy, 480' RIGHT of rwy centreline. Road and vehicle to 2083 ASL 0.1 NM past departure end of rwy.

Rwy 26 - ½ **-** Do not climb between hdg **285°** CCW to **217°** until clear of CYA209(T) and CYA218(P).
or
When CYA202(S) is active: Climb between hdg **285°** CW to **039°** or hdg **217°** CCW to **115°** until clear of CYA209(T), CYA218(P) and CYA202(S).
Note: Road and vehicle to 2077 ASL 0.1 NM past departure end of rwy. Trees to 2106 ASL 0.1 NM past departure end of rwy.

TAKE-OFF MINIMA
Rwys 08; 26: ✱

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDMONTON/UNIV OF ALBERTA (STOLLERY CHILDREN'S HOSP MAHI), AB


HELIPORT CHART — CEW7

TML Edmonton – **119.5**

TFC – **123.2**

ATF*

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA

NOT ASSESSED

SCALE IN FEET

100 0 100

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HELIPORT CHART — CEW7


EFF 24 MAR 22

EDMONTON/VILLENEUVE, AB

AERODROME CHART — CZVL

ATIS – **128.35** AWOS – **128.35**	GND – **120.8**	TWR – **118.8** TFC – **118.8** ATF*	TML – **119.5**

DECL DISTS	08	26	16	34				
TORA	5001	5001	3496	3496				
TODA	5001	5001	3696	3696				
ASDA	5001	5001	3496	3496				
LDA	5001	5001	3496	3496				



* DEPARTURE PROCEDURE

Rwy 08 - ½ - Climb between hdg **043°** CCW to **289°** or between hdg **107°** CW to **207°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2238 ASL aprx 500' past departure end of rwy, 450' LEFT of rwy centreline.

Rwy 16 - ½ - Climb between hdg **208°** CCW to **099°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2293 ASL aprx 0.2 NM past departure end of rwy, 400' RIGHT of rwy centreline.

Rwy 26 - ½ - Climb between hdg **188°** CCW to **099°** or between hdg **294°** CW to **045°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2274 ASL abeam departure end of rwy, 500' LEFT of rwy centreline.

Rwy 34 - ½ - Climb between hdg **291°** CW to **045°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2274 ASL aprx 200' past departure end of rwy, 500' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDSON, AB

AERODROME CHART — CYET

AWOS – **128.75**		TFC – **123.2** ATF	RADIO Edmonton – **126.7**

DECL DISTS	07	25
TORA	6000	6000
TODA	6200	6200
ASDA	6000	6000
LDA	5406	5516



***** DEPARTURE PROCEDURE

Rwy 07 - ½ **-** Climb hdg **074°** to **4900**. Climb between hdg **176°** CCW to **236°** to avoid Blasting Area aprx 34 NM SW of aerodrome.
Note: Road to 3040 ASL aprx 100' past departure end of rwy. Trees to 3130 ASL aprx 0.1 NM past departure end of rwy, 500' LEFT of rwy centreline

Rwy 25 - SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **4000**. Then climb between hdg **285°** CW to hdg **176°** to avoid Blasting Areas aprx 25 NM West and 34 NM SW of aerodrome.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07; 25: *****	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ELK POINT, AB


AERODROME CHART — CEJ6

TML Cold Lake – **124.5**

TFC – **123.2**

ATF

DECL DISTS	08	26						
TORA	4498	4498						
TODA	4498	4498						
ASDA	4498	4498						
LDA	4498	4281						



***** DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Trees to 2021 ASL 0.2 NM past departure end of rwy.

Rwy 26 - ½

Note: Road to 2005 ASL 0.1 NM past departure end of rwy. Trees to 2040 ASL within 0.3 NM past departure end of rwy.

Note: Departing aircraft to remain below **6000**' until clear of CYR268, or otherwise authorized by ATC.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *****	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ESTEVAN REGIONAL, SK

AERODROME CHART — CYEN

AUTO – **127.8**			◕ UNICOM – **123.0** ATF					

DECL DISTS	08	26	15	33				
TORA	5003	5003	3001	3001				
TODA	5003	5003	3001	3001				
ASDA	5003	5003	3001	3001				
LDA	5003	5003	3001	3001				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEN


EFF 2 DEC 21

FAIRVIEW, AB

AERODROME CHART — CEB5

AUTO – **122.97**		UNICOM – **122.8** ATF	CTR Edmonton – **135.27**

DECL DISTS	04	22
TORA	3506	3506
TODA	3506	3506
ASDA	3506	3506
LDA	3506	3506



TAKE-OFF MINIMA
Rwy 04, 22: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FLIN FLON, MB

AERODROME CHART — CYFO

			◒ RADIO Saskatoon – **122.0** ◒ TFC – **122.0** MF			RADIO Edmonton – **123.27**		

DECL DISTS	01	19						
TORA	5004	5004						
TODA	5988	5988						
ASDA	5004	5004						
LDA	5004	5004						



***** DEPARTURE PROCEDURE

Rwy 01 - ½

Note: Trees to 1041 ASL aprox 0.1 NM past departure end of rwy. Trees to 1093 ASL approx 0.3 NM past departure end of rwy.

Rwy 19 - ½

Note: Trees to 1037 ASL aprox 0.2 NM past departure end of rwy, 640' RIGHT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 01, 19: *****	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


FOND-DU-LAC, SK

AERODROME CHART — CZFD

AUTO – **122.17**

TFC – **123.2** ATF

DECL DISTS	10	28						
TORA	3805	3805						
TODA	4789	4297						
ASDA	3805	3805						
LDA	3805	3805						



✱ DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 924 ASL aprx 0.1 NM past departure end of rwy, both LEFT and RIGHT of rwy centreline.

Rwy 28 - ½

Note: Trees to 912 ASL aprx 0.1 NM past departure end of rwy, 280' both LEFT and RIGHT of rwy centreline. Powerline to 932 ASL aprx 0.8 NM past departure end of rwy, 1000' RIGHT of rwy centreline.

TAKE-OFF MINIMA
Rwys 10; 28: ✱

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT CHIPEWYAN, AB

AERODROME CHART — CYPY

AWOS – **128.0**		TFC – **123.2** ATF	RADIO Edmonton – **123.47**

DECL DISTS	04	22
TORA	5000	5000
TODA	5984	5984
ASDA	5000	5000
LDA	5000	5000



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 04; 22: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT MACKAY/ALBIAN, AB

AERODROME CHART — CAL4

AUTO – **122.97**	CLNC DEL Edmonton – **134.02**	UNICOM – **123.3** (AU) TFC – **123.5** ATF*	CTR Edmonton – **134.02**

DECL DISTS	13	31
TORA	7549	7549
TODA	8533	8533
ASDA	7549	7549
LDA	7549	7549



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CAL4


EFF 29 DEC 22

FORT MACKAY/FIREBAG, AB

AERODROME CHART — CYFI

AUTO – **129.65**	CLNC DEL Edmonton – **134.02**	◕ UNICOM – **122.8** (AU) TFC – **123.5** ATF*	CTR Edmonton – **134.02**

DECL DISTS	17	35
TORA	6890	6890
TODA	7874	7874
ASDA	6890	6890
LDA	6890	6890



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17, 35: ½	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYFI


EFF 17 JUN 21

FORT MACKAY/HORIZON, AB

AERODROME CHART — CYNR

AUTO – **122.07**	CLNC DEL Edmonton – **134.02**	◕ UNICOM – **122.7** (AU) TFC – **123.5** ATF*	CTR Edmonton – **134.02**

DECL DISTS	17	35
TORA	6001	6001
TODA	6001	6001
ASDA	6001	6001
LDA	6001	6001



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17; 35: *	1000 0 1000 2000

AERODROME CHART — CYNR

EFF 19 MAY 22


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT MCMURRAY, AB

AERODROME CHART — CYMM

ATIS – **128.5** AWOS – **128.5**	CLNC DEL – **121.9** GND – **121.9**	TWR – **118.1 236.6** RADIO Peace River – **118.1** MF	CTR Edmonton – **135.7** RADIO Edmonton – **123.55**

DECL DISTS	08	26
TORA	7503	7503
TODA	8487	8487
ASDA	7503	7503
LDA	7503	7003



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08: (1/4sm) RWY 26: RVR 1200	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 08: * Rwy 26: ½	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Arrival Communication Procedures

1. Aircraft arriving at YMM will exit the runway and contact ground frequency (121.9) to request taxi instructions.
2. YMM Tower (or YPE Peace River Radio during the hours of 2245-0615 local) will give taxi instructions.

Departure Communication Procedures

1. Contact ground 121.9 (or Peace River Radio 118.1 during the hours of 2245-0615 local) for runway and taxi instructions.
2. Aircraft on Apron II (North) will contact YMM Ground on 121.9 (or Peace River Radio on 118.1 during the hours of 2245-0615 local for runway and taxi instructions.

De-Ice Bay Procedure

Fort McMurray International operates a central de-icing facility which is located on the main/south ramp (Apron I) on the south side of the airport. All bays are capable of both engine on and engine off de-icing operations concurrently. All de-icing is to be accomplished at this facility.

1. De-icing is accomplished by each of the ground handling companies that operate at the Fort McMurray International Airport.
2. Coordinate any special treatment with your Ground Handler prior to taxi to the CDF.
3. Entry point to the CDF, if transitioning from the North, is via taxi-way J to Apron I – use west entrance.
4. If required to hold – the designated holding area is to your immediate right upon entering Apron I.
5. CDF flow is from west to east.
6. Contact YMM Ground on 121.9 (or Peace River Radio on 118.1 during the hours of 2245-0615 local) for runway and taxi instructions.
7. Exit is via taxi-way H.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FORT MCMURRAY, AB

DE-ICING OPERATIONS

CYMM

ATIS – **128.5** AWOS – **128.5**	CLNC DEL – **121.9** GND – **121.9**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DE-ICING OPERATIONS CYMM

EFF 5 DEC 19

FORT VERMILION (WOP MAY MEMORIAL), AB


AERODROME CHART — CEZ4

CTR Edmonton – **135.1**

TFC – **123.2**

ATF

DECL DISTS	08	26						
TORA	4000	4000						
TODA	4000	4000						
ASDA	4000	4000						
LDA	4000	4000						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CEZ4

EFF 31 DEC 20


GILLAM, MB

AERODROME CHART — CYGX

CTR Winnipeg – **134.65**
RADIO Edmonton – **123.37**

TFC – **122.1** MF

DECL DISTS	05	23
TORA	5034	5034
TODA	6018	6018
ASDA	5034	5034
LDA	5034	5034



TAKE-OFF MINIMA
Rwys 05, 23: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGX


EFF 24 MAR 22

GIMLI/GIMLI INDUSTRIAL PARK AIRPORT, MB

AERODROME CHART — CYGM

AUTO– **122.97**		◕ UNICOM – **122.15**	CTR Winnipeg – **118.0**

DECL DISTS	15	33
TORA	6794	6794
TODA	7778	7778
ASDA	6794	6794
LDA	6794	6794



★ DEPARTURE PROCEDURE

Rwy 15 -½- Climb between hdg **190°** CW to **220°** to remain clear of CYA 420 (T) and CYA 404 (T) when active.
Note: Trees to 791 ASL within 0.1NM past the departure end of rwy both LEFT and RIGHT of rwy centerline.

Rwy 33 - ½ - Climb hdg **327°** to **1900** then climb between hdg **007°** CW to **147°** to remain clear of CYA 420(T) and CYA 404(T) when active.
Note: Trees to 805 ASL 0.4nm past departure end of rwy, 350° RIGHT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15; 33: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGM

EFF 2 DEC 21


GODS LAKE NARROWS, MB

AERODROME CHART — CYGO

UNICOM – **122.8** (AU)

ATF

DECL DISTS	14	32
TORA	3810	3810
TODA	3810	4210
ASDA	3810	3810
LDA	3810	3810



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050
420 FT/NM	630	840	980	1120	1260	1400	1750	2100

* DEPARTURE PROCEDURE

Rwy 14 - ½ - Requires a minimum climb gradient of **210** ft/NM to **900**.
Note: Trees to 667 ASL past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1200** BPOC.

Rwy 32 -½ - Requires a minimum climb gradient of **420** ft/NM to **900**.
Note: Trees to 659 ASL past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1200** BPOC.

TAKE-OFF MINIMA

Rwys 14, 32: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGO

EFF 21 MAY 20


GODS RIVER, MB

AERODROME CHART — CZGI

UNICOM – **122.8** (AU)

ATF

DECL DISTS	09	27
TORA	3532	3532
TODA	3532	4516
ASDA	3532	3532
LDA	3532	3532



TAKE-OFF MINIMA
Rwys 09, 27: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZGI


EFF 21 MAY 20

GRANDE PRAIRIE, AB

AERODROME CHART — CYQU

ATIS – **128.6**	CLNC DEL – **121.9**	RADIO – **118.1**	CTR Edmonton – **134.5** RADIO Edmonton – **123.47**
		MF	

DECL DISTS	07	25	12	30				
TORA	6200	6200	8502	8502				
TODA	7184	7184	9368	9402				
ASDA	6200	6200	8502	8502				
LDA	6200	6200	8102	8502				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 30: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 07; 12; 25: ½ Rwy 30: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQU

EFF 29 DEC 22

HARDISTY, AB

AERODROME CHART


CEA5

CTR Edmonton – **133.45**

TFC – **123.2**

ATF

DECL DISTS	08	26						
TORA	3006	3006						
TODA	3006	3006						
ASDA	3006	3006						
LDA	3006	3006						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


HATCHET LAKE, SK

AERODROME CHART — CJL2

UNICOM – **123.3** (AU)

ATF

DECL DISTS	07	25						
TORA	5823	5823						
TODA	5823	5823						
ASDA	5823	5823						
LDA	5823	5823						



★ DEPARTURE PROCEDURE

Rwy 07 - ½

Note: Trees to 1397 ASL abeam departure end of rwy, 110' LEFT and RIGHT of rwy centerline.

Rwy 25 - ½

Note: Trees to 1379 ASL abeam departure end of rwy, 130' LEFT and RIGHT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07; 25: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CJL2


EFF 24 MAR 22

HIGH LEVEL, AB

AERODROME CHART — CYOJ

AWOS – **128.22**		RADIO – **123.25** TFC – **123.25** **MF**	CTR Edmonton – **123.7 135.1** RADIO Edmonton – **123.37**

DECL DISTS	13	31
TORA	5002	5002
TODA	5896	5986
ASDA	5002	5002
LDA	5002	5002



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYOJ

EFF 27 JAN 22

HIGH PRAIRIE, AB


AERODROME CHART — CZHP

CTR Edmonton – **135.27**

TFC – **122.8**

ATF

DECL DISTS	07	25
TORA	4332	4332
TODA	4332	4332
ASDA	4332	4332
LDA	4332	4332



TAKE-OFF MINIMA
Rwys 07, 25: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZHP

EFF 5 NOV 20

HIGH RIVER, AB


AERODROME CHART — CEN4

CTR Edmonton – **132.75**

TFC – **123.0**

MF

DECL DISTS	07	25	15	33				
TORA	4160	4160	2726	2726				
TODA	4160	4160	2726	2726				
ASDA	4160	4160	2726	2726				
LDA	3473	3685	2726	2726				



* DEPARTURE PROCEDURE

Rwy 07 - ½ - Climb hdg **066°** to **4800** BPOC.
Note: When CYA263(S) active: Requires a minimum climb gradient of **350** ft/NM to **6800** hdg **066°** to **6800** BPOC.

Rwy 25 - ½ - Proc NOT auth when CYA263(S) is active. Requires a minimum climb gradient of **250** ft/NM to **11200**. Climb hdg **246°** to **4300** BPOC.
Note: Road and vehicles to 3442 ASL abeam departure end of rwy. Hangar to 3462 ASL abeam departure end of rwy, 500' LEFT of rwy centreline. Powerline to 3469 ASL abeam departure end of rwy, 510' LEFT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **5000**, continue climb hdg **066°** to **7000** BPOC.

TAKE-OFF MINIMA

Rwys 07; 25: *
Rwys 15; 33: NOT ASSESSED

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HINTON/JASPER-HINTON, AB

AERODROME CHART — CEC4

AUTO – **122.55**		◒ UNICOM – **123.35** (AU) ATF	RADIO Edmonton – **123.55**

DECL DISTS	02	20
TORA	4510	4510
TODA	4510	4510
ASDA	4510	4510
LDA	4305	4203



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02; 20:*	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CEC4

EFF 10 AUG 23


HUDSON BAY, SK

AERODROME CHART — CYHB

CTR Winnipeg – **135.62**

TFC – **122.8** ATF

DECL DISTS	06	24
TORA	5001	5001
TODA	5001	5001
ASDA	5001	5001
LDA	5001	5001



* DEPARTURE PROCEDURE

Rwy 24 - ½

Note: Trees to 1228 ASL 0.3 NM past departure end of rwy both LEFT and RIGHT of rwy centreline. Hill to 1271 ASL 0.4 NM past departure end of rwy.

TAKE-OFF MINIMA
Rwy 06: ½
Rwy 24: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HUMBOLDT, SK


AERODROME CHART — CJU4

CTR Winnipeg – **133.9**

TFC – **123.2**

ATF

DECL DISTS	10	28	17	35				
TORA	2506	2506	2552	2552				
TODA	2506	2506	2552	2552				
ASDA	2506	2506	2552	2552				
LDA	2506	2506	2552	2552				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	500 0 500

AERODROME CHART — CJU4

EFF 23 FEB 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ÎLE-À-LA-CROSSE, SK

AERODROME CHART — CJF3

TFC – **123.2** ATF

DECL DISTS	15	33
TORA	3908	3908
TODA	3908	3908
ASDA	3908	3908
LDA	3908	3908



TAKE-OFF MINIMA
Rwys 15; 33: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ILFORD, MB


AERODROME CHART — CZBD

UNICOM – **122.8**

ATF

CTR Winnipeg – **133.15**

DECL DISTS	09	27						
TORA	2989	2989						
TODA	2989	3973						
ASDA	2989	2989						
LDA	2989	2989						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09, 27: *	500 0 500


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ISLAND LAKE, MB

AERODROME CHART — CYIV

AWOS – **128.1**		RADIO Thunder Bay – **122.2** MF	RADIO Edmonton – **122.37**

DECL DISTS	12	30
TORA	4000	4000
TODA	4984	4984
ASDA	4000	4000
LDA	4000	4000



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12; 30: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

JENPEG, MB


AERODROME CHART — CZJG

UNICOM – **122.8**

CTR Winnipeg – **135.1**

ATF

DECL DISTS	15	33
TORA	3796	3796
TODA	3796	3796
ASDA	3796	3796
LDA	3796	3796



* DEPARTURE PROCEDURE

Rwy 15 - ½

Note: Vehicles on road to 737 ASL abeam departure end of rwy, 410' LEFT of rwy centerline. Trees to 817 ASL abeam LEFT and RIGHT side of departure end of rwy.

Rwy 33 - ½

Note: Trees to 817 ASL abeam departure end of rwy, 410' LEFT of rwy centerline.

TAKE-OFF MINIMA

Rwys 15, 33: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KELSEY, MB

AERODROME CHART — CZEE

AUTO – **122.55**		UNICOM – **122.8** ATF	CTR Winnipeg – **133.15**

DECL DISTS	12	30
TORA	3800	3800
TODA	3800	3800
ASDA	3955	3956
LDA	3800	3800




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KEY LAKE, SK

AERODROME CHART — CYKJ

AUTO – **127.7**		UNICOM – **122.7** ATF	RADIO Edmonton – **123.37** DRCO

DECL DISTS	03	21
TORA	5281	5281
TODA	5915	6116
ASDA	5281	5281
LDA	5281	5281



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03; 21: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KILLAM-SEDGEWICK/FLAGSTAFF REGIONAL, AB


AERODROME CHART — CEK6

DEP Edmonton – **133.45**

TFC – **123.2**

ATF

DECL DISTS	12	30						
TORA	2952	2952						
TODA	2952	2952						
ASDA	2952	2952						
LDA	2952	2952						



TAKE-OFF MINIMA

Rwys 12, 30: NOT ASSESSED

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KINDERSLEY REGIONAL, SK

AERODROME CHART — CYKY

			UNICOM – **122.8** ATF	RADIO Edmonton – **123.47**

DECL DISTS	08	26	17	35				
TORA	3507	3507	2281	2281				
TODA	3507	3507	2281	2281				
ASDA	3507	3507	2281	2281				
LDA	3507	3507	2281	2281				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17, 35: NOT ASSESSED Rwys 08, 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KIPLING, SK

AERODROME CHART — CKD5

TFC – **123.2** ATF

DECL DISTS	10	28						
TORA	3001	3001						
TODA	3001	3001						
ASDA	3001	3001						
LDA	3001	3001						



* DEPARTURE PROCEDURE

Rwy 10 - ½
Note: Railway to 2181 ASL, within 260' LEFT of extended rwy centreline.

Rwy 28 - ½ - Requires a minimum climb gradient of **340** ft/NM to **2500**.
Note: Antenna 2238 ASL 0.2 NM from departure end of runway 230' LEFT of extended rwy centreline.
Railway to 2181 ASL, 260' RIGHT of extended rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the arpt at or above **2700** BPOC. Max 210 KIAS.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA CRETE (JAKE FEHR MEMORIAL), AB


AERODROME CHART — CFN5

CTR Edmonton – **123.7 135.1**

TFC – **123.2**

ATF

DECL DISTS	07	25						
TORA	4403	4403						
TODA	4403	4403						
ASDA	4403	4403						
LDA	4403	4403						



TAKE-OFF MINIMA
Rwys 07; 25: *

SCALE IN FEET

1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA RONGE (BARBER FIELD), SK

AERODROME CHART — CYVC

		RADIO – **122.2**	CTR Winnipeg – **126.4** RADIO Edmonton – **123.55**
		MF	

DECL DISTS	18	36	11	29
TORA	5002	5002	2396	2396
TODA	5986	5986	2986	2986
ASDA	5002	5002	2396	2396
LDA	5002	5002	2396	2396



* DEPARTURE PROCEDURE

Rwy 11 - ½ - Requires a minimum climb gradient of **420** ft/NM to **1600**.
Note: Trees to 1374 ASL aprx 0.1 NM from departure end of rwy, LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1800** BPOC.

Rwy 18 - ½ - Requires a minimum climb gradient of **440** ft/NM to **1500**.
Note: Trees to 1376 ASL aprx 0.1 NM from departure end of rwy, 550' LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1800** BPOC.

Rwy 29 - ½ - Requires a minimum climb gradient of **260** ft/NM to **1500**.
Note: Trees to 1389 ASL aprx 0.1 NM from departure end of rwy, LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1800** BPOC.

Rwy 36 - ½ -
Note: Trees to 1369 ASL abeam departure end of rwy, both LEFT and RIGHT of centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300
420 FT/NM	630	840	980	1120	1260	1400	1750	2100
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200

TAKE-OFF MINIMA
Rwys 11, 18, 29, 36: ✱

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVC

EFF 12 AUG 21


LAC BROCHET, MB

AERODROME CHART — CZWH

UNICOM – **122.8** (AU)

ATF

DECL DISTS	03	21
TORA	3500	3500
TODA	4484	4484
ASDA	3500	3500
LDA	3500	3500



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZWH

EFF 12 AUG 21


LAC DU BONNET, MB

AERODROME CHART

CYAX

TFC – **122.8** ATF

DECL DISTS	18	36						
TORA	3609	3609						
TODA	3609	3609						
ASDA	3609	3609						
LDA	3609	3609						



* DEPARTURE PROCEDURE

Rwy 18 - ½ - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

Rwy 36 - ½ **-** NO turn below **1700**.
Note: Trees to 899 ASL abeam departure end of rwy, 460' RIGHT of rwy centreline. Trees to 924 ASL abeam departure end of rwy, 300' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18, 36: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CYAX


EFF 5 DEC 19

LAC LA BICHE, AB

AERODROME CHART — CYLB

AUTO – **122.12**		TFC – **123.2** ATF	RADIO Edmonton – **123.47**

DECL DISTS	11	29
TORA	5704	5704
TODA	5704	5704
ASDA	5704	5704
LDA	5704	5704



***** DEPARTURE PROCEDURE

Rwy 11 - ½

Note: Trees to 1874 ASL 0.1 NM past departure end of rwy, 470' RIGHT of rwy centreline

Rwy 29 - ½

Note: Trees to 1937 ASL 0.2 NM past departure end of rwy, 700' LEFT of rwy centreline.
Trees to 1940 ASL 0.3 NM past departure end of rwy, 310' RIGHT of rwy centreline.
Hill to 1986 ASL 0.4 NM past departure end of rwy, 1030' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LACOMBE, AB

AERODROME CHART — CEG3


ATIS Red Deer – **124.0**

UNICOM – **123.3**

CTR Edmonton – **132.85**

ATF

DECL DISTS	17	35
TORA	3004	3004
TODA	3004	3004
ASDA	3004	3004
LDA	3004	3004



* DEPARTURE PROCEDURE

Rwy 17 - ½ **-** NO LEFT turn below **3600**.
Note: Hangar line to 2805 ASL abeam departure end of rwy, 250' RIGHT of rwy centreline. Trees to 2837 ASL 0.2 NM past departure end of rwy, 500' RIGHT of rwy centreline. Road lights to 2822 ASL 0.1 NM past departure end of rwy, 400' LEFT of rwy centreline.

Rwy 35 - ½
Note: Trees to 2794 ASL 0.1 NM past departure end of rwy.

TAKE-OFF MINIMA

Rwys 17; 35: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LETHBRIDGE, AB

AERODROME CHART — CYQL

ATIS – **124.4** AWOS – **124.4**		RADIO – **121.0** TFC – **121.0** **MF**	CTR Edmonton – **132.75 265.2** RADIO Edmonton – **123.47**

DECL DISTS	06	24	13	31
TORA	6500	6500	5500	5500
TODA	7484	7484	6484	6484
ASDA	6500	6500	5500	5500
LDA	6500	6500	5500	5500



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LITTLE GRAND RAPIDS, MB

AERODROME CHART — CZGR

UNICOM – **122.8** (AU)

ATF

DECL DISTS	18	36						
TORA	2798	2798						
TODA	2798	2823						
ASDA	2798	2798						
LDA	2798	2798						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18,36: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LLOYDMINSTER, AB

AERODROME CHART — CYLL

AWOS – **128.55**		RADIO Lloyd – **122.2** TFC – **122.2** MF	CTR Edmonton – **133.45 340.7** RADIO Edmonton – **123.55**

DECL DISTS	08	26	13	31				
TORA	5577	5577	1202	1202				
TODA	5577	5577	1202	1202				
ASDA	5577	5577	1202	1202				
LDA	5577	5577	1202	1202				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: * Rwys 13; 31: NOT ASSESSED	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYLL

EFF 10 AUG 23

LUSELAND, SK


AERODROME CHART — CJR2

TFC – **123.2**

ATF

RADIO Edmonton – **126.7**

DECL DISTS	11	29
TORA	3010	3010
TODA	3010	3010
ASDA	3010	3010
LDA	3010	3010



TAKE-OFF MINIMA

Rwy 11: ½
Rwy 29: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LYNN LAKE, MB

AERODROME CHART — CYYL

AWOS – **128.0**	◕ UNICOM – **122.3** ◕ TFC – **122.3** **MF**	CTR Winnipeg – **135.05** RADIO Edmonton – **123.47**

DECL DISTS	08	26	17	35				
TORA	2521	2521	5004	5004				
TODA	2521	2521	5988	5988				
ASDA	2521	2521	5004	5004				
LDA	2521	2521	5004	5004				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys: 17, 35:*	1000 0 1000
Rwys: 08, 26: Not Assessed	

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYL


EFF 24 MAR 22

MAIDSTONE, SK

AERODROME CHART — CJH3

AUTO Lloydminster – **128.55**		TFC – **123.2** ATF	RADIO Edmonton – **123.37**

DECL DISTS	12	30
TORA	3610	3610
TODA	3610	3807
ASDA	3610	3610
LDA	3610	3610



✱DEPARTURE PROCEDURE

Rwy 12 - ½ - Requires a minimum climb gradient of **230** ft/NM to **2300**.
Climb hdg **121°** to **2400** BPOC.
Note: Buildings to 1988 ASL abeam departure end of rwy, 160' LEFT of rwy centerline. Roadway and vehicles to 1990 ASL abeam departure end of rwy, 160' RIGHT of rwy centerline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **3000** BPOC.

Rwy 30 - ½
Note: Powerline to 2020 ASL abeam departure end of rwy, 290' LEFT of rwy centerline. Major roadway, vehicles, and light posts to 2040 ASL 1 NM past departure end of rwy, LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12; 30: ✱	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MANNING, AB

AERODROME CHART — CFX4

AUTO – **122.55**		TFC – **123.2** ATF	CTR Edmonton – **135.27**

DECL DISTS	07	25
TORA	5580	5580
TODA	6422	6364
ASDA	5580	5580
LDA	5580	5580



TAKE-OFF MINIMA
Rwy 07: ½ Rwy 25: *

SCALE IN FEET

1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MAPLE CREEK, SK

AERODROME CHART — CJQ4

		UNICOM – **122.8**	RADIO Edmonton – **123.37**
		ATF	

DECL DISTS	06	24	17	35				
TORA	3078	3078	1936	1936				
TODA	3078	3078	1936	1936				
ASDA	3078	3078	1936	1936				
LDA	3078	3078	1936	1936				



*****DEPARTURE PROCEDURE

Rwy 06 - ½ **-** Climb between hdg **098°** CCW to **241°** to **5900** BPOC.
Note: Trees to 2547 ASL abeam departure end of rwy, 450' LEFT and RIGHT of rwy centreline.

Rwy 24 - ½ **-** Climb between hdg **149°** CW to **061°** to **5800** BPOC.
Note: Trees to 2549 ASL abeam departure end of rwy, 430' LEFT of rwy centreline. Trees to 2544 ASL aprx 0.1 NM past departure end of rwy, 40' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys: 06, 24: *****	1000 0 1000
Rwys: 17, 35: NOT ASSESSED	

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MCARTHUR RIVER, SK


AERODROME CHART — CKQ8

AUTO – **122.27**

UNICOM – **123.3** (AU)

ATF

DECL DISTS	18	36
TORA	5278	5278
TODA	5653	5558
ASDA	5278	5278
LDA	5278	5278



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CKQ8

EFF 23 FEB 23

MEADOW LAKE, SK


AERODROME CHART — CYLJ

TFC – **122.8**

TML Cold Lake – **124.5**

ATF

DECL DISTS	09	27	17	35				
TORA	5000	5000	2297	2297				
TODA	5984	5984	2297	2297				
ASDA	5000	5000	2297	2297				
LDA	5000	5000	2297	2297				



* DEPARTURE PROCEDURE

Rwy 09 - ½
Note: Trees to 1698 ASL aprx 0.3 NM past departure end of rwy, both LEFT and RIGHT of rwy centreline.

Rwy 17 - ½
Note: Trees to 1698 ASL aprx 0.2 NM past departure end of rwy, both LEFT and RIGHT of rwy centreline.

Rwy 27 - ½ - Requires a minimum climb gradient of **210** ft/NM to **1800**.
Note: Trees to 1714 ASL aprx 0.7 NM past departure end of rwy, 720' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2100** BPOC.

Rwy 35 - ½
Note: Trees to 1701 ASL aprx 0.5 NM past departure end of rwy.

TAKE-OFF MINIMA

Rwys 09, 17, 27, 35: *****

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MEDICINE HAT, AB

AERODROME CHART — CYXH

ATIS – **124.87** AWOS – **124.87**		RADIO – **122.2** TFC – **122.2** MF	RADIO – **122.2** RADIO Edmonton – **123.37**

DECL DISTS	03	21	09	27				
TORA	5003	5003	2850	2850				
TODA	5987	5987	3834	3834				
ASDA	5003	5003	2850	2850				
LDA	5003	5003	2850	2850				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MELFORT (MILLER FIELD), SK


AERODROME CHART — CJZ3

UNICOM – **122.8**

CTR Winnipeg – **133.9**

ATF

DECL DISTS	08	26						
TORA	3028	3028						
TODA	3028	3028						
ASDA	3028	3028						
LDA	3028	3028						



TAKE-OFF MINIMA

Rwy 08: *
Rwy 26: ½

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MOOSE JAW/AIR VICE MARSHAL C.M. MCEWEN, SK

AERODROME CHART (DND) CYMJ

ATIS – **131.3 257.8**	CLNC DEL – **135.3 234.4** GND – **121.8 275.8**	TWR – **126.2 295.6**	DEP – **119.0 227.6**

DECL DISTS	11L	29R	11R	29L	03	21				
TORA	8320	8320	7280	7280	3460	3460				
TODA	8320	8320	7280	7280	3460	3460				
ASDA	8520	8520	7480	7480	3720	3680				
LDA	8320	8320	7280	7280	3460	3460				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11L, 11R, 29L, 29R: ½	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART (DND) CYMJ

EFF 8 SEP 22

MOOSE JAW MUNICIPALITY, SK

AERODROME CHART — CJS4


ATIS Moose Jaw – **131.3**

UNICOM – **122.8**

DEP Moose Jaw – **135.3**

ATF*

DECL DISTS	13	31
TORA	4000	4000
TODA	4000	4000
ASDA	4000	4000
LDA	4000	4000




TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31:*	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MORDEN REGIONAL, MB

AERODROME CHART — CJA3

ATIS Winnipeg – **120.2**		TFC – **123.0** ATF		CTR Winnipeg – **121.0**				
DECL DISTS	**10**	**28**	**18**	**36**				
TORA	3937	3937	2089	2089				
TODA	3937	3937	2089	2089				
ASDA	3937	3937	2089	2089				
LDA	3937	3937	2089	2089				



* DEPARTURE PROCEDURE

Rwy 10 - ½ - Climb hdg **102°** to **1500**, then climb between hdg **074°** CW to **282°** to avoid CYR 412.
Note: Trees to 1005 ASL abeam departure end of rwy, 450' LEFT of rwy centreline and aprx 0.3 NM past departure end of rwy, 30' RIGHT of rwy centreline. Hangar to 995 ASL abeam departure end of rwy, 300' LEFT of rwy centreline. Road to 980 ASL abeam departure end of rwy, 300' LEFT of rwy centreline.

Rwy 28 - ½ - Climb between hdg **019°** CCW to **102°** to avoid CYR 412.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *****	1000 0 1000
Rwys 18; 36: NOT ASSESSED	

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CJA3

EFF 15 JUN 23

NEEPAWA, MB

AERODROME CHART


CJV5

UNICOM – **122.8**

ATF

CTR Winnipeg – **132.25**

DECL DISTS	04	22						
TORA	3507	3507						
TODA	3507	3507						
ASDA	3507	3507						
LDA	3507	3507						



TAKE-OFF MINIMA

All Ryws: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CJV5

EFF 30 JAN 20

NIPAWIN, SK

AERODROME CHART — CYBU


AWOS – **128.75**

UNICOM – **122.8**

ATF

CTR Winnipeg – **133.9**

DECL DISTS	03	21	12	30						
TORA	2933	2933	2900	2900						
TODA	2933	2933	2900	2900						
ASDA	2933	2933	2900	2900						
LDA	2933	2933	2900	2900						



✱DEPARTURE PROCEDURE

Rwy 03 - ½
Note: Vehicles to 1233 ASL at departure end of rwy, 480' LEFT and RIGHT of rwy centreline. Powerline to 1334 ASL aprx 0.7 NM past departure end of rwy, 1600' LEFT of rwy centreline.

Rwy 21 - ½
Note: Buildings and towers to 1368 ASL aprx 0.3 NM past departure end of rwy, 640' to 1270' RIGHT of rwy centreline.

TAKE-OFF MINIMA

Rwys 03; 21: ✱
Rwys 12, 30: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBU


EFF 23 FEB 23

NORTH BATTLEFORD, SK

AERODROME CHART — CYQW

AWOS – **128.12**		TFC – **122.1** MF	RADIO Edmonton – **123.37**

DECL DISTS	06	24	12	30				
TORA	2572	2572	5000	5000				
TODA	2572	2572	5984	5984				
ASDA	2572	2572	5000	5000				
LDA	2572	2572	5000	5000				



✱ DEPARTURE PROCEDURE

Rwy 12 - ½

Note: Trees to 1841 ASL 0.2 NM past departure end of rwy, 70' RIGHT of rwy centreline.
Trees to 1874 ASL 0.3 NM past departure end of rwy, 160' LEFT of rwy centreline.
Powerline to 1932 ASL 0.3 NM past departure end of rwy, 1220' LEFT of rwy centreline.

Rwy 30 - ½

Note: Trees to 1841 ASL 0.2 NM past departure end of rwy, along rwy centerline.

TAKE-OFF MINIMA

Rwys 12, 30: ✱
Rwys 06, 24: NOT ASSESSED

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQW


EFF 3 NOV 22

NORWAY HOUSE, MB

AERODROME CHART — CYNE

AWOS – **127.7**		RADIO Kenora – **122.1** TFC – **122.1** **MF**	DEP Winnipeg – **135.1** RADIO Edmonton – **123.37**

DECL DISTS	06	24
TORA	3902	3902
TODA	4886	4886
ASDA	3902	3902
LDA	3902	3902



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYNE

EFF 8 SEP 22

OLDS-DIDSBURY, AB


AERODROME CHART — CEA3

CTR Edmonton – **132.85**

TFC – **123.2**

ATF

DECL DISTS	04	22	10	28				
TORA	1933	1933	4000	4000				
TODA	1933	1933	4000	4000				
ASDA	1933	1933	4000	4000				
LDA	1933	1933	4000	4000				



* DEPARTURE PROCEDURE

Rwy 10 - ½ - Climb between hdg **177°** CCW to **283°** to remain clear of CYA226 and CYA227 when active.
Note: Terrain to 3360 ASL abeam departure end of rwy, 250' RIGHT of rwy centerline. Powerlines to 3362 ASL abeam departure end of rwy, 290' RIGHT of rwy centerline.

Rwy 28 - ½ - Climb between hdg **248°** CW to **103°** to remain clear of CYA226 and CYA227 when active.
Note: Trees and terrain to 3380 ASL 0.1 NM past departure end of rwy, 660' LEFT of rwy centerline. Trees and terrain to 3406 ASL 0.2 NM past departure end of rwy, 290' LEFT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: NOT ASSESSED Rwys 10, 28: *	1000 0 1000

AERODROME CHART — CEA3

EFF 23 FEB 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OXFORD HOUSE, MB

AERODROME CHART — CYOH

AUTO – **122.12**		◒ UNICOM – **122.8** (AU) ATF	

DECL DISTS	05	23
TORA	3828	3828
TODA	4389	4202
ASDA	3828	3828
LDA	3828	3828



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 23: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYOH


EFF 12 AUG 21

PEACE RIVER, AB

AERODROME CHART — CYPE

		RADIO – **122.0** MF	CTR Edmonton – **135.27** RADIO Edmonton – **123.27**

DECL DISTS	04	22
TORA	5000	5000
TODA	5984	5984
ASDA	5000	5000
LDA	5000	5000



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPE

EFF 12 OCT 17


PIKWITONEI, MB

AERODROME CHART — CZMN

UNICOM – **122.8** (AU)

ATF

DECL DISTS	05	23						
TORA	2192	2192						
TODA	2963	3176						
ASDA	2192	2192						
LDA	2192	2192						



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZMN


EFF 10 SEP 20

PINCHER CREEK, AB

AERODROME CHART — CZPC

AWOS – **127.65**		TFC – **123.2** ATF	CTR Edmonton – **132.75 265.2**

DECL DISTS	08	26
TORA	6597	6597
TODA	6597	6597
ASDA	6597	6597
LDA	6000	6448



* DEPARTURE PROCEDURE

Rwy 08 - ½ - Requires a minimum climb gradient of **320** ft/NM on hdg **076°** to **6800** BPOC.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **5000**. Then climb outbound on track **049°** from "9Y" NDB to **8000** BPOC.

Rwy 26 - ½ - Requires a minimum climb gradient of **430** ft/NM on hdg **256°** to **8200** BPOC.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **5000**. Then climb outbound on track **049°** from "9Y" NDB to **8000** BPOC.

NOTE: Ctc Edmonton Radio for clnc prior to entering controlled airspace.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
320 FT/NM	480	640	750	860	960	1070	1340	1600
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: *****	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

POINTS NORTH LANDING, SK

AERODROME CHART — CYNL

AWOS – **122.55**		68 Points North UNICOM – **123.3** (AU) ATF	

DECL DISTS	16	34
TORA	5848	5848
TODA	6832	6832
ASDA	6048	6048
LDA	5848	5848



✱DEPARTURE PROCEDURE

Rwy 16 - ½

Note: Trees and terrain to 1625 ASL aprx 0.1 NM past departure end of rwy, 310' LEFT of rwy centreline, trees to 1688 ASL aprx 0.6 NM past departure end of rwy, 340' RIGHT of rwy centreline.

Rwy 34 - ½

Note: Traffic and trees to 1688 ASL aprx 0.2 NM past departure end of rwy, 210' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 16; 34: ✱	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYNL

EFF 23 FEB 23

PONOKA (LABRIE FIELD), AB


AERODROME CHART — CEH3

UNICOM – **123.3**

CTR Edmonton – **132.85**

ATF

DECL DISTS	16	34
TORA	3089	3089
TODA	3089	3089
ASDA	3089	3089
LDA	3089	3089



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16, 34: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


POPLAR RIVER, MB

AERODROME CHART — CZNG

CTR Winnipeg – **135.1**

UNICOM – **122.8**
TFC – **122.8**
ATF

DECL DISTS	10	28						
TORA	2500	2500						
TODA	3484	2500						
ASDA	2500	2500						
LDA	2500	2500						



* DEPARTURE PROCEDURE

Rwy 10 - ½
Note: Trees to 851 ASL abeam departure end of rwy, both LEFT and RIGHT of rwy centreline.

Rwy 28 - ½
Note: Road to 740 ASL past departure end of rwy.
Trees to 855 ASL aprx 0.3 NM past departure end of rwy, 250' LEFT of rwy centreline and aprx 0.2 NM past departure end of rwy, 650' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	500 0 500


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PORTAGE LA PRAIRIE/SOUTHPORT, MB

AERODROME CHART — CYPG

ATIS – **120.85**	GND – **121.7**	TWR – **126.2** TFC – **126.2** ATF+	TML Winnipeg – **121.0**

DECL DISTS	13R	31L	13L	31R	02	20	09	27
TORA	7000	7000	3120	3120	3033	3033	2670	2670
TODA	7984	7984	4120	4120	4033	4033	3654	3654
ASDA	7000	7000	3120	3120	3033	3033	2670	2670
LDA	7000	7000	3120	3120	3033	3033	2670	2670



*DEPARTURE PROCEDURE

Rwy 02 - ½
Note: Trees to 903 ASL 0.3 NM past departure end of rwy, 620' RIGHT of rwy centreline.

Rwy 09 - ½
Note: Trees to 903 ASL aprx 0.2 NM past departure end of rwy, 460' RIGHT of rwy centreline.

Rwy 13R - ½
Note: Trees to 956 ASL aprx 0.4 NM past departure end of rwy, 430' RIGHT of rwy centreline.

Rwy 20 - ½
Note: Trees to 972 ASL 0.6 NM past departure end of rwy, 550' LEFT of rwy centreline. Trees to 988 ASL 0.8 NM past departure end of rwy, 1040' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 13L; 27; 31L; 31R: ½ Rwys 02; 09; 13R; 20: *

SCALE IN FEET
1000 0 1000 2000 3000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPG


EFF 23 FEB 23

PRINCE ALBERT (GLASS FIELD), SK

AERODROME CHART — CYPA

			RADIO – **122.3**			MF	CTR Winnipeg – **133.9** RADIO Edmonton – **123.47**	

DECL DISTS	08	26						
TORA	5001	5001						
TODA	5968	5985						
ASDA	5001	5001						
LDA	5001	5001						



***** DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Trees to 1551 ASL aprx 0.4 NM past departure end of rwy, 1150' RIGHT of rwy centreline.

Rwy 26 - ½

Note: Trees to 1486 ASL aprx 0.4 NM past departure end of rwy, 1150' LEFT of rwy centreline.
Trees to 1529 ASL aprx 0.6 NM past departure end of rwy, 1450' RIGHT of rwy centreline.

RVO	LVO
RWY 08: RVR 1200 RWY 26: (¼ sm)	

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: *****	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PROVOST, AB


AERODROME CHART — CEH6

UNICOM – **122.8**

CTR Edmonton – **133.45**

ATF

DECL DISTS	12	30
TORA	5202	5202
TODA	5202	5202
ASDA	5202	5202
LDA	4328	4818



TAKE-OFF MINIMA
Rwys 12; 30: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PUKATAWAGAN, MB


AERODROME CHART — CZFG

UNICOM – **122.8** (AU)

CTR Winnipeg – **135.05**

ATF

DECL DISTS	15	33
TORA	2998	2998
TODA	3982	3982
ASDA	2998	2998
LDA	2998	2998



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZFG

EFF 30 JAN 20


RAINBOW LAKE, AB

AERODROME CHART — CYOP

UNICOM – **122.8** (AU)

ATF

DECL DISTS	09	27
TORA	5002	5002
TODA	5002	5002
ASDA	5002	5002
LDA	5002	5002



TAKE-OFF MINIMA
Rwys 09; 27: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYOP


EFF 5 NOV 20

RED DEER REGIONAL, AB

AERODROME CHART — CYQF

ATIS – **124.0** AWOS – **124.0**	GND – **121.9**	TWR – **118.5** TFC – **118.5** **MF**	CTR Edmonton – **132.85** RADIO Edmonton – **123.47**

DECL DISTS	12	30	17	35				
TORA	3454	3254	7500	7500				
TODA	3454	3254	8484	8484				
ASDA	3454	3454	7500	7500				
LDA	3254	3454	7500	7500				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RED EARTH CREEK, AB


AERODROME CHART — CEH5

CTR Edmonton – **135.27**

TFC – **123.2**

ATF

DECL DISTS	13	31
TORA	3542	3542
TODA	3542	3542
ASDA	3542	3542
LDA	3542	3542



* DEPARTURE PROCEDURE

Rwy 13 - ½

Note: Trees to 1839 ASL abeam departure end of rwy, 420' LEFT and RIGHT of rwy centreline. Antenna tower to 1842 ASL aprx 0.2 NM past departure end of rwy, 590' RIGHT of rwy centreline. Trees to 1884 ASL aprx 0.3 NM past departure end of rwy, 860' LEFT of rwy centreline.

Rwy 31 - ½

Note: Trees to 1816 ASL abeam departure end of rwy, 320' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 13; 31: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RED SUCKER LAKE, MB


AERODROME CHART — CYRS

AUTO – **122.07**

UNICOM – **122.8** (AU)

ATF

DECL DISTS	09	27						
TORA	3555	3555						
TODA	5331	5331						
ASDA	3555	3555						
LDA	3555	3555						



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150

* DEPARTURE PROCEDURE

Rwy 09 - ½ - Requires a minimum climb gradient of **230** ft/NM to **1000**.
Note: Trees to 891 ASL abeam departure end of rwy, aprx 450' LEFT and 250' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1500** BPOC.

Rwy 27 - ½ - No LEFT turn below **1200**.
Note: Trees to 884 ASL abeam departure end of rwy, 400' RIGHT of rwy centreline and aprox 0.8 NM past departure end of rwy.

TAKE-OFF MINIMA

Rwys 09, 27: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

REGINA INTL, SK

AERODROME CHART — CYQR

ATIS – **127.0**	GND – **121.9**	TWR – **118.6** RADIO – **118.6** MF	CTR Winnipeg – **120.1** RADIO Edmonton – **123.55**

DECL DISTS	08	26	13	31				
TORA	6200	6200	7901	7901				
TODA	7184	7184	8885	8885				
ASDA	6200	6200	7901	7901				
LDA	6200	6200	7901	7901				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 13: RVR 1200 RWY 31: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26, 31: ½ Rwy 13: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


AERODROME CHART — CYQR

EFF 23 FEB 23

REGINA INTL, SK

PARKING AREAS

CYQR



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYQR

EFF 24 MAR 22

ROCKY MOUNTAIN HOUSE, AB

AERODROME CHART — CYRM


AUTO – **131.97**

TFC – **122.8**

MF

CTR Edmonton – **134.3**

DECL DISTS	13	31
TORA	5513	5513
TODA	6303	6213
ASDA	5513	5513
LDA	5513	5513



TAKE-OFF MINIMA
Rwys 13; 31: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRM

EFF 23 FEB 23

ROSETOWN, SK


AERODROME CHART

CJX4

CTR Winnipeg – **134.32**

TFC – **122.8**

DECL DISTS	08	26						
TORA	2529	2529						
TODA	2529	2529						
ASDA	2529	2529						
LDA	2529	2529						



***** DEPARTURE PROCEDURE

Rwy 26 - ½

Note: Hangers to 1965 ASL 0.1 NM past departure end of rwy, 300' RIGHT of rwy centreline.

TAKE-OFF MINIMA

Rwy 08: ½

Rwy 26: *****

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RUSSELL, MB


AERODROME CHART — CJW5

UNICOM – **122.8**

CTR Winnipeg – **132.52**

ATF

DECL DISTS	14	32	17	35				
TORA	1900	1900	4003	4003				
TODA	1900	1900	4003	4003				
ASDA	1900	1900	4003	4003				
LDA	1900	1900	4003	4003				



★ DEPARTURE PROCEDURE

Rwy 17 - ½

Note: Trees to 1867 ASL aprx 0.1NM past departure end of rwy, 450' RIGHT and 140' LEFT of rwy centreline. Berm to 1829' abeam departure end of rwy, 180' RIGHT of rwy centreline.

Rwy 35 - ½

Note: Silos to 1862 ASL abeam departure end of rwy, 550' RIGHT of rwy centreline. Power poles to 1850 ASL aprx 0.1NM past departure end of rwy, 370' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE
Rwys 14, 32: NOT ASSESSED Rwys 17, 35: ★	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SASKATOON/JOHN G. DIEFENBAKER INTL, SK

AERODROME CHART — CYXE

ATIS – **128.4**	◕ GND – **121.9**	◕ TWR – **118.3** ◕ RADIO – **118.3** ◕MF*	TML – **119.9** RADIO Edmonton – **122.37**

DECL DISTS	09	27	15	33				
TORA	8300	8300	6200	6200				
TODA	9284	9284	7184	7184				
ASDA	8300	8300	6200	6200				
LDA	8300	8300	6200	6200				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 09: RVR 1200 RWY 15, 27, 33: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

If any portion of the airport drops below ½ SM or 2600 RVR but is at or above ¼ SM or 1200 RVR, the airport is considered to be operating in RVOP with no restrictions to aircraft or vehicles.

If any portion of the airport drops below ¼ SM or 1200 RVR, provided the runway of intended use is at or above ¼ SM or 1200 RVR, the following procedures shall be implemented:

- Any runway that is below ¼ SM or 1200 RVR will not be used for arrivals or departures.
- Restrictions apply to vehicles and aircraft on the manoeuvring area. Only one aircraft, helicopter or vehicle will be given permission to operate on the manoeuvring area at any given time (except as permitted below under Vehicle Exceptions).
- Towing of aircraft on the manoeuvring area is not permitted.

Departures

An aircraft may be taxied for departure if the runway of intended use is at or above ¼ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility drops below ¼ SM or 1200 RVR after taxi clearance was issued, the aircraft may continue to taxi.

An aircraft may depart during RVOP operations provided the RVR serving the departure runway is at or above ¼ SM or 1200 RVR.

Arrivals

An aircraft may land and taxi if the runway of intended use is at or above ¼ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

Arrivals will be in accordance with applicable approach minima or approach ban considerations. After landing, the aircraft may taxi provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility for the runway of intended use drops below ¼ SM or 1200 RVR after an arriving aircraft crosses the final approach fix (FAF), the aircraft may land and taxi in.

Vehicle Exceptions

A group of vehicles may be considered one movement provided they are traveling together and use a single call sign.

Vehicles are permitted to operate on an inactive runway. Once vehicles are established and restricted to remain on the inactive runway, RVOP may resume on the remaining manoeuvring area.

Emergency vehicles responding to emergency situations are exempt.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


SHAMATTAWA, MB

AERODROME CHART — CZTM

UNICOM – **122.8** (AU)

ATF

DECL DISTS	01	19
TORA	4006	4006
TODA	4021	4990
ASDA	4006	4006
LDA	4006	4006



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA

Rwys 01; 19: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SHAUNAVON, SK

AERODROME CHART — CJC5

LWIS – **122.55**		UNICOM – **122.8** ATF	CTR Winnipeg – **132.8**

DECL DISTS	12	30	02	20				
TORA	2969	2969	1844	1844				
TODA	2969	2969	1844	1844				
ASDA	2969	2969	1844	1844				
LDA	2969	2969	1844	1844				



* DEPARTURE PROCEDURE

Rwy 12 - ½

Note: Road to 3042 ASL abeam departure end of rwy, 500' RIGHT of rwy centreline.

Rwy 30 - ½

Note: Silos to 3079 ASL aprx 0.3 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12; 30: * Rwys 02; 20: NOT ASSESSED	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SLAVE LAKE, AB

AERODROME CHART — CYZH

AWOS – **127.0**		TFC – **123.2** MF	CTR Edmonton – **124.85 304.2** RADIO Edmonton – **123.37**

DECL DISTS	10	28
TORA	5569	5569
TODA	6068	5897
ASDA	5569	5569
LDA	5569	5012



* DEPARTURE PROCEDURE

Rwy 10 - ½ **-** Climb hdg **100°** to **2700** BPOC.

Note: Trees to 2029 ASL aprx 0.2 NM from departure end of rwy, LEFT and RIGHT of rwy centreline.

Rwy 28 - ½ **-** Climb hdg **280°** to **3000** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SOUTH INDIAN LAKE, MB


AERODROME CHART — CZSN

UNICOM – **122.8** (AU)

CTR Winnipeg – **133.15**

ATF

DECL DISTS	18	36
TORA	3509	3509
TODA	4493	4493
ASDA	3509	3509
LDA	3509	3509



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
300 FT/NM	450	600	700	800	900	1000	1250	1500

* DEPARTURE PROCEDURE

Rwy 18 -½- Requires a minimum climb gradient of **230** ft/NM to **1300**.
Note: Trees to 1052 ASL aprx 0.8NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.

Rwy 36 -½- Requires a minimum climb gradient of **300** ft/NM to **1200**. NO LEFT turn below **1800**.
Note: Trees to 1101 ASL aprx 0.8NM past departure end of rwy
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.

TAKE-OFF MINIMA

Rwys 18; 36: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. PAUL, AB


AERODROME CHART — CEW3

UNICOM – **122.8**

TML Cold Lake – **124.5**

ATF

DECL DISTS	08	26
TORA	3498	3498
TODA	3498	3498
ASDA	3498	3498
LDA	3498	3498



* DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Power line to 2181 ASL abeam departure end of rwy, 550' RIGHT of rwy centreline. Hangars to 2171 ASL abeam departure end of rwy, 550' LEFT of rwy centreline. Trees to 2181 ASL 0.1 NM past departure end of rwy, 650' RIGHT of rwy centreline.

Rwy 26 - ½

Note: Trees to 2163 ASL abeam departure end of rwy, 170' RIGHT of rwy centreline. Buildings to 2188 ASL 0.2 NM past departure end of rwy, 600' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. THERESA POINT, MB

AERODROME CHART — CYST

AWOS Island Lake – **128.1**		RADIO Thunder Bay – **122.2** MF	

DECL DISTS	04	22
TORA	3391	3391
TODA	4375	4375
ASDA	3391	3391
LDA	3391	3391



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYST

EFF 10 AUG 23

STEINBACH (SOUTH), MB


AERODROME CHART — CKK7

UNICOM – **122.7**

TML Winnipeg – **119.9**

ATF

DECL DISTS	07	25	18	36				
TORA	1834	1834	3112	3112				
TODA	1834	1834	3112	3112				
ASDA	1834	1834	3112	3112				
LDA	1834	1834	3112	3112				



TAKE-OFF MINIMA
Rwys 18, 36: *
Rwys 07, 25: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

STETTLER, AB


AERODROME CHART — CEJ3

UNICOM – **123.0**

CTR Edmonton – **132.85**

ATF

DECL DISTS	07	25						
TORA	3000	3000						
TODA	3000	3000						
ASDA	3000	3000						
LDA	3000	3000						



* DEPARTURE PROCEDURE

Rwy 07 - ½

Note: Hangar to 2754 ASL aprx 30' past departure end of rwy, 400' RIGHT of rwy centreline.
Trees to 2744 ASL aprx 120' past departure end of rwy, 530' RIGHT of rwy centreline.

Rwy 25 - ½

Note: Trees to 2744 ASL aprx 170' past departure end of rwy, 200' RIGHT of rwy centreline.

TAKE-OFF MINIMA
Rwys 07; 25: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CEJ3


EFF 5 OCT 23

STONY RAPIDS, SK

AERODROME CHART — CYSF

AWOS – **128.75**		◕ RADIO Regina – **122.1** ◕ TFC – **122.1** MF	RADIO Edmonton – **122.37**

DECL DISTS	06	24
TORA	5052	5052
TODA	6036	5552
ASDA	5052	5052
LDA	5052	5052



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SUNDRE, AB


AERODROME CHART — CFN7

CTR Edmonton – **134.3**

TFC – **123.2**

ATF

DECL DISTS	06	24	15	33				
TORA	2439	2439	4346	4346				
TODA	2439	2439	4346	4346				
ASDA	2439	2439	4346	4346				
LDA	2439	2439	4346	4346				



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 15; 33: *	1000 0 1000
Rwy 06; 24: NOT ASSESSED	

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SWAN RIVER, MB


AERODROME CHART — CZJN

CTR Winnipeg – **135.62**

TFC – **122.8**

ATF

DECL DISTS	02	20	08	26				
TORA	3935	3935	1957	1957				
TODA	3935	3935	1957	1957				
ASDA	3935	3935	1957	1957				
LDA	3935	3935	1957	1957				



TAKE-OFF MINIMA
All Rwys: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZJN


EFF 20 APR 23

SWIFT CURRENT, SK

AERODROME CHART — CYYN

AWOS – **124.7**	TFC – **122.3** MF	CTR Winnipeg – **132.8** RADIO Edmonton – **123.27 351.3**

DECL DISTS	04	22	13	31				
TORA	2495	2495	4250	4250				
TODA	2495	2495	4250	4250				
ASDA	2495	2495	4250	4250				
LDA	2495	2495	4250	4250				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13, 31: ½ Rwys 04, 22: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYN


EFF 12 AUG 21

TABER, AB

AERODROME CHART — CED5

		UNICOM – **122.8** ATF	CTR Edmonton – **132.75** **265.2**

DECL DISTS	05	23	13	31				
TORA	3005	3005	1930	1930				
TODA	3005	3005	1930	1930				
ASDA	3005	3005	1930	1930				
LDA	3005	3005	1930	1930				



TAKE-OFF MINIMA	SCALE IN FEET
ALL Rwys: ½	500 0 500 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CED5


EFF 21 JUL 16

TADOULE LAKE, MB

AERODROME CHART — CYBQ

AWOS – **128.62**		UNICOM – **122.8** (AU) ATF	RADIO Edmonton – **126.7** DRCO

DECL DISTS	07	25
TORA	3201	3201
TODA	4185	3201
ASDA	3201	3201
LDA	3201	3201



***** DEPARTURE PROCEDURE

Rwy 07 - ½

Note: Trees to 893 ASL abeam departure end of rwy, 200˚ RIGHT of rwy centreline.

Rwy 25 - ½

Note: Trees to 960 ASL abeam departure end of rwy, 400˚ RIGHT and 300˚ LEFT of rwy centreline and aprx 0.2 NM past departure end of rwy

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07, 25: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBQ


EFF 24 MAR 22

THE PAS, MB

AERODROME CHART — CYQD

MET – **124.7**		RADIO Saskatoon – **122.2** TFC – **122.2** MF	RADIO Edmonton – **123.55**

DECL DISTS	13	31
TORA	5901	5901
TODA	6885	6669
ASDA	5901	5901
LDA	5901	5901



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQD

EFF 15 JUN 23

THE PAS/GRACE LAKE, MB

AERODROME CHART


CJR3

TFC – **122.2**

ATF

RADIO Edmonton – **123.55**

DECL DISTS	08	26	17	35				
TORA	3265	3265	2853	2853				
TODA	3465	3465	3053	3053				
ASDA	3265	3265	2853	2853				
LDA	3265	3265	2853	2853				



TAKE-OFF MINIMA

Rwys 26; 17: NOT ASSESSED
Rwys 08; 35: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


THICKET PORTAGE, MB

AERODROME CHART — CZLQ

UNICOM – **122.8** (AU)

ATF

DECL DISTS	12	30						
TORA	2211	2211						
TODA	3195	3195						
ASDA	2211	2211						
LDA	2211	2211						



TAKE-OFF MINIMA

Rwy 12: *
Rwy 30: ½

SCALE IN FEET

500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZLQ


EFF 16 JUL 20

THOMPSON, MB

AERODROME CHART — CYTH

ATIS – **127.65**		RADIO – **122.5** MF*	CTR Winnipeg – **133.15** RADIO Edmonton – **123.55**

DECL DISTS	06	24	15	33
TORA	5800	5800	5079	5079
TODA	6784	6784	5279	5279
ASDA	5800	5800	5079	5079
LDA	5800	5800	5079	5079



* DEPARTURE PROCEDURE

Rwy 06 -½
Note: Trees to 779 ASL aprx 0.2 NM past departure end of rwy, 860' RIGHT of rwy centreline. Trees to 792 ASL aprx 0.4 NM past departure end of rwy, 960' LEFT of rwy centreline.
Rwy 15 -½
Note: Twr to 818 ASL aprx 0.3 NM past departure end of rwy, 1030' RIGHT of rwy centreline.
Rwy 24 -½
Note: Trees to 754 ASL aprx 0.2 NM past departure end of rwy, 830' RIGHT of rwy centreline. Trees to 776 ASL aprx 0.3 NM past departure end of rwy, 940' LEFT of rwy centreline.
Rwy 33 -½
Note: Trees to 787 ASL aprx 0.1 NM past departure end of rwy, 560' RIGHT of rwy centreline. Trees to 787' aprx 0.1 NM past departure end of rwy 600' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 15; 24; 33: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


THREE HILLS, AB

AERODROME CHART — CEN3

CTR Edmonton – **124.45 132.85**

TFC – **123.2** ATF

DECL DISTS	12	30
TORA	3000	3000
TODA	3000	3000
ASDA	3000	3000
LDA	3000	3000



✱ DEPARTURE PROCEDURE
Rwy 30 - ½
Note: Building to 3088 ASL 0.1NM past departure end of rwy, 370' left of centreline.

TAKE-OFF MINIMA

Rwy 12: ½
Rwy 30: ✱

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TISDALE, SK


AERODROME CHART — CJY3

CTR Winnipeg – **133.9**

TFC – **122.8**

ATF

DECL DISTS	08	26	14	32	17	35		
TORA	2534	2534	3013	3013	2086	2086		
TODA	2534	2534	3013	3013	2086	2086		
ASDA	2534	2534	3013	3013	2086	2086		
LDA	2534	2534	3013	3013	2086	2086		



* DEPARTURE PROCEDURE

Rwy 14 - ½

Note: Road to 1530' ASL abeam departure end of rwy, 530' LEFT of rwy centreline.

Rwy 32 - ½ **-** Requires a minimum climb gradient of **310** ft/NM to **1800**.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **2000** BPOC.
Note: Poles and wires to 1548 ASL aprx 0.1 NM past departure end of rwy.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
310 FT/NM	470	620	730	830	930	1040	1300	1550

TAKE-OFF MINIMA

Rwys 14; 32: *
Rwys 08, 17, 26, 35: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CJY3


EFF 23 FEB 23

URANIUM CITY, SK

AERODROME CHART — CYBE

TFC – **123.2** ATF

DECL DISTS	06	24
TORA	3935	3935
TODA	4919	4919
ASDA	3935	3935
LDA	3935	3935



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBE

EFF 29 DEC 22

VALLEYVIEW, AB


AERODROME CHART — CEL5

CTR Edmonton – **134.5**

TFC – **123.2**

ATF

DECL DISTS	07	25						
TORA	3335	3335						
TODA	3335	3335						
ASDA	3335	3335						
LDA	3335	3335						



TAKE-OFF MINIMA
All Rwys: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VEGREVILLE, AB


AERODROME CHART — CEV3

UNICOM – **122.8**

CTR Edmonton – **133.45 340.7**

ATF

DECL DISTS	13	31						
TORA	4001	4001						
TODA	4001	4001						
ASDA	4001	4001						
LDA	4001	4001						



TAKE-OFF MINIMA
Rwy 13; 31: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WAINWRIGHT, AB


AERODROME CHART — CYWV

CTR Edmonton – **133.45**

TFC – **122.8**

ATF*

DECL DISTS	13	31
TORA	3000	3000
TODA	3000	3000
ASDA	3000	3000
LDA	3000	3000



TAKE-OFF MINIMA
Rwy 13: *
Rwy 31: NOT ASSESSED

SCALE IN FEET

500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WESTLOCK, AB


AERODROME CHART — CES4

UNICOM – **122.8**

CTR Edmonton – **134.7**

ATF

DECL DISTS	10	28
TORA	3397	3397
TODA	3397	3397
ASDA	3397	3397
LDA	3200	3209



* DEPARTURE PROCEDURE

Rwy 10 - ½ **-** When CYA209 and/or CYA218 are active: climb between hdg **166°** CCW to **281°** to remain clear of CYA209 and CYA218 BPOC.

or

When CYA202 is active: climb between hdg **080°** CCW to **281° -**OR**-** climb between hdg **136°** CW to **166°** to remain clear of CYA202, CYA209, and CYA218 BPOC.

Note: Trees to 2236 ASL 0.2NM past departure end of rwy, LEFT and RIGHT of rwy centreline.

Rwy 28 - ½ **-** When CYA209 and/or CYA218 are active: climb between hdg **226°** CW to **101° -**OR**-** climb between hdg **154°** CCW to **101°** to remain clear of CYA209 and CYA218 BPOC.

or

When CYA202 is active: climb between hdg **226°** CW to **081°** to remain clear of CYA202, CYA209 and CYA218 BPOC.

Note: Road to 2214 ASL abeam departure end of rwy, 300' RIGHT of rwy centreline. Power pole to 2236 ASL 0.1NM past departure end of rwy, 590' LEFT of rwy centreline. Trees to 2246 ASL within 0.1NM of departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WETASKIWIN REGIONAL, AB


AERODROME CHART — CEX3

UNICOM – **123.5**

TML Edmonton – **119.5**

ATF

DECL DISTS	12	30
TORA	3888	3888
TODA	3888	4305
ASDA	3888	3888
LDA	3888	3518



TAKE-OFF MINIMA

All Rwys: *

SCALE IN FEET

1000 0 1000

AERODROME CHART — CEX3

EFF 5 OCT 23

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WEYBURN, SK


AERODROME CHART — CJE3

UNICOM – **122.8**

CTR Winnipeg – **123.8**

ATF

DECL DISTS	06	24	12	30				
TORA	3016	3016	3998	3998				
TODA	3016	3016	3998	3998				
ASDA	3016	3016	3998	3998				
LDA	3016	3016	3998	3998				



* DEPARTURE PROCEDURE

Rwy 06 - ½
Note: Trees to 1954 ASL aprx 0.1 NM past departure end of rwy, 250' RIGHT of rwy centreline.
Rwy 12 - ½
Note: Trees to 1946 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT of rwy centreline.
Rwy 24 - ½
Note: Hangar to 1963 ASL aprx 0.1 NM past departure end of rwy, 440' LEFT of rwy centreline.
Rwy 30 - ½
Note: Trees to 1965 ASL aprx 0.2 NM past departure end of rwy, 700' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 12; 24; 30: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CJE3


EFF 14 JUL 22

WHITECOURT, AB

AERODROME CHART — CYZU

			◕ RADIO – **122.3**			CTR Edmonton – **132.05**		
			◕ TFC – **122.3**			RADIO Edmonton – **123.27**		
						MF		

DECL DISTS	11	29						
TORA	5797	5797						
TODA	5797	5797						
ASDA	5797	5797						
LDA	5797	5797						



TAKE-OFF MINIMA
Rwys 11; 29: *

SCALE IN FEET
1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WINNIPEG/JAMES ARMSTRONG RICHARDSON INTL, MB

AERODROME CHART — CYWG

ATIS – **120.2**	CLNC DEL – **121.3** GND – **121.9**	TWR – **118.3**	DEP – **119.9** (E) **121.0** (W) RADIO Edmonton – **123.25**

DECL DISTS	13	31	18	36				
TORA	8841	8841	11000	11000				
TODA	9825	9825	11984	11984				
ASDA	8841	8841	11000	11000				
LDA	8841	8701	11000	11000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 13, 31, 36: RVR 1200 RWY 18: (1/4sm)	RWY 36: RVR 600

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: ½	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYWG

EFF 5 OCT 23

Low Visibility Procedures (RVR less than 1200 to 600 ft)

Expect Delays

When low visibility procedures are in effect, ATC will restrict operations to one aircraft on the maneuvering area at a time (1 departure or 1 arrival at a time).

Departures

Only departures on Runway 36 or 18 shall be permitted. Intersection departures will not be permitted.

Although Winnipeg Tower does not control aircraft push backs or taxiing on aprons, pilots are recommended to contact Winnipeg Tower before maneuvering on Apron I.

Contact ATC for a start / taxi time.

Sequencing of Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is a minimum of:

Aircraft/Pilot Take-Off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

"AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR"

Arrivals

When Low Visibility Procedures are in effect the arrival RWY is 36 in accordance with applicable approach minima or approach ban considerations.

Winnipeg Tower will restrict operations to one aircraft on the maneuvering area at a time (1 departure or 1 arrival at a time). Approximately 6 movements per hour.

Airport Services and Equipment Available Under Low Visibility Operations

Airport Surface Detection Equipment (ASDE).

Runway Certification

Rwy	Certification
36	RVR 600
13	RVR 1200
31	RVR 1200
18	¼ SM (Based on reported visibility)


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY CYWG

ATIS – **120.2**

CLNC DEL – **121.3**

GND – **121.9**
PAD CTL – **122.92**



DE-ICING BAYS	DESCRIPTION
1, 3, 4, 6	Not avbl to acft with wingspan 125' or greater.
2	Avbl to acft with wingspan 214' or greater with discretionary oversteer at entrance.
5	Not avbl to acft with wingspan 214' or greater.

DE-ICING OPERATIONS

For more information, ctc Icehouse 204-987-9436.

1. Prior to push back, notify PAD CONTROL (122.925) and WINNIPEG GND when de-icing is required.
2. Hold short of Central De-icing Facility (CDF) and ctc PAD CONTROL on 122.925.
   Note: In the event that the "Hold" light and/or inset lgt cannot be utilized, the CDF will deploy a "Follow Me" vehicle.
3. All de-icing operations are performed with acft engines running, unless otherwise advised by PAD CONTROL.
   CAUTION: all operating engines must be maintained at gnd idle thrust settings. De-icing operation limited to maximum wind gusts of 40kts.
4. Once de-icing is complete, acft will be instructed to ctc WINNIPEG GND for taxi clnc. DO NOT ENTER TWY H WITHOUT ATC CLEARANCE. MINIMUM BREAKAWAY THRUST MUST BE USED.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

CYWG

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON I)
CYWG

EFF 8 SEP 22

PARKING AREAS (APRON V)


CYWG

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON V)
CYWG

EFF 8 SEP 22

PARKING AREAS (APRON VII) CYWG



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON VII) CYWG

EFF 8 SEP 22

Aircraft Parking Positions (APRON I, APRON V and APRON VII)

Position	Coordinates	Position	Coordinates
2	495424.27N 0971317.65W	41	495416.13N 0971347.23W
3	495424.57N 0971319.76W	42	495414.80N 0971347.92W
4	495424.75N 0971321.91W	43	495413.46N 0971348.61W
4A	495424.48N 0971322.45W	45	495409.05N 0971351.36W
5	495424.96N 0971324.06W	54	495349.26N 0971320.58W
6	495424.65N 0971326.94W	55	495349.28N 0971317.01W
7	495424.92N 0971329.94W	56	495349.13N 0971313.21W
8	495424.76N 0971332.10W	57	495348.99N 0971309.41W
9	495424.49N 0971334.23W	58	495348.84N 0971305.60W
10	495424.13N 0971336.33W	59	495345.54N 0971321.83W
11	495423.71N 0971338.39W	61	495414.82N 0971340.50W
12	495423.15N 0971340.41W	62	495413.00N 0971341.45W
15	495421.91N 0971341.59W	63	495410.63N 0971342.68W
16	495420.51N 0971341.0W	64	495408.97N 0971344.38W
17	495419.14N 0971340.74W	64A	495409.39N 0971343.72W
18	495419.09N 0971338.53W	65	495406.12N 0971345.59W
19	495419.48N 0971336.44W	71	495404.16N 0971348.39W
20	495419.85N 0971334.38W	71A	495403.31N 0971346.43W
21	495420.20N 0971332.28W	72	495402.97N 0971345.97W
30	495423.42N 0971313.54W	73	495401.10N 0971343.40W
31	495423.89N 0971315.57W	73A	495400.08N 0971341.75W
32	495429.06N 0971314.87W	74	495359.61N 0971341.50W
33	495428.67N 0971312.94W	75	495357.83N 0971338.80W
34	495428.23N 0971311.05W	75A	495357.56N 0971338.20W
35	495427.73N 0971309.19W	76	495356.25N 0971337.06W


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WINNIPEG/ST. ANDREWS, MB

AERODROME CHART — CYAV

ATIS – **125.8**	GND – **121.8**	TWR – **118.5** TFC – **118.5** ATF+	DEP – **119.9**

DECL DISTS	04	22	13	31	18	36		
TORA	2852	2852	3002	3002	3000	3000		
TODA	3836	3836	3986	3986	3984	3984		
ASDA	2852	2852	3002	3002	3000	3000		
LDA	2852	2852	3002	3002	3000	3000		



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAV


EFF 8 SEP 22

WOLLASTON LAKE, SK

AERODROME CHART — CZWL

AUTO – **122.07**		UNICOM – **122.8** TFC – **123.3** ATF	RADIO Edmonton – **123.55** DRCO

DECL DISTS	17	35
TORA	3793	3793
TODA	4777	4777
ASDA	3793	3793
LDA	3793	3793



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
270 FT/NM	410	540	630	720	810	900	1130	1350

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17; 35: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

YORK LANDING, MB


AERODROME CHART — CZAC

UNICOM – **122.8** (AU)

CTR Winnipeg – **133.15**

ATF

DECL DISTS	10	28						
TORA	3396	3396						
TODA	4380	4380						
ASDA	3396	3396						
LDA	3396	3396						



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 753 ASL abeam departure end of rwy, 350' LEFT and RIGHT of rwy centreline and aprx 0.1 NM past departure end of rwy. Powerline to 761 ASL aprx 0.3 NM past departure end of rwy, 1000' RIGHT of rwy centerline.

Rwy 28 - ½

Note: Trees to 760 ASL abeam departure end of rwy, 250' LEFT and RIGHT of rwy centreline and 0.2 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	1000 0 1000

AERODROME CHART — CZAC

EFF 21 MAY 20


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

YORKTON REGIONAL, SK

AERODROME CHART — CYQV

AWOS – **128.72**	RADIO Regina – **119.65 296.6** TFC – **119.65 296.6** **MF**	CTR Winnipeg – **132.52** RADIO Edmonton – **123.47**

DECL DISTS	04	22	13	31				
TORA	4800	4800	2984	2984				
TODA	5784	5784	3968	3968				
ASDA	4800	4800	2984	2984				
LDA	4800	4800	2984	2984				



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 04: ½ Rwy 22: * Rwys 13, 31: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQV

EFF 10 AUG 23

ANGLING LAKE/WAPEKEKA, ON


AERODROME CHART — CKB6

AWOS Big Trout Lake – **128.7**

TFC – **123.2**

ATF

DECL DISTS	12	30
TORA	3609	3609
TODA	3609	3609
ASDA	3609	3609
LDA	3609	3609



* DEPARTURE PROCEDURE

Rwy 12 - ½

Note: Trees to 747 ASL past departure end of rwy.

Rwy 30 - ½

Note: Trees to 762 ASL past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12, 30: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ARMSTRONG, ON

AERODROME CHART — CYYW

MET – **128.65** | TFC – **122.8** | ATF

DECL DISTS	12	30
TORA	4006	4006
TODA	4006	4006
ASDA	4006	4006
LDA	4006	4006



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12, 30: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYW


EFF 24 MAR 22

ARNPRIOR, ON

AERODROME CHART — CNP3

		UNICOM – **122.7** ATF	CTR Montreal – **124.27**

DECL DISTS	10	28	16	34				
TORA	3937	3937	2360	2360				
TODA	3937	3937	2360	2360				
ASDA	3937	3937	2360	2360				
LDA	3937	3937	2360	2360				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: * Rwys 16, 34: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNP3

EFF 5 NOV 20


ATIKOKAN MUNICIPALITY, ON

AERODROME CHART — CYIB

RADIO London – **123.27**

TFC – **122.3** MF

DECL DISTS	04	22
TORA	3495	3495
TODA	4479	4479
ASDA	3495	3495
LDA	3495	3495



***** DEPARTURE PROCEDURE

Rwy 04 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

Rwy 22 - ½

Note: Trees to 1499 ASL past initial climb area.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


ATTAWAPISKAT, ON

AERODROME CHART — CYAT

AWOS – **128.77**

TFC – **122.8** ATF

DECL DISTS	06	24
TORA	3495	3495
TODA	3695	3695
ASDA	3495	3495
LDA	3495	3495



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BAR RIVER, ON


AERODROME CHART — CPF2

UNICOM – **122.8**

CTR Toronto – **132.65**

ATF

DECL DISTS	18	36
TORA	4384	4384
TODA	4384	4384
ASDA	4384	4384
LDA	4384	4384



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 FT/NM	530	700	820	940	1050	1170	1460	1750

* DEPARTURE PROCEDURE

Rwy 18 - ½ - Requires a minimum climb gradient of **350** ft/NM to **1200**. Climb hdg **178°** to **1200** BPOC.
Note: Trees to 643 ASL abeam departure end of rwy and Trees to 750 ASL aprx 0.65 NM past departure end of rwy, 1400' LEFT and RIGHT of centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700** BPOC.

Rwy 36 - ½ - Climb hdg **358°** to **1200** BPOC.
Note: Trees to 650 ASL aprx 0.5 NM past departure end of rwy, RIGHT of centreline.

TAKE-OFF MINIMA

Rwys 18; 36: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BARRIE-ORILLIA/LAKE SIMCOE, ON

AERODROME CHART — CYLS


AUTO – **122.55**

UNICOM – **122.7**

ATF

CTR Toronto – **124.02**

DECL DISTS	10	28						
TORA	6001	6001						
TODA	6001	6001						
ASDA	6001	6001						
LDA	5958	5698						



* DEPARTURE PROCEDURE

Rwy 10 - ½ - Climb between hdg **180°** CCW to **277°** to remain clear of CYR502 and CYA509(P).
Note: Roadway to 974 ASL 0.1 NM past departure end of rwy. Trees to 1001 ASL 0.1 NM past departure end of rwy, 630' LEFT of rwy centreline. Trees to 1042 ASL 0.6 NM past departure end of rwy.

Rwy 28 - ½ - Climb hdg **277°** to **1500**. Then climb between hdg **280°** CW to **097°** to remain clear of CYR502 and CYA509(P).
Note: Trees to 1004 ASL abeam departure end of rwy, 570' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28 : *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BEARSKIN LAKE, ON


AERODROME CHART

CNE3

AWOS Big Trout Lake – **128.7**

TFC – **123.2** ATF

DECL DISTS	07	25
TORA	3503	3503
TODA	3503	3503
ASDA	3503	3503
LDA	3503	3503



TAKE-OFF MINIMA
Rwys 07, 25: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BIG TROUT LAKE, ON

AERODROME CHART — CYTL

AWOS – **128.7**		TFC – **123.2** ATF	RADIO London – **123.55**

DECL DISTS	14	32
TORA	3906	3906
TODA	4306	4306
ASDA	3906	3906
LDA	3906	3906



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32 : *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYTL

EFF 27 JAN 22

BRAMPTON-CALEDON, ON


AERODROME CHART — CNC3

UNICOM – **123.3**

TML Toronto – **119.3**

ATF*

	08	26	15	33				
TORA	2500	2500	3500	3500				
TODA	2500	2500	3500	3500				
ASDA	2500	2500	3500	3500				
LDA	2309	2500	3500	3500				



* DEPARTURE PROCEDURE

Rwy 08 - ½
Note: Trees to 947 ASL within 400 feet of departure end of rwy, 300' RIGHT of centreline.
Rwy 15 - ½
Note: Trees to 954 ASL within 0.3 NM of departure end of rwy, both LEFT and RIGHT of rwy centreline.
Rwy 26 - ½ - NO RIGHT turn below **1800**.
Note: Railroad to 954 ASL abeam departure end of rwy. Road to 952 ASL aprx 360' past departure end of rwy, LEFT and RIGHT of rwy centreline.
Rwy 33 - ½ - NO LEFT turn below **1700**.
Note: Terrain rising to 939 ASL, abeam departure end of rwy, 300' LEFT of rwy centreline.

TAKE-OFF MINIMA

All Rwys: *


SCALE IN FEET
500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BRANTFORD, ON

AERODROME CHART — CYFD

				UNICOM – **122.82**		CTR Toronto – **119.7** ATF		
DECL DISTS	**05**	**23**	**11**	**29**	**17**	**35**		
TORA	5036	5036	2626	2626	2626	2626		
TODA	5036	5636	3610	3610	3610	3526		
ASDA	5036	5036	2626	2626	2626	2626		
LDA	5036	5036	2626	2626	2626	2626		



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BROCKVILLE REGIONAL TACKABERRY APRT, ON

AERODROME CHART — CNL3


AUTO Ogdensburg Intl – **118.52**

UNICOM – **123.0**

ATF

CTR Montreal – **134.67**

DECL DISTS	04	22	16	34				
TORA	4505	4505	2203	2203				
TODA	4505	4505	2203	2203				
ASDA	4505	4505	2203	2203				
LDA	4505	4505	2203	2203				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNL3

EFF 23 FEB 23

BURLINGTON EXECUTIVE, ON

AERODROME CHART — CZBA


AUTO – **122.55**

UNICOM – **123.5**

TML Toronto – **119.3**

ATF*

DECL DISTS	09	27	14	32				
TORA	2464	2464	3950	3950				
TODA	2464	2464	3950	3950				
ASDA	2464	2464	3950	3950				
LDA	2136	2210	3769	3541				



*DEPARTURE PROCEDURE

Rwy 14 - ½ - Climb hdg **141°** to **1500** BPOC.
Note: Trees to 663 ASL abeam departure end of rwy.

Rwy 32 - ½ - Requires a minimum climb gradient of **340** ft/NM to **1800**. Climbing RIGHT turn, intercept INBD track **191°** to "ZHM" NDB to **3000** BPOC.
Note: Trees to 689 ASL aprx 0.2 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1800** BPOC.

TAKE-OFF MINIMA

Rwys 14; 32: *
Rwys 09; 27: NOT ASSESSED

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZBA


EFF 2 DEC 21

CAT LAKE, ON

AERODROME CHART — CYAC

TFC – **123.2** **ATF**

DECL DISTS	11	29						
TORA	3963	3963						
TODA	3963	3963						
ASDA	3963	3963						
LDA	3963	3963						



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAC

EFF 24 MAR 22

CENTRALIA/JAMES T. FIELD MEMORIAL, ON


AERODROME CHART — CYCE

UNICOM – **122.8**

ATF

CTR Toronto – **135.30**

DECL DISTS	10	28	16	34				
TORA	5013	5013	4392	4392				
TODA	5013	5013	4392	4392				
ASDA	5013	5013	4392	4392				
LDA	5013	5013	4392	4392				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10-28: *	1000 500 0 1000 2000
Rwys 16-34: NOT ASSESSED	

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYCE


EFF 8 SEP 22

CHAPLEAU, ON

AERODROME CHART — CYLD

TFC– **122.8** ATF

DECL DISTS	05	23	10	28				
TORA	3006	3006	5003	5003				
TODA	3990	3990	5987	5987				
ASDA	3006	3006	5003	5003				
LDA	3006	3006	5003	5003				



* DEPARTURE PROCEDURE

Rwy 05 - ½
Note: Trees to 1564 ASL abeam departure end of rwy, 300' LEFT of rwy centreline and aprx 0.1 NM past departure end of rwy.

Rwy 10 - ½
Note: Trees to 1561 ASL abeam departure end of rwy, 350' LEFT and RIGHT of rwy centreline and aprx 0.4 NM past departure end of rwy.

Rwy 23 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2300** BPOC.

Rwy 28 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2300** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYLD


EFF 15 JUN 23

CHATHAM-KENT, ON

AERODROME CHART — CYCK

AWOS – **122.97**		UNICOM – **123.2** ATF	ARR Selfridge – **119.6 318.2** O/T CTR Cleveland – **132.25 298.87**

DECL DISTS	06	24
TORA	5502	5502
TODA	5502	5502
ASDA	5502	5502
LDA	5002	5002



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24 : *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYCK


EFF 23 FEB 23

COCHRANE, ON

AERODROME CHART — CYCN

AUTO – **122.55**		TFC – **122.8** ATF	CTR Toronto – **128.3**

DECL DISTS	13	31
TORA	4484	4484
TODA	4484	4484
ASDA	4484	4484
LDA	4484	4484



✱ DEPARTURE PROCEDURE

Rwy 13 - ½

Note: Trees to 932 ASL aprx 0.1 NM past departure end of rwy, LEFT and RIGHT of rwy centreline.

Rwy 31 - ½

Note: Trees to 877 ASL aprx 0.2 NM past departure end of rwy, 600' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 31, 13: ✱	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

COLLINGWOOD, ON

AERODROME CHART — CNY3


AUTO – **122.17**

◕ UNICOM – **122.85**

ATF

CTR Toronto – **124.02**

DECL DISTS	01	19	13	31				
TORA	2548	2548	5000	5000				
TODA	2548	2548	5984	5000				
ASDA	2548	2548	5000	5000				
LDA	2548	2548	5000	5000				



TAKE-OFF MINIMA

Rwys 01;19: NOT ASSESSED
Rwys 13; 31: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNY3

EFF 23 FEB 23

CORNWALL REGIONAL, ON


AERODROME CHART — CYCC

UNICOM – **122.77**

CTR Boston – **135.25 377.1**

ATF

DECL DISTS	10	28						
TORA	3510	3510						
TODA	4174	3765						
ASDA	3510	3510						
LDA	3510	3510						



* DEPARTURE PROCEDURE

Rwy 10 - ½ - Climb between hdg **041°** CW to **277°** to remain clear of CYA524(S).
Note: Road to 209 ASL aprx 0.1NM past Initial Climb Area.
Trees to 244 ASL aprx 0.1NM past Initial Climb Area, 400' RIGHT of rwy centreline.

Rwy 28 - ½ - Requires a minimum climb gradient of **290** ft/NM to **400**.
Climb between hdg **345°** CCW to **097°** to remain clear of CYA524(S).
Note: Trees to 244 ASL past Initial Climb Area, 350' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **4200** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DEER LAKE, ON

AERODROME CHART — CYVZ

TFC – **122.8** ATF

DECL DISTS	13	31						
TORA	3506	3506						
TODA	4490	4490						
ASDA	3506	3506						
LDA	3506	3506						



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVZ


EFF 27 JAN 22

DETOUR LAKE, ON

AERODROME CHART — CDT9

AUTO – **122.17**		◕ UNICOM – **122.95** ATF	CTR Toronto – **128.3 133.72**

DECL DISTS	10	28
TORA	5002	5002
TODA	5002	5002
ASDA	5002	5002
LDA	5002	5002



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees and terrain to 968 ASL 0.1 NM past departure end of rwy, 490° RIGHT of rwy centreline.
Powerline to 981 ASL 0.2 NM past departure end of rwy, 680° LEFT of rwy centreline.

Rwy 28 - ½

Note: Powerline running parallel to departure path RIGHT of rwy centreline to 1072 ASL.
Trees to 968 ASL abeam departure end of rwy, 470° LEFT and RIGHT of rwy centreline.
Trees and terrain to 1067 ASL 0.6 NM past departure end of rwy, 400° LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DRYDEN REGIONAL, ON

AERODROME CHART — CYHD

AWOS – **128.7**		RADIO Sioux Lookout – **122.1** MF	CTR Winnipeg – **132.2**

DECL DISTS	12	30
TORA	5993	5993
TODA	6193	6977
ASDA	5993	5993
LDA	5993	5796



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHD


EFF 12 AUG 21

EARLTON (TIMISKAMING REGIONAL), ON

AERODROME CHART — CYXR

AWOS – **128.6**		TFC – **122.0** MF	RADIO London – **123.37**

DECL DISTS	08	26	16	34				
TORA	5998	5998	3019	3019				
TODA	6598	6898	3119	3119				
ASDA	5998	5998	3019	3019				
LDA	5998	5998	3019	3019				



TAKE-OFF MINIMA
Rwy 08: ½
Rwy 26: *
Rwys 16, 34: NOT ASSESSED

SCALE IN FEET
1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

EDENVALE, ON

AERODROME CHART — CNV8

AUTO – **123.17**		UNICOM – **122.77** ATF	CTR Toronto – **124.02**

DECL DISTS	08	26	13	31				
TORA	3014	3014	3936	3936				
TODA	3014	3014	3936	3936				
ASDA	3014	3014	3936	3936				
LDA	3014	3014	3936	3936				



* DEPARTURE PROCEDURE

Rwy 13 - ½ **-** Climb between hdg **308°** CW to **145°** to remain clear of CYR 502.
Note: Trees and terrain to 742 abeam departure end of rwy, 410' RIGHT of rwy centreline.
Trees and terrain to 774 ASL 0.3 NM past departure end of rwy, 290' LEFT of rwy centreline.

Rwy 31 -½ **-** Climb between hdg **216°** CW to **128°** to remain clear of CYR 502.
Note: Trees, silo, powerlines and terrain to 768 ASL abeam
departure end of rwy, LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: * Rwys 08; 26: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ELLIOT LAKE MUNICIPALITY, ON


AERODROME CHART — CYEL

UNICOM – **123.0**

CTR Toronto – **135.4**

ATF

DECL DISTS	12	30
TORA	4495	4495
TODA	4495	4495
ASDA	4495	4495
LDA	4495	4495



TAKE-OFF MINIMA
Rwy 12, 30: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEL

EFF 25 FEB 21


FORT ALBANY, ON

AERODROME CHART

CYFA

TFC – **122.8** ATF

DECL DISTS	10	28						
TORA	3601	3601						
TODA	3601	3601						
ASDA	3601	3601						
LDA	3601	3601						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART

CYFA


EFF 5 OCT 23

FORT FRANCES MUNICIPALITY, ON

AERODROME CHART — CYAG

AUTO Falls Intl – **120.0**		UNICOM – **122.8** ATF	CTR Minneapolis – **120.9** RADIO London – **123.55**

DECL DISTS	12	30
TORA	4493	4493
TODA	5477	5477
ASDA	4493	4493
LDA	4493	4493



TAKE-OFF MINIMA
Rwys 12; 30: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAG

EFF 8 SEP 22


FORT HOPE, ON

AERODROME CHART

CYFH

TFC – **122.8** ATF

DECL DISTS	09	27						
TORA	3497	3497						
TODA	3497	3497						
ASDA	3497	3497						
LDA	3497	3497						



*****DEPARTURE PROCEDURE

Rwy 09 - ½

Note: Trees to 1038 ASL abeam departure end of rwy, 350' LEFT and RIGHT of rwy centreline and aprx 0.1 NM past departure end of rwy.

Rwy 27 - ½

Note: Trees to 996 ASL abeam departure end of rwy, 450' RIGHT and 300' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 09, 27: *****

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


FORT SEVERN, ON

AERODROME CHART — CYER

AWOS – **124.55**

TFC – **122.8** ATF

DECL DISTS	15	33
TORA	3519	3519
TODA	3519	3519
ASDA	3519	3519
LDA	3519	3519



TAKE-OFF MINIMA
Rwys 15; 33: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYER


EFF 5 OCT 23

GERALDTON (DISTRICT HOSPITAL), ON

HELIPORT CHART — CPJ4

			UNICOM – 122.8 ATF CYGQ	RADIO London – 123.47

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100

HELIPORT CHART — CPJ4

EFF 24 JUL 14


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GERALDTON (GREENSTONE REGIONAL), ON

AERODROME CHART — CYGQ

AWOS – **128.1**		UNICOM – **122.8** ATF	RADIO London – **123.47**

DECL DISTS	08	26
TORA	5007	5007
TODA	5207	5207
ASDA	5007	5007
LDA	5007	5007



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GODERICH, ON


AERODROME CHART — CYGD

CTR Toronto – **135.3**

◕ UNICOM – **122.7** (AU)

ATF

DECL DISTS	05	23	10	28	14	32		
TORA	1871	1871	3002	3002	5034	5034		
TODA	1871	1871	3002	3002	5034	5034		
ASDA	1871	1871	3002	3002	5034	5034		
LDA	1871	1871	3002	3002	5034	5034		



TAKE-OFF MINIMA

Rwys 05, 23: NOT ASSESSED
Rwys 10, 14, 28, 32: *

SCALE IN FEET
1000 0 1000

AERODROME CHART — CYGD

EFF 23 FEB 23


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GORE BAY-MANITOULIN, ON

AERODROME CHART — CYZE

AWOS – **128.72**		UNICOM – **122.8** ATF	CTR Toronto – **135.4** RADIO London – **126.7**

DECL DISTS	11	29	05	23				
TORA	5500	5500	2615	2615				
TODA	6484	6484	2615	2615				
ASDA	5500	5550	2615	2615				
LDA	5500	5500	2615	2615				



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 05; 23: NOT ASSESSED Rwy 11; 29: *	1000 0 1000

AERODROME CHART — CYZE

EFF 3 NOV 22


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HAMILTON, ON

AERODROME CHART — CYHM

ATIS – **128.1**	GND – **121.6**	TWR – **125.0**	CTR Toronto – **119.7**

DECL DISTS	06	24	12	30
TORA	6010	6010	10006	10006
TODA	6994	6994	10990	10395
ASDA	6010	6010	10006	10006
LDA	6010	6010	8398	10006



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 12: RVR 1200 RWY 30: (¼sm)	RWY 12: RVR 600


TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 12; 24; 30: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HAMILTON, ON

TAXI CHART CYHM

ATIS – **128.1**	GND – **121.6**	TWR – **125.0**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Low Visibility Procedures (Less than RVR 1200 to RVR 600)

Application

These procedures apply to ground movements of aircraft departing under low visibility conditions. Departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast.
"LOW VISIBILITY PROCEDURES IN EFFECT"

General

Low Visibility Taxi Routes

Taxi routes during low visibility operations are exclusive to the following routes:

1. Route 1 – Taxiway C
2. Route 2 – Taxiway B, rwy 06, taxiway C.
3. Taxiway surfaces are painted with enhanced yellow and black centreline markings. Aircraft restricted to one movement in or out at any time during low visibility operations. Alternate routing may be specified by ATC as required.

ATC may find it necessary to suspend, restrict, or terminate low visibility operations.

Departures

When low visibility procedures are in effect all departures shall be from the displaced threshold of rwy 12. Intersection take-offs are not authorized.

Declared Distances from displaced threshold of rwy 12

TORA 8400

TODA 9400

ASDA 8400

Sequencing of Aircraft Ground Movements for Take-off.

Do not request taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

Arrivals

Taxi route will be specified by ATC.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HAMILTON, ON

PARKING AREAS

CYHM

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYHM

EFF 23 FEB 23

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	430949.20N 0795529.86W	9	430954.03N 0795543.36W
2	430950.45N 0795529.28W	9A	430953.41N 0795543.61W
2A	430950.48N 0795529.77W	10	430954.15N 0795545.67W
3	430950.94N 0795530.89W	10A	430954.15N 0795548.33W
4	430950.70N 0795532.63W	11	430954.71N 0795548.14W
5	430951.63N 0795534.37W	12	430955.27N 0795550.61W
6	430951.58N 0795536.52W	13	430955.84N 0795553.08W
7	430952.52N 0795538.25W	14	430945.56N 0795526.30W
8	430952.47N 0795540.41W	15	430943.69N 0795527.05W

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HANOVER/SAUGEEN MUNICIPALITY, ON


AERODROME CHART — CYHS

UNICOM – **122.8**

CTR Toronto – **132.57**

ATF

DECL DISTS	01	19	09	27				
TORA	4001	4001	2502	2502				
TODA	4001	4001	2502	2502				
ASDA	4001	4001	2502	2502				
LDA	4001	4001	2171	2382				



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


AERODROME CHART — CYHS

HEARST (RENE FONTAINE) MUNICIPALITY, ON

AERODROME CHART — CYHF

			UNICOM – **122.8** (AU) ATF	RADIO London – **126.7** DRCO

DECL DISTS	04	22
TORA	4495	4495
TODA	4495	4495
ASDA	4495	4495
LDA	4495	4495



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHF


EFF 3 NOV 22

HORNEPAYNE MUNICIPALITY, ON

AERODROME CHART — CYHN

		UNICOM – **122.8** ATF	RADIO London – **126.7** DRCO

DECL DISTS	07	25
TORA	3504	3504
TODA	3504	3504
ASDA	3504	3504
LDA	3504	3504



TAKE-OFF MINIMA
Rwys 07, 25: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHN

EFF 20 JUN 19

KAPUSKASING, ON


AERODROME CHART — CYYU

CTR Toronto – **132.7**

TFC – **122.2**

MF

DECL DISTS	17	35
TORA	5506	5506
TODA	5966	6490
ASDA	5506	5506
LDA	5506	5506



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17, 35: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYU


EFF 5 OCT 23

KASABONIKA, ON

AERODROME CHART — CYAQ

TFC – **123.2** ATF

DECL DISTS	03	21
TORA	3519	3519
TODA	4503	4503
ASDA	3519	4319
LDA	3519	3519



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAQ


EFF 10 AUG 23

KASHECHEWAN, ON

AERODROME CHART — CZKE

TFC – **122.8** ATF

DECL DISTS	06	24						
TORA	3903	3903						
TODA	3903	3903						
ASDA	3903	3903						
LDA	3903	3903						



TAKE-OFF MINIMA	
All Rwys:	*

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZKE


EFF 10 AUG 23

KEEWAYWIN, ON

AERODROME CHART — CPV8

TFC – **122.8** ATF

DECL DISTS	13	31
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CPV8


EFF 24 MAR 22

KENORA, ON

AERODROME CHART — CYQK

		RADIO – **122.2**	CTR Winnipeg – **132.2** RADIO London – **123.37** MF

DECL DISTS	08	26
TORA	5800	5800
TODA	6200	6784
ASDA	5800	5800
LDA	5800	5800



***** DEPARTURE PROCEDURE

Rwy 08 - ½
Note: Trees to 1436 ASL aprx 500' past departure end of rwy.

Rwy 26 - ½
Note: Trees to 1419 ASL aprx 0.2 NM past departure end of rwy. Power line to 1427 ASL aprx 0.4 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26:*****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KINCARDINE, ON


AERODROME CHART — CYKM

UNICOM – **122.8** (AU)

ATF

CTR Toronto – **132.57**

DECL DISTS	05	23	13	31				
TORA	2083	2083	4085	4085				
TODA	2083	2083	4285	4285				
ASDA	2083	2083	4085	4085				
LDA	2083	2083	4085	4085				



*DEPARTURE PROCEDURE

Rwy 05 - ½ - Requires a minimum climb gradient of **230** ft/NM to **1500**.
Climb hdg **048°** to **1500**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.
Note: Trees to 834 ASL aprx 450' past departure end of rwy.
Road to 799' ASL aprx 300' past departure end of rwy.
Building to 847 ASL aprx 0.3NM past departure end of rwy, 780' RIGHT of rwy centreline.

Rwy 13 - ½ - Requires a minimum climb gradient of **280** ft/NM to **1600**.
Climb hdg **127°** to **1600**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.
Note: Road to 787 ASL aprx 500' past departure end of rwy.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKM


EFF 20 APR 23

KINGFISHER LAKE, ON

AERODROME CHART — CNM5

TFC – **123.2** ATF

DECL DISTS	12	30						
TORA	3520	3520						
TODA	3520	3520						
ASDA	3520	3520						
LDA	3520	3520						



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNM5


EFF 24 MAR 22

KINGSTON, ON

AERODROME CHART — CYGK

ATIS – **135.55**		RADIO – **122.5** TFC – **122.5** MF	CTR Montreal – **135.05** RADIO London – **123.55**

DECL DISTS	01	19	07	25				
TORA	6001	6001	3909	3909				
TODA	7001	6985	4893	4893				
ASDA	6001	6001	3909	3909				
LDA	5622	5000	3909	3909				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGK


EFF 16 JUL 20

KIRKLAND LAKE, ON

AERODROME CHART — CYKX

		UNICOM – **122.8** ATF	RADIO London – **123.37**

DECL DISTS	08	26						
TORA	4505	4505						
TODA	4855	4905						
ASDA	4505	4505						
LDA	4505	4505						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KITCHENER/WATERLOO, ON

AERODROME CHART — CYKF

ATIS – **125.1**	GND Waterloo – **121.8**	TWR Waterloo – **126.0** **118.55**	CTR Toronto – **128.27**
MET – **125.1**		TFC – **126.0** MF	

DECL DISTS	08	26	14	32				
TORA	7003	7003	4103	4103				
TODA	7987	7659	5087	4634				
ASDA	7003	7003	4103	4103				
LDA	7003	7003	4103	4103				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08, 26: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKF


EFF 15 JUN 23

LANSDOWNE HOUSE, ON

AERODROME CHART — CYLH

AWOS – **128.4**		TFC – **122.8** ATF	RADIO London – **123.37** DRCO

DECL DISTS	08	26
TORA	3484	3484
TODA	4468	4468
ASDA	3484	3484
LDA	3484	3484



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LEAMINGTON, ON

AERODROME CHART


CLM2

ARR Detroit – **134.3**

TFC – **123.2**

ATF

DECL DISTS	01	19
TORA	3832	3832
TODA	3832	3832
ASDA	3832	3832
LDA	2674	2890



TAKE-OFF MINIMA
Rwys 01, 19: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CLM2

EFF 5 DEC 19

LINDSAY/KAWARTHA LAKES MUNICIPAL AIRPORT, ON


AERODROME CHART — CNF4

UNICOM – **122.72**

ATF

CTR Toronto – **134.25**

DECL DISTS	03	21	13	31				
TORA	2666	2666	3508	3508				
TODA	2863	2666	3705	3705				
ASDA	2666	2666	3508	3508				
LDA	2301	2666	3508	3508				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNF4


EFF 23 FEB 23

LONDON, ON

AERODROME CHART — CYXU

ATIS – **127.8**	GND – **121.9**	TWR – **119.4** **125.65** RADIO Sudbury – **119.4** MF*	CTR Toronto – **135.3**

DECL DISTS	09	27	15	33				
TORA	6300	6300	8800	8800				
TODA	7284	7284	9784	9625				
ASDA	6300	6300	8800	8800				
LDA	6300	6300	8800	8800				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 15: RVR 1200 RWY 33: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	2000 0 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MANITOUWADGE, ON

AERODROME CHART — CYMG

AUTO – **129.15**		◕ UNICOM – **122.8** ATF	CTR Winnipeg – **134.07**

DECL DISTS	05	23
TORA	3603	3603
TODA	3603	3603
ASDA	3603	3603
LDA	3603	3603



TAKE-OFF MINIMA
Rwys 05; 23: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMG

EFF 22 APR 21

MANITOWANING/MANITOULIN EAST MUNICIPALITY, ON


AERODROME CHART — CYEM

UNICOM – **122.8**

CTR Toronto – **135.4**

ATF

DECL DISTS	02	20						
TORA	3498	3498						
TODA	4482	4482						
ASDA	3728	3728						
LDA	3498	3498						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02; 20: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYEM

EFF 2 DEC 21

MARATHON, ON


AERODROME CHART — CYSP

CTR Winnipeg – **134.07**

TFC – **122.8**

ATF

DECL DISTS	16	34	16	34				
TORA	3933	3933	3933	3933				
TODA	4300	4133	3933	3933				
ASDA	4300	3933	3933	3933				
LDA	3933	3735	3933	3735				



TAKE-OFF MINIMA

Rwys 16, 34: *

SCALE IN FEET

1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MIDLAND/HURONIA, ON

AERODROME CHART — CYEE

			UNICOM – **122.85** (AU)			ATF	CTR Toronto – **124.02**	

DECL DISTS	16	34
TORA	3996	3996
TODA	4196	4266
ASDA	3996	3996
LDA	3996	3996



* DEPARTURE PROCEDURE

Rwy 16 - ½
Note: Trees to 830 ASL aprx 0.1 NM past departure end of rwy.

Rwy 34 - ½
Note: Hangar to 808 ASL aprx 400' past departure end of rwy, 350' RIGHT of rwy centreline.
Hangar to 808 ASL aprx 850' past departure end of rwy, 350' LEFT of rwy centreline.

TAKE-OFF MINIMA
All Rwys: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MOOSONEE, ON

AERODROME CHART — CYMO

AWOS – **124.8**		RADIO Timmins – **122.5** TFC – **122.5** MF*	CTR Toronto – **133.72**

DECL DISTS	06	24	14	32
TORA	4001	4001	3555	3555
TODA	4985	4985	4539	4539
ASDA	4001	4001	3555	3555
LDA	4001	4001	3555	3555



TAKE-OFF MINIMA
Rwys 06; 24; 32: *
Rwy 14: ½

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMO


EFF 24 MAR 22

MUSKOKA, ON

AERODROME CHART — CYQA

AWOS – **124.57**		RADIO Timmins – **122.3** MF	RADIO Timmins – **122.3**

DECL DISTS	18	36
TORA	6000	6000
TODA	6984	6700
ASDA	6000	6000
LDA	5200	6000



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18; 36: *	1000 0 1000

AERODROME CHART — CYQA

EFF 10 AUG 23


MUSKRAT DAM, ON

AERODROME CHART — CZMD

AWOS – **124.45**

TFC – **123.2** ATF

DECL DISTS	05	23
TORA	3508	3508
TODA	3508	3508
ASDA	3508	3508
LDA	3508	3508



TAKE-OFF MINIMA
Rwys 05; 23: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZMD

EFF 8 SEP 22

NAKINA, ON

AERODROME CHART


CYQN

UNICOM – **122.8**

RADIO London – **123.47**

ATF

DECL DISTS	09	27						
TORA	3500	3500						
TODA	3500	3500						
ASDA	3500	3500						
LDA	3500	3500						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09, 27: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


NORTH BAY, ON

AERODROME CHART — CYYB

ATIS – **124.9** AWOS – **124.9**		RADIO – **118.3** TFC – **118.3**	CTR Toronto – **127.25**

MF*

DECL DISTS	08	26	13	31	18	36		
TORA	10004	10004	2000	2000	4492	4492		
TODA	10988	10988	2000	2000	5476	5476		
ASDA	10004	10004	2000	2000	4492	4492		
LDA	10004	10004	2000	2000	4492	4492		



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08: RVR 1200 RWY 26: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 18; 36: * Rwy 26: ½ Rwys 13; 31: NOT ASSESSED	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYB


EFF 15 JUN 23

NORTH SPIRIT LAKE, ON

AERODROME CHART — CKQ3

TFC – **122.8** ATF

DECL DISTS	13	31
TORA	3518	3518
TODA	3518	3518
ASDA	3518	3518
LDA	3518	3518



TAKE-OFF MINIMA
Rwys 13; 31: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CKQ3


EFF 27 JAN 22

OGOKI POST, ON

AERODROME CHART — CYKP

AWOS – **128.12**		TFC – **123.2** ATF	CTR – Winnipeg **135.47**

DECL DISTS	09	27
TORA	3514	3514
TODA	3514	3514
ASDA	3514	3514
LDA	3514	3514



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 09; 27: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OTTAWA/CARP, ON

AERODROME CHART — CYRP

ATIS Ottawa – **121.15**		UNICOM – **122.8** ATF*	DEP Ottawa – **128.17**

DECL DISTS	04	22	10	28				
TORA	2205	2205	3936	3936				
TODA	2205	2205	4920	4743				
ASDA	2205	2205	3936	3936				
LDA	2009	2107	3936	3936				



TAKE-OFF MINIMA
Rwys 10; 28: *
Rwys 04; 22: NOT ASSESSED

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OTTAWA/MACDONALD-CARTIER INTL, ON

AERODROME CHART — CYOW

ATIS – **121.15** (En) **132.95** (Fr)	CLNC DEL – **119.4** GND – **121.9**	TWR – **118.8**	DEP – **128.17** RADIO Quebec – **123.15**

DECL DISTS	04	22	07	25	14	32		
TORA	3300	3300	8000	8000	10005	10005		
TODA	3300	3300	8984	8984	10989	10989		
ASDA	3300	3300	8000	8000	10005	10005		
LDA	3050	3300	8000	8000	10005	10005		



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07, 32: RVR 1200 RWY 14, 25: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000 3000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYOW


EFF 5 OCT 23

OTTAWA/MACDONALD-CARTIER INTL, ON

CARTE D'AÉRODROME — CYOW

ATIS – **132.95** (Fr) **121.15** (Ang)	CLNC DEL – **119.4** GND – **121.9**	TWR – **118.8**	DEP – **128.17** RADIO Québec – **123.15**

DIST DÉCLARÉES	04	22	07	25	14	32		
TORA	3300	3300	8000	8000	10005	10005		
TODA	3300	3300	8984	8984	10989	10989		
ASDA	3300	3300	8000	8000	10005	10005		
LDA	3050	3300	8000	8000	10005	10005		



NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
Piste 07, 32: RVR 1200 Piste 14, 25: (¼ sm)	NON AUTORISÉ

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Toutes Pistes: *	1000 0 1000 2000 3000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME — CYOW

EFF 5 OCT 23

OTTAWA/MACDONALD-CARTIER INTL, ON

TAXI CHART — CYOW

ATIS – **121.15** (En) **132.95** (Fr)	CLNC DEL – **119.4** GND – **121.9**	TWR – **118.8**




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OTTAWA/MACDONALD-CARTIER INTL, ON

CARTE DE CIRCULATION — CYOW

ATIS – **132.95** (Fr) **121.15** (Ang)	CLNC DEL – **119.4** GND – **121.9**	TWR – **118.8**



CARTE DE CIRCULATION — CYOW

EFF 5 OCT 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Gate De-icing – Originating Flights

1. Gate de-icing is approved for environmental frost under the following conditions:
   - Active precipitation is not forecasted for the operational period.
   - Apron conditions are such as to allow the recovery of spent fluid (no snow, ice, sand, gravel, etc.).
   - The required fluid to de-ice is optimal for the presenting frost and up to the minimum 1 litre/square metre.
   - Winds are light to variable (8 knots).
2. De-icing for originating flights will take place 60-90 minutes before scheduled departure time.
3. Staff will conduct initial inspection of acft to determine the requirement for de-icing and will proceed with spray if rqrd.
4. Airlines must ensure acft are configured and ready for de-icing prior to the above time. De-icing will take place under the assumption that originating flights are configured.
5. De-icing confirmation will be sent electronically or via fax to airline operations following de-icing. Flight crews requiring additional information may contact PAD CONTROL on 122.92.
6. No holdover time is provided for on gate de-icing.
7. The process of **"Pre-Spray"** (Lines 2-3) 60-90 mins before push is being reviewed due to frost regeneration (fall weather patterns with high humidity and close OAT/DP spread).
8. Unless requested of de-ice crews, the PIC is responsible for **"Pre-flight take off inspections."** Any treatments by de-ice crews for Pre-Sprays will be followed by an **"appropriate post de-ice inspection."** The **"Pre-Spray"** treatments 60-90 mins before push do not include a **"pre-take off"** inspection.

Gate De-icing – Turn Flights

1. All conditions of gate de-icing exist from above list.
2. De-ice crews will not interact with turn aircraft unless requested – Contact PAD CONTROL on 122.92 to arrange. There will be no pre-emptive contact with the aircraft without request for service. Pre-take off De-ice check remains with the flight crew unless a live spray is completed at pushback.

Centralized De-icing Facility Operations

1. Flow – North to South
   - Entry point is K or AA via Alpha. Acft must hold short of the CDF on the entry point and establish radio contact with PAD CONTROL on 122.92.

   Flow – South to North
   - Entry point is CC or BB via Alpha. Acft must hold short of the CDF on the entry point and establish radio contact with PAD CONTROL on 122.92.
2. Follow taxi instructions via East Line to Bays 1, 2, 3 via West Line Bays 4, 5, 6.
3. Aircraft will be staged on the East/West Line short of AA/BB when necessary.
4. When exiting CC/K – Acft must maintain listening watch on the E/W staging lines on 122.92 until reaching Twy A.

NOTE: Aircraft intended on returning to terminal gates after de-icing must drip dry for 25 minutes on CDF.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

De-icing Requirements

1. Wings and Stabs refers to the upper surfaces of the wings, upper/lower surface of the Horizontal Stabilizers and both sides (including rudder) of the Vertical Stabilizer.
2. Fuselage includes all components from the front cabin doors aft and Wings and Stabs.
3. Full Body includes the cockpit/radome plus Fuselage, Wings and Stabilizers.
4. Individual treatments like “inspections only”, “radome”, “winglets” can be done upon request.
5. Hard leading edges tactiles/underwing inspections and treatments may require engine shut down if inlet is in close proximity to surface requiring attention.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


OTTAWA/MACDONALD-CARTIER INTL, ON

DE-ICING OPERATIONS

CYOW

ATIS – **121.15** (En)
132.95 (Fr)

GND – **121.9**
PAD CTL – **122.92**
ICEMAN – **122.35**



DE-ICING OPERATIONS

1. Ctc PAD CONTROL on 122.925 30 min prior to dep if de-icing is rqrd. Notify of any special treatments prior to taxi to CDF.
2. Ctc Ottawa GND after pushback for taxi to CDF.
3. Hold short of the CDF on K, AA, BB or CC and ctc PAD CONTROL for further taxi.
4. Follow instructions and electronic sign boards to de-icing bays.
5. Stop on the 2nd (illuminated) yellow stop bar, immediately set brakes and advise PAD CONTROL. DO NOT MOVE ACFT. This will allow positioning of trucks while you configure your aircraft.
6. Once instructed switch to ICEMAN on 122.350, confirm brakes are set, confirm treatment and that acft is configured for treatment (engines at idle/props feathered/pacs off). If you can't reduce engines to idle ICEMAN must know, de-icing may not be possible with running engines.
7. After de-icing, configure acft for taxi, however, DO NOT MOVE ACFT.
8. Once instructed, ctc PAD CONTROL for taxi.
9. Follow instructions to designated exit point. Holding short of Twy A, ctc GND 121.9.

TYPE 1 - All Clear Lift-Off E188

TYPE IV - UCAR ADF ENDURANCE EG106 100%

BAY RESTRICTIONS

Bay 1, 3, 4, 6 - May be used by acft with wingspans 36m (118') or less.

Bay 2 - May be used by acft with the wingspans 65m (213') or less. If CC/K used, the Taxi must be on the West taxi line only with crossover to/from Bay 2.

Bay 5 - May be used by acft with the wingspan 80m (262') or less. If CC/K used, taxi must be on the west taxi line only with crossover to/from Bay 5.

AD HOC FLIGHTS

1. Obtain a projected acceptance time for de-icing from PAD CONTROL on 122.925 or via phone 613-248-0228 .
2. Submit Authorization form via fax 613-248-0860 or via e-mail YOW_InlandOps@Inlandgroup.ca.
3. An estimate of litres required will be provided to flight crew.
4. Ad hoc aircraft not abiding by the above may be denied service at the CDF.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Dégivrage à la barrière – vols cédulés

1. Le dégivrage aux portes d'embarquement est approuvé pour le givre dans les conditions suivantes :
   - Les précipitations actives ne sont pas prévues pour la période opérationnelle.
   - Les conditions du tablier sont telles qu'elles permettent de récupérer le fluide usé (pas de neige, de glace, de sable, de gravier, etc.).
   - Le liquide de dégivrage requis est optimal pour le givre présent et ce, jusqu'à un minimum de 1 litre / mètre carré.
   - Les vents sont de légers à variables (8 nœuds).
2. Dégivrage pour les vols cédulés aura lieu 60 – 90 minutes avant l'heure de départ cédulé.
3. Technicien doit faire une inspection initiale de l'appareil pour déterminer les besoins en dégivrage et vont procéder au dégivrage si requis.
4. Les sociétés aériennes doivent s'assurer que l'appareil est configuré et prêt pour le dégivrage. Le dégivrage va avoir lieu en prenant compte que les vols cédulés sont configurés.
5. La confirmation de dégivrage sera envoyée électroniquement ou par fax à la société aérienne après le dégivrage. L'équipage requérant de l'information additionnelle peut contacter CTL DÉGIVRAGE sur 122.92.
6. Aucun temps d'efficacité n'est fourni pour le dégivrage à la barrière.
7. Le processus de **« Pré-application »** (lignes 2-3), 60-90 minutes avant le refoulement est en cours de révision en raison de la régénération du givre (conditions météorologiques automnal, incluant une forte humidité et une relation étroite entre la TAE / PR).
8. À moins que les équipes de dégivrage ne le demandent, le commandant de bord est responsable des **« inspections avant le décollage »**. Tout traitement effectué par les équipes de dégivrage pour les pré-applications sera suivi d'une **« inspection post-dégivrage appropriée »**. Les traitements de **« pré-application »** de 60 à 90 minutes avant le refoulement n'incluent pas une inspection de **« pré-décollage »**.

Dégivrage à la barrière – vols en transit

1. Toutes les conditions de dégivrage aux portes d'embarquement existent depuis la liste ci-dessus.
2. Les équipes de dégivrage n'interagiront pas avec le virage des avions à moins que cela ne soit demandé – Contactez PAD CONTROL sur 122.92 pour organiser la manoeuvre. Il n'y aura pas de contact préventif avec l'aéronef sans demande de service. La vérification de dégivrage avant le décollage demeure à l'équipage de l'aéronef à moins qu'une application directe soit complétée au refoulement.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Opération au centre de dégivrage

1. Circulation – Nord vers Sud
   - Point d'entrée est K ou AA via Apha. L'appareil doit se tenir à l'écart du CDF au point d'entrée et établir le contact radio avec CTL DÉGIVRAGE sur 122.92.

   Circulation – Sud vers Nord
   - Points d'entrée est CC ou BB via Alpha. L'appareil doit se tenir à l'écart du CDF au point d'entrée et établir le contact radio avec CTL DÉGIVRAGE sur 122.92.
2. Suivre les instructions pour le taxi via la ligne Est pour les baies 1,2,3 ou via la ligne Ouest pour les baie 4,5,6.
3. L'appareil sera mis en attente sur la ligne Est/Ouest à l'écart de AA/BB lorsque nécessaire.
4. À la sortie de CC / K – L'aéronef doit rester attentif aux lignes d'arrêt E / W et au 122.92 jusqu'à ce qu'il atteigne le Twy A.

Note : L'appareil qui doit retourner à la barrière doit rester au CDF pendant 25 minutes afin d'assécher l'appareil

Besoins en dégivrage

1. Ailes et Stabilisateurs se réfère aux surfaces supérieures des ailes, aux surfaces supérieures / inférieures des Stabilisateurs Horizontaux et des deux côtés (y compris le gouvernail) du Stabilisateur Vertical.
2. Le Fuselage comprend toutes les composantes, des portes de cabine avant vers l'arrière ainsi que les Ailes et Stabilisateurs.
3. L'appareil complet comprend la cabine de pilotage, le radôme ainsi que le Fuselage et les Ailes et Stabilisateurs.
4. Des traitements individuels tels que « inspections seulement », « radôme », « ailettes » peuvent être effectués sur demande.
5. Les inspections tactiles et les traitements sous les ailes peuvent nécessiter la fermeture d'un moteur si l'entrée est à proximité de la surface nécessitant une attention.


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

OTTAWA/MACDONALD-CARTIER INTL, ON

OPÉRATIONS DE DÉGIVRAGE CYOW

ATIS – **132.95** (Fr) **121.15** (Ang)

GND – **121.9**
PAD CTL – **122.92**
ICEMAN – **122.35**



1. Ctc CTL DÉGIVRAGE 122.925 30 min avant le dép si dégivrage est requis. SVP aviser de tout traitement spécial avant de rouler à l'installation centrale de dégivrage.
2. Ctc Ottawa SOL, après refoulement pour circuler au CDF.
3. Rester à l'écart du CDF sur K, AA, BB ou CC et ctc CTL DÉGIVRAGE pour circuler.
4. Suivez les instructions et les panneaux électroniques pour procéder à la baie de dégivrage.
5. Arrêtez-vous sur la deuxième barre d'arrêt jaune (éclairée), actionnez immédiatement les freins et confirmez avec PAD CONTROL. NE PAS BOUGER l'AÉRONEF. Cela permettra de positionner les camions pendant que vous configurez votre avion.
6. Une fois qu'on vous le demande, passez à ICEMAN au 122.350. Confirmez que les freins sont serrés, le traitement désiré et que votre avion est configuré pour le traitement (Moteurs au ralenti / hélices mises en drapeau). Si vous ne pouvez pas réduire les moteurs au ralenti, avisez ICEMAN, il se peut que le dégivrage ne soit possible avec les moteurs en marche.
7. Après dégivrage, configurez l'appareil pour circuler, toutefois, NE PAS BOUGER L'APPAREIL.
8. Une fois avisé, ctc CTL DÉGIVRAGE pour circuler.
9. Suivre les instructions pour le point de sortie désigné. À l'écart de la voie de circulation A ctc SOL 121.9.

TYPE 1 - All Clear Lift-Off E188	TYPE IV - UCAR ADF ENDURANCE EG106 100%

RESTRICTIONS DES BAIES DE DÉGIVRAGE

Baies 1, 3, 4, 6 - Peuvent être utilisées par les aéronefs d'envergure de 36m (118') ou moins

Baie 2 - Peut être utilisé par un aéronef ayant une envergure de 65m (213 pi) ou moins. Si CC / K est utilisé, le taxi doit être sur la ligne de taxi Ouest uniquement avec un croisement vers / depuis la baie 2.

Baie 5 - Peut être utilisé par un aéronef ayant une envergure de 80m (262 pi) ou moins. Si CC/K est utilisée, le taxi doit être sur la ligne de taxi Ouest uniquement avec un croisement vers/de la baie 5.

VOLS AD HOC

1. Obtenir une heure projetée pur le dégivrage en contactant CTL DÉGIVAGE sur 122.925 ou par téléphone au 613-248-0228.
2. Soumettre le formulaire d'autorisation par fax au 613-248-0860 ou par courriel à YOW_inlandOps@Inlandgroup.ca.
3. Un estimé des litres de glycol requis sera transmis à l'équipage.
4. Un vol AD HOC ne se conformant pas à la procédure ci-haut mentionné, peut se voir refuser l'accés au centre de dégivrage.

OPÉRATIONS DE DÉGIVRAGE CYOW

EFF 23 FÉV 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

PARKING AREAS (APRON I)

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

CYOW

EFF 14 JUL 22

OTTAWA/MACDONALD-CARTIER INTL, ON

PARKING AREAS (APRON II)

CYOW

ATIS – **121.15** (En) **132.95** (Fr)

CLNC DEL – **119.4**

GND – **121.9**

FOR GATE ASSIGNMENT – **122.4**

PARKING AREAS (APRON II)

CYOW

EFF 23 FEB 23

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	451924.63N 0754009.54W	22	451914.35N 0753958.30W
2	451925.41N 0754010.91W	23	451916.59N 0753953.78W
3	451925.75N 0754012.03W	24	451913.55N 0753956.76W
4	451925.24N 0754012.76W	25	451915.52N 0753951.86W
5	451924.33N 0754013.41W	26	451912.76N 0753955.23W
6	451923.71N 0754014.08W	27	451914.48N 0753950.87W
11	451922.52N 0754013.87W	28	451912.56N 0753953.96W
12	451921.98N 0754012.88W	29	451913.62N 0753951.25W
12A	451922.26N 0754011.86W	29B	451913.07N 0753950.35W
13	451921.23N 0754011.33W	30	451913.28N 0753952.66W
14	451920.37N 0754009.32W	40	451914.50N 0753943.93W
14A	451920.71N 0754009.34W	40A	451914.98N 0753943.93W
15	451919.16N 0754006.84W	41	451915.20N 0753942.36W
15A	451919.43N 0754006.43W	42	451915.91N 0753940.78W
16	451918.14N 0754005.01W	42A	451916.02N 0753941.60W
17	451917.36N 0754003.51W	43	451916.62N 0753939.22W
17A	451918.05N 0754003.73W	43A	451917.05N 0753939.32W
18	451916.38N 0754002.17W	50	451925.44N 0754019.54W
19	451918.23N 0753957.43W	50A	451926.06N 0754019.69W
20	451915.71N 0753959.82W	50B	451924.77N 0754020.73W
21	451917.30N 0753955.62W		

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OTTAWA/MACDONALD-CARTIER INTL, ON

AIRES DE STATIONNEMENT (AIRE DE TRAFIC I) CYOW

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT (AIRE DE TRAFIC I) CYOW

OTTAWA/MACDONALD-CARTIER INTL, ON

AIRES DE STATIONNEMENT (AIRE DE TRAFIC II) CYOW

ATIS – **132.95** (Fr) **121.15** (Ang)

CLNC DEL – **119.4**

GND – **121.9**

POSITIONNEMENT – **122.4**

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT (AIRE DE TRAFIC II) CYOW

EFF 23 FÉV 23

Poste de stationnement d'aéronef

Position	Coordonnées	Position	Coordonnées
1	451924.63N 0754009.54W	22	451914.35N 0753958.30W
2	451925.41N 0754010.91W	23	451916.59N 0753953.78W
3	451925.75N 0754012.03W	24	451913.55N 0753956.76W
4	451925.24N 0754012.76W	25	451915.52N 0753951.86W
5	451924.33N 0754013.41W	26	451912.76N 0753955.23W
6	451923.71N 0754014.08W	27	451914.48N 0753950.87W
11	451922.52N 0754013.87W	28	451912.56N 0753953.96W
12	451921.98N 0754012.88W	29	451913.62N 0753951.25W
12A	451922.26N 0754011.86W	29B	451913.07N 0753950.35W
13	451921.23N 0754011.33W	30	451913.28N 0753952.66W
14	451920.37N 0754009.32W	40	451914.50N 0753943.93W
14A	451920.71N 0754009.34W	40A	451914.98N 0753943.93W
15	451919.16N 0754006.84W	41	451915.20N 0753942.36W
15A	451919.43N 0754006.43W	42	451915.91N 0753940.78W
16	451918.14N 0754005.01W	42A	451916.02N 0753941.60W
17	451917.36N 0754003.51W	43	451916.62N 0753939.22W
17A	451918.05N 0754003.73W	43A	451917.05N 0753939.32W
18	451916.38N 0754002.17W	50	451925.44N 0754019.54W
19	451918.23N 0753957.43W	50A	451926.06N 0754019.69W
20	451915.71N 0753959.82W	50B	451924.77N 0754020.73W
21	451917.30N 0753955.62W		


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

OTTAWA/ROCKCLIFFE, ON

AERODROME CHART — CYRO

			UNICOM – **123.5** ATF	TML Ottawa – **128.17** RADIO Gatineau – **122.3**

DECL DISTS	09	27	09	27				
TORA	3319	3319	1783	1783				
TODA	3319	3319	1783	1783				
ASDA	3319	3319	1783	1783				
LDA	3119	3105	1783	1783				



***** DEPARTURE PROCEDURE

Rwy 27 - ½ - Requires minimum climb gradient of **280** ft/NM to **2500**. Climb hdg **273°** to **2500** BPOC.
Note: Trees to 219 ft ASL aprx 342' from departure end of runway.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1400** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
280 FT/NM	420	560	660	750	840	940	1170	1400

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 09: NOT ASSESSED Rwy 27: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OWEN SOUND/BILLY BISHOP REGIONAL, ON


AERODROME CHART — CYOS

UNICOM – **123.0** (AU)

ATF

CTR Toronto – **132.57**

DECL DISTS	18	36
TORA	3933	3933
TODA	3933	4917
ASDA	3933	3933
LDA	3933	3933



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


PARRY SOUND AREA MUNICIPALITY, ON

AERODROME CHART — CNK4

UNICOM – **122.8**

RADIO London – **123.47** ATF

DECL DISTS	17	35
TORA	4901	4901
TODA	4901	4901
ASDA	4901	4901
LDA	4901	4901



* DEPARTURE PROCEDURE

Rwy 17 - ½

Note: Hangars to 855 ASL abeam departure end of rwy, 300' LEFT and 390' RIGHT of runway centerline.

Rwy 35 - ½

Note: Trees at 857 ASL abeam departure end of runway, 350' LEFT of runway centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 17; 35: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PEAWANUCK, ON

AERODROME CHART — CYPO

AWOS – **128.52**		TFC – **122.8** ATF	RADIO London – **123.27**

DECL DISTS	11	29
TORA	3520	3520
TODA	3520	3520
ASDA	3520	3520
LDA	3520	3520



***** DEPARTURE PROCEDURE

Rwy 11 - ½
Note: Trees to 210 ASL abeam departure end of rwy, 250' LEFT and RIGHT of rwy centreline.

Rwy 29 - ½
Note: Trees to 217 ASL abeam departure end of rwy, 250' LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA
All Rwys: *****

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPO

EFF 5 OCT 23


PELEE ISLAND, ON

AERODROME CHART — CYPT

CTR Cleveland – **126.35 360.0**

TFC – **123.2** ATF

DECL DISTS	10	28	01	19				
TORA	3303	3303	2113	2113				
TODA	3303	4203	2113	2113				
ASDA	3303	3303	2113	2113				
LDA	3303	3303	1813	2113				



TAKE-OFF MINIMA

Rwy 10: *
Rwy 28: ½

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPT


EFF 25 APR 19

PEMBROKE, ON

AERODROME CHART — CYTA

			ADVSY Petawawa – **126.4** **250.1** UNICOM – **122.8** (AU) ATF	CTR Montreal – **135.2**

DECL DISTS	17	35
TORA	5000	5000
TODA	5700	5900
ASDA	5000	5000
LDA	5000	5000



* DEPARTURE PROCEDURE

Rwy 17 - ½ -
Climb between hdg **022°**
CW to **260°** to remain clear of CYR511, CYR512 and CYR544.
When CYR540 and/or CYR542 active:
Climb between hdg **022°** CW to **230°**
to remain clear of CYR511, CYR512, CYR544, CYR540 & CYR542.
Note: Trees to 623 ASL aprx 850' past departure end of rwy, 300' LEFT and RIGHT of centreline.

Rwy 35 - SPEC VIS - Restricted to Categories A, B and C. Climb in visual conditions to cross the arpt at or above **1200** (CAT A, B) **1300** (CAT C). Remain clear of CYR511, CYR512 and CYR544 BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 17, 35: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PETERBOROUGH, ON

AERODROME CHART — CYPQ

AWOS – **126.92**	UNICOM – **123.0** MF	CTR Toronto – **134.25**

DECL DISTS	09	27	13	31				
TORA	7005	7005	2000	2000				
TODA	7300	7300	2000	2000				
ASDA	7005	7005	2000	2000				
LDA	7005	7005	2000	2000				



* DEPARTURE PROCEDURE

Rwy 09 - ½ - Requires a minimum climb gradient of **260** ft/NM to **900**.
NO LEFT turn below **1500**.
Note: Trees to 718 ASL aprx 0.1 NM past departure end of rwy, 550' RIGHT of rwy centreline and aprx 0.3 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700** BPOC.

Rwy 27 - ½
Note: Trees to 755 ASL abeam departure end of rwy, 300' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: * Rwys 13; 31: NOT ASSESSED	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


PICKLE LAKE, ON

AERODROME CHART

CYPL

AWOS – **127.67**		RADIO Thunder Bay – **122.2** TFC – **122.2** MF	RADIO London – **123.47**

DECL DISTS	09	27
TORA	5217	5217
TODA	6201	6201
ASDA	5217	5217
LDA	5217	5217



* DEPARTURE PROCEDURE

Rwy 09 - ½

Note: Trees to 1329 ASL aprx 0.4NM past departure end of rwy, 350° RIGHT of centreline and 650' LEFT of centreline. Power line to 1377 ASL aprx 1NM past deprture end of rwy, 1550' LEFT of centreline.

TAKE-OFF MINIMA
Rwy 09: * Rwy 27: ½

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


PIKANGIKUM, ON

AERODROME CHART — CYPM

CTR Winnipeg – **135.32**

TFC – **122.8** ATF

DECL DISTS	09	27
TORA	3508	3508
TODA	4492	4492
ASDA	3508	3508
LDA	3508	3508



TAKE-OFF MINIMA
Rwys 09; 27:*

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

POPLAR HILL, ON


AERODROME CHART — CPV7

CTR Winnipeg – **135.32**

TFC – **122.8**

ATF

DECL DISTS	13	31
TORA	3508	3508
TODA	3508	3508
ASDA	3508	3508
LDA	3508	3508



TAKE-OFF MINIMA
Rwys 13, 31: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CPV7

EFF 27 JAN 22


PORT CARLING/FIG AIR, ON

HELIPORT CHART

CFA2

			CTR Toronto – **124.02**
		TFC – **122.8** ATF	

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	2000 0 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RED LAKE, ON

AERODROME CHART — CYRL

			◕ RADIO Kenora – **122.3** ◕ TFC – **122.3** MF				CTR Winnipeg – **135.32** RADIO London – **123.55**	

DECL DISTS	08	26						
TORA	5001	5001						
TODA	5985	5395						
ASDA	5001	5001						
LDA	5001	5001						



* DEPARTURE PROCEDURE

Rwy 08 - ½
Note: Trees to 1380 ASL aprx
300' past departure end of rwy,
550' LEFT and RIGHT of rwy centreline.

Rwy 26 - ½
Note: Trees to 1376 ASL aprx
200' past departure end of rwy,
550' LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 08; 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ROUND LAKE (WEAGAMOW LAKE), ON

AERODROME CHART — CZRJ

TFC – **123.2** ATF

DECL DISTS	03	21
TORA	3613	3613
TODA	4597	4597
ASDA	3613	3613
LDA	3613	3613



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03; 21: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SACHIGO LAKE, ON

AERODROME CHART — CZPB

TFC – **123.2** ATF

DECL DISTS	10	28
TORA	3506	3506
TODA	3506	3506
ASDA	3506	3506
LDA	3506	3506



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 1006 ASL within aprx 0.5 NM past departure end of rwy.

Rwy 28 - ½

Note: Trees to 992 ASL within aprx 0.7 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZPB

EFF 24 MAR 22


SANDY LAKE, ON

AERODROME CHART — CZSJ

AWOS – **124.82**

TFC – **122.8** ATF

DECL DISTS	11	29
TORA	3507	3507
TODA	3507	3507
ASDA	3507	3507
LDA	3507	3507



*DEPARTURE PROCEDURE

Rwy 11 - ½

Note: Trees to 955 ASL abeam departure end of rwy, 370' LEFT of rwy centreline.
Tower to 955 ASL 380' past departure end of rwy, 460' RIGHT of rwy centreline.

Rwy 29 - ½ - Requires a minimum climb gradient of **450** ft/NM to **1200**.
Note: Trees to 977 ASL abeam departure end of rwy, 500' both LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1500** BPOC.

TAKE-OFF MINIMA
Rwys 11; 29: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SARNIA (CHRIS HADFIELD), ON

AERODROME CHART — CYZR

AWOS – **119.12**		TFC – **123.0**	ATF	CTR Toronto – **134.37**

DECL DISTS	06	24	15	33
TORA	2990	2990	5106	5106
TODA	3482	3289	6090	5811
ASDA	2990	2990	5106	5106
LDA	2990	2990	5106	5106



* DEPARTURE PROCEDURE

Rwy 06 - ½
Note: Trees to 610 ASL abeam departure end of rwy, 500' RIGHT of rwy centreline and aprx 400' past departure end of rwy.

Rwy 15 - ½
Note: Trees to 629 ASL aprx 0.2 NM past departure end of rwy 500' LEFT of rwy centreline.
Trees to 686 ASL aprx 0.4 NM past departure end of rwy, 1000' LEFT and RIGHT of rwy centreline. Silos to 707 ASL aprx 0.7 NM past departure end of rwy, 550' RIGHT of rwy centreline.

Rwy 24 - ½
Note: Trees to 689 ASL aprx 300' past departure end of rwy.

Rwy 33 - ½
Note: Buildings to 633 ASL aprx 0.1 NM past departure end of rwy, 650' RIGHT of rwy centreline.
Trees to 645 ASL aprx 0.2 NM past departure end of rwy, 700' LEFT of rwy centreline.
Trees to 669 ASL aprx 0.4 NM past departure end of rwy, 800' RIGHT of rwy centreline

TAKE-OFF MINIMA
Rwys 06; 15; 24; 33: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZR


EFF 23 FEB 23

SAULT STE. MARIE, ON

AERODROME CHART — CYAM

ATIS – 133.05	GND – 121.7	TWR – 118.8	CTR Toronto – 132.65 344.5
		TFC – 118.8 MF*	

DECL DISTS	04	22	12	30				
TORA	6000	6000	6000	6000				
TODA	6984	6984	6984	6984				
ASDA	6000	6000	6000	6000				
LDA	6000	6000	6000	6000				



* DEPARTURE PROCEDURE
Rwy 04 - ½- NO LEFT turn below **1700**.
Note: Trees to 695 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT and RIGHT of rwy centreline.
Rwy 12 - ½-
Note: Trees to 726 ASL aprx 0.46 NM past departure end of rwy, 1000' LEFT and RIGHT of rwy centreline.
Rwy 22 - ½-
Note: Trees to 686 ASL aprx 0.42 NM past departure end of rwy, 900' LEFT and RIGHT of rwy centreline.
Rwy 30 - ½- NO RIGHT turn below **1300**.
Note: Trees to 646 ASL aprx 0.1 NM past departure end of rwy, 500' LEFT and RIGHT of rwy centreline.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 12: RVR 1200 RWY 30: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 12, 22, 30: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAM


EFF 10 AUG 23

SIOUX LOOKOUT, ON

AERODROME CHART — CYXL

ATIS – **124.75**		RADIO – **122.0**	CTR Winnipeg – **132.2** RADIO London – **126.0**
		MF	

DECL DISTS	16	34
TORA	5300	5300
TODA	6284	6000
ASDA	5300	5300
LDA	5002	5300



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 16; 34: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16; 34: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


SLATE FALLS, ON

AERODROME CHART

CKD9

			TFC – **123.2**			ATF	RADIO London – **126.0**	

DECL DISTS	10	28
TORA	3507	3507
TODA	3507	3507
ASDA	3507	3507
LDA	3507	3507



*DEPARTURE PROCEDURE

Rwy 10 - ½
Note: Trees to 1431 ASL aprx 0.4 NM past departure end of rwy, 800' RIGHT of rwy centreline.

Rwy 28 - ½
Note: Trees to 1424 ASL aprx 0.1 NM past departure end of rwy, 650' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwy 10; 28: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. CATHARINES/NIAGARA DISTRICT, ON

AERODROME CHART — CYSN

ATIS – **128.52**		RADIO – **123.25**	CTR Toronto – **133.4**
		TFC – **123.25** MF	RADIO London – **126.7**

DECL DISTS	01	19	06	24	11	29		
TORA	2498	2498	5000	5000	1988	1988		
TODA	2695	3348	5984	5197	2972	2185		
ASDA	2498	2498	5000	5000	1988	1988		
LDA	2498	2498	5000	5000	1988	1988		



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSN

EFF 12 AUG 21

ST. THOMAS MUNICIPALITY, ON

AERODROME CHART — CYQS


AUTO – **122.55**

◕ UNICOM – **122.7**

ATF

CTR Toronto – **135.3**

DECL DISTS	03	21	09	27	15	33		
TORA	2607	2607	5013	5013	2610	2610		
TODA	3591	3591	5997	5543	3594	3594		
ASDA	2607	2607	5013	5013	2610	2610		
LDA	2607	2607	5013	5013	2610	2610		



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQS

EFF 29 DEC 22

STRATFORD MUNICIPALITY, ON

AERODROME CHART


CYSA

UNICOM – **122.8**

ATF

CTR Toronto – **135.3**

DECL DISTS	05	23	17	35				
TORA	5003	5003	2699	2699				
TODA	5603	5987	2699	2699				
ASDA	5003	5003	2699	2699				
LDA	5003	3972	2699	2699				



* DEPARTURE PROCEDURE

Rwy 05 - ½
Note: Trees to 1261 ASL aprx 0.2 NM past departure end of rwy, 310' RIGHT of rwy centreline. Trees to 1261 ASL aprx 0.3 NM past departure end of rwy, 750' LEFT of rwy centreline.

Rwy 17 - ½
Note: Road to 1221 ASL abeam departure end of rwy, 520' LEFT of rwy centreline. Trees to 1264 ASL aprx 0.3 NM past departure end of rwy, 350' RIGHT of rwy centreline.

Rwy 23 - ½
Note: Tower to 1241 ASL aprx 0.2 NM past departure end of rwy, 340' LEFT of rwy centreline. Powerlines to 1241 ASL aprx 0.2 NM past departure end of rwy, 510' LEFT of rwy centreline.

Rwy 35 - ½
Note: Trees to 1258 ASL abeam departure end of rwy, 380' RIGHT of rwy centreline. Powerlines to 1231 ASL aprx 0.1 NM past departure end of rwy, 340' LEFT of rwy centreline. Powerlines to 1231 ASL aprx 0.1 NM past departure end of rwy, 120' RIGHT of rwy centreline.

TAKE-OFF MINIMA

All Rwys: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CYSA


EFF 27 JAN 22

STURGEON FALLS (WEST NIPISSING GEN HOSPITAL), ON

HELIPORT CHART — CNM3

		A/G Ambulance Dispatch – **129.27**	CTR Toronto – **127.25**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA

NOT ASSESSED

SCALE IN FEET

0 100 200 300


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SUDBURY, ON

AERODROME CHART — CYSB

ATIS – **127.4**	CLNC DEL – **121.8**	RADIO – **125.5**	CTR Toronto – **135.5**
		MF*	

DECL DISTS	04	22	12	30				
TORA	6600	6600	5000	5000				
TODA	7584	7584	5984	5984				
ASDA	6600	6600	5000	5000				
LDA	6600	6600	5000	5000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 04, 22: RVR 1200 (1/4sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04; 12; 22; 30: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SUMMER BEAVER, ON

AERODROME CHART — CJV7

TFC – **123.2** ATF

DECL DISTS	17	35
TORA	3509	3509
TODA	4493	4009
ASDA	3509	3509
LDA	3509	3509



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CJV7


EFF 19 MAY 22

THUNDER BAY, ON

AERODROME CHART — CYQT

ATIS – **128.8**	GND – **121.9**	TWR – **118.1** RADIO – **118.1** MF*	TML – **119.2** RADIO London – **122.37**

DECL DISTS	07	25	12	30				
TORA	7318	7318	5297	5126				
TODA	7702	8220	5797	5626				
ASDA	7318	7318	5297	5126				
LDA	7318	7318	5297	5126				



LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)		
FROM	TO	LDA in ft
Thld rwy 25	Short of rwy 12-30	5770

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07: RVR 1200 RWY 12, 25, 30: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07; 12; 25; 30:*	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

THUNDER BAY, ON

PARKING AREAS

CYQT

PARKING AREAS

CYQT

EFF 5 NOV 20

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1B	482217.78N 0891847.56W	3B	482222.20N 0891843.42W
1C	482218.44N 0891847.55W	4	482221.51N 0891841.70W
1D	482217.61N 0891848.07W	4A	482221.84N 0891841.74W
1E	482216.32N 0891848.11W	5	482222.93N 0891840.12W
1F	482217.16N 0891847.16W	6	482224.27N 0891840.57W
2A	482219.47N 0891846.12W	7	482224.68N 0891841.37W
2B	482220.48N 0891845.78W	8	482225.10N 0891842.18W
3A	482221.25N 0891844.20W	10	482219.40N 0891853.46W

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TILLSONBURG, ON


AERODROME CHART — CYTB

UNICOM – **123.0**

ATF

CTR Toronto – **135.3**

DECL DISTS	02	20	08	26	14	32		
TORA	2348	2348	5502	5502	2258	2258		
TODA	2348	2348	5502	6486	2258	2258		
ASDA	2348	2348	5502	5502	2258	2258		
LDA	2248	2248	5502	4502	1958	2158		



TAKE-OFF MINIMA

Rwys 08; 26: *
Rwys 02; 14; 20; 32: NOT ASSESSED

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TIMMINS (VICTOR M. POWER), ON

AERODROME CHART — CYTS

ATIS – **124.95**		RADIO – **122.3** MF	CTR Toronto – **128.3**

DECL DISTS	03	21	10	28				
TORA	6000	6000	4907	4907				
TODA	6600	6984	5891	5891				
ASDA	6000	6000	4907	4907				
LDA	6000	6000	4907	4907				



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYTS


EFF 3 JAN 19

TORONTO/BILLY BISHOP TORONTO CITY AIRPORT, ON

AERODROME CHART — CYTZ

ATIS – **133.6** AWOS – **133.6**	GND – **121.7**	TWR City – **119.2 118.2** TFC – **118.2** ATF*	TML Toronto – **133.4**

DECL DISTS	06	24	08	26				
TORA	2460	2460	3988	3988				
TODA	2460	2910	4338	4338				
ASDA	2460	2460	3988	3988				
LDA	2460	2460	3988	3988				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08, 26: RVR 1200	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 24, 26: * Rwys 06: NOT ASSESSED	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYTZ

EFF 22 APR 21

Toronto/Buttonville Initial Take-Off Area (ITOA)

Purpose

The purpose of this notice is to allow aircraft operators at Toronto/Buttonville Municipal Airport to:

1. Utilize the 161' of paved strip end portion prior to the threshold of Runway 15 for aircraft take-off manoeuvers;
2. Use the new declared distances terminology stated below in order to take into consideration the area prior to the threshold of Runway 15, and;
3. The 161' of paved strip end portion has the same pavement bearing strength as the runway, exceeds the runway width due to the extension of the fillet from taxiway D and is maintained to the same standard as the runway.The subject area is referred to as the Initial Take-Off Area (ITOA) and is defined below.

Visual Aids

The area for runway 15 that can be used for departure operations is marked with a white transverse stripe, located 161' from the end of the pavement. This defines the limits of the usable length for aircraft operations. Six (6) red, unidirectional and medium intensity edge lights outline the 161' paved area. Runway 15 end lights have been inset.

The expanded taxiway adjoining the threshold of Runway 15 allows the pilot to either enter the pre-threshold Initial Take-Off Area (ITOA), just north of the white transverse stripe (at the actual runway threshold) or, taxi directly onto the runway at the original threshold.

Definitions

Initial Take-Off Area (ITOA): A prepared area prior to a threshold, which is available for aircraft take-off manoeuvres as a supplemental distance to the TORA, TODA and ASDA. The new declared distances that will include the ITOA shall be declared as ETORA, ETODA, EASDA (the prefix E means Extended). This extended distance shall not be applied to any declared landing distance available for the reciprocal runway.

Extended Take-Off Run Available (ETORA): The length of the runway declared available and suitable for the ground run of an airplane taking-off, including the Initial Take-Off Area (ITOA).

Extended Take-Off Distance Available (ETODA): The length of the take-off run available, including the Initial Take-Off Area (ITOA), plus the length of the clearway, if provided.

Extended Accelerate-Stop Distance Available (EASDA): The length of the take-off run available, including the Initial Take-Off Area (ITOA), plus the length of the stopway, if provided.

Declared Distances - CYKZ - Rwy 15

Extended Take-Off Run Available (ETORA) - **4058**.

Extended Take-Off Distance Available (ETODA) - **4258**.

Extended Accelerate-Stop Distance Available (EASDA) - **4058**.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/BUTTONVILLE MUNICIPAL, ON


AERODROME CHART — CYKZ

TML Toronto – **133.4**
Radio London – **123.15**

TFC – **124.8**

MF*

DECL DISTS	03	21	15	33				
TORA	2694	2694	3897	3897				
TODA	2794	2794	4097	4097				
ASDA	2694	2694	3897	3897				
LDA	2694	2694	3897	3897				



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03, 15, 21, 33 : *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKZ

EFF 28 FEB 19

TORONTO/DOWNSVIEW, ON

AERODROME CHART — CYZD

AUTO – **122.97**		UNICOM – **126.2**	TML Toronto – **133.4**
			MF*

DECL DISTS	15	33
TORA	7003	7003
TODA	7803	7987
ASDA	7003	7003
LDA	7003	7003


DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300
300 FT/NM	450	600	700	800	900	1000	1250	1500

* DEPARTURE PROCEDURE

Rwy 15 - ½ - Requires a minimum climb gradient of **300** ft/NM to **2600**. Climb hdg **153°** to **2600** BPOC.
Note: Road to 670 ASL 200' past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.

Rwy 33 - ½ - Requires a minimum climb gradient of **260** ft/NM to **1600**.
Note: Building to 683 ASL 850' past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 15, 33: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15; 33: *	1000 0 1000 2000 3000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/LESTER B. PEARSON INTL, ON

AERODROME CHART — CYYZ

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**	DEP – **128.8 127.57**

DECL DISTS	05	23	06L	24R	06R	24L	15L	33R	15R	33L
TORA	10775	10775	9697	9589	9000	8898	10886	11050	9088	9078
TODA	10895	11850	10484	10681	9984	10800	12034	12034	10072	10072
ASDA	10775	10775	9697	9589	9000	8898	10886	11050	9088	9078
LDA	10640	10089	9697	9392	9000	8898	10886	11050	8500	8490



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	2000 0 2000 4000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYZ

EFF 10 AUG 23

LDA for High Intensity Runway Operations				
From threshold rwy:	To exit point	LDA in ft	Preferred exit for med/heavy jet transport	Preferred exit for prop/turboprop transport
05	15R F P H3 15L B	5030 5630 6570 6670 8536 9278	H3	H3
06L	C1 C3	4790 6797	C3	C1
06R	D1 D3 D5	4424 5682 7483	D3 D5	D1
15L	B4 R S B1 B3	4050 5118 6154 6500 8250	B1 B3	B1
15R	F1	6276	F1	F1
23	H3 P F 15R H2 H4 J2	3427 3516 4449 5064 5176 6593 7577	H2 H4	H2
24L	D2 D4 D8	4061 5682 7883	D4 D8	D2
24R	C2 C4	5090 6984	C2 C4	C2
33L	F2 F4 H 05	4860 6060 6680 7424	F2 F4	F2
33R	B3 B1 S/B2 R B4 H 23	2805 4550 4895 5920 6994 9160 9900	B2 B4	B2

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


When authorized by ATC, intersection departures are available as follows:

RUNWAY	INTERSECTION	RUNWAY REMAINING
05	J2 H4 H6	8120 7129 10512
06L	D4 C4	7763 7182
06R	D8 D4 Y	7883 5682 4401
15L	H N B4	8996 7766 6841
15R	H F4	7270 6633
23	H/J B	10246 9058
24L	D5 Y W	7381 4753 6567
24R	D5 C3	7973 6693
33L	F1	6854
33R	V T B3	10669 9219 8251

Departures from holding bay inner centerlines rwy 06L/D6, 24R/C5 and 05/H6 subtract 263' from declared distances.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Notes

Twy “K” is uncontrolled and is restricted to aircraft with wingspans of 41.15m/135ft (B757W) or less and an Aircraft Load Rating of 9.0 or less. Other aircraft may be authorized with prior approval from operator (416) 776-3056.

Discretionary oversteering required for aircraft with wingspans 38m/124ft (B757) or greater:

- Rwy 06L onto “E”, “D3” and “D5”.
- Rwy 24R onto “D3”, “E”, “D4” and “D10/D8 southbound”.

A340-500/600, A350-900/1000, B777-300, and A380 discretionary oversteering required at all intersections.

Specific aircraft operations plan in effect for aircraft with wingspans 65m/214ft up to 79.9m/262ft. Restrictions in place include;

- No holding short of Runway 06L/24R after exit from Runway 06R/24L.
- Aircraft (as defined above) operations on any parallel taxiway system, such as Alpha-Bravo, Charlie-Delta, or Delta-Victor (Alpha to Echo), restrict operations on adjacent taxiway to aircraft with wingspans less than 36m.
- Strict adherence to taxiway centre line is required all times.
- Discretionary oversteering is required at all intersections.
- No taxiing on apron taxi lane between AJ and AK (between gates C31-C34).
- No taxiing on apron taxi lane between AJ and AT (between gates B15-B18).
- No turns from twy E onto CDF Pads 1 through 6.
- When aircraft on CDF taxilane 5, CDF taxilane 6 restricted to A320 or smaller (wingspan of 34.1m) and vice versa.The same applies to taxilanes 7 and 8, and vice versa.
- No taxiing on twy D between twy D4 and twy E.
- No taxiing on twy B between rwy 05/23 and twy J.
- When aircraft taxiing within Holding Bays rwys 06L/24R/05, adjacent parallel taxilane restricted to aircraft with wingspans less than 36m.
- Tow only authorized onto parking stands H1 and H6.

While taxiing on twy V (Pad 1) and twy T (Pad 5) through the CDF strict adherence to the centreline is required. When in contact with ATC use Centre Lane. When in contact with Pad Control or Iceman, use assigned Lane. Pad 1 (twy V) and Pad 5 (twy T) Centre Lane will accommodate aircraft with wingspans 79.9m/261ft and smaller. Aircraft with wingspans less than 36m may use North/South Lanes.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Hot Spots

Note: HS 4 to 8 - Short distance between parallel runways. Manage your taxi speed. Expect to hold short of parallel runway.

HS 1 – Taxiing northbound on rwy 33R aircraft fail to hold short of and incur on rwy 05/23.

HS 2 – Taxiing northbound on twy B aircraft miss turn onto twy H and incur on rwy 05/23.

HS 3 – Taxiing eastbound on twy H aircraft continue onto twy Q and incur on rwy 23.

HS 4 – Exiting rwy 24L onto twy D8 aircraft fail to hold short of and incur on rwy 06L/24R.

HS 5 – Exiting rwy 24L onto twy D4 aircraft fail to hold short of and incur on rwy 06L/24R.
Note: Angled rwy hold position in effect on twy D4 south of rwy 06L/24R.

HS 6 – Exiting rwy 06R onto twy D3 aircraft fail to hold short of and incur on rwy 06L/24R.

HS 7 – Exiting rwy 06R onto twy D5 aircraft fail to hold short of and incur on rwy 06L/24R.
Note: Angled rwy hold position in effect on twy D5 south of rwy 06L/24R.

HS 8 – Taxiing southbound on twy D7 aircraft fail to hold short of the 24L approach hold line and incur on rwy 06R/24L.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/LESTER B. PEARSON INTL, ON

TAXI CHART

CYYZ

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAXI CHART CYYZ

EFF 10 AUG 23

Low Visibility Procedures (RVR less than 1200 to 600 ft)

Application

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast:

"LOW VISIBILITY PROCEDURES IN EFFECT"

General

Low Visibility Taxi Routes

Typical taxi routes are shown on the Low Visibility Taxi Charts. Taxiway surfaces are painted with enhanced yellow and black centerline markings. In addition, taxiways A, C, F, H, J, N, T, P, R, S, V, E, D, B, T1, and T3 aprons are equipped with green centreline lights. Yellow in-set taxiway intersection lights that consist of three lights spaced 1.5 meters apart at 90 degrees to the direction of travel are located at taxiway/taxiway intersections and apron entry/exit points coincident with lighted locations signs. Aircraft may be directed to hold or report by any of these positions.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area. In the event of an ASDE failure, ATC may suspend, restrict or terminate low visibility operations.

Departures

When low visibility procedures are in effect the Departure runways are 05, 06L and 33R. Intersection take-offs from 06L are not authorized. Intersection take-offs on 33R from Victor Taxiway and on 05 from H6 may be assigned by ATC.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

Stop Bar/Guard Light system

Each taxiway entrance onto runways 05, 06L and 33R is equipped with a stop bar consisting of red in-set lights and red elevated lights located at the taxi holding position. Yellow flashing runway guard lights (wig-wags) are installed at each end of the stop bar. When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.

"AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR"

Arrivals

When low visibility procedures are in effect the Arrival runways are 05 and 06L. For 05, approved exits are Taxiways F (northbound), H3, B, H/J and Q. For 06L, approved exits are Taxiways C1, C3 and C7. Aircraft exiting either runway must proceed beyond the alternating green and yellow centreline lights to ensure the aircraft is clear of the runway and the ILS sensitive area.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART

TORONTO/LESTER B. PEARSON INTL, ON

CYYZ

LAND RWY 05, DEPART RWY 05 (RVR LESS THAN 1200 TO 600 FT)

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



NOTE:
Alternate routing may be assigned by ATC as required.

Aircraft engine run ups cannot commence during Low Visibility conditions.

Multilateration:
Pilots must keep their transponder on at all times when maneuvering on the aprt, turned on prior to brake release and on arrival, on until final engine shutdown. Pilots that do not have a transponder code issued by ATC must squawk 1000 when taxiing.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART

LAND RWY 06L, DEPART RWY 06L (RVR LESS THAN 1200 TO 600 FT)

TORONTO/LESTER B. PEARSON INTL, ON

CYYZ

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



NOTE:
Alternate routing may be assigned by ATC as required.

Aircraft engine run ups cannot commence during Low Visibility conditions.

Multilateration:
Pilots must keep their transponder on at all times when maneuvering on the aprt, turned on prior to brake release and on arrival, on until final engine shutdown. Pilots that do not have a transponder code issued by ATC must squawk 1000 when taxiing.

Aircraft exiting at the end of runway 06L on the centreline lighted C7 taxiway, must proceed beyond the alternating green and yellow centreline lights to ensure the aircraft is clear of the runway and the ILS sensitive area.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LOW VISIBILITY TAXI CHART

TORONTO/LESTER B. PEARSON INTL, ON
CYYZ

LAND RWY 06L, DEPART RWY 33R (RVR LESS THAN 1200 TO 600 FT)

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



NOTE:
Alternate routing may be assigned by ATC as required.

Aircraft engine run ups cannot commence during Low Visibility conditions.

Multilateration:
Pilots must keep their transponder on at all times when maneuvering on the aprt, turned on prior to brake release and on arrival, on until final engine shutdown. Pilots that do not have a transponder code issued by ATC must squawk 1000 when taxiing.

Aircraft exiting at the end of runway 06L on the centreline lighted C7 taxiway, must proceed beyond the alternating green and yellow centreline lights to ensure the aircraft is clear of the runway and the ILS sensitive area.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY (CDF)

Overview

All de-icing ops are performed with acft engines oprg, unless otherwise advised by Pad Control or ICEMAN.

Pad 1 & 5

- Centre lane will accommodate all acft.
- Acft with wingspans less than 36m may use North/South lanes.


Pad 2, 3, 4 & 6

- Centre lanes will accommodate acft with wingspans 64.9m/213ft and smaller.
- Acft with wingspans less than 36m may use North/South lanes.

1. Prior to departing Parking Position, ctc CLNC DEL/APRON/GND (as applicable) and advise, "ACFT DE-ICING REQUIRED".
2. On twys T, V and E, hold short of ICE# and when directed by Ground Control monitor Pad Control on 131.17. Follow Pad Control taxi instructions to the entrance of the de-icing pad.
3. When directed by Pad Control, ctc ICEMAN on the assigned freq. (129.62 or 131.37).
4. Follow verbal instructions, guidance displays and lights (as applicable) into staging and/or de-icing bays.
5. Once aircraft is in final stop position, brakes are set and aircraft configured for de-icing, ctc ICEMAN and advise, "BRAKES SET, ACFT CONFIGURED, READY TO DE-ICE". At this time, pass along any specific fluid and/or treatment requirements.
6. After de-icing, do not move aircraft. Ctc Pad Control on 131.17 when instructed by ICEMAN to obtain taxi instruction.
7. Follow Pad Control instruction designated exit points. When instructed by Pad Control ctc Ground Control on assigned freq.
8. Specific aircraft operations plan in effect for aircraft with wingspans 65m/214ft up to 79.9m/262ft. Restrictions in place include:
   - For Central De-icing Facility (CDF) operations, no turns from twy E into any of the de-icing pads are permitted. The only taxi routes permitted for de-icing are via twy T into Pad 5 and via twy V into Pad 1.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY

CYYZ

EFF 24 MAR 22

ENGINE FAN BLADE ICE SHEDDING PROCEDURES CYYZ

Single engine taxi operations should not be used during contaminated airfield conditions or when operations require the crossing of active runways. This will enhance safety and reduce the likelihood of engine inlet contamination during active precipitation, while eliminating any requirement to conduct engine-start activities on the airfield.

The completion of aircraft engine run-up for engine fan blade ice shedding must be conducted on taxiway areas as outlined in the Engine Fan Blade Ice Shedding Chart. Strict adherence to the centerline is mandatory during engine fan blade ice shedding. Proper coordination with air traffic control (ATC) (clearance delivery, ground, or tower) is required.

On initial contact with Clearance Delivery (121.3 MHz), flight crews shall advise:

- De-icing requirements
- Run-up requirement prior to take-off
- Duration of run-up (if required)

Subsequently, if engine run-up requirements change, flight crews shall notify ATC as soon as practicable. The Airport Authority will ensure engine fan blade ice shedding areas in use are inspected and treated as required. Should taxiway surface conditions make engine run-up unsafe, flight crews shall coordinate with ATC to have the run-up conducted at the takeoff position.

Departing Rwy 06L or 06R Ice Shed Area (IS) see chart.

- IS1 Taxiway F between Taxiway T and Taxiway V.
- IS2 Taxiway D at the Runway 06L CAT II/III hold line.
- IS6 Taxiway B between Taxiway T and Taxiway V.
- IS11 Taxiway D between Runway 33R approach hold line and Taxiway A.

Departing Rwy 24R or 24L Ice Shed Area (IS) see chart.

- IS3 Taxiway D between Taxiway D3 and Taxiway D5.
- IS6 Taxiway B between Taxiway T and Taxiway V.
- IS11 Taxiway D between Runway 33R approach hold line and Taxiway A.
- IS12 Taxiway C between Taxiway D3 and Taxiway C3.

Departing Rwy 23 Ice Shed Area (IS) see chart.

- IS4 Taxiway A between Taxiway AE and Taxiway H.
- IS8 Taxiway F between Taxiway N and Taxiway FA.
- IS9 Taxiway N between Taxiway F and Taxiway E.

Departing Rwy 05 Ice Shed Area (IS) see chart.

- IS1 Taxiway F between Taxiway T and Taxiway V.
- IS5 Taxiway H between Taxiway H4 and Runway 05 CAT III hold line.
- IS8 Taxiway F between Taxiway N and Taxiway FA.
- IS9 Taxiway N between Taxiway F and Taxiway E.
- IS10 Taxiway H between Taxiway H2 and Taxiway H4.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Departing Rwy 33R Ice Shed Area (IS) see chart.

- IS1 Taxiway F between Taxiway T and Taxiway V.
- IS6 Taxiway B between Taxiway T and Taxiway V.
- IS11 Taxiway D between Runway 33R approach hold line and Taxiway A.
- IS13 Taxiway V holding short of Taxiway E (west side).

Departing Rwy 33L Ice Shed Area (IS) see chart.

- IS1 Taxiway F between Taxiway T and Taxiway V.

Departing Rwy 15L Ice Shed Area (IS) see chart.

- IS4 Taxiway A between Taxiway AE and Taxiway H.
- IS7 Taxiway F between Runway 05/23 and Taxiway J.
- IS9 Taxiway N between Taxiway F and Taxiway E.

Departing Rwy 15R Ice Shed Area (IS) see chart.


- IS7 Taxiway F between Runway 05/23 and Taxiway J.
- IS8 Taxiway F between Taxiway N and Taxiway FA.
- IS9 Taxiway N between Taxiway F and Taxiway E.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/LESTER B. PEARSON INTL, ON

ENGINE FAN BLADE ICE SHEDDING PROCEDURES CYYZ

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.07** (S) **122.82** GND – **121.9 121.65 119.1** PAD CTL – **131.17 131.95**	TWR – **118.35 118.7**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ENGINE FAN BLADE ICE SHEDDING PROCEDURES CYYZ

EFF 10 AUG 23

TORONTO/LESTER B. PEARSON INTL, ON

PARKING AREAS (TERMINAL 1)

CYYZ

PARKING AREAS (TERMINAL 1)

CYYZ

EFF 20 APR 23

TORONTO/LESTER B. PEARSON INTL, ON

PARKING AREAS (TERMINAL 1 EAST HOLD)

CYYZ

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (TERMINAL 1 EAST HOLD)

CYYZ

EFF 20 APR 23

PARKING AREAS (TERMINAL 3)

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (TERMINAL 3)

CYYZ

EFF 20 APR 23

Taxilane	Taxilane Segment	Acft Code/ Limitation	Max Wingspan	Comments
Pier A North	Between AG and Gate A1A	DH8-400	28.4m/93'	
1	Between AT & Stand B8	C	36m/118'	
	Between Stand B8 & Stand B7D	DH8-400	28.4m/93'	
1S	Between AT and Hangar	E	65m/213'	
2	Between AT and Hangar	D	51.9m/170'	
2	Between 2C & Stand B8	C	36m/118'	
1 / 2	1B/2B Radius	C	36m/118'	
3	Between AJ & 3B	E	65m/213'	
	Between 3B & 3C	C	36m/118'	Code E to Stand C29 & C27
4	Between AJ & 4B	E	65m/213'	
	Between 4B & 4C	C	36m/118'	Code E to Stand C29 & C27
3 / 4	3B/4B Radius	D	51.9m/170'	
	3C/4C Radius	C	36m/118'	
N/S	Between AT & AK	E	65m/213'	
5	Between AK & 5E	E	65m/213'	AK to 5D closed when Lane 5S in use.
	Between 5E & 5G	D	51.9m/170'	
5S	Between AK & Stand C35	F	79.9m/262'	A380 only. Strict Adherence to C/L. Closes Lane 5A-5D. Lane 6 between 6A and 6C closed, remainder of Lane 6 restricted to Code C or smaller.
5-6	Crossover	E	65m/213'	Closed when Lane 5S in use
6	Between AK & 6C	E	65m/213'	Code E allowed to Stand 124. AK to 6C closed when Lane 5S in use.
	Between 6C & 6D	C	36m/118'	Code E allowed to Stand 124. No code E push tail East onto Lane 6 from Stand 124.
	Between 6D & 6F	C	36m/118'	
	Between 6F & Stand 101	DH8-400	28.4m/93'	
5 / 6	5C/6C Radius	E	65m/213'	No B777 due to Jet Blast
	5G/6F Radius	C	36m/118'	
7	Between AL & 7D	F	79.9m/262'	Simultaneous use of lane 7 & 8, Max span 64.9m/213', Code E
	Between 7D & 7E	C	36m/118'	
8	Between AL & 8D	F	79.9m/262'	Simultaneous use of lane 7 & 8, Max span 64.9m/213', Code E
	Between 8D & 8E	C	36m/118'	
7 / 8	7D/8D Radius	F	79.9m/262'	
	7E/8E Radius	C	36m/118'	
7S	Between 7C & 7S	E	65m/213'	
	Between 8C & 7S	E	65m/213'	
	Between 7S & 151	E	65m/213'	No 77W/773, Closes Taxilane 7 & 8 beyond 7C/8C.
	Between 7S & 161A	E	65m/213'	Closes Taxilane 7 & 8 beyond 7C/8C.
N/S	Between AK & AM	F	79.9m/262'	
9	Between DR & 9C	E	65m/213'	
	Between 9C & 9D	C	36m/118'	


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Taxilane	Taxilane Segment	Acft Code/ Limitation	Max Wingspan	Comments
10	Between DR & 10C	D	51.9m/170'	
	Between 10C & 10D	C	36m/118'	
9 / 10	9C/10C Radius	D	51.9m/170'	
	9D/10D Radius	C	36m/118'	
E/W	Between AM & DV	F	79.9m/262'	Strict adherence to C/L
11	Between DT & H4	E	65m/213'	Strict adherence to C/L
12	Between H1/H10 & H4	E	65m/213'	Strict adherence to C/L
E/W	Between DV & H12B	E	65m/213'	
E/W/N/S	Between H12B & H17	E	65m/213'	Tow Operations Only

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/LESTER B. PEARSON INTL, ON

PARKING AREAS (INFIELD) CYYZ



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (INFIELD) CYYZ


EFF 15 JUN 23

PARKING AREAS (FEDEX) CYYZ

ATIS – **120.82 133.1**	CLNC DEL – **121.3** APRON – **122.27** (N) **122.82**

VAR 10° W 2003 ANNUAL RATE OF CHANGE 0

Fedex apron restricted to Code D aircraft (maximum wingspans 51.9m/170ft) or smaller.



Fedex Apron Procedures
All aircraft must contact North Apron (122.275) prior to engine start at gate, entering apron, push back or taxi.
Minimum breakaway power to be used.
Marshaller(s) required at all gates.

Note:
Multilateration:
Pilots must keep their transponder on at all times when maneuvering on the aprt, turned on prior to brake release and on arrival, on until final engine shutdown. Pilots that do not have a transponder code issued by ATC must squawk 1000 when taxiing.


SCALE IN FEET
500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TORONTO/LESTER B. PEARSON INTL, ON

COMMUTER PARKING AREAS

CYYZ



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

COMMUTER PARKING AREAS

CYYZ


EFF 12 AUG 21

TORONTO/OSHAWA EXECUTIVE AIRPORT, ON

AERODROME CHART — CYOO

ATIS – **125.67**	GND – **118.4**	TWR – **120.1**	TML Toronto – **133.4**
MET – **125.67**		TFC – **120.1**	MF*

DECL DISTS	05	23	12	30				
TORA	2654	2654	4250	4250				
TODA	3054	3554	4250	4250				
ASDA	2654	2654	4250	4250				
LDA	2654	2654	4250	4250				



★ DEPARTURE PROCEDURE

Rwy 05 - ½ - Requires a minimum climb gradient of **260** ft/NM to **1100**.
Note: Trees to 561 ASL aprx 0.1 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1300** BPOC.

Rwy 12 - ½
Note: Trees to 541 ASL aprx 0.1 NM past departure end of rwy, 350' LEFT and 600' RIGHT from rwy centreline.

Rwy 23 - ½
Note: Trees to 528 ASL aprx 300' past departure end of rwy, 400' RIGHT of rwy centreline.

Rwy 30 - ½ - Requires a minimum climb gradient of **270** ft/NM to **700**.
Note: Trees to 570 ASL abeam departure end of rwy, 500' LEFT of rwy centreline and aprx 0.1 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1300** BPOC.

TORA FOR INTERSECTION DEPARTURES		
RWY	INTXN	TORA In ft
30	B	4000

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 12, 30: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 12; 23; 30: ★	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TRENTON, ON

AERODROME CHART (DND) CYTR

ATIS – **135.45 257.7**	CLNC DEL – **124.35 286.4** GND – **121.9 275.8**	TWR – **128.7 236.6**	TML – **128.4 324.3**

DECL DISTS	06	24
TORA	10001	10001
TODA	10001	10001
ASDA	10001	10001
LDA	10001	9001



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 06: ½ Rwy 24: *	2000 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TRENTON, ON


PARKING AREAS (DND)

CYTR

ATIS – **135.45 257.7**

CLNC DEL – **124.35 286.4**

GND – **121.9 275.8**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (DND)

CYTR

EFF 5 OCT 23

VICTOR MINE, ON

AERODROME CHART


CVM2

AUTO – **122.55**

UNICOM – **123.2**

ATF

DECL DISTS	10	28						
TORA	4921	4921						
TODA	4921	4921						
ASDA	5118	5118						
LDA	4921	4921						



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Departure procedure not authorized when blasting area defined for Victor Mine within the CFS Caution is active.

Trees to 319 ASL 0.1 NM past departure end of rwy, 400' LEFT of rwy centreline.
Rock pile to 315 ASL 0.2 NM past departure end of rwy, 830' RIGHT of rwy centreline.

Rwy 28 - ½

Note: Departure procedure not authorized when blasting area defined for Victor Mine within the CFS Caution is active.

Trees to 302 ASL abeam departure end of rwy, 330' LEFT of rwy centreline.
Trees to 319 ASL 0.1 NM past departure end of rwy, 520' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WAWA, ON


AERODROME CHART — CYXZ

UNICOM – **122.8** (AU)

CTR Toronto – **124.07**

ATF

DECL DISTS	03	21
TORA	4429	4429
TODA	4429	4429
ASDA	4429	4429
LDA	4429	3740



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

* DEPARTURE PROCEDURE

Rwy 03 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2200** BPOC.

Rwy 21 - ½ - Requires a minimum climb gradient of **260** ft/NM to **1300**. Climb hdg **216°** to **1400** BPOC.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **2200** BPOC.

Note: Trees to 1020 ASL aprx 400' past departure end of rwy, 500' LEFT of rwy centreline and aprx 0.2 NM past departure end of rwy.

TAKE-OFF MINIMA

Rwys 03, 21: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WEBEQUIE, ON

AERODROME CHART — CYWP

TFC – **122.8** ATF

DECL DISTS	02	20
TORA	3507	3507
TODA	4491	4491
ASDA	3507	3507
LDA	3507	3507



TAKE-OFF MINIMA
Rwys 02;20: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WELLAND/NIAGARA CENTRAL DOROTHY RUNGELING, ON


AERODROME CHART — CNQ3

UNICOM – **123.5**

ATF

TML Toronto – **133.4 (N)**
ARR Buffalo – **126.5 (S)**

DECL DISTS	05	23	16	34				
TORA	3493	3493	2663	2663				
TODA	3493	3493	2663	2663				
ASDA	3493	3493	2663	2663				
LDA	3493	3493	2663	2663				



TAKE-OFF MINIMA

Rwys 05, 23: *
Rwys 11, 16, 29, 34: NOT ASSESSED

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNQ3

EFF 23 FEB 23

WIARTON, ON


AERODROME CHART — CYVV

CTR Toronto – **132.57**

TFC – **122.2**

MF

DECL DISTS	05	23	11	29				
TORA	5033	5033	3456	3456				
TODA	6017	6017	4440	4440				
ASDA	5033	5033	3456	3456				
LDA	5033	5033	3456	3456				



TAKE-OFF MINIMA

Rwys 23: *
Rwys 05; 11; 29: NOT ASSESSED

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WINDSOR, ON

AERODROME CHART — CYQG

ATIS – **134.5**	GND – **121.7**	TWR – **124.7**	TFC – **124.7**	MF*	ARR Detroit – **118.95 132.35 134.3 284.0**	RADIO London – **123.37**

DECL DISTS	07	25	12	30
TORA	9000	9000	5150	5150
TODA	9984	9330	5445	5445
ASDA	9000	9000	5150	5150
LDA	8098	7857	4580	4829



★DEPARTURE PROCEDURE

Rwy 07 -½-
Note: Power line to 675 ASL aprx 0.3 NM past departure end of rwy, 300' LEFT of rwy centreline.

Rwy 12 -½ -
Note: Trees to 696 ASL aprx 0.2 NM past departure end of rwy, RIGHT of rwy centreline.

Rwy 25 -½ -
Note: Trees to 709 ASL aprx 0.1 NM past departure end of rwy.

Rwy 30 -½ - Requires a minimum climb gradient of **210** ft/NM to **1300**.
Note: Railroad to 645 ASL aprx 300' past departure end of rwy. Church to 730 ASL aprx 0.6 NM past departure end of rwy, 550' LEFT of rwy centreline.
or
SPEC VIS - Climb visual conditions to cross aprt at or above **1400** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07, 25: RVR 1200 (1/4sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: ★	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQG

EFF 5 OCT 23

WINGHAM/RICHARD W. LEVAN, ON


AERODROME CHART — CPR7

CTR Toronto – **135.3 266.3**

TFC – **123.0**

ATF*

DECL DISTS	13	31
TORA	4000	4000
TODA	4000	4000
ASDA	4000	4000
LDA	4000	4000



* DEPARTURE PROCEDURE

Rwy 13 - ½

Note: Trees to 1162 ASL within 1.0NM of departure end of rwy. Silo to 1162 ASL aprx 0.5 NM past departure end of the rwy, 850' LEFT of rwy centreline.

Rwy 31 - ½

Note: Terrain to 1079 ASL abeam departure end of rwy, both LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13, 31: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WUNNUMIN LAKE, ON

AERODROME CHART — CKL3

TFC – **123.2** ATF

DECL DISTS	16	34
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



***** DEPARTURE PROCEDURE

Rwy 16 - ½

Note: Terrain to 852 ASL abeam departure end of rwy, RIGHT of centreline.

Note: Trees to 943 ASL abeam departure end of rwy, 230' LEFT of centreline.

Note: Trees to 962 ASL aprx 0.1 NM from departure end of rwy, both LEFT and RIGHT of centreline.

Rwy 34 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

TAKE-OFF MINIMA
Rwys 16; 34: *****

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CKL3


EFF 27 JAN 22

AKULIVIK, QC

AERODROME CHART — CYKO

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	08	26
TORA	3521	3521
TODA	3521	3521
ASDA	3521	3521
LDA	3521	3521



TAKE-OFF MINIMA
Rwys 08, 26: *

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKO


EFF 20 APR 23

AKULIVIK, QC

CARTE D'AÉRODROME — CYKO

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	08	26						
TORA	3521	3521						
TODA	3521	3521						
ASDA	3521	3521						
LDA	3521	3521						



* PROCÉDURE DE DÉPART

Piste 08 - ½
Note: Colline jusqu'à 102 ASL aprx 0.1 NM passé l'extrémité de la piste de départ, 570' à GAUCHE de l'axe de piste.

Piste 26 - ½
Note: Colline jusqu'à 70 ASL aprx 0.1 NM passé l'extrémité de la piste de départ, 650' à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 08, 26: *	1000 500 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ALMA, QC

AERODROME CHART — CYTF

AUTO – **123.17**		UNICOM – **122.35** TFC – **122.35** MF*	TML Bagotville – **127.2**

DECL DISTS	13	31
TORA	5000	5000
TODA	5000	5000
ASDA	5000	5000
LDA	5000	5000



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ALMA, QC

CARTE D'AÉRODROME — CYTF

AUTO – **123.17**		UNICOM – **122.35** TFC – **122.35** MF*	TML Bagotville – **127.2**

DIST DÉCLARÉES	13	31
TORA	5000	5000
TODA	5000	5000
ASDA	5000	5000
LDA	5000	5000



* PROCÉDURE DE DÉPART

PIste 13 - ½ **-** Requiert une pente de montée minimal de **230** pieds/NM jusqu'à **700**.
Note: Arbres jusqu'à 529 ASL à moins de 0,4 NM de l'extrémité de la piste de départ.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1500** ou plus haut BPOC.
Procédure SPEC VIS obligatoire lorsque zone de dynamitage située 3.6 NM
SW ou 3.1 NM SW de Chicoutimi/St-Honoré (CYRC) est active.

PIste 31 - ½
Note: Arbres jusqu'à 525 ASL à moins de 0,5 NM de l'extrémité de la piste de départ.

Toutes Pistes: Procédure de départ non autorisée lorsque CYR651, CYR652, CYR653, CYR654, CYR655, CYR656 active.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 13; 31: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYTF

EFF 14 JUIL 22

AMOS/MAGNY, QC


AERODROME CHART — CYEY

UNICOM – **123.0**

CTR Montreal – **125.9**

ATF

DECL DISTS	14	32
TORA	4992	4992
TODA	6012	6012
ASDA	4992	4992
LDA	4992	4992



TAKE-OFF MINIMA

Rwys 14, 32: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AMOS/MAGNY, QC


CARTE D'AÉRODROME — CYEY

UNICOM – **123.0**

CTR Montreal – **125.9**

ATF

DIST DÉCLARÉES	14	32						
TORA	4992	4992						
TODA	6012	6012						
ASDA	4992	4992						
LDA	4992	4992						



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 14, 32: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYEY


EFF 31 DÉC 20

AUPALUK, QC

AERODROME CHART — CYLA

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DECL DISTS	04	22
TORA	3521	3521
TODA	4505	4505
ASDA	3521	3521
LDA	3521	3521



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYLA


EFF 7 OCT 21

AUPALUK, QC

CARTE D'AÉRODROME — CYLA

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DIST DÉCLARÉES	04	22
TORA	3521	3521
TODA	4505	4505
ASDA	3521	3521
LDA	3521	3521



MINIMUM DE DÉCOLLAGE
Pistes 04, 22: *

ÉCHELLE EN PIEDS
1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYLA


EFF 7 OCT 21

BAGOTVILLE, QC

AERODROME CHART (DND) CYBG

ATIS – **124.2** (En) **125.8** (Fr) **302.5**	CLNC DEL – **119.0 384.5** GND – **121.7 275.8**	TWR – **126.2 337.7**	TML – **127.2 227.6**

DECL DISTS	11	29	18	36				
TORA	10000	10000	6029	6029				
TODA	10000	10000	6029	6029				
ASDA	10200	10200	6029	6029				
LDA	10000	10000	6029	6029				



* DEPARTURE PROCEDURE

Rwy 11 - ½ - Climb rwy hdg to **2000** BPOC.

Rwy 18 - ½ - Requires a minimum climb gradient of **230** ft/NM to **3800**.
or
SPEC VIS - Climb in visual conditions to cross aprt at or above **2000** BPOC.

Rwy 36 - ½ - Requires a minimum climb gradient of **240** ft/NM to **3900**.
or
Climb in visual conditions to cross aprt at or above **2000** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
240 FT/NM	360	480	560	640	720	800	1000	1200

TAKE-OFF MINIMA
Rwy 29: ½ Rwys 11; 18; 36: *

SCALE IN FEET
2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART (DND) CYBG


EFF 5 OCT 23

BAGOTVILLE, QC

CARTE D'AÉRODROME — CYBG

ATIS – **125.8** (Fr) **124.2** (Ang) **302.5**	CLNC DEL – **119.0 384.5** GND – **121.7 275.8**	TWR – **126.2 337.7**	TML – **127.2 227.6**

DIST DÉCLARÉES	11	29	18	36				
TORA	10000	10000	6029	6029				
TODA	10000	10000	6029	6029				
ASDA	10200	10200	6029	6029				
LDA	10000	10000	6029	6029				



* PROCÉDURE DE DÉPART

Piste 11 - ½ **-** Monter rwy hdg jusqu'à **2000** BPOC.

Piste 18 - ½ **-** Requiert une pente de montée minimale de **230** pieds/NM jusqu'à **3800.**
ou
SPEC VIS - Monter en conditions visuelles pour traverser aprt à ou au-dessus **2000** BPOC.

Piste 36 - ½ - Requiert une pente de montée minimale de **240** pieds/NM jusqu'à **3900.**
ou
SPEC VIS **-** Monter en conditions visuelles pour traverser aprt à ou au-dessus **2000** BPOC.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
230 pieds/NM	350	460	540	620	690	770	960	1150
240 pieds/NM	360	480	560	640	720	800	1000	1200

MINIMUM DE DÉCOLLAGE

Piste 29: ½
Pistes 11; 18; 36: *

ÉCHELLE EN PIEDS

2000 0 2000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

BAIE-COMEAU, QC

AERODROME CHART — CYBC

AWOS – **125.85** (En) **128.15** (Fr)		RADIO Mont-Joli – **118.3** MF	CTR Montreal – **134.65 227.2**

DECL DISTS	10	28
TORA	6000	6000
TODA	6984	6984
ASDA	6000	6000
LDA	6000	6000



✱ DEPARTURE PROCEDURE

Rwy 10 - ½ - To remain clear of CYA643 when active, flight between "YBC" **R-028** CCW to **R-263** beyond 17 DME prohibited below **7000**. To remain clear of CYR630 when active, flight between "YBC" **R-028** CCW to **R-263** beyond 17 DME prohibited.
Note: Trees to 115 ASL aprx 0.2 NM past departure end of rwy, 750' LEFT and RIGHT of rwy centreline.

Rwy 28 - ½ - NO RIGHT turn below **600**.
To remain clear of CYA643 when active, flight between "YBC" **R-263** CW to **R-028** beyond 17 DME prohibited below **7000**. To remain clear of CYR630 when active, flight between "YBC" **R-263** CW to **R-028** beyond 17 DME prohibited.
Note: Trees to 112 ASL aprx 0.1 NM past departure end of rwy, 690' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: ✱	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBC


EFF 15 JUN 23

BAIE-COMEAU, QC

CARTE D'AÉRODROME — CYBC

AWOS – **128.15** (Fr) **125.85** (Ang)		RADIO Mont-Joli – **118.3** MF	CTR Montreal – **134.65 227.2**

DIST DÉCLARÉES	10	28
TORA	6000	6000
TODA	6984	6984
ASDA	6000	6000
LDA	6000	6000



* PROCÉDURE DE DÉPART

Piste 10 - ½ **-** Pour demeurer à l'écart de CYA643 lorsque active, le vol entre "YBC" **R-028** sens antihoraire jusqu'à **R-263** au-delà de 17 DME est interdit en dessous de **7000**. Pour demeurer à l'écart de CYR630 lorsque active, le vol entre "YBC" **R-028** sens antihoraire jusqu'à **R-263** au-delà de 17 DME est interdit.
Note: Arbres jusqu'à 115 ASL aprx 0,2 NM passé l'extrémité de la piste de départ, 750' à GAUCHE et à DROITE de l'axe de piste.

Piste 28 - ½ **-** AUCUN virage à DROITE en-dessous de **600**.
Pour demeurer à l'écart de CYA643 lorsque active, le vol entre "YBC" **R-263** sens horaire jusqu'à **R-028** au-delà de 17 DME est interdit en dessous de **7000**.
Pour demeurer à l'écart de CYR630 lorsque active, le vol entre "YBC" **R-263** sens horaire jusqu'à **R-028** au-delà de 17 DME est interdit.
Note: Arbres jusqu'à 112 ASL aprx 0,1 NM passé l'extrémité de la piste de départ, 690' à GAUCHE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 10, 28: *****	1000 0 1000 2000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

BONAVENTURE, QC

AERODROME CHART — CYVB

AUTO – **122.05**		UNICOM – **123.0** (AU) MF	RADIO Quebec – **123.55** DRCO

DECL DISTS	13	31
TORA	5983	5983
TODA	5983	5983
ASDA	5983	5983
LDA	5983	5983



TAKE-OFF MINIMA
Rwys 13; 31: *

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVB


EFF 14 JUL 22

BONAVENTURE, QC

CARTE D'AÉRODROME — CYVB

AUTO – **122.05**		UNICOM – **123.0** (AU) **MF**	RADIO Quebec – **123.55** **DRCO**

DIST DÉCLARÉES	13	31
TORA	5983	5983
TODA	5983	5983
ASDA	5983	5983
LDA	5983	5983



* PROCÉDURE DE DÉPART

Piste 13 - ½

Note: Arbres jusqu'à 140 ASL aprx 100' passé l'extrémité de la piste départ, 220' à gauche de l'axe de piste.

Arbres jusqu'à 154 ASL par le travers de l'extrémité de la piste de départ, 300' à gauche de l'axe de piste.

Ligne de transmission jusqu'à 154 ASL aprx 500' passé l'extrémité de la piste départ

Piste 31 -½ - Requiert une pente de montée minimale de **270** pieds/NM jusqu'à **500.**

Note: Arbres 211 ASL aprx 300' passé l'extrémité de la piste de départ, 500' à GAUCHE de l'axe de piste.

ou

SPEC VIS - Monter visuel au-dessus de l'aéroport jusqu'à **1000** BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 13; 31: *	1000 0 1000 2000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYVB

EFF 14 JUIL 22

BROMONT (ROLAND DÉSOURDY), QC

AERODROME CHART — CZBM


AUTO – **122.97**

◕ UNICOM – **122.15** (AU)

MF

CTR Montreal – **132.35**

DECL DISTS	05	23
TORA	5004	5004
TODA	5004	5988
ASDA	5004	5004
LDA	5004	5004



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 23: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZBM

EFF 12 AUG 21

BROMONT (ROLAND DÉSOURDY), QC

CARTE D'AÉRODROME — CZBM


AUTO – **122.97**

◕ UNICOM – **122.15** (AU)

MF

CTR Montreal – **132.35**

DIST DÉCLARÉES	05	23
TORA	5004	5004
TODA	5004	5988
ASDA	5004	5004
LDA	5004	5004



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 05; 23: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CHARLEVOIX, QC

AERODROME CHART — CYML

AUTO – **122.55** (En)		UNICOM – **123.0**	CTR Montreal – **125.1 299.6** ATF

DECL DISTS	14	32
TORA	4501	4501
TODA	5485	4501
ASDA	4501	4501
LDA	4501	4501



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CHARLEVOIX, QC

CARTE D'AÉRODROME — CYML

AUTO – **122.55** (Ang)		UNICOM – **123.0**	CTR Montreal – **125.1 299.6** ATF

DIST DÉCLARÉES	14	32
TORA	4501	4501
TODA	5485	4501
ASDA	4501	4501
LDA	4501	4501



* PROCÉDURE DE DÉPART

Piste 14 - ½ - Monter sur cap **143°** jusqu'à **2200** BPOC.

Piste 32 - ½ - Requiert une pente de montée minimale de **310** pi/NM jusqu'à **2400**. Monter sur cap **323°** jusqu'à **2200** BPOC.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2800** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 14; 32: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYML


EFF 29 DÉC 22

CHEVERY, QC

AERODROME CHART — CYHR

AUTO – **122.55** (En)		TFC – **123.5** ATF*	

DECL DISTS	07	25
TORA	4500	4500
TODA	4500	4500
ASDA	4500	4500
LDA	4500	4500



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07, 25: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CHEVERY, QC

CARTE D'AÉRODROME — CYHR

AUTO – **122.55** (Ang)		TFC – **123.5** ATF*	

DIST DÉCLARÉES	07	25
TORA	4500	4500
TODA	4500	4500
ASDA	4500	4500
LDA	4500	4500



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 07, 25: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CHIBOUGAMAU/CHAPAIS, QC

AERODROME CHART — CYMT

MET – **126.25** (En) **128.75** (Fr)		RADIO Val-d'Or – **122.0** TFC – **122.0** MF	RADIO Quebec – **123.37**

DECL DISTS	04	22
TORA	6495	6495
TODA	7479	7479
ASDA	6495	6495
LDA	6495	6495



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMT


EFF 14 JUL 22

CHIBOUGAMAU/CHAPAIS, QC

CARTE D'AÉRODROME — CYMT

MET – **128.75** (Fr) **126.25** (Ang)		RADIO Val-d'Or – **122.0** TFC – **122.0** MF	RADIO Quebec – **123.37**

DIST DÉCLARÉES	04	22
TORA	6495	6495
TODA	7479	7479
ASDA	6495	6495
LDA	6495	6495



* PROCÉDURE DE DÉPART

Piste 04 - ½

Note: Arbres jusqu'à 1380 ASL aprx 0,1 NM passé l'extrémité de la piste de départ, 400' à GAUCHE et à DROITE de l'axe de piste.

Piste 22 - ½

Note: Arbres jusqu'à 1329 ASL par le travers de la fin de la piste, 100' à GAUCHE et à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 04, 22: *	1000 0 1000 2000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYMT


EFF 14 JUIL 22

CHICOUTIMI/ST-HONORÉ, QC

AERODROME CHART — CYRC

ATIS – **134.8** (En) **124.95** (Fr)	◕ GND – **121.9**	◕ TWR – **118.4** ◕ TFC – **118.4** ATF*	TML Bagotville – **127.2 227.6**

DECL DISTS	06	24	12	30	18	36		
TORA	3735	3735	6085	6085	3597	3597		
TODA	4719	4719	6719	6085	4581	4581		
ASDA	3735	3735	6085	6085	3597	3597		
LDA	3735	3735	6085	6085	3597	3597		



TAKE-OFF MINIMA	SCALE IN FEET
Rwy 06: NOT ASSESSED Rwys 12; 18; 24; 30; 36: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRC


EFF 20 APR 23

CHICOUTIMI/ST-HONORÉ, QC

CARTE D'AÉRODROME — CYRC

ATIS – **124.95** (Fr) **134.8** (Ang)	◕ GND – **121.9**	◕ TWR – **118.4** ◕ TFC – **118.4** ATF*	TML Bagotville – **127.2 227.6**

DIST DÉCLARÉES	06	24	12	30	18	36		
TORA	3735	3735	6085	6085	3597	3597		
TODA	4719	4719	6719	6085	4581	4581		
ASDA	3735	3735	6085	6085	3597	3597		
LDA	3735	3735	6085	6085	3597	3597		



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 06: NON ÉVALUÉ Pistes 12; 18; 30; 24; 36: *	1000 0 1000 2000

CARTE D'AÉRODROME — CYRC

EFF 20 AVR 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CHISASIBI, QC


AERODROME CHART — CSU2

AUTO – **122.17**

TFC – **123.2**

MF*

DECL DISTS	14	32
TORA	3789	3789
TODA	3789	3789
ASDA	3789	3789
LDA	3789	3789



TAKE-OFF MINIMA
Rwys 14, 32:*

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CSU2


EFF 17 JUN 21

CHISASIBI, QC

CARTE D'AÉRODROME — CSU2

AUTO – **122.17** | TFC – **123.2** | MF*

DIST DÉCLARÉES	14	32
TORA	3789	3789
TODA	3789	3789
ASDA	3789	3789
LDA	3789	3789



MINIMUM DE DÉCOLLAGE
Pistes 14; 32: *

ÉCHELLE EN PIEDS
1000 0 1000

CARTE D'AÉRODROME — CSU2

EFF 17 JUIN 21

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

DRUMMONDVILLE, QC

AERODROME CHART — CSC3


AUTO – **122.55**

UNICOM – **122.8**

CTR Montreal – **132.35**

MF

DECL DISTS	06	24
TORA	6003	6003
TODA	6003	6003
ASDA	6003	6003
LDA	6003	6003



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

* DEPARTURE PROCEDURE

Rwy 06 - ½

When CYR606 is active: Climb between hdg **008°** CW to **308°** to remain clear of CYR606.

Note: Trees and power line to 413 ASL aprx 0.1 NM past departure end of rwy. Power line to 483 ASL aprx 0.6 NM past departure end of rwy.

Rwy 24 - ½ - Requires a minimum climb gradient of **210** ft/NM to **1000**. Climb hdg **236°** to **1000** BPOC. When CYR606 is active: Climb between hdg **308°** CCW to **008°** to remain clear of CYR606.

Note: Trees to 452 ASL abeam departure end of rwy, 450' LEFT and RIGHT of rwy centreline, and aprx 0.4 NM past departure end of rwy.

or

SPEC VIS - Climb in visual conditions to cross the airport at or above **2000** BPOC.

TAKE-OFF MINIMA

Rwys 06, 24: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CSC3

EFF 31 DEC 20

DRUMMONDVILLE, QC

CARTE D'AÉRODROME — CSC3


AUTO – **122.55**

UNICOM – **122.8**

CTR Montreal – **132.35**

MF

DIST DÉCLARÉES	06	24
TORA	6003	6003
TODA	6003	6003
ASDA	6003	6003
LDA	6003	6003



* PROCÉDURE DE DÉPART

PIste 06 - ½ **-**
Lorsque CYR606 est active: Monter entre caps **008°** et **308°** sens horaire pour demeurer à l'écart de CYR606.
Note: Arbres et ligne électrique jusqu'à 413 ASL aprx 0,1 NM passé l'extrémité de la piste de départ. Ligne électrique jusqu'à 483 ASL aprx 0,6 NM passé l'extrémité de la piste de départ.

PIste 24 - ½ - Requiert une pente de montée minimale de **210** pi/NM jusqu'à **1000**. Monter sur cap **236°** jusqu'à **1000** BPOC. Lorsque CYR 606 est actif: Monter entre caps **308°** et **008°** sens antihoraire pour demeurer à l'écart de CYR606.
Note: Arbres jusqu'à 452 ASL par le travers de l'extrémité de la piste de départ, 450' à GAUCHE et à DROITE de l'axe de piste, et aprx 0,4 NM passé l'extrémité de la piste de départ.

ou

SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **2000** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE
Pistes 06, 24: *****

ÉCHELLE EN PIEDS
1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

DU ROCHER-PERCÉ (PABOK), QC

AERODROME CHART — CTG3

AUTO – **122.97**		◕ UNICOM – **122.35** (AU) ATF	CTR Montreal – **134.17** RADIO Quebec – **123.47**

DECL DISTS	08	26
TORA	4982	4982
TODA	4982	4982
ASDA	4982	4982
LDA	4982	4982



* DEPARTURE PROCEDURE

Rwy 08 - ½ **-** Requires a minimum climb gradient of **410** ft/NM to **400**.
or
SPEC VIS **-** Climb in visual conditions to cross the airport at or above **1000** BPOC.

Rwy 26 - ½
Note: Road to 110 ASL abeam departure end of rwy, 450' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
410 FT/NM	620	820	960	1100	1230	1370	1710	2050

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08; 26: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DU ROCHER-PERCÉ (PABOK), QC

CARTE D'AÉRODROME — CTG3

AUTO – **122.97**		UNICOM – **122.35** (AU) ATF	CTR Montreal – **134.17** RADIO Quebec – **123.47**

DIST DÉCLARÉES	08	26
TORA	4982	4982
TODA	4982	4982
ASDA	4982	4982
LDA	4982	4982



* PROCÉDURE DE DÉPART

Piste 08 - ½ - Requiert une pente de montée minimale de **410** pi/NM jusqu'à **400**.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1000** ou plus haut BPOC.

Piste 26 - ½

Note: Chemin jusqu'à 110 ASL par le travers de l'extrémité de la piste de départ, 450' à DROITE de l'axe de piste.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
410 Pieds/NM	620	820	960	1100	1230	1370	1710	2050

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 08; 26: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

EASTMAIN RIVER, QC

AERODROME CHART — CZEM

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	02	20
TORA	3512	3512
TODA	3512	3512
ASDA	3512	3512
LDA	3512	3512



✱ DEPARTURE PROCEDURE

Rwy 02 - ½
Note: Road to 43 ASL aprx 100' past departure end of rwy, 550' RIGHT of rwy centreline. Trees to 149 ASL aprx 400' past departure end of rwy, 600' LEFT and RIGHT of rwy centreline.

Rwy 20 - ½
Note: Trees to 166 ASL abeam departure end of rwy, 200' RIGHT and 500' LEFT of rwy centreline and aprx 0.2 NM past departure end of rwy.

TAKE-OFF MINIMA
Rwys 02, 20: ✱

SCALE IN FEET
1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CZEM


EFF 29 DEC 22

EASTMAIN RIVER, QC

CARTE D'AÉRODROME — CZEM

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DIST DÉCLARÉES	02	20
TORA	3512	3512
TODA	3512	3512
ASDA	3512	3512
LDA	3512	3512



MINIMUM DE DÉCOLLAGE

Pistes 02, 20: *

ÉCHELLE EN PIEDS

1000 500 0 1000

CARTE D'AÉRODROME — CZEM

EFF 29 DÉC 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ÉLÉONORE, QC

AERODROME CHART — CEL8

AUTO – **122.55** | TFC – **123.2** MF*

DECL DISTS	09	27
TORA	3930	3930
TODA	3930	3930
ASDA	3930	3930
LDA	3737	3736



TAKE-OFF MINIMA
Rwy 09, 27: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ÉLÉONORE, QC

CARTE D'AÉRODROME — CEL8

AUTO – **122.55** | TFC – **123.2** | MF*

DIST DÉCLARÉES	09	27
TORA	3930	3930
TODA	3930	3930
ASDA	3930	3930
LDA	3737	3736



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 09, 27: *	1000 0 1000

CARTE D'AÉRODROME — CEL8

EFF 25 AVR 19

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


FONTANGES, QC

AERODROME CHART — CTU2

UNICOM – **123.0** (AU)

MF*

DECL DISTS	09	27
TORA	4890	4890
TODA	4890	4890
ASDA	4890	4890
LDA	4890	4890



* DEPARTURE PROCEDURE

Rwy 09 - ½ **-**
Note: Tower to 1570 ASL aprx 750' past departure end of rwy, 200' LEFT of rwy centreline.

Rwy 27 - ½ **-**
Note: Road to 1554 ASL abeam departure end of rwy, RIGHT of rwy centreline.
Trees to 1559 ASL abeam departure end of rwy, 450' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 09, 27: *

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CTU2

EFF 17 JUN 21


FONTANGES, QC

CARTE D'AÉRODROME — CTU2

UNICOM – **123.0** (AU)

MF*

DIST DÉCLARÉES	09	27
TORA	4890	4890
TODA	4890	4890
ASDA	4890	4890
LDA	4890	4890



* PROCÉDURE DE DÉPART

Piste 09 - ½ **-**
Note:Tour jusqu'à 1570 ASL aprx 750' passé l'extrémité de la piste de départ, 200' à GAUCHE de l'axe de piste.

Piste 27 - ½ -
Note: Route jusqu'à 1554 ASL par le travers de l'extrémité de départ de la piste, à DROITE de l'axe de piste.
Arbres jusqu'à 1559 ASL par le travers de l'extrémité de départ de la piste, 450' à GAUCHE de l'axe de piste.

MINIMUM DE DÉCOLLAGE
Pistes 09, 27: *

ÉCHELLE EN PIEDS

1000 0 1000 2000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

GASPÉ (MICHEL-POULIOT), QC

AERODROME CHART — CYGP

AUTO – **127.8** (En) **124.9** (Fr)		RADIO Mont-Joli – **122.3** MF	CTR Montreal – **134.17** RADIO Quebec – **123.47**

DECL DISTS	10	28
TORA	5488	5488
TODA	5980	5980
ASDA	5488	5488
LDA	5488	5488



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10, 28: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GASPÉ (MICHEL-POULIOT), QC

CARTE D'AÉRODROME — CYGP

AUTO – **124.9** (Fr) **127.8** (Ang)		RADIO Mont-Joli – **122.3**	CTR Montreal – **134.17** RADIO Quebec – **123.47** MF

DIST DÉCLARÉES	10	28
TORA	5488	5488
TODA	5980	5980
ASDA	5488	5488
LDA	5488	5488



★PROCÉDURE DE DÉPART

Piste 10 - ½ **-** Monter sur cap **103°** jusqu'à **2000** BPOC.
Note: Arbres jusqu'à 154 ASL aprx 0.2NM passé l'extrémité de la piste de départ.

Piste 28 - ½ **-** Requiert une pente de montée minimale de **270** pi/NM jusqu'à **1700**. Monter entre caps **306°** et **336°** sens horaire jusqu'à **2100** BPOC.
Note: Arbres jusqu'à 184 ASL aprx 0.2 NM passé l'extrémité de la piste de départ.
ou
SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **2000** ou plus haut, puis continuer la montée entre caps **290°** et **140°** sens horaire jusqu'à **2400** BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Rwys 10, 28: ★	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


HAVRE ST-PIERRE, QC

AERODROME CHART — CYGV

AWOS – **125.95** (En)
128.3 (Fr)

RADIO Madeleine – **122.0**
TFC – **122.0**
MF*

DECL DISTS	08	26
TORA	4498	4498
TODA	5098	5098
ASDA	4498	4498
LDA	4498	4498



TAKE-OFF MINIMA

Rwys 08; 26: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HAVRE ST-PIERRE, QC

CARTE D'AÉRODROME — CYGV

AWOS – **128.3** (Fr) **125.95** (Ang)		◕ RADIO Madeleine – **122.0** ◕ TFC – **122.0** MF*	

DIST DÉCLARÉES	08	26
TORA	4498	4498
TODA	5098	5098
ASDA	4498	4498
LDA	4498	4498

63 37 — 63 36.5

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
380 pieds/NM	570	760	890	1020	1140	1270	1590	1900

* PROCÉDURE DE DÉPART

Piste 08 -½- Monter entre caps **068°** et **263°** sens horaire jusqu'à **4500** BPOC.

PIste 26 - ½ - Requiert une pente de montée minimale de **380** pi/NM jusqu'à **1000**. Monter entre caps **280°** et **083°** sens antihoraire jusqu'à **3800** BPOC.
Note: Arbres jusqu'à 122 ASL aprx 700' passé l'extrémité de la piste de départ, 50' à DROITE de l'axe de piste.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **3000** ou plus haut BPOC.

ALT 125

26 AS

263°

P1

50 17

4498 x 100

CYGV
N50 16.92
W63 36.67

monte 0.33%

ALT 110

P1

083°

AO* 08

50 16.7 — 50 16.7

DÉC 20° W 2012

VARIATION ANNUELLE DE 11° E

63 37 — 63 36.5

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 08; 26: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYGV


EFF 25 FÉV 21

ÎLES-DE-LA-MADELEINE, QC

AERODROME CHART — CYGR

			RADIO Madeleine – **123.15** RADIO Mont-Joli – **123.15** MF*	CTR Moncton – **134.35** RADIO Quebec – **123.55**

DECL DISTS	07	25	16	34				
TORA	4493	4493	3608	3608				
TODA	4493	4493	3808	3808				
ASDA	4493	4493	3608	3608				
LDA	4493	4493	3608	3608				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07, 25: (¼sm) RWY 16, 34: (¼sm) Day only	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 07, 16, 25, 34: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGR

EFF 25 FEB 21

ÎLES-DE-LA-MADELEINE, QC

CARTE D'AÉRODROME — CYGR

				◕ RADIO Madeleine – **123.15** ◕ RADIO Mont-Joli – **123.15** MF*			CTR Moncton – **134.35** RADIO Quebec – **123.55**	

DIST DÉCLARÉES	07	25	16	34				
TORA	4493	4493	3608	3608				
TODA	4493	4493	3808	3808				
ASDA	4493	4493	3608	3608				
LDA	4493	4493	3608	3608				

* PROCÉDURE DE DÉPART

Piste 07 - ½

Note: Arbres et route jusqu'à 30 ASL à l'intérieur de 0,1 NM passé l'extrémité de la piste de départ.

Piste 16 - ½ - Requiert une pente de montée minimale de **370**pi/NM jusqu'à **400**.

Note: Terrain jusqu'à 66 ASL par le travers de l'extrémité de la piste de départ, 350' à DROITE de l'axe de piste et aprx 200' passé l'extrémité de la piste de départ.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **700** ou plus haut BPOC.

Piste 25 - ½


Note: Arbres jusqu'à 60 ASL à l'intérieur de 0,2 NM passé l'extrémité de la piste de départ. Arbres jusqu'à 174 ASL aprx 0,6 NM passé l'extrémité de la piste de départ, 1400' à GAUCHE de l'axe de piste.

Piste 34 - ½

Note: Terrain jusqu'à 17 ASL à l'intérieur de 0,1 NM passé l'extrémité de la piste de départ.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
370 pieds/NM	560	740	870	990	1110	1240	1550	1850



NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
Pistes 07, 25: (¼sm) Pistes 16, 34: (¼sm) Jour seulement	NON AUTORISÉ
MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 16, 25, 34: * Piste 07: ½	1000 0 1000

CARTE D'AÉRODROME — CYGR

EFF 25 FÉV 21


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

INUKJUAK, QC

AERODROME CHART — CYPH

AWOS – **125.3** (En) **127.7** (Fr)		UNICOM – **122.1** TFC – **122.1** MF*	RADIO Quebec – **123.55**

DECL DISTS	06	24
TORA	3520	3520
TODA	3520	3520
ASDA	3520	3520
LDA	3520	3520



* DEPARTURE PROCEDURE

Rwy 06 - ½

Note: Terrain to 82 ASL abeam departure end of rwy, 350' LEFT of rwy centreline.

Rwy 24 - ½ **-** Requires a minimum climb gradient of **350** ft/NM to **500**.

Note: Terrain to 161 ASL aprx 0.3 NM past departure end of rwy, 1000' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **800** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 ft/NM	530	700	820	940	1050	1170	1460	1750

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPH


EFF 14 JUL 22

INUKJUAK, QC

CARTE D'AÉRODROME — CYPH

AWOS – **127.7** (Fr) **125.3** (Ang)		UNICOM – **122.1** TFC – **122.1** MF*	RADIO Quebec – **123.55**

DIST DÉCLARÉES	06	24
TORA	3520	3520
TODA	3520	3520
ASDA	3520	3520
LDA	3520	3520



TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
350 pieds/NM	530	700	820	940	1050	1170	1460	1750

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06; 24: *	500 0 500

CARTE D'AÉRODROME — CYPH

EFF 14 JUIL 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

IVUJIVIK, QC

AERODROME CHART — CYIK

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	07	25
TORA	3521	3521
TODA	4505	4505
ASDA	3521	3521
LDA	3521	3521



TAKE-OFF MINIMA
Rwy 07, 25: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYIK


EFF 20 APR 23

IVUJIVIK, QC

CARTE D'AÉRODROME — CYIK

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	07	25
TORA	3521	3521
TODA	4505	4505
ASDA	3521	3521
LDA	3521	3521



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 07, 25: *	1000 0 1000

CARTE D'AÉRODROME — CYIK

EFF 20 AVR 23


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

KANGIQSUALUJJUAQ (GEORGES RIVER), QC

AERODROME CHART — CYLU

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DECL DISTS	16	34
TORA	3521	3521
TODA	3521	3521
ASDA	3521	3521
LDA	3521	3521



TAKE-OFF MINIMA
Rwy 16: *
Rwy 34: ½

SCALE IN FEET
500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYLU


EFF 10 SEP 20

KANGIQSUALUJJUAQ (GEORGES RIVER), QC

CARTE D'AÉRODROME — CYLU

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DIST DÉCLARÉES	16	34
TORA	3521	3521
TODA	3521	3521
ASDA	3521	3521
LDA	3521	3521



MINIMUM DE DÉCOLLAGE
Piste 16: *
Piste 34: ½

ÉCHELLE EN PIEDS
500 0 500

CARTE D'AÉRODROME — CYLU

EFF 10 SEP 20

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


KANGIQSUJUAQ (WAKEHAM BAY), QC

AERODROME CHART — CYKG

APRT RADIO – **122.1**
TFC – **122.1**
MF*

RADIO Quebec – **123.47** DRCO

DECL DISTS	15	33
TORA	3520	3520
TODA	3520	3520
ASDA	3520	3520
LDA	3520	3520



* DEPARTURE PROCEDURE

Rwy 15 - ½ **-** Climb hdg **146°** to **1000** BPOC.
Note: Terrain to 577 ASL aprx 0.5 NM past departure end of rwy, 1300' RIGHT of rwy centreline.

Rwy 33 - ½ **-** Climb hdg **326°** to **2300** BPOC.
Note: Terrain to 532 ASL abeam departure end of rwy, aprx 500' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15; 33: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

KANGIQSUJUAQ (WAKEHAM BAY), QC

CARTE D'AÉRODROME — CYKG

			APRT RADIO – **122.1** TFC – **122.1** MF*			RADIO Quebec – **123.47** DRCO		

DIST DÉCLARÉES	15	33
TORA	3520	3520
TODA	3520	3520
ASDA	3520	3520
LDA	3520	3520



* PROCÉDURE DE DÉPART

Piste 15 - ½ - Monter sur cap **146°** jusqu'à **1000** BPOC.
Note: Terrain jusqu'à 577 ASL aprx 0,5 NM passé l'extrémité de la piste de départ, 1300' à DROITE de l'axe de piste.

Piste 33 - ½ - Monter sur cap **326°** jusqu'à **2300** BPOC.
Note: Terrain jusqu'à 532 ASL par le travers de l'extrémité de la piste de départ, aprx 500' à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 15; 33: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

KANGIRSUK, QC

AERODROME CHART — CYAS

			APRT RADIO – **122.1** TFC – **122.1** MF*				RADIO Quebec – **126.7** DRCO	

DECL DISTS	03	21						
TORA	3521	3521						
TODA	4505	3521						
ASDA	3521	3521						
LDA	3521	3521						



* DEPARTURE PROCEDURE

Rwy 03 - ½

Note: Terrain to 437 ASL abeam departure end of runway, 500' RIGHT of rwy centreline.

Rwy 21 - ½

Note: Road to 370 ASL aprx 400' past departure end of rwy, 150' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03, 21: *	1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


AERODROME CHART — CYAS

EFF 15 JUN 23

KANGIRSUK, QC

CARTE D'AÉRODROME — CYAS

			◕ APRT RADIO – **122.1** ◕ TFC – **122.1** MF*			RADIO Quebec – **126.7** DRCO		
DIST DÉCLARÉES	**03**	**21**						
TORA	3521	3521						
TODA	4505	3521						
ASDA	3521	3521						
LDA	3521	3521						



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 03, 21: *	1000 500 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYAS

EFF 15 JUIN 23


KATTINIQ/DONALDSON, QC

AERODROME CHART — CTP9

UNICOM – **122.8** (AU)

MF*

DECL DISTS	11	29
TORA	6500	6500
TODA	6500	6500
ASDA	6500	6500
LDA	6500	6500



* DEPARTURE PROCEDURE

Rwy 11 - ½ **-** Departure not auth when blasting areas active.

Rwy 29 - ½ **-** Departure not auth when blasting areas active.
Note: Terrain to 2000 ASL aprx 0.3 NM past departure end of rwy, 950' LEFT of rwy centreline.

TAKE-OFF MINIMA
Rwys 11, 29: *

SCALE IN FEET

1000 0 1000 2000 3000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


KATTINIQ/DONALDSON, QC

CARTE D'AÉRODROME — CTP9

UNICOM – **122.8** (AU)

MF*

DIST DÉCLARÉES	11	29
TORA	6500	6500
TODA	6500	6500
ASDA	6500	6500
LDA	6500	6500



***** PROCÉDURE DE DÉPART

Piste 11 - ½ - Départ non auth lorsque zones de dynamitage sont active.

PIste 29 - ½ - Départ non auth lorsque zones de dynamitage sont active.

Note: Terrain jusqu'à 2000 ASL aprx 0,3 NM passé l'extrémité de la piste de départ, 950' à GAUCHE de l'axe de piste.

MINIMUM DE DÉCOLLAGE
Pistes 11, 29: *

ÉCHELLE EN PIEDS

1000 0 1000 2000 3000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

KUUJJUAQ, QC

AERODROME CHART — CYVP

		RADIO – **122.3 296.6** MF*	RADIO Quebec – **123.27 5680**

DECL DISTS	07	25	13	31				
TORA	6000	6000	5001	5001				
TODA	6984	6984	5701	5701				
ASDA	6000	6000	5001	5001				
LDA	6000	6000	5001	5001				



* DEPARTURE PROCEDURE

Rwy 07 - ½
Note: Building to 138 ASL aprx 0.1NM past departure end of rwy, 650' LEFT of rwy centreline.

Rwy 13 - ½
Note: Trees to 82 ASL abeam departure end of rwy, 350' LEFT of rwy centreline.

Rwy 25 - ½ - Requires a minimum climb gradient of **390** ft/NM to **500**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **900** BPOC.

Rwy 31 - ½
Note: Trees to 144 ASL abeam departure end of rwy, 200' LEFT and RIGHT of rwy centreline, and trees to 259 ASL aprx 0.8 NM past departure end of rwy, 1800' LEFT of rwy centreline.

Note: Seaplane activities Stewart Lake (2.5 NM North of Aprt).

TAKE-OFF MINIMA
All Rwys: *

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVP


EFF 3 NOV 22

KUUJJUAQ, QC

CARTE D'AÉRODROME — CYVP

		RADIO – **122.3 296.6** MF*	RADIO Quebec – **123.27 5680**

DIST DÉCLARÉES	07	25	13	31				
TORA	6000	6000	5001	5001				
TODA	6984	6984	5701	5701				
ASDA	6000	6000	5001	5001				
LDA	6000	6000	5001	5001				



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Toutes pistes: *	1000 0 1000 2000

CARTE D'AÉRODROME — CYVP

EFF 3 NOV 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

KUUJJUARAPIK, QC

AERODROME CHART — CYGW

AWOS – **124.35** (En) **125.15** (Fr)		RADIO La Grande – **122.2** MF*	RADIO Quebec – **123.47**

DECL DISTS	03	21
TORA	5082	5082
TODA	6066	6066
ASDA	5082	5082
LDA	5082	5082



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYGW


EFF 29 DEC 22

KUUJJUARAPIK, QC

CARTE D'AÉRODROME — CYGW

AWOS – **125.15** (Fr) **124.35** (Ang)		RADIO La Grande – **122.2** MF*	RADIO Quebec – **123.47**

DIST DÉCLARÉES	03	21
TORA	5082	5082
TODA	6066	6066
ASDA	5082	5082
LDA	5082	5082



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 03; 21: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LA GRANDE RIVIÈRE, QC

AERODROME CHART — CYGL

			RADIO – **122.3**	RADIO Quebec – **123.37**
			MF*	

DECL DISTS	13	31
TORA	6487	6487
TODA	6487	6487
ASDA	6487	6487
LDA	6487	6487



*DEPARTURE PROCEDURE

Rwy 13 - ½
Note: Trees to 768 ASL abeam departure end of rwy, 200' both LEFT and RIGHT of centreline.

Rwy 31 - ½
Note: Trees to 718 ASL aprx 100' beyond departure end of rwy, 250' both LEFT and RIGHT of centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13, 31: *	1000 0 1000

AERODROME CHART — CYGL

EFF 24 MAR 22


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA GRANDE RIVIÈRE, QC

CARTE D'AÉRODROME — CYGL

		RADIO – **122.3** MF*	RADIO Quebec – **123.37**

DIST DÉCLARÉES	13	31
TORA	6487	6487
TODA	6487	6487
ASDA	6487	6487
LDA	6487	6487



* PROCÉDURE DE DÉPART

Plste 13 - ½
Note: Arbres jusqu'à 768 ASL par le travers de la fin de la piste, 200' à GAUCHE et à DROITE de l'axe de piste.

Plste 31 - ½
Note: Arbres jusqu'à 718 ASL aprx 100' passé l'extrémité de départ de la piste, 250' à GAUCHE et à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 13, 31: *	1000 0 1000

CARTE D'AÉRODROME — CYGL

EFF 24 MAR 22

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LA GRANDE RIVIÈRE, QC

PARKING AREAS

CYGL

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS


CYGL

EFF 22 APR 21

LA GRANDE RIVIÈRE, QC

AIRES DE STATIONNEMENT

CYGL



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT

CYGL

EFF 22 AVR 21


LA GRANDE-3, QC

AERODROME CHART — CYAD

◕ UNICOM – **123.0** (AU)

MF*

DECL DISTS	10	28
TORA	5009	5009
TODA	5993	5993
ASDA	5009	5009
LDA	5009	5009



* DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 791 ASL abeam departure end of rwy, 300' LEFT and RIGHT of rwy centreline.

Rwy 28 - ½

Note: Trees to 787 ASL abeam departure end of rwy, 200' LEFT and 300' RIGHT of rwy centreline.

TAKE-OFF MINIMA
Rwys 10, 28: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAD

EFF 7 OCT 21


LA GRANDE-3, QC

CARTE D'AÉRODROME — CYAD

UNICOM – **123.0** (AU)

MF*

DIST DÉCLARÉES	10	28
TORA	5009	5009
TODA	5993	5993
ASDA	5009	5009
LDA	5009	5009



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 10, 28: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYAD


EFF 7 OCT 21

LA GRANDE-4, QC

AERODROME CHART — CYAH

AWOS – **118.45** (En) **119.65** (Fr)		UNICOM – **131.2** (AU) MF*	RADIO Quebec – **123.55**

DECL DISTS	09	27
TORA	5009	5009
TODA	5993	5993
ASDA	5009	5009
LDA	5009	5009



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYAH


EFF 10 SEP 20

LA GRANDE-4, QC

CARTE D'AÉRODROME — CYAH

AWOS – **119.65** (Fr) **118.45** (Ang)		UNICOM – **131.2** (AU) MF*	RADIO Quebec – **123.55**

DIST DÉCLARÉES	09	27
TORA	5009	5009
TODA	5993	5993
ASDA	5009	5009
LDA	5009	5009



* PROCÉDURE DE DÉPART

Piste 09 - ½ - AUCUN virage à DROITE en dessous de **1800** BPOC.
Note: Arbres jusqu'à 1149 ASL par le travers de l'extrémité de la piste de départ, à GAUCHE et à DROITE de l'axe de piste.

Piste 27 - ½ - Requiert une pente de montée minimale de **420** pi/NM jusqu'à **1900**. AUCUN virage à GAUCHE en dessous de **1600**.
Note: Arbres jusqu'à 1016 ASL par le travers de l'extrémité de la piste de départ, 350' à GAUCHE et 250' à DROITE de l'axe de piste.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2200** ou plus haut BPOC.

MINIMA DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Toutes Pistes: *	1000 0 1000

CARTE D'AÉRODROME — CYAH

EFF 10 SEP 20

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LA MACAZA/MONT-TREMBLANT, QC


AERODROME CHART — CYFJ

UNICOM – **122.7** (AU)

CTR Montreal – **133.9**

MF

DECL DISTS	02	20
TORA	5902	5902
TODA	6886	6886
ASDA	6164	6394
LDA	5902	5902



*DEPARTURE PROCEDURE

Rwy 02 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2200** BPOC.

Rwy 20 - ½ **-** Requires a minimum climb gradient of **350** ft/NM to **1400**. NO LEFT turn below **2400**. **Note:** Trees to 895 ASL abeam departure end of rwy, 400' LEFT and RIGHT of rwy centreline and aprx 0.3 NM past departure end of rwy.

or

SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **2200** BPOC.

TAKE-OFF MINIMA

Rwys 02, 20: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYFJ

EFF 5 OCT 23

LA MACAZA/MONT-TREMBLANT, QC


CARTE D'AÉRODROME — CYFJ

UNICOM – **122.7** (AU)

CTR Montreal – **133.9**

MF

DIST DÉCLARÉES	02	20
TORA	5902	5902
TODA	6886	6886
ASDA	6164	6394
LDA	5902	5902



MINIMUM DE DÉCOLLAGE
Pistes 02, 20: *

ÉCHELLE EN PIEDS

1000 0 1000 2000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME — CYFJ

EFF 5 OCT 23

LA ROMAINE, QC

AERODROME CHART — CTT5

AWOS Natashquan – **126.25** (En) **125.3** (Fr)				◕ UNICOM – **123.5** (AU) (Fr) ATF*				
DECL DISTS	**11**	**29**						
TORA	3933	3933						
TODA	3933	3933						
ASDA	3933	3933						
LDA	3933	3933						



* DEPARTURE PROCEDURE

Rwy 11 - ½ - For Western departure only: Climbing LEFT turn HDG **310°**. Make sure there is no conflict with ACFT departing Kegaska (CTK6) BPOC. Common FREQ 123.5.
Note: Trees to 238 ASL aprx 0.9 NM past departure end of rwy.

Rwy 29 - ½ - For Western departure only: Climbing RIGHT turn HDG **310°**. Make sure there is no conflict with ACFT departing Kegaska (CTK6) BPOC. Common FREQ 123.5.
Note: Hills **200'** aprx 0.2 NM NW of thld rwy 11. Trees to 196 ASL aprx 0.7 NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA ROMAINE, QC

CARTE D'AÉRODROME — CTT5

AWOS Natashquan – **125.3** (Fr) **126.25** (Ang)		◕ UNICOM – **123.5** (AU) (Fr) ATF*	

DIST DÉCLARÉES	11	29
TORA	3933	3933
TODA	3933	3933
ASDA	3933	3933
LDA	3933	3933



* PROCÉDURE DE DÉPART

Piste 11 - ½ - Pour les départs vers l'OUEST seulement: Monter en virage à GAUCHE sur un cap de **310°**. S'assurer qu'aucun conflit n'existe avec les aéronefs au départ de Kegaska (CTK6) BPOC. Fréquence commune 123.5.
Note: Arbres jusqu'à 238 ASL aprx 0.9 NM passé l'extrémité de départ de la piste.

Piste 29 - ½ - Pour les départs vers l'OUEST seulement: Monter en virage à DROITE sur un cap de **310°**. S'assurer qu'aucun conflit n'existe avec les aéronefs au départ de Kegaska (CTK6) BPOC. Fréquence commune 123.5.
Note: Colline **200'** aprx 0.2 NM au NO du seuil de piste 11. Arbres jusqu'à 196 ASL aprx 0.7 NM passé l'extrémité de départ de la piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 11, 29: *	1000 0 1000 2000

CARTE D'AÉRODROME — CTT5

EFF 29 DÉC 22

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LA SARRE, QC

AERODROME CHART


CSR8

CTR Montreal – **125.9**

TFC – **122.8**

ATF

DECL DISTS	18	36						
TORA	4702	4702						
TODA	4702	4702						
ASDA	4702	4702						
LDA	4702	4702						



TAKE-OFF MINIMA
Rwys 18, 36: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA SARRE, QC


CARTE D'AÉRODROME — CSR8

CTR Montreal – **125.9**

TFC – **122.8**

ATF

DIST DÉCLARÉES	18	36
TORA	4702	4702
TODA	4702	4702
ASDA	4702	4702
LDA	4702	4702



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 18, 36: *	1000 0 1000

CARTE D'AÉRODROME — CSR8

EFF 21 MAI 20


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LA TUQUE, QC

AERODROME CHART — CYLQ

AUTO – **122.97**		◕ UNICOM – **122.32** (AU)	CTR Montreal – **134.5**

DECL DISTS	01	19
TORA	5000	5000
TODA	5000	5000
ASDA	5000	5000
LDA	5000	5000



* DEPARTURE PROCEDURE

Rwy 01 - ½ **-** Requires a minimum climb gradient of **400** ft/NM to **1600**.
or
SPEC VIS **-** Climb in visual condition to cross the aprt at or above **1800** BPOC.
Note: Trees to 640 ASL abeam departure end of rwy, 50' LEFT and RIGHT of rwy centreline and aprx 100' past departure end of rwy.

Rwy 19 - ½ - Requires a minimum climb gradient of **450** ft/NM to **1600**.
or
SPEC VIS - Climb in visual condition to cross the aprt at or above **1800** BPOC.
Note: Trees to 630 ASL aprx 100' past departure end of rwy, 500' LEFT and RIGHT of rwy centreline and aprx 0.1 NM past departure end of rwy.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000
450 FT/NM	680	900	1050	1200	1350	1500	1880	2250

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 01; 19: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LA TUQUE, QC

CARTE D'AÉRODROME — CYLQ

AUTO – **122.97**		◕ UNICOM – **122.32** (AU)	CTR Montreal – **134.5**

DIST DÉCLARÉES	01	19						
TORA	5000	5000						
TODA	5000	5000						
ASDA	5000	5000						
LDA	5000	5000						



* PROCÉDURE DE DÉPART

Piste 01 - ½ - Requiert une pente de montée minimale de **400** pi/NM jusqu'à **1600**.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1800** ou plus haut BPOC.
Note: Arbres jusqu'à 640 ASL par le travers de l'extrémité de la piste de départ, 50° à GAUCHE et DROITE de l'axe de piste et aprx 100° passé l'extrémité de la piste de départ.

PIste 19 - ½ - Requiert une pente de montée minimale de **450** pi/NM jusqu'à **1600**.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1800** ou plus haut BPOC.
Note: Arbres jusqu'à 630 ASL aprx 100° passé l'extrémité de la piste de départ, 500° à GAUCHE et DROITE de l'axe de piste et aprx 0.1 NM passé l'extrémité de la piste de départ.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
400 pieds/NM	600	800	940	1070	1200	1340	1670	2000
450 pieds/NM	680	900	1050	1200	1350	1500	1880	2250

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 01; 19: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


LACHUTE, QC

AERODROME CHART

CSE4

		UNICOM – **123.0** ATF*				TML Montreal – **124.65 268.3**		

DECL DISTS	10	28						
TORA	3989	3989						
TODA	3989	3989						
ASDA	3989	3989						
LDA	3094	3779						



TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART CSE4

EFF 26 MAY 16

LACHUTE, QC


CARTE D'AÉRODROME — CSE4

UNICOM – **123.0**

TML Montreal – **124.65 268.3**

ATF*

DIST DÉCLARÉES	10	28						
TORA	3989	3989						
TODA	3989	3989						
ASDA	3989	3989						
LDA	3094	3779						



MINIMUM DE DÉCOLLAGE
Toutes pistes: *

ÉCHELLE EN PIEDS

1000 0 1000

CARTE D'AÉRODROME — CSE4

EFF 26 MAI 16

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LAC-SAINT-JEAN, QC


AERODROME CHART — CYDO

UNICOM – **122.7**

ATF

RADIO Quebec – **123.55**

DECL DISTS	11	29	03	21				
TORA	5001	5001	3563	3563				
TODA	5001	5001	3563	3563				
ASDA	5001	5001	3563	3563				
LDA	5001	5001	3563	3563				



* DEPARTURE PROCEDURE

Rwy 11 - ½
Departure not auth when CYA641(M) active.
Climbing not auth above **7000** when CYR628 active.
Climb between hdg **118°** CW to **290°** when CYA642(M) active.
Note: Trees to 391 ASL aprx 360' past departure end, 560' LEFT of rwy centreline.

Rwy 29 - ½
Departure not auth when CYA641(M) active.
Climbing not auth above **7000** when CYR628 active.
Climb between hdg **003°** CCW to **110°** when CYA642(M) active.

TAKE-OFF MINIMA

Rwys 11; 29: *
Rwys 03; 21: NOT ASSESSED

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYDO


EFF 5 OCT 23

LAC-SAINT-JEAN, QC

CARTE D'AÉRODROME — CYDO

		UNICOM – **122.7** ATF	RADIO Quebec – **123.55**

DIST DÉCLARÉES	11	29	03	21				
TORA	5001	5001	3563	3563				
TODA	5001	5001	3563	3563				
ASDA	5001	5001	3563	3563				
LDA	5001	5001	3563	3563				



* PROCÉDURE DE DÉPART

Piste 11 - ½
Départ non autorisé lorsque CYA641(M) est actif.
Montée non autorisée au-dessus de **7000** lorsque CYR628 est actif.
Monter entre caps **118°** et **290°** sens horaire pour demeurer à l'écart CYA642(M) lorsque actif.
Note: Arbres jusqu'à 391 ASL aprx 360' passé l'extrémité de la piste de départ, 450' à GAUCHE de l'axe de piste.

Piste 29 - ½
Départ non autorisé lorsque CYA641(M) est actif.
Montée non autorisée au-dessus de **7000** lorsque CYR628 est actif.
Monter entre caps **003°** et **110°** sens antihoraire pour demeurer à l'écart de CYA642(M) lorsque actif.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 11; 29: * Pistes 03; 21: PAS ÉVALUÉ	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LEBEL-SUR-QUÉVILLON, QC


AERODROME CHART — CSH4

CTR Montreal – **125.9**

TFC – **123.2**

ATF

DECL DISTS	15	33
TORA	4212	4212
TODA	4212	4212
ASDA	4212	4212
LDA	4212	4212



TAKE-OFF MINIMA
Rwys 15, 33: ★

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CSH4

EFF 20 JUN 19

LEBEL-SUR-QUÉVILLON, QC


CARTE D'AÉRODROME — CSH4

CTR Montreal – **125.9**

TFC – **123.2**

ATF

DIST DÉCLARÉES	15	33
TORA	4212	4212
TODA	4212	4212
ASDA	4212	4212
LDA	4212	4212



MINIMUM DE DÉCOLLAGE
Pistes 15, 33: ★

ÉCHELLE EN PIEDS

1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

LOURDES-DE-BLANC-SABLON, QC

AERODROME CHART — CYBX

AUTO – **128.15** (En) **124.35** (Fr)		RADIO Mont-Joli – **122.0** MF*	CTR Gander – **133.0**

DECL DISTS	05	23
TORA	4500	4500
TODA	5484	5484
ASDA	4500	4500
LDA	4500	4500



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450

* DEPARTURE PROCEDURE
Rwy 05 - ½ **-** Requires a minimum climb gradient of **290** ft/NM to **900**.
or
SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **900** BPOC.

TAKE-OFF MINIMA
Rwy 05: *
Rwy 23: ½

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYBX


EFF 14 JUL 22

LOURDES-DE-BLANC-SABLON, QC

CARTE D'AÉRODROME — CYBX

AUTO – **124.35** (Fr) **128.15** (Ang)		RADIO Mont-Joli – **122.0** MF*	CTR Gander – **133.0**

DIST DÉCLARÉES	05	23
TORA	4500	4500
TODA	5484	5484
ASDA	4500	4500
LDA	4500	4500



TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
290 pieds/NM	440	580	680	780	870	970	1210	1450

* PROCÉDURE DE DÉPART

Piste 05 - ½ - Requiert une pente de montée minimale de **290** pieds/NM jusqu'à **900**.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **900** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 05: * Piste 23: ½	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYBX

EFF 14 JUIL 22

MANIWAKI, QC


AERODROME CHART — CYMW

UNICOM – **122.8**

CTR Montreal – **126.57**

ATF

DECL DISTS	03	21						
TORA	4921	4921						
TODA	4921	4921						
ASDA	4921	4921						
LDA	4921	4921						



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMW

EFF 21 MAY 20

MANIWAKI, QC


CARTE D'AÉRODROME — CYMW

UNICOM – **122.8**

CTR Montreal – **126.57**

ATF

DIST DÉCLARÉES	03	21						
TORA	4921	4921						
TODA	4921	4921						
ASDA	4921	4921						
LDA	4921	4921						



*PROCÉDURE DE DÉPART

PIste 03 - ½

Note: Arbres jusqu'à 729 ASL par le travers de l'extrémité de départ de la piste, 350° à droite de l'axe de piste.

PIste 21 - SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport jusqu'à **1800** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 03, 21: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYMW

EFF 21 MAI 20

MATAGAMI, QC

AERODROME CHART — CYNM


MET – **127.45** (En) **125.3** (Fr)

UNICOM – **122.8** (Fr)

ATF

RADIO Quebec – **123.55** DRCO

DECL DISTS	15	33
TORA	5001	5001
TODA	5985	5985
ASDA	5001	5001
LDA	5001	5001



TAKE-OFF MINIMA	
Rwys 15, 33: *	

SCALE IN FEET

1000 500 0 500 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYNM


EFF 10 SEP 20

MATAGAMI, QC

CARTE D'AÉRODROME — CYNM

MET – **125.3** (Fr) **127.45** (Ang)		UNICOM – **122.8** (Fr) ATF	RADIO Quebec – **123.55** DRCO

DIST DÉCLARÉES	15	33
TORA	5001	5001
TODA	5985	5985
ASDA	5001	5001
LDA	5001	5001



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 15, 33: *	1000 500 0 500 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYNM


EFF 10 SEP 20

MATANE/RUSSELL-BURNETT, QC

AERODROME CHART — CYME

		UNICOM – **122.8** ATF	CTR Montreal – **134.65 227.2**

DECL DISTS	09	27
TORA	5500	5500
TODA	5900	6500
ASDA	5500	5500
LDA	5500	5500



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYME


EFF 14 JUL 22

MATANE/RUSSELL-BURNETT, QC

CARTE D'AÉRODROME — CYME

			◕ UNICOM – **122.8** ATF				CTR Montreal – **134.65 227.2**	

DIST DÉCLARÉES	09	27						
TORA	5500	5500						
TODA	5900	6500						
ASDA	5500	5500						
LDA	5500	5500						



* PROCÉDURE DE DÉPART

Piste 09 - ½ - Requiert une pente de montée minimale de **390** pi/NM jusqu'à **600**. Monter sur cap **090°** jusqu'à **1500** PBOC.
Note: Arbres jusqu'à 165 ASL par le travers de l'extrémité de la piste de départ, 200' à DROITE et 250' à GAUCHE de l'axe de piste et aprx 350' passé l'extrémité de la piste de départ.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2100** ou plus haut BPOC.

PIste 27 - ½ - Requiert une pente de montée minimale de **370** pi/NM jusqu'à **1100**. AUCUN virage en dessous de **1100** BPOC.
Note: Arbres jusqu'à 220 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 600' à GAUCHE de l'axe de piste.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2100** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 09; 27: *	1000 0 1000

CARTE D'AÉRODROME — CYME

EFF 14 JUIL 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

MONT-JOLI, QC

AERODROME CHART — CYYY

		RADIO – **122.1** MF*	CTR Montreal – **134.65 227.2** RADIO Quebec – **123.37**

DECL DISTS	06	24	15	33				
TORA	6000	6000	3954	3954				
TODA	6984	6400	4454	4104				
ASDA	6000	6000	3954	3954				
LDA	6000	6000	3954	3724				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYY

EFF 29 DEC 22

MONT-JOLI, QC

CARTE D'AÉRODROME — CYYY

		RADIO – **122.1** MF*	CTR Montreal – **134.65 227.2** RADIO Quebec – **123.37**

DIST DÉCLARÉES	06	24	15	33
TORA	6000	6000	3954	3954
TODA	6984	6400	4454	4104
ASDA	6000	6000	3954	3954
LDA	6000	6000	3954	3724

68 13 — 68 12.5 — 68 12

48 37

* PROCÉDURE DE DÉPART

Toutes Pistes: Procédure de départ non auth lorsque la zone de dynamitage est active (OCSL par NOTAM), de la surface jusqu'à **2000**, 1.8 NM au sud-est de l'aérodrome.

PIste 06 - ½ - Monter sur cap **057°** jusqu'à **1200** BPOC.
Note: Terrain jusqu'à 144 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 400' à DROITE de l'axe de piste.

Piste 15 - ½
Requiert une pente de montée minimale de **400** pi/NM jusqu'à **1000**.
AUCUN virage à DROITE en dessous de **2000**.
Note: Arbres jusqu'à 243 ASL aprx 500' passé l'extrémité de la piste de départ.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1700** ou plus haut BPOC.

Piste 24 - ½ - AUCUN virage à GAUCHE en dessous de **2300**.
Note: Arbres jusqu'à 220 ASL aprx 0.1 NM passé l'extrémité de la piste de départ.

Piste 33 - ½ - Monter sur cap **330°** jusqu'à **1300** BPOC.
Note: Arbres jusqu'à 167 ASL aprx 150' passé l'extrémité de la piste de départ. 450' à GAUCHE de l'axe de piste.

AS 24 — ALT 125 — 237° — P2 — 6000 x 150

CYYY
N48 36.54
W68 12.48

DÉC 18° W 2012
VARIATION ANNUELLE DE 8° E

48 36.5

15 — 150° — 057° — Descend 0.38% — ALT 131 — P2

monte 1.03% — 3954 x 150 — A — B — FSS — 330° — ALT 172 — 33

AO — 06 — ALT 148

Piste 33 seuil décalé 230'

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
400 pieds/NM	600	800	940	1070	1200	1340	1670	2000

48 36

68 13 — 68 12.5 — 68 12

MINIMUM DE DÉCOLLAGE

Toutes les pistes: *

ÉCHELLE EN PIEDS
1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYYY


EFF 29 DÉC 22

MONT-LAURIER, QC

AERODROME CHART — CSD4

AUTO – **129.07** (En) **123.42** (Fr)		UNICOM – **122.8** ATF	CTR Montreal – **126.57** RADIO Quebec – **123.47**

DECL DISTS	08	26
TORA	4002	4002
TODA	4002	4002
ASDA	4002	4002
LDA	3805	4002



TAKE-OFF MINIMA
Rwys 08, 26: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MONT-LAURIER, QC

CARTE D'AÉRODROME — CSD4

AUTO – **123.42** (Fr) **129.07** (Ang)		UNICOM – **122.8** ATF	CTR Montreal – **126.57** RADIO Quebec – **123.47**

DIST DÉCLARÉES	08	26
TORA	4002	4002
TODA	4002	4002
ASDA	4002	4002
LDA	3805	4002



* PROCÉDURE DE DÉPART

PIste 08 - ½ **-** Requiert une pente de montée minimale de **280** pi/NM jusqu'à **1500**. AUCUN virage à GAUCHE en dessous de **2400**.
Note: Arbres jusqu'à 896 ASL par le travers de l'extrémité de la piste de départ, 150' à GAUCHE et à DROITE de l'axe de piste.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2600** ou plus haut BPOC.

Piste 26 - ½ **-** Requiert une pente de montée minimale de **220** pi/NM jusqu'à **1300**. Monter sur cap **257°** jusqu'à **2100** BPOC.
Note: Arbres jusqu'à 893 ASL par le travers de l'extrémité de la piste de départ, 150' à DROITE de l'axe de piste.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2600** ou plus haut BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 08; 26: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

MONTRÉAL INTL (MIRABEL), QC

AERODROME CHART — CYMX

ATIS Mirabel – **125.7** (En) **126.1** (Fr)	APRON Mirabel – **122.4** GND – **121.8** GND ADV – **121.8**	TWR – **119.1** RADIO Mirabel – **119.1** MF*	TML Montreal – **124.65 268.3**

DECL DISTS	06	24	11	29				
TORA	12000	12000	12000	12000				
TODA	12984	12984	12984	12984				
ASDA	12000	12000	12000	12000				
LDA	12000	12000	12000	12000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06, 24: RVR 1200	RWY 06: RVR 600

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 11; 24; 29: *	6000 0 6000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMX

EFF 15 JUN 23

MONTRÉAL INTL (MIRABEL), QC

CARTE D'AÉRODROME — CYMX

ATIS Mirabel – **126.1** (Fr) **125.7** (Ang)	AIRE DE TRAFIC Mirabel – **122.4** GND – **121.8** GND ADV – **121.8**	TWR – **119.1** RADIO Mirabel – **119.1** MF*	TML Montreal – **124.65 268.3**

DIST DÉCLARÉES	06	24	11	29				
TORA	12000	12000	12000	12000				
TODA	12984	12984	12984	12984				
ASDA	12000	12000	12000	12000				
LDA	12000	12000	12000	12000				

74 05 74 04 74 03 74 02 74 01 74 00 73 59

45 43 45 42 45 41 45 40 45 39

DÉC 15' W 2003
VARIATION ANNUELLE DE 3' E

TORA POUR LES DÉPARTS D'INTERSECTIONS

PISTE	INTXN	TORA	PISTE	INTXN	TORA	PISTE	INTXN	TORA	PISTE	INTXN	TORA
06	B6	8323	24	B6	3809	11	A5	3834	29	A5	8342
	B4	6323		B4	5820		A6	8177		A6	3666
	B5	3733		B5	8401						

Conformément à l'allnéa 602.96(3)(d) du RAC, aucun commandant de bord d'un aéronef qui circule au sol pour procéder à un départ pendant des opérations ILS CAT II ne dolt procéder au-delà du polnt d'attente ILS CAT II sans avolr obtenu une autorisation IFR valide de l'ATC.

Consultez le Supplément de vol - Canada pour obtenir les procédures liées à la fréquence GND ADV

Aéronef au départ: Passez de GND ADV à la MF avant de circuler sur l'aire de manoeuvre

CYMX
N45 40.79
W74 02.32

HÉLIBELLULE
Mirajet
ICar
TWR/FSS
Aire de trafic principale
Aire de trafic cargo
Aire de trafic industrielle

ALT 247
ALT 238
ALT 256
ALT 271

AN
113°
293°
12,000
descend 0.65% premiers 3412'
060°
240°
12,000 CONC

Twy I direction E seulement.
Twy J direction W seulement.

Caserne
LIGNE D'ATTENTE CAT II
CENTRE DE DÉGIVRAGE voir CFS "PRO"

* PROCÉDURE DE DÉPART
Référez au page PROCÉDURE DE DÉPART.

Après atterrissage piste 06, virages à gauche sur B6 ou B4 non autorisés pour aéronef à réaction de 79' ou plus d'envergure.

NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
PISTES 06, 24: RVR 1200	PISTE 06: RVR 600
MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06; 11; 24; 29:*	6000 0 6000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYMX

EFF 15 JUIN 23

Operations in Reduced and Low Visibility Conditions

- Runway 06 is certified for use in low visibility operations (RVR600).
- Runway 24 is certified for use in reduced visibility conditions (RVR1200).
- Plan activation is mandatory when one of the RVR readings or the reported ground visibility is below ½ SM. Runways 24 and 06 can be used.
- When the reading of one of the RVR readings or the reported ground visibility is less than ¼ SM while remaining at or above ⅛ SM, runway 06 must be used.
- Only one aircraft movement (RVOP and LVOP) is authorised on the manoeuvring area. In low visibility operation (LVOP), it is mandatory that the "Follow Me" vehicle escorts the aircraft.
- With the exception of aircraft returning to aprons, movement of all traffic ceases when one of the RVR reading or the reported ground visibility is below ⅛ SM.
- When the two RVR readings or the reported ground visibility increases and indicates ½ SM or more, normal operations may resume.
- Taxiway I is used for eastbound traffic as published in the CFS.
- Taxiway J is used for westbound traffic as published in the CFS.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Opérations en conditions de visibilité réduite et faible

- La piste 06 est homologuée pour les opérations en conditions de visibilité faible (RVR600).
- La piste 24 est homologuée pour les conditions en conditions de visibilité réduite (RVR1200).
- Le plan est déclenché lorsque la lecture d'un des RVR ou la visibilité au sol signalée est inférieure à ½ SM. Les pistes 24 ou 06 peuvent être utilisées.
- Lorsque la lecture d'un des RVR ou la visibilité signalée au sol est de moins de ¼ SM mais de plus de ⅛ SM, la piste 06 doit être utilisée.
- Un seul mouvement d'aéronef à tout moment (RVOP et LVOP) est autorisé sur l'aire de manœuvre. En condition de faible visibilité (LVOP), il doit obligatoirement être escorté d'un véhicule « Follow Me ».
- À l'exception des mouvements associés au retour des aéronefs aux aires de trafic, toute circulation au sol est interrompue lorsque la lecture d'un des RVR ou la visibilité signalée au sol est de moins de ⅛ SM.
- Lorsque la lecture des deux RVR ou que la visibilité signalée au sol augmente et indique ½ SM ou plus, le retour aux opérations normales peut être initié.
- La voie de circulation I est utilisée par le trafic en direction Est tel que publié au CFS.
- La voie de circulation J est utilisée en direction Ouest tel que publié au CFS.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


MONTRÉAL INTL (MIRABEL), QC

PARKING AREAS

CYMX

ATIS Mirabel –**125.7** (En)
126.1 (Fr)

APRON Mirabel – **122.4**
DE ICE Aeromag 2000 – **122.25**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYMX


EFF 15 JUN 23

MONTRÉAL INTL (MIRABEL), QC

AIRES DE STATIONNEMENT — CYMX

ATIS Mirabel – **126.1** (Fr)
125.7 (Ang)

AIRE DE TRAFIC Mirabel – **122.4**
DÉGIVRAGE Aeromag 2000 – **122.25**



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT — CYMX


EFF 15 JUIN 23

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

AERODROME CHART — CYUL

ATIS – **133.7** (En) **127.5** (Fr)	CLNC DEL – **125.6** APRON – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3** **119.9** **124.3** **267.1**	DEP – **120.42** (S) (SE) (SW) **124.65** (W) (NW) (NE) **268.3** RADIO Quebec – **123.55**

DECL DISTS	06L	24R	06R	24L	10	28		
TORA	11000	11000	9600	9600	7000	7000		
TODA	11000	11000	9600	9600	7000	7000		
ASDA	11000	11000	9600	9600	7150	7000		
LDA	11000	11000	9600	9600	7000	7000		



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06L, 06R, 24L, 24R: RVR 1200	RWY 06L: RVR 600
TAKE-OFF MINIMA	
Rwys 06L; 06R; 24L; 24R: *	SCALE IN FEET: 2000 0 2000 4000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

When authorized by ATC, intersection departures are available as follows:

RUNWAY	INTERSECTION	TORA
06L	G	10197
	B4	7677
	B1	6002
	B2	5237
	B3	4902
	B5	2898
06R	A4	7872
	A2	5399
	A1	4339
	L	2453
	A3	2342
10	G	6167
	F	4871
	B2	4846
	E	3040
24L	A3	7402
	L	7250
	A1	5400
	A2	4341
24R	B5	8244
	B3	6243
	B2	5908
	B1	5145
	B4	3470
	G	915
28	K	6658
	D	6584
	E	4146
	B2	2305
	F	2275

Departures from inner centerline of holding bay rwy 06R subtract 276' from declared distances.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

CARTE D'AÉRODROME — CYUL

ATIS – **127.5** (Fr) **133.7** (Ang)	CLNC DEL – **125.6** AIRE DE TRAFIC – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3** **119.9** **124.3** **267.1**	DEP – **120.42** (S) (SE) (SW) **124.65** (W) (NW) (NE) **268.3** RADIO Québec – **123.55**

DIST DÉCLARÉES	06L	24R	06R	24L	10	28		
TORA	11000	11000	9600	9600	7000	7000		
TODA	11000	11000	9600	9600	7000	7000		
ASDA	11000	11000	9600	9600	7150	7000		
LDA	11000	11000	9600	9600	7000	7000		



NIVEAU DE SERVICES DE LA PISTE	
RVO	LVO
PISTE 06L, 06R, 24L, 24R: RVR 1200	PISTE 06L: RVR 600
MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06L; 06R; 24L; 24R: *	2000 0 2000 4000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYUL

EFF 5 OCT 23

Lorsque autorisé par ATC, les départs d'intersection sont disponibles comme suit :

PISTE	INTERSECTION	TORA
06L	G	10197
	B4	7677
	B1	6002
	B2	5237
	B3	4902
	B5	2898
06R	A4	7872
	A2	5399
	A1	4339
	L	2453
	A3	2342
10	G	6167
	F	4871
	B2	4846
	E	3040
24L	A3	7402
	L	7250
	A1	5400
	A2	4341
24R	B5	8244
	B3	6243
	B2	5908
	B1	5145
	B4	3470
	G	915
28	K	6658
	D	6584
	E	4146
	B2	2305
	F	2275

Les départs de l'axe intérieur de la baie d'attente Piste 06R soustraire 276' des distances déclarées.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Notes

Widebody Aircraft:

A380, A124, A346, B748 & B773 – Right turn prohibited from A4 or A2 to A.

A380, A124, A346, B748 & B773 – Left turn difficult from A1 to A. Use of A3 or holding bay 24L recommended.

A380, A340-500/600, A350-1000 & B777 – Right turn prohibited from A4 to D.

Code F aircraft – Standard routes. Follow ATC and Apron Control instructions.

A380 – It is mandatory to use the procedures for runway widths of 58 m or less without paved shoulders. (All runways 60 m wide with 7.5 m shoulders: first meter paved, remaining, grass).

Minimum Rwy to Twy Separation			
	Rwy	**Twy**	**Separation (m)**
1	06L – 24R	B	225
2	06R – 24L	A	232
3	10 – 28	H	190
4	06L – 24R	North Ramp	210
5	06R – 24L	AM	233
6	10 – 28	North Ramp	182.5

Minimum Twy to Twy Separation			
	Twy	**Twy**	**Separation (m)**
1	I	H	195.9
2	K	J	195.8
3	A	D	85.6

Minimum Twy to Taxilane Separation			
	Twy	**Taxilane**	**Separation (m)**
1	North Ramp	South taxilane*	80.5
2	AM	East Holding point*	80.6
* closed during code F Aircraft operations			


Minimum Twy to Obstacle Separation			
	Twy	**Obstacle**	**Separation (m)**
1	G	T395	50.9
2	A	Road 630*	47.5
3	North Ramp	Road E1 to E3*	43.3
4	North Ramp	Road, stands 17 to 27*	47.7
5	Ramp NW – SE	Road, stands 11B to 15*	47
6	Ramp NW – SE	Road, stands 15 to 15B*	42.5
* closed during code F Aircraft operations			

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

TAXI CHART CYUL

ATIS – **133.7** (En) **127.5** (Fr)	CLNC DEL – **125.6** APRON – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3 119.9 124.3 267.1**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TAXI CHART CYUL

EFF 5 OCT 23

Notes

Avion gros-porteurs :

A380, A124, A346, B748 & B773 – Virage à droite interdit de A4 ou A2 vers A.

A380, A124, A346, B748 & B773 – Virage à gauche difficile de A1 vers A. Utilisation de A3 ou de la baie d'attente 24L recommandée.

A380, A340-500/600, A350-1000 & B777 – Virage à droite interdit de A4 vers D.

Aéronefs de code F – Routes normalisées. Suivre les instructions d'ATC et contrôle du tablier.

A380 – Il est obligatoire d'utiliser les procédures pour pistes de 58 m ou moins sans accotement pavé. (Pistes 60 m de largeur avec accotements de 7.5 m; premier mètre pavé, reste en gazon).

Dégagement minimum RWY à TWY			
	RWY	**TWY**	**Dégagement (m)**
1	06L – 24R	B	225
2	06R – 24L	A	232
3	10 – 28	H	190
4	06L – 24R	Rampe nord	210
5	06R – 24L	AM	233
6	10 – 28	Rampe nord	182.5

Dégagement minimum TWY à TWY			
	TWY	**TWY**	**Dégagement (m)**
1	I	H	195.9
2	K	J	195.8
3	A	D	85.6

Dégagement minimum TWY à voie d'accès de poste de stationnement			
	TWY	**Voie d'accès de poste de stationnement**	**Dégagement (m)**
1	Rampe nord	Voie d'accès de poste de stationnement Sud*	80.5
2	AM	Point d'attente Est*	80.6
*Fermé pendant opérations d'aéronefs de code F			

Dégagement minimum TWY à obstacle			
	TWY	**Obstacle**	**Dégagement (m)**
1	G	T395	50.9
2	A	Route 630*	47.5
3	Rampe nord	Route E1 à E3*	43.3
4	Rampe nord	Route, postes 17 à 27*	47.7
5	Rampe NW – SE	Route, postes 11B à 15*	47
6	Rampe NW – SE	Route, postes 15 à 15B*	42.5
*Fermé pendant opérations d'aéronefs de code F			

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

CARTE DE CIRCULATION — CYUL

ATIS – **127.5** (Fr) **133.7** (Ang)	CLNC DEL – **125.6** AIRE DE TRAFIC – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3 119.9 124.3 267.1**

73 46 — 73 45 — 73 44 — 73 43

VOIR CARTE D'AIRES DE STATIONNEMENT POUR PROCÉDURES SUR LE TABLIER

Voie de circulation Q non contrôlée limitée aux aéronefs d'une envergure de moins de 36m (118')

Voies de circulation L et R limitées aux aéronefs avec une envergure de moins de 36m (118') et de 95,500 kg ou moins

45 29 — 45 28 — 45 27

DEC 15° W 2013
VARIATION ANNUELLE DE 4° E

Virages à gauche sur twy B de twy B3 & B5 interdits aux aéronefs de 36m (118') et plus d'envergure

STATIONNEMENT CENTRE

ABRI DE FOUILLE

CENTRE DE DÉGIVRAGE

11 000

B (ASDE)

fstd aéronef en remorquage seulement

272

GND OUEST

GND EST

GND OUEST AIRE DE TRAFIC OUEST

GND EST AIRE DE TRAFIC EST

7000

9600

LIGNE D'ARRÊT OBLIGATOIRE

TRAVERSE DE VÉHICULE EN PROVENANCE DE LA ROUTE DE SERVICE

CAT I POINT D'ATTENTE

AVIATION GÉNÉRALE TABLIER NON-CONTRÔLÉ

DOUANES

TOUR DE CONTRÔLE DU TABLIER

TOUR DE CONTRÔLE

HS 1 — HS 2 — HS 3 — HS 5 — HS 6 — HS 7 — HS 8

24R — 24L — 06L — 06R — 10 — 28

POINTS CHAUDS

HS 1 - Les aéronefs circulant en direction sud-ouest sur la voie A manquent la ligne d'arrêt pour la piste 10/28.

HS 2 - Les aéronefs circulant en direction nord-est sur la voie A manquent la ligne d'arrêt pour la piste 10/28.

HS 3 - Les aéronefs circulant en direction est sur la voie J manquent la ligne d'arrêt pour la piste 10/28.

HS 5 - Les aéronefs circulant en direction sud-est sur la voie A4 manquent le virage à gauche sur la voie A.

HS 6 - Les aéronefs circulant en direction sud sur la voie A3 vers la voie L manquent la ligne d'arrêt pour la piste 06R/24L.

HS 7 - Les aéronefs circulant en direction nord sur la voie B4 manquent le virage sur la voie B et se retrouvent sur la piste 06L/24R.

HS 8 - Les aéronefs circulant en direction nord-est sur la voie R manquent la ligne d'arrêt pour la piste 24L.

NOTE:
Voir CARTE DE CIRCULATION pour notes additionelles des voies de circulation.

Multilatération:
Laissez votre transpondeur allumé en tout temps lorsque vous circulez.

Capacité des baies d'attente:
2 aéronefs de moins de 36m (118') d'envergure
Aéronefs de 36m (118') ou plus d'envergure:
Baie d'attente 06L: utiliser ligne nord
Baie d'attente 24R: utiliser ligne centre
Baie d'attente 24L: utiliser ligne sud
Baie d'attente 06R: 2 aéronefs simultanés, aéronef de 65m (213') et moins d'envergure utiliser la ligne sud, aéronefs de 65m (213') d'envergure et plus utiliser la ligne nord.

VOIR CARTE DES AIRES DE STATIONNEMENT CENTRALE et POSITIONS DE DÉGIVRAGE et PROCÉDURES

ÉCHELLE EN PIEDS
2000 — 0 — 2000 — 4000

73 46 — 73 45 — 73 44 — 73 43

CARTE DE CIRCULATION — CYUL

EFF 5 OCT 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Low Visibility Procedures (RVR less than 1200 to 600 ft)

1. Application

These procedures apply to ground movements of aircraft during low visibility conditions (Runway Visual Range [RVR] less than 1200 to 600 ft). Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented to ensure the safe and efficient movement of aircraft. The following message will be added to the ATIS broadcast: **"LOW VISIBILITY PROCEDURES IN EFFECT"**

2. Surface Guidance and Control System

Surface guidance and control system have been installed to facilitate the ground movements of aircraft under low visibility conditions. This system, controlled by ATC, is:

- Taxiway centreline lights on holding bay 24R.
- Taxiway uni-directional centreline lights on taxiways A (between J and A4), A4 (between A and the apron), B, B3, B4 (from B to runway 10/28), B5, D, E (from the apron to I), F, H, I, J and K.
- Bi-directional centreline lights on the North ramp from taxiway G to A4, South ramp from G to gate 65, and East and West taxilanes up to gate 66.
- Stop Bars on all access to runway 06L/24R: on the holding bays of runways 06L and 24R, at the end of runway 28 before the intersection with runway 06L/24R and on taxiways B1, B2, B3, B4, B5, and G (illuminated under 1200 RVR).

  NOTE: AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR

- Runway guard lights on all access to runways: on the holding bays of runways 06L, 24R, 06R and 24L, at the end of runway 28 before the intersection with runway 06L/24R, on runways 06L and 24R before the intersection with runway 10/28 and on taxiways A, A1, A2, A3, A4, B1, B2, B3, B4, B5, D, E, F, G, J, L and R (illuminated whenever the associated runway is in use).

NOTE: The above mentioned taxiway centreline lights and stop bars may be used at or above 1200 RVR.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

3. Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft and vehicles operating on the manoeuvring area. In the event of an ASDE failure, ATC may restrict low visibility operations.

4. "Follow me" Vehicle

A "Follow Me" vehicle will be provided on pilot's request.

5. Departure Routes

Runway 06L is the only one certified for take-offs during low visibility conditions (RVR less than 1200 to 600 ft). All departures under low visibility conditions will be on runway 06L. Intersection take-offs are not authorized.

Sequencing of aircraft ground movements for take-off: Do not request start, push back or taxi clearance until reported RVR is greater than:

Aircraft/Pilot Take-off Minima	MInimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

Unless otherwise advised by ATC, the following standard routes will be used, under low visibility conditions, for aircraft departing on runway 06L (see low visibility taxi chart).

From the main apron to the de-icing bay: aircraft will taxi on E and H or on D and K.

From the main apron to runway 06L: aircraft will taxi on the main apron to the holding bay runway 06L.

From the de-icing bay to runway 06L: aircraft will taxi on I, B, B4, F and on the apron to the holding bay runway 06L.

From the de-icing bay to the main apron aircraft will taxi on taxiways J, A and A4.

From general aviation to 06L, aircraft will taxi on taxiway R, across threshold 24L, taxiways A and A4, north side of the apron to the holding 06L.

6. Arrival Routes

Aircraft will exit runway 06L on taxiways B1, B3, B5 or holding bay 24R, taxiways B, B4, F and then follow Apron Control instructions. Aircraft destined to the general aviation sector will exit the main apron at A4, and will taxi via runway 06R, and taxiways L and R.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LOW VISIBILITY TAXI CHART
(RVR LESS THAN 1200 TO 600 FT)


MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL

ATIS – **133.7** (En) **127.5** (Fr)	CLNC DEL – **125.6** APRON – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3 119.9 124.3 267.1**

LEGEND

- STOP BARS
- RUNWAY GUARD LIGHTS
- TAXIWAY CENTRELINE LIGHTS (BIDIRECTIONAL)
- DIRECTION OF AIRCRAFT MOVEMENTS

VAR 15° W 2013
ANNUAL RATE OF CHANGE 4' E



Multilateration:
Keep transponder on at all times when taxiing.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Procédures en conditions de faible visibilité
(RVR en dessous de 1200 jusqu'à 600 pieds)

1. Application

Ces procédures s'appliquent aux aéronefs circulant au sol en conditions de faible visibilité (portée visuelle de piste [RVR] en dessous de 1200 jusqu'à 600 pieds). Les départs et les arrivées en dessous de 600 RVR ne sont pas autorisés. Lorsque les conditions météorologiques indiquent que la portée visuelle de piste pourrait descendre en dessous de 1200 RVR, les procédures suivantes seront mises en place afin d'assurer la sécurité et l'efficacité des mouvements d'aéronefs. Le message suivant sera alors diffusé l'ATIS : **« PROCÉDURES EN CONDITIONS DE FAIBLE VISIBILITÉ EN VIGUEUR »**.

2. Système de guidage et de contrôle de la circulation de surface

Un système de guidage et de contrôle de la circulation de surface a été mis en place afin de faciliter le mouvement des aéronefs en conditions de faible visibilité. Ce système, commandé par l'ATC, comprend :

- Des feux axiaux de sortie sur la baie d'attente 24R.
- Des feux axiaux unidirectionnels sur les voies de circulation A (entre J et A4), A4 (entre A et l'aire de trafic), B, B3, B4 (de B à la piste 10/28), B5, D, E (de l'aire de trafic à I), F, H, I, J et K.
- Des feux axiaux bi-directionnels sur la rampe nord de la voie de circulation G à A4, sur la rampe sud entre G et la barrière 65, et sur les lignes de guidage est et ouest jusqu'à la barrière 66.
- Des barres d'arrêt sur tous les accès à la piste 06L/24R : dans les baies d'attente des pistes 06L et 24R, à l'extrémité de la piste 28 avant l'intersection de la piste 06L/24R et sur les voies de circulation B1, B2, B3, B4, B5, et G (allumées en dessous de 1200 RVR).

  Note : NE JAMAIS TRAVERSER UNE BARRE D'ARRÊT ALLUMÉE

- Des feux de protection de piste sur les accès de toutes les pistes : les baies d'attente des pistes 06L, 24R, 06R et 24L, à l'extrémité de la piste 28 avant l'intersection de la piste 06L/24R, sur les pistes 06L et 24R avant l'intersection de la piste 10/28 et sur les voies de circulation A, A1, A2, A3, A4, B1, B2, B3, B4, B5, D, E, F, G, J, L et R (allumés en tout temps sur les accès des pistes en service).

  Note : Les feux axiaux de voies de circulation et les barres d'arrêt sus-mentionnées pourraient être utilisés dans des conditions égales ou supérieure à 1200 RVR.

3. Radar de surveillance des mouvements de surface (ASDE)

Un radar de surveillance des mouvements de surface est utilisé pour la localisation des aéronefs et des véhicules sur les aires mouvements. En cas de panne de ce radar l'ATC peut restreindre les actions en conditions de faible visibilité.

4. Véhicule « Follow Me »

Un véhicule équipé d'une affiche « Follow Me » sera disponible à la demande des pilotes.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

5. Trajets pour les départs

Seule la piste 06L est homologuée pour des décollages en conditions de faible visibilité (RVR en dessous de 1200 et pouvant atteindre 600 pieds). Tous les départs en conditions de faible visibilité se feront sur la piste 06L. Les décollages à partir d'intersections ne sont pas autorisés.

Mise en séquence des mouvements au sol d'aéronefs pour décollages : ne pas demander de démarrer les moteurs, de refouler ou une autorisation de circuler à moins que le RVR rapporté ne soit supérieur aux valeurs suivantes :

Minima de décollage du pilote ou de l'aéronef	RVR minimum pour démarrer les moteurs
1200 RVR	1000 RVR
600 RVR	600 RVR

À moins d'avis contraire de l'ATC, les trajets suivants seront utilisés en conditions de faible visiblilité pours les aéronefs au décollage de la piste 06L (voir carte de circulation en conditions de faible visibilité).

Du tablier principal en direction de l'aire de dégivrage : les aéronefs circuleront sur les voies de circulation E et H ou D et K.

Du tablier principal en direction de la piste 06L : les aéronefs circuleront sur le tablier jusqu'à la baie d'attente de la piste 06L.

De l'aire de dégivrage en direction de la piste 06L : les aéronefs circuleront sur les voies de circulation I, B, B4, F et le tablier jusqu'à la baie d'attente de la piste 06L.

De l'aire de dégivrage en direction du tablier principal : les aéronefs circuleront sur les voies de circulation J, A et A4.

De l'aviation générale, la voie de circulation R, traverser le seuil 24L, les voies de circulation A et A4, voie de circulation du côté nord de l'aire de trafic jusqu'à la baie d'attente 06L.

6. Trajets pour les arrivées

Les aéronefs quitteront la piste 06L en utilisant les voies de circulation B1, B3, B5 ou par la baie d'attente de la piste 24R, les voies de circulation B, B4, F puis suivront les instructions du contrôle du tablier. Les aéronefs se dirigeant à l'aviation générale quitteront l'aire de trafic à A4 et utiliseront la piste 06R, et les voies de circulation L et R.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


CARTE DE CIRCULATION EN CONDITIONS DE FAIBLE VISIBILITÉ (RVR en dessous de 1200 jusqu'à 600 pieds)

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL

ATIS – **127.5** (Fr) **133.7** (Ang)	CLNC DEL – **125.6** AIRE DE TRAFIC – **122.27** (W) **122.07** (E) GND – **121.0** (W) **121.9** (E) **275.8**	TWR – **119.3 119.9 124.3 267.1**

LÉGENDE


- BARRES D'ARRÊT
- FEUX DE PROTECTION DE PISTE
- FEUX AXIAUX DE VOIES DE CIRCULATION (BIDIRECTIONNELS)
- SENS DE LA CIRCULATION



Multilatération:
Laissez votre transpondeur allumé en tout temps lorsque vous circulez.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

PARKING CENTRE AREAS AND DE-ICING POSITIONS AND PROCEDURES CYUL



DE-ICING

1. Contact MONTREAL DE-ICE on 123.425, no later than 30 min prior push-back, with de-icing type.
2. On Twys J or K, hold short of the de-icing pad and contact AEROMAG PAD CONTROL 122.525.
3. On Twy E hold short of H or I and contact AEROMAG PAD CONTROL on 122.525.
4. Follow AEROMAG PAD CONTROL instructions and guiding lines to the assigned de-icing bay and confirm "brakes set" when in position.
5. On AEROMAG PAD CONTROL instructions, contact ICEMAN on 123.125 & confirm aircraft configured for de-icing and engines at idle.
6. When de-icing is completed and on ICEMAN instructions only, contact AEROMAG PAD CONTROL on 122.525 before moving aircraft.
7. Exiting de-icing pad on AEROMAG PAD CONTROL instructions contact ground control:
   on Twy J, holding short of Rwy 10/28,
   on Twy K, holding short of Rwy 10/28,
   on Twy H or I holding short of Twy E.

De-Icing bays capacity:

1 & 3:	Maximum wingspan 36m (118');
2:	Maximum wingspan 80m (262');
4, 5 & 9:	Maximum wingspan 65m (213');
6 & 8:	Maximum wingspan 36m (118');
7:	Maximum wingspan 45.8m (150');

RUNWAY INCURSION HOT SPOTS HS 1 to 3
See Taxi chart for complete information.


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AIRES DE STATIONNEMENT CENTRE et POSITIONS DE DÉGIVRAGE et PROCÉDURES

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL

ATIS – **127.5** (Fr) **133.7** (Ang)

DÉGIVRAGE – **123.42**
GND – **121.0 121.9 275.8**
PAD CTL Aeromag – **122.52**
ICEMAN – **123.12**



DÉGIVRAGE

1. Contacter MONTRÉAL CENTRE DÉGIVRAGE sur 123.425, au plus tard 30 minutes avant le refoulement, et confirmer le type de dégivrage.
2. Sur Twys J ou K à l'écart du tablier de dégivrage, contacter AEROMAG CONTRÔLE DÉGIVRAGE sur 122.525.
3. Sur Twy E à l'écart de H ou I, contacter AEROMAG CONTRÔLE DÉGIVRAGE sur 122.525.
4. Suivez les instructions d'AEROMAG CONTRÔLE DÉGIVRAGE et les lignes de guidage jusqu'à la baie assignée et confirmer que les freins sont serrés après arrêt.
5. Sur instructions d'AEROMAG CONTRÔLE DÉGIVRAGE contacter ICEMAN sur 123.125 et confirmer que l'appareil est configuré pour le dégivrage et que les moteurs sont sur régime ralenti.
6. Lorsque le dégivrage est complété et seulement sur instructions du ICEMAN contacter AÉROMAG CONTRÔLE DÉGIVRAGE sur 122.525 avant tout mouvement.
7. À la sortie du tablier de dégivrage, sur instructions d'AÉROMAG CONTRÔLE DÉGIVRAGE, contacter le contrôle-sol:
   sur Twy J, à l'écart piste 10/28:
   sur Twy K, à l'écart piste 10/28:
   sur Twy H ou à l'écart Twy E:

Capacité des baies
- 1 & 3: Envergure maximale 36m (118');
- 2: Envergure maximale 80m (262');
- 4, 5 & 9: Envergure maximale 65m (213');
- 6 & 8: Envergure maximale 36m (118');
- 7: Envergure maximale 45.8m (150');

POINTS CHAUDS incursions de piste HS 1 à 3
Voir Carte de circulation pour information détaillée.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

PARKING AREAS

CYUL

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYUL

AIRES DE STATIONNEMENT — CYUL

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT — CYUL

EFF 15 JUIN 23

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

START BOXES

CYUL

ATIS – **133.7** (En) **127.5** (Fr)

APRON – **122.27** (W) **122.07** (E)

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Holding bays capacity:
2 acft with wingspans of less than 36m (118')
Acft with wingspans of 36m (118') or greater:
Holding bay 06L: use North line
Holding bay 24R: use centre line
Holding bay 24L: use South line
Holding bay 06R: 2 acft simultaneously; acft with wingspans of less than 65m (213') use South line and acft with wingspans of 65m (213') or greater use North line.

START BOXES

CYUL

EFF 5 OCT 23

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

POINTS DE DÉPART

CYUL

ATIS – **127.5** (Fr) **133.7** (Ang)

AIRE DE TRAFIC – **122.27** (W) **122.07** (E)

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

POINTS DE DÉPART

CYUL

EFF 5 OCT 23

NORTH PARKING AREA CYUL

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


ATIS – **133.7** (En) **127.5** (Fr)

APRON – **122.27** (W) **122.07** (E)

NORTH PARKING AREA CYUL

EFF 5 OCT 23

AIRE DE STATIONNEMENT NORD — CYUL



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRE DE STATIONNEMENT NORD — CYUL

EFF 5 OCT 23

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

PLAN OF OPERATIONS IN THE ABSENCE OF APRON CONTROL CYUL

Source of Canadian Civil Aeronautical Data © 2023 NAV CANADA All rights reserved

PLAN OF OPERATIONS IN THE ABSENCE OF APRON CONTROL CYUL

EFF 5 OCT 23

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC

PLAN D'OPÉRATIONS EN L'ABSENCE DE CONTRÔLE SUR L'AIRE DE TRAFIC CYUL

Source des données aéronautiques civiles pour le Canada © : 2023 NAV CANADA Tous droits réservés

PLAN D'OPÉRATIONS EN L'ABSENCE DE CONTRÔLE SUR L'AIRE DE TRAFIC CYUL


EFF 5 OCT 23

MONTRÉAL/ST-HUBERT, QC

AERODROME CHART — CYHU

ATIS – **124.9** (En) **124.1** (Fr) AWOS – **124.9** (En) **124.1** (Fr)	GND – **126.4**	TWR – **118.4 121.3** RADIO Rouyn – **118.4** MF	TML Montreal – **125.15 268.3**

DECL DISTS	06L	24R	06R	24L	10	28		
TORA	7801	7801	3922	3922	2420	2420		
TODA	7801	7801	3922	3922	2420	2420		
ASDA	7801	7801	3922	3922	2420	2420		
LDA	6696	7801	3922	3922	2420	2420		



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHU


EFF 23 FEB 23

MONTRÉAL/ST-HUBERT, QC

CARTE D'AÉRODROME — CYHU

ATIS – **124.1** (Fr) **124.9** (Ang) AWOS – **124.1** (Fr) **124.9** (Ang)	GND – **126.4**	TWR – **118.4** **121.3** RADIO Rouyn – **118.4** MF	TML Montreal – **125.15** **268.3**

DIST DÉCLARÉES	06L	24R	06R	24L	10	28		
TORA	7801	7801	3922	3922	2420	2420		
TODA	7801	7801	3922	3922	2420	2420		
ASDA	7801	7801	3922	3922	2420	2420		
LDA	6696	7801	3922	3922	2420	2420		



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06L, 06R, 10, 24L, 24R et 28: *	1000 0 1000 2000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYHU


EFF 23 FÉV 23

NATASHQUAN, QC

AERODROME CHART — CYNA

AWOS – **126.25** (En) **125.3** (Fr)	RADIO Madeleine – **122.2** TFC – **122.2** MF*	CTR Montreal – **134.82** RADIO Quebec – **123.85**

DECL DISTS	14	32
TORA	4495	4495
TODA	5479	5479
ASDA	4495	4495
LDA	4495	4495



***DEPARTURE PROCEDURE**

Rwy 14 - ½
Note: Road to 48 ASL abeam departure end of rwy, aprx 500' RIGHT of rwy centreline. Trees to 118 ASL aprx 0.5 NM past departure end of rwy, 700' LEFT of rwy centreline.

Rwy 32 - ½
Note: Trees to 145 ASL aprx 0.4 NM past departure end of rwy, aprx 150' RIGHT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

NATASHQUAN, QC

CARTE D'AÉRODROME — CYNA

AWOS – **125.3** (Fr) **126.25** (Ang)	RADIO Madeleine – **122.2** TFC – **122.2** MF*	CTR Montreal – **134.82** RADIO Quebec – **123.85**

DIST DÉCLARÉES	14	32
TORA	4495	4495
TODA	5479	5479
ASDA	4495	4495
LDA	4495	4495



* PROCÉDURE DE DÉPART

Piste 14 - ½

Note: Route jusqu'à 48 ASL par le travers de l'extremité de la piste de départ, 500' à DROITE de l'axe de piste. Arbres jusqu'à 118 ASL aprx 0.5 NM passé l'extrémité de la piste de départ, 700' à GAUCHE de l'axe de piste.

Piste 32 - ½

Note: Arbres jusqu'à 145 ASL aprx 0,4 NM passé l'extrémité de la piste de départ, aprx 150' à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 14; 32: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

NEMISCAU, QC

AERODROME CHART — CYHH

		UNICOM – **131.7** (AU) MF*	RADIO Quebec – **123.27**

DECL DISTS	09	27
TORA	5000	5000
TODA	6000	6000
ASDA	5000	5000
LDA	5000	5000



***** DEPARTURE PROCEDURE

Rwy 09 - ½ - Departure Procedure not auth when blasting area is active (OCSL by NOTAM), SFC to **1275**, 11 NM SE of aerodrome. NO LEFT turn below **1900**.
Note: Trees to 889 ASL abeam departure end of rwy 200' LEFT and RIGHT of rwy centreline and aprx 300' past departure end of rwy.

Rwy 27 - ½ - Climb hdg **270°** to **1500** BPOC.
Note: Trees to 883 ASL abeam departure end of rwy, 400' RIGHT of rwy centreline and aprx 0.1NM past departure end of rwy, 600' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *****	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHH


EFF 7 OCT 21

NEMISCAU, QC

CARTE D'AÉRODROME — CYHH

		UNICOM – **131.7** (AU) MF*	RADIO Quebec – **123.27**

DIST DÉCLARÉES	09	27
TORA	5000	5000
TODA	6000	6000
ASDA	5000	5000
LDA	5000	5000



*PROCÉDURE DE DÉPART

PIste 09 - ½ - Procedure de départ non auth lorsque la zone de dynamitage est active (OCSL par NOTAM), de la surface jusqu'à **1275**, 11 NM au sud-est de l'aérodrome. AUCUN virage à GAUCHE en dessous de **1900**.
Note: Arbres jusqu'à 889 ASL par le travers de l'extrémité de la piste de départ, 200' à GAUCHE et à DROITE de l'axe de piste et aprx 300' passé l'extrémité de la piste de départ.

PIste 27 - ½ - Monter sur cap **270°** jusqu'à **1500** BPOC.
Note: Arbres jusqu'à 883 ASL par le travers de l'extrémité de la piste de départ, 400' à DROITE de l'axe de piste, et aprx 0.1NM passé l'extrémité de la piste de départ, 600' à GAUCHE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Toutes pistes: *	1000 0 1000

CARTE D'AÉRODROME — CYHH

EFF 7 OCT 21


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

OTTAWA/GATINEAU, QC

AERODROME CHART — CYND

			◕ RADIO Gatineau – **122.3** ◕ TFC – **122.3** MF				DEP Ottawa – **128.17** RADIO Quebec – **123.37**	

DECL DISTS	09	27						
TORA	6000	6000						
TODA	6000	6000						
ASDA	6200	6200						
LDA	6000	6000						




Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

OTTAWA/GATINEAU, QC

CARTE D'AÉRODROME — CYND

			◕ RADIO Gatineau – **122.3** ◕ TFC – **122.3** MF				DEP Ottawa – **128.17** RADIO Quebec – **123.37**	

DIST DÉCLARÉES	09	27						
TORA	6000	6000						
TODA	6000	6000						
ASDA	6200	6200						
LDA	6000	6000						



***** PROCÉDURE DE DÉPART

PIste 09 - ½

Note: Arbres jusqu'à 321 ASL à moins de 0.5 NM de l'extrémité de la piste de départ, 600' à GAUCHE et à DROITE de l'axe de piste. Ligne de transmission jusqu'à 344 ASL aprx 0.7 NM passé l'extrémité de la piste de départ, 1650' à DROITE de l'axe de piste.

Piste 27 - ½

Note: Terrain jusqu'à 253 ASL passé l'extrémité de la piste de départ. Arbres jusqu'à 260 ASL par le travers de l'extrémité de la piste de départ, 300' à GAUCHE de l'axe de piste et aprx 500' passé l'extrémité de la piste de départ. Arbres jusqu'à 308 ASL aprx 0.4 NM passé l'extrémité de la piste de départ, 750' à DROITE de l'axe de piste.

LÉGENDE

1 Les Ailes d'époque du Canada
2 Hangar 2
3 Hangar 3
4 Hangar 4
5 Aérogare/FBO/FSS

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 09; 27: *****	1000 0 1000

CARTE D'AÉRODROME — CYND

EFF 5 OCT 23


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

PORT-MENIER, QC

AERODROME CHART — CYPN

AUTO – **122.17**		◕ UNICOM – **123.5** (AU) ATF*	RADIO Quebec – **123.47**

DECL DISTS	11	29
TORA	4888	4888
TODA	4888	5868
ASDA	4888	4888
LDA	4888	4888



* DEPARTURE PROCEDURE

Rwy 11 - ½

Note: Trees to 246 ASL aprx 0.1 NM past departure end of rwy, 700' LEFT of rwy centreline and aprx 0.2 NM past departure end of rwy, 700' RIGHT of rwy centreline.

Rwy 29 - ½

Note: Trees to 197 ASL aprx 0.2 NM past departure end of rwy, 500' LEFT and RIGHT of rwy centreline..

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPN


EFF 3 NOV 22

PORT-MENIER, QC

CARTE D'AÉRODROME — CYPN

AUTO – **122.17**		UNICOM – **123.5** (AU) ATF*	RADIO Quebec – **123.47**

DIST DÉCLARÉES	11	29
TORA	4888	4888
TODA	4888	5868
ASDA	4888	4888
LDA	4888	4888



* PROCÉDURE DE DÉPART

Piste 11 - ½

Note: Arbres jusqu'à 246 ASL aprx 0.1 NM passé l'extrémité de la piste de départ, 700' à GAUCHE de l'axe de piste et aprx 0.2 NM passé l'extrémité de la piste de départ, 700' à DROITE de l'axe de piste.

Piste 29 - ½

Note: Arbres jusqu'à 197 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 500' à GAUCHE et à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 11; 29: *	1000 0 1000 2000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

POSTE MONTAGNAIS (MILE 134), QC


AERODROME CHART — CSF3

UNICOM – **131.7** (AU)

CTR Montreal – **132.25**

ATF

DECL DISTS	17	35
TORA	4436	4436
TODA	4436	4436
ASDA	4436	4436
LDA	4436	4436



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 FT/NM	530	700	820	940	1050	1170	1460	1750

***** DEPARTURE PROCEDURE

Rwy 17: - ½

Note: Trees to 2086 ASL aprx 350' past departure end of rwy, 250' LEFT of rwy centreline and aprx 0.1 NM past departure end of rwy.

Rwy 35: - ½ - Requires a minimum climb gradient of **350** ft/NM to **2700**.

Note: Trees to 2041 ASL abeam departure end of rwy, 300' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **3000** BPOC.

TAKE-OFF MINIMA

Rwys 17; 35: *****

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

POSTE MONTAGNAIS (MILE 134), QC


CARTE D'AÉRODROME CSF3

UNICOM – **131.7** (AU)

CTR Montreal – **132.25**

ATF

DIST DÉCLARÉES	17	35
TORA	4436	4436
TODA	4436	4436
ASDA	4436	4436
LDA	4436	4436



* PROCÉDURE DE DÉPART

Piste 17: - ½

Note: Arbres jusqu'à 2086 ASL aprx 350' passé l'extrémité de la piste de départ, 250' à GAUCHE de l'axe de piste et aprx 0,1 NM passé l'extrémité de la piste de départ.

Piste 35: - ½ - Requiert une pente de montée minimale de **350** pi/NM jusqu'à **2700**.

Note: Arbres jusqu'à 2041 ASL par le travers de l'extrémité de départ, 300' à DROITE de l'axe de piste.

ou

SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **3000** ou plus haut BPOC.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
350 Pieds/NM	530	700	820	940	1050	1170	1460	1750

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 17; 35: *	1000 0 1000 2000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

POURVOIRIE MIRAGE, QC

AERODROME CHART — CPM3

TFC – **122.85** ATF

DECL DISTS	09	27						
TORA	3520	3520						
TODA	3520	3520						
ASDA	3520	3520						
LDA	3520	3520						



* DEPARTURE PROCEDURE

Rwy 09 - ½

Note: Road to 1338 ASL abeam departure end of rwy, 250' LEFT of rwy centreline. Trees to 1348 ASL abeam departure end of rwy, 330' LEFT and 300' RIGHT of rwy centerline.

Rwy 27 - ½

Note: Road to 1335 ASL abeam departure end of rwy, 100' RIGHT of rwy centreline. Trees to 1345 ASL abeam departure end of rwy, 200' LEFT and 180' RIGHT of rwy centerline.

TAKE-OFF MINIMA
Rwys 09; 27: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

POURVOIRIE MIRAGE, QC

CARTE D'AÉRODROME CPM3

TFC – **122.85** ATF

DIST DÉCLARÉES	09	27						
TORA	3520	3520						
TODA	3520	3520						
ASDA	3520	3520						
LDA	3520	3520						



★ PROCÉDURE DE DÉPART

Piste 09 - ½

Note: Chemin jusqu'à 1338 ASL par le travers de l'extrémité de la piste de départ, 250° à GAUCHE de l'axe de piste. Arbres jusqu'à 1348 ASL par le travers de l'extrémité de la piste de départ, 330° à GAUCHE et 300° à DROITE de l'axe de piste.

Piste 27 - ½

Note: Chemin jusqu'à 1335 ASL par le travers de l'extrémité de la piste de départ, 100° à DROITE de l'axe de piste. Arbres jusqu'à 1345 ASL par le travers de l'extrémité de la piste de départ, 200° à GAUCHE et 180° à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 09; 27:★	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME CPM3


EFF 5 OCT 23

PUVIRNITUQ, QC

AERODROME CHART — CYPX

AWOS – **128.65** (En) **120.45** (Fr)	◕ UNICOM – **123.5** ◕ TFC – **123.5** MF*	CTR Montreal – **132.27** RADIO Quebec – **123.27**

DECL DISTS	01	19
TORA	6299	6299
TODA	7283	7283
ASDA	6299	6299
LDA	6299	6299



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 01; 19: ½	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPX


EFF 29 DEC 22

PUVIRNITUQ, QC

CARTE D'AÉRODROME — CYPX

AWOS – **120.45** (Fr) **128.65** (Ang)		◕ UNICOM – **123.5** ◕ TFC – **123.5** MF*	CTR Montreal – **132.27** RADIO Quebec – **123.27**

DIST DÉCLARÉES	01	19
TORA	6299	6299
TODA	7283	7283
ASDA	6299	6299
LDA	6299	6299



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 01; 19: ½	2000 0 2000

CARTE D'AÉRODROME — CYPX

EFF 29 DÉC 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

QUAQTAQ, QC

AERODROME CHART — CYHA

APRT RADIO – **122.1**
TFC – **122.1**
MF*

DECL DISTS	18	36
TORA	3520	3520
TODA	3520	4504
ASDA	3520	3520
LDA	3520	3520



TAKE-OFF MINIMA	
Rwy 18:	*
Rwy 36:	½

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYHA


EFF 14 JUL 22

QUAQTAQ, QC

CARTE D'AÉRODROME — CYHA

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	18	36
TORA	3520	3520
TODA	3520	4504
ASDA	3520	3520
LDA	3520	3520



MINIMUM DE DÉCOLLAGE

Piste 18: *
Piste 36: ½

ÉCHELLE EN PIEDS

1000 0 1000

CARTE D'AÉRODROME — CYHA

EFF 14 JUIL 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

QUÉBEC/JEAN LESAGE INTL, QC

AERODROME CHART — CYQB

ATIS – **134.6** (En) **128.3** (Fr)	GND – **121.9 250.0**	TWR – **118.65 236.6**	TML – **124.0 127.85 322.8** RADIO Quebec – **123.27**

DECL DISTS	06	24	11	29
TORA	9000	9000	5700	5700
TODA	9984	9984	5700	5700
ASDA	9000	9000	5700	5700
LDA	9000	9000	5700	5700



LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)		
FROM	TO	LDA in ft
Thld Rwy 24	Short of Rwy 11-29	5434
Thld Rwy 29	Short of Rwy 06-24	3849

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06: RVR 1200 RWY 24: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

QUÉBEC/JEAN LESAGE INTL, QC

CARTE D'AÉRODROME — CYQB

ATIS – **128.3** (Fr) **134.6** (Ang)	GND – **121.9 250.0**	TWR – **118.65 236.6**	TML – **124.0 127.85 322.8** RADIO Quebec – **123.27**

DIST DÉCLARÉES	06	24	11	29				
TORA	9000	9000	5700	5700				
TODA	9984	9984	5700	5700				
ASDA	9000	9000	5700	5700				
LDA	9000	9000	5700	5700				



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYQB

EFF 29 DÉC 22

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

Reduced Visibility Operations - 24 hours

Reduced Visibility Operations on runway 06-24: these are operations when reported visibility is less than RVR 2,600 feet or ½ statute mile and greater than or equal to RVR 1,200 feet or ¼ statute mile, per advisory circular CI 302-001.

Low visibility operations (LVOP) (below RVR 1200') are not permitted.

Departures & Arrivals

Follow-me car

A "Follow-me" car will be available at all times, under any circumstances, upon a pilot's request. This service is available for one aircraft at a time based on first come, first served principles; some exceptions may apply.

During RVOP conditions, run-ups and towing will not be authorized on the maneuvering areas. Furthermore, vehicle access to the maneuver area during reduced visibility operations is restricted to essential operational functions only.

Night Only: When reported visibility is less than RVR 1800 or 3/8 SM, a "Follow-me" car is mandatory per advisory circular AC 302-004.

Operation Terms

20 minutes prior to a flight's departure time, the pilot shall contact NAV CANADA's ground controller to request a "Follow-me" car escort for taxiing on the manoeuvring area.

The pilot shall provide the following information:

- Exact position on the airfield (gate or FBO);
- Type of aircraft and airline;
- Flight departure time (if available);
- Runway used for take-off;

The "Follow-me" car will position itself 30m in front of the aircraft. Hazard lights will be activated when ready for taxiing and for the duration of the escort procedure.

Upon receiving authorization to proceed, the "Follow-me" car will follow the guide lines at no more than 30kph (16 knots) up to the desired destination.

Runway Level of Service

Rwy 06	RVR 1200
Rwy 24	(¼ sm)

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Procédure d'opérations avec une visibilité réduite
(RVR en-dessous de 2600 jusqu'à 1200 pieds)

Opérations visibilité réduite 24 heures

Les opérations effectuées sur la piste 06-24 : lorsque la visibilité signalée est inférieure à un RVR 2600 ou ½ mille terrestre, mais supérieure ou égale à une RVR 1200 ou ¼ mille terrestre, est en conformité avec le circulaire CI 302-001.

Les opérations par faible visibilité (LVOP) (en bas de RVR 1200') ne sont pas permises.

Départs & Arrivées

Véhicule « Follow-me »

Un véhicule « Follow-me » sera disponible en tout temps, pour toutes circonstances, à la demande des pilotes. Ce service s'applique pour un vol à la fois, sur une base de premier arrivé, premier servi, sauf exception.

Lors d'opérations RVOP, aucun remorquage ni essai moteur n'est permis sur les aires de manœuvre. De plus, l'accès par véhicule à l'aire de manœuvre lors de conditions de visibilité réduite sera restreint aux fonctions essentielles aux opérations seulement.

Nuit seulement : Lorsque la visibilité signalée est inférieure à une RVR 1800 ou 3/8 SM, un véhicule « Follow-me » est obligatoire en conformité avec le circulaire CI 302-004.

Conditions d'exploitation

20 minutes avant l'heure de départ ou à l'arrivée du vol, le pilote place une demande pour l'assistance d'un véhicule d'escorte « Follow-me » afin de circuler sur les aires de manœuvre en communiquant avec le contrôleur sol de NAV CANADA.

Le pilote doit fournir les informations suivantes:

- La position exacte sur le site (numéro de barrière ou FBO);
- Le type d'appareil et la compagnie aérienne;
- L'heure de départ du vol (si applicable);
- La destination sur le site (seuil de piste, numéro de barrière ou FBO);

Le véhicule « Follow-me » se présentera devant l'appareil à une distance de 30m et les feux de détresse (Hazard) seront activés afin de démontrer qu'il est prêt à circuler, et ce, pour toute la durée de l'escorte;

Après autorisation de circuler, le véhicule « Follow-me » suivra les lignes guides à une vitesse de 30 kph (16 nœuds) jusqu'à la destination demandée.

Niveau de service de la piste


Piste 06	RVR 1200
Piste 24	(¼ sm)

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

QUÉBEC/JEAN LESAGE INTL, QC

PARKING AREAS

CYQB



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


PARKING AREAS

CYQB

EFF 27 JAN 22

QUÉBEC/JEAN LESAGE INTL, QC

AIRES DE STATIONNEMENT — CYQB



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT — CYQB

EFF 27 JAN 22


RENARD, QC

AERODROME CHART — CFX5

UNICOM – **122.8** (AU)

ATF

DECL DISTS	06	24
TORA	4902	4902
TODA	4902	4902
ASDA	4902	4902
LDA	4902	4902



TAKE-OFF MINIMA
Rwy 06, 24: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


RENARD, QC

CARTE D'AÉRODROME — CFX5

UNICOM – **122.8** (AU)

ATF

DIST DÉCLARÉES	06	24						
TORA	4902	4902						
TODA	4902	4902						
ASDA	4902	4902						
LDA	4902	4902						



MINIMUM DE DÉCOLLAGE
Rwy 06, 24: *

ÉCHELLE EN PIEDS

1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

RIMOUSKI, QC


AERODROME CHART — CYXK

RADIO Mont-Joli – **122.1**

CTR Montreal – **134.65 227.2**

MF*

DECL DISTS	07	25
TORA	4600	4600
TODA	4600	4600
ASDA	4600	4600
LDA	4600	4600




TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07, 25: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RIMOUSKI, QC

CARTE D'AÉRODROME — CYXK

			RADIO Mont-Joli – **122.1** MF*	CTR Montreal – **134.65 227.2**				
DIST DÉCLARÉES	**07**	**25**						
TORA	4600	4600						
TODA	4600	4600						
ASDA	4600	4600						
LDA	4600	4600						



* PROCÉDURE DE DÉPART

Piste 07 - ½ **-** AUCUN virage à DROITE en dessous de **1700**.
Note: Arbres jusqu'à 122 ASL par le travers de l'extrémité de départ de la piste, 350° à GAUCHE de l'axe de piste.

Piste 25 - ½ - Requiert une pente de montée minimale de **210** pi/NM jusqu'à **1600**. Monter sur cap **246°** jusqu'à **1100** BPOC.
Note: Route jusqu'à 81 ASL par le travers de l'extrémité de depart de la piste, 500' à GAUCHE de l'axe de piste.
ou
SPEC VIS - Effectuer une montée à vue pour survole l'aéroport à ou plus haut que **1100** (CAT A), **1200** (CAT B & C), et **1300** (CAT D) BPOC.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 07, 25: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

RIVIÈRE-DU-LOUP, QC

AERODROME CHART — CYRI

AUTO – **122.02**		◕ UNICOM – **122.77**	CTR Montreal – **125.1 299.6** ATF

DECL DISTS	05	23
TORA	6001	6001
TODA	6001	6001
ASDA	6001	6001
LDA	6001	6001



TAKE-OFF MINIMA
Rwy 05: *
Rwy 23: ½

SCALE IN FEET
1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRI

EFF 14 JUL 22

RIVIÈRE-DU-LOUP, QC

CARTE D'AÉRODROME — CYRI


AUTO – **122.02**

UNICOM – **122.77**

ATF

CTR Montreal – **125.1 299.6**

DIST DÉCLARÉES	05	23
TORA	6001	6001
TODA	6001	6001
ASDA	6001	6001
LDA	6001	6001



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 05: *	1000 0 1000 2000
Piste 23: ½	

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYRI


EFF 14 JUIL 22

ROBERVAL, QC

AERODROME CHART — CYRJ

			◕ RADIO Rouyn – **122.2** ◕ TFC – **122.2** MF				RADIO Quebec – **123.55** **5680**	

DECL DISTS	16	34						
TORA	5000	5000						
TODA	5645	5815						
ASDA	5000	5000						
LDA	5000	5000						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16; 34: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRJ


EFF 12 AUG 21

ROBERVAL, QC

CARTE D'AÉRODROME — CYRJ

		RADIO Rouyn – **122.2** TFC – **122.2** MF	RADIO Quebec – **123.55** **5680**

DIST DÉCLARÉES	16	34
TORA	5000	5000
TODA	5645	5815
ASDA	5000	5000
LDA	5000	5000



***** PROCÉDURE DE DÉPART

PIste 16 - ½ - AUCUN virage à DROITE en dessous de **1400**.
Lorsque CYR651 CYR652 CYR653 ou CYA641(M) sont actives:
Monter entre caps **139°** et **327°** sens horaire.
Lorsque CYR657 est active.
Monter entre caps **213°** et **256°** sens antihoraire.
Note: Arbres jusqu'à 641 ASL par le travers de l'extrémité de départ de la piste, 450' à DROITE de l'axe de piste.
Ligne électrique jusqu'à 658 ASL par le travers de l'extrémité de départ de la piste, 350' à DROITE de l'axe de piste.

PIste 34 - ½ **-** Lorsque CYR651, CYR653 ou CYA641 sont actives:
Monter sur cap **340°** jusqu'à **1800** puis monter en virage à GAUCHE direct vers NDB "RJ".
Monter en navette sur route **118°** en rapprochement jusqu'à la MEA BPOC.
Note: Arbres jusqu'à 696 ASL aprx 0.2 NM passé l'extrémité de départ de la piste.

MINIMUM DE DÉCOLLAGE
Pistes 16; 34: *****

ÉCHELLE EN PIEDS
1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ROUYN-NORANDA, QC

AERODROME CHART — CYUY

		RADIO – **122.2**	CTR Montreal – **125.9** RADIO Quebec – **123.47**
		MF	

DECL DISTS	08	26
TORA	7500	7500
TODA	8310	11250
ASDA	7500	7500
LDA	7500	7500



***** DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Trees to 1100 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT and RIGHT of rwy centreline.

Rwy 26 - ½

Note: Trees to 1070 ASL aprx 0.7 NM past departure end of rwy.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08, 26: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwy 08, 26: *****	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYUY


EFF 1 FEB 18

ROUYN-NORANDA, QC

CARTE D'AÉRODROME — CYUY

		RADIO – **122.2** MF	CTR Montreal – **125.9** RADIO Quebec – **123.47**

DIST DÉCLARÉES	08	26
TORA	7500	7500
TODA	8310	11250
ASDA	7500	7500
LDA	7500	7500



***** PROCÉDURE DE DÉPART

Piste 08 - ½

Note: Arbres jusqu'à 1100 ASL aprx 0.1 NM passé l'extrémité de la piste de départ, 600' à GAUCHE et à DROITE de l'axe de piste.

Piste 26 - ½

Note: Arbres jusqu'à 1070 ASL aprx 0.7 NM passé l'extrémité de la piste de départ.

NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
PISTE 08, 26: (¼sm)	NON AUTORISÉ

MINIMUM DE DÉCOLLAGE	ÉCHELLES EN PIEDS
Piste 08, 26: *****	1000 0 1000 2000

CARTE D'AÉRODROME — CYUY

EFF 1 FÉV 18


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

SAGARD, QC

HELIPORT CHART — CSG9

AUTO Charlevoix – **122.55** (En)		TFC – **123.2** ATF*	CTR Montreal – **125.1 299.6**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	50 0 50

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


SAGARD, QC

CARTE D'HÉLIPORT

CSG9

AUTO Charlevoix – **122.55** (Ang)		TFC – **123.2** ATF*	CTR Montreal – **125.1 299.6**

DIST DÉCLARÉES								
TORA								
TODA								
ASDA								
LDA								



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
NON ÉVALUÉ	50 0 50


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

SALLUIT, QC

AERODROME CHART — CYZG

			APRT RADIO – **122.1** TFC – **122.1** MF*			RADIO Quebec – **126.7** DRCO		

DECL DISTS	03	21						
TORA	3523	3523						
TODA	4507	3523						
ASDA	3523	3523						
LDA	3523	3523						



TAKE-OFF MINIMA
Rwys 03, 21: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZG


EFF 20 APR 23

SALLUIT, QC

CARTE D'AÉRODROME — CYZG

			◕ APRT RADIO – **122.1** ◕ TFC – **122.1** MF*			RADIO Quebec – **126.7** DRCO		

DIST DÉCLARÉES	03	21
TORA	3523	3523
TODA	4507	3523
ASDA	3523	3523
LDA	3523	3523



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 03, 21: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

SCHEFFERVILLE, QC

AERODROME CHART — CYKL

AWOS – **124.6** (En) **127.5** (Fr)		TFC – **122.2** MF*	RADIO Quebec – **123.47** **126.7**

DECL DISTS	17	35
TORA	5002	5002
TODA	5986	5527
ASDA	5002	5002
LDA	5002	5002



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKL


EFF 27 JAN 22

SCHEFFERVILLE, QC

CARTE D'AÉRODROME — CYKL

AWOS – **127.5** (Fr) **124.6** (Ang)		TFC – **122.2** MF*	RADIO Quebec – **123.47** **126.7**

DIST DÉCLARÉES	17	35
TORA	5002	5002
TODA	5986	5527
ASDA	5002	5002
LDA	5002	5002



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 17; 35: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYKL


EFF 27 JAN 22

SEPT-ÎLES, QC

AERODROME CHART — CYZV

		RADIO – **118.1**	CTR Montreal – **135.55 381.9** RADIO Quebec – **123.27** MF

DECL DISTS	09	27	13	31				
TORA	6552	6552	5771	5771				
TODA	7536	7536	6755	6755				
ASDA	6552	6552	5771	5771				
LDA	6552	6552	5771	5771				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 09: RVR 1200 RWY 27: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 13; 27; 31: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYZV


EFF 17 JUN 21

SEPT-ÎLES, QC

CARTE D'AÉRODROME — CYZV

		RADIO – **118.1** MF	CTR Montreal – **135.55 381.9** RADIO Quebec – **123.27**

DIST DÉCLARÉES	09	27	13	31				
TORA	6552	6552	5771	5771				
TODA	7536	7536	6755	6755				
ASDA	6552	6552	5771	5771				
LDA	6552	6552	5771	5771				



NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
PISTE 09: RVR 1200 PISTE 27: (¼ sm)	NON AUTORISÉ
MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 09; 13; 27; 31: *	1000 0 1000 2000

CARTE D'AÉRODROME — CYZV

EFF 17 JUIN 21

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
RESERVED GATES					
1, 2, 3, 4	28.4	32.8	• Nose southwest • Mandatory pushback • Screened passengers primarily at parking spaces 1, 2 and 3 • Screened or unscreened passengers at parking space 4 • If aircraft at parking space 2, then parking space 1B is closed	DHC-8-Q400	DHC-8-300 Saab 340 B1900C B1900D
5	17.7	17.7	• Nose southwest • Mandatory pushback • Screened or unscreened passengers	B1900	B1900C B1900D
1A	35.8	39.5	• Screened passengers only • Arrival by twy A and B • Mandatory pushback	B737-800	All B737
1B	35.8	39.5	• No aircraft allowed at aircraft parking space 2 • Screened passengers only • Arrival by twy C and D • Mandatory pushback	B737-800	All B737
EAST PARKING - General Aviation CTC OPR 418-962-8211					
6, 8	17.7	17.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	B1900D	King Air B200 B1900C C550
7	27.5	25.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	DHC-8-300	
9	27.5	25.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path • Priority for Medevac at parking space	DHC-8-300	DHC-8-200 B1900D Challenger 605
10	17	18	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	B1900C	King Air B200
12	17	18	• Nose to west	B1900C	King Air B200

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
WEST PARKING					
W1	40.4	34.4	• Power out is permitted for 737 only when parking spaces W2, 1, 1A and 1B are unoccupied • Power out is permitted for propeller when parking space W2 is unoccupied	B737-300	DHC-8-Q400 B1900
W2	40.4	34.4	• Reserved to C130 Hercules • Power out is permitted when parking space W1 is unoccupied	B737-800	C130 Hercules DHC-8-Q400
NORTH PARKING - General Aviation CTC OPR 418-962-8211					
Other parking spaces available in self-service Possible up to DHC-8-300 when parked at a 45° angle				DHC-8-300	

Notes:

- The movement guide line on the main apron is restricted to aircraft with wingspan of 36 m or less;
- The Hercules is not permitted on twy C and D; after landing on rwy 09, backtrack to twy A;
- If impossible to park according to marking, because operational constraints (wind etc.), use the NORTH parking (GENERAL AVIATION);
- North parking (GENERAL AVIATION) limited to the aircraft whose tail does not exceed:
  - 17 m when the tail is on the edge of the traffic area, or
  - 12 m when the tail is parked along the edge of the apron.


ATTENTION: Parking inside the perimeter only (white full lines) in order not to infringe the zoning of the runway, the taxiway or the parking spaces.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SEPT-ÎLES, QC

PARKING AREAS

CYZV



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYZV

EFF 5 DEC 19

SEPT-ÎLES, QC

AIRES DE STATIONNEMENT (PROCÉDURES) CYZV

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros appareil permis	Autres appareils permis
BARRIÈRES RÉSERVÉES					
1, 2, 3, 4	28,4	32,8	• Nez sud-ouest • Refoulement obligatoire • Passagers fouillés principalement aux postes 1, 2 et 3 • Passagers fouillés ou non fouillés au poste 4 • Si appareil au poste 2 alors poste 1B fermé	DHC-8-Q400	DHC-8-300 Saab 340 B1900C B1900D
5	17,7	17,7	• Nez sud-ouest • Refoulement obligatoire • Passagers fouillés ou non fouillés	B1900	B1900C B1900D
1A	35,8	39,5	• Passagers fouillés seulement • Arrivée par twy A et B • Refoulement obligatoire	B737-800	Tous les B737
1B	35,8	39,5	• Aucun appareil autorisé au poste de stationnement 2 • Passagers fouillés seulement • Arrivée par twy C et D • Refoulement obligatoire	B737-800	Tous les B737
STATIONNEMENT EST - Aviation Générale - Pour réservation appeler EXP 418-962-8211					
6, 8	17,7	17,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	B1900D	King Air B200 B1900C C550
7	27,5	25,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	DHC-8-300	
9	27,5	25,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier • Priorité au Medevac	DHC-8-300	DHC-8-200 B1900D Challenger 605
10	17	18	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	B1900C	King Air B200
12	17	18	• Nez à l'ouest	B1900C	King Air B200

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros appareil permis	Autres appareils permis
STATIONNEMENT OUEST					
W1	40,4	34,4	• Sortie sur pouvoir autorisé (power out) pour les B737 seulement si les postes W2, 1, 1A et 1B sont inoccupés • Sortie sur pouvoir autorisé (power out) pour les aéronefs à hélices si le poste W2 est inoccupé	B737-300	DHC-8-Q400 B1900
W2	40,4	34,4	• Réservé à C130 Hercules • Sortie sur pouvoir autorisé (power out) si le poste W1 est inoccupé	B737-800	C130 Hercules DHC-8-Q400
STATIONNEMENT NORD - Aviation Générale CTC EXP 418-962-8211					
Autres espaces disponibles en libre-service Possible jusqu'à DHC-8-300 lorsque stationné à angle 45°				DHC-8-300	

Notes :


- La ligne de guidage sur l'aire de trafic principale est restreinte aux appareils de 36 m ou moins d'envergure;
- Le Hercule n'est pas autorisé sur twy C et D; après atterrissage piste 09, circulation à rebours jusqu'au twy A;
- Si impossible de stationner selon le marquage, à cause de constraintes opérationnelles (vent etc.), utiliser le stationnement nord (AVIATION GÉNÉRALE);
- Stationnement nord (AVIATION GÉNÉRALE) restreint aux aéronefs dont l'empennage ne dépasse pas :
  - 17 m lorsque la queue est en bordure de l'aire de trafic, ou
  - 12 m lorsque la queue est stationnée en bordure nord du tablier.

ATTENTION : Stationnement à l'intérieur du périmètre (lignes blanches) seulement afin de ne pas enfreindre le zonage de la piste, de la voie de circulation ou les postes de stationnement.

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

SEPT-ÎLES, QC

AIRES DE STATIONNEMENT CYZV



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT CYZV


EFF 5 DÉC 19

SHERBROOKE, QC

AERODROME CHART — CYSC

AWOS – **126.25** (En) **128.15** (Fr)		UNICOM – **123.5** MF	CTR Montreal – **132.55**

DECL DISTS	13	31
TORA	5901	5901
TODA	6885	6885
ASDA	5901	5901
LDA	5901	5901



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 13; 31: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSC


EFF 20 APR 23

SHERBROOKE, QC

CARTE D'AÉRODROME — CYSC

AWOS – **128.15** (Fr) **126.25** (Ang)	◕ UNICOM – **123.5**	CTR Montreal – **132.55** MF

DIST DÉCLARÉES	13	31
TORA	5901	5901
TODA	6885	6885
ASDA	5901	5901
LDA	5901	5901



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 13; 31: *	1000 0 1000

CARTE D'AÉRODROME — CYSC

EFF 20 AVR 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ST-AUGUSTIN, QC


AERODROME CHART — CYIF

UNICOM – **123.5** (AU)

RADIO Quebec – **119.57**

ATF*

DECL DISTS	01	19
TORA	4595	4595
TODA	4595	4595
ASDA	4595	4595
LDA	4595	4595



* DEPARTURE PROCEDURE

Rwy 01 - ½ **-** Requires a minimum climb gradient of **360** ft/NM to **700**. NO RIGHT turn below **1200**.
Note: Trees to 45 ASL abeam departure end of rwy, both LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb visual over aprt to **1200** BPOC.

Rwy 19 - ½ **-** Climb hdg **190°** to **900** BPOC.
Note: Trees to 134 ASL abeam departure end of rwy, both LEFT and RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
360 FT/NM	540	720	840	960	1080	1200	1500	1800

TAKE-OFF MINIMA

Rwys 01, 19: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYIF

EFF 10 SEP 20

ST-AUGUSTIN, QC

CARTE D'AÉRODROME


CYIF

UNICOM – **123.5** (AU)

RADIO Quebec – **119.57**

ATF*

DIST DÉCLARÉES	01	19
TORA	4595	4595
TODA	4595	4595
ASDA	4595	4595
LDA	4595	4595



*PROCÉDURE DE DÉPART

Piste 01 - ½ **-** Requiert une pente de montée minimale de **360** pi/NM jusqu'à **700**. AUCUN virage à DROITE en dessous de **1200**.
Note: Arbres jusqu'à 45 ASL par le travers de l'extrémité de départ de la piste, à GAUCHE et à DROITE de l'axe de piste.

ou

SPEC VIS - Monter visuel au-dessus de l'aéroport jusqu'à **1200** BPOC.

Piste 19 - ½ **-** Monter sur cap **190°** jusqu'à **900** BPOC.
Note: Arbres jusqu'à 134 ASL par le travers de l'extrémité de départ de la piste, à GAUCHE et à DROITE de l'axe de piste.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
360 pieds/NM	540	720	840	960	1080	1200	1500	1800

MINIMUM DE DÉCOLLAGE

Pistes 01, 19: *

ÉCHELLE EN PIEDS

1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ST-BRUNO-DE-GUIGUES, QC

AERODROME CHART — CTA4

		UNICOM – **123.2** ATF	RADIO Quebec – **123.47**

DECL DISTS	10	28
TORA	4494	4494
TODA	5478	5478
ASDA	4494	4494
LDA	4494	4494



★ DEPARTURE PROCEDURE

Rwy 10 - ½

Note: Trees to 850 ASL aprx 0.2 NM past departure end of rwy, 250° LEFT of rwy centreline.

Rwy 28 - ½ **-** NO LEFT turn below **1300**.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST-BRUNO-DE-GUIGUES, QC

CARTE D'AÉRODROME


CTA4

UNICOM – **123.2**

RADIO Quebec – **123.47**

ATF

DIST DÉCLARÉES	10	28						
TORA	4494	4494						
TODA	5478	5478						
ASDA	4494	4494						
LDA	4494	4494						



MINIMUM DE DÉCOLLAGE

Pistes 10; 28: *

ÉCHELLE EN PIEDS

1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

STE-ANNE-DES-MONTS, QC

AERODROME CHART — CYSZ

AUTO – **122.02**		TFC – **122.8** ATF	CTR Montreal – **134.65 227.2**

DECL DISTS	14	32
TORA	3934	3934
TODA	3934	3934
ASDA	3934	3934
LDA	3934	3934



TAKE-OFF MINIMA
Rwys 14; 32: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

STE-ANNE-DES-MONTS, QC

CARTE D'AÉRODROME — CYSZ

AUTO – **122.02**		TFC – **122.8** ATF	CTR Montreal – **134.65 227.2**

DIST DÉCLARÉES	14	32
TORA	3934	3934
TODA	3934	3934
ASDA	3934	3934
LDA	3934	3934



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 14; 32: *	1000 0 1000

CARTE D'AÉRODROME — CYSZ

EFF 20 AVR 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ST-GEORGES, QC

AERODROME CHART — CYSG


AUTO – **123.17**

◕ UNICOM – **122.15** (AU)

MF

CTR Montreal – **132.35**

DECL DISTS	06	24
TORA	5112	5112
TODA	5299	6096
ASDA	5112	5112
LDA	5112	5112



TAKE-OFF MINIMA	
Rwys 06, 24: *	

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSG


EFF 15 JUN 23

ST-GEORGES, QC

CARTE D'AÉRODROME — CYSG

AUTO – **123.17**		◕ UNICOM – **122.15** (AU) **MF**	CTR Montreal – **132.35**

DIST DÉCLARÉES	06	24
TORA	5112	5112
TODA	5299	6096
ASDA	5112	5112
LDA	5112	5112



MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06, 24: ★	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME — CYSG

EFF 15 JUIN 23

ST-HYACINTHE, QC


AERODROME CHART — CSU3

CTR Montreal – **132.35**

TFC – **123.2**

MF

DECL DISTS	02	20
TORA	3823	3823
TODA	3823	3823
ASDA	3823	3823
LDA	3397	3469



TAKE-OFF MINIMA

Rwys 02; 20: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CSU3

EFF 23 FEB 23

ST-HYACINTHE, QC


CARTE D'AÉRODROME CSU3

CTR Montreal – **132.35**

TFC – **123.2**

MF

DIST DÉCLARÉES	02	20
TORA	3823	3823
TODA	3823	3823
ASDA	3823	3823
LDA	3397	3469



MINIMUM DE DÉCOLLAGE

Pistes 02; 20: *

ÉCHELLE EN PIEDS


1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

ST-JEAN, QC

AERODROME CHART — CYJN

		GND – **121.7**		TWR – **118.2** TFC – **118.2** ATF		TML Montreal – **125.15 268.3**				
DECL DISTS	**02**	**20**	**06**	**24**	**11**	**29**				
TORA	2438	2438	2349	2349	4012	4012				
TODA	3088	3422	3333	3333	4262	4287				
ASDA	2438	2438	2349	2349	4012	4012				
LDA	2438	2438	2349	2349	3412	4012				



* DEPARTURE PROCEDURE
Refer to DEPARTURE PROCEDURE page.

Note: All Rwys departure procedures not authorized when blasting area defined for St-Jean within the CFS Caution is active.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
220 FT/NM	330	440	520	590	660	740	920	1100

TAKE-OFF MINIMA
Rwys 02, 06, 11, 20, 24, 29 *


SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST-JEAN, QC

CARTE D'AÉRODROME — CYJN

		GND – **121.7**		TWR – **118.2** TFC – **118.2** ATF		TML Montreal – **125.15 268.3**		
DIST DÉCLARÉES	**02**	**20**	**06**	**24**	**11**	**29**		
TORA	2438	2438	2349	2349	4012	4012		
TODA	3088	3422	3333	3333	4262	4287		
ASDA	2438	2438	2349	2349	4012	4012		
LDA	2438	2438	2349	2349	3412	4012		



* PROCÉDURE DE DÉPART
Référez au page PROCÉDURE DE DÉPART.

Note: Toutes les procédures de départ non autorisées pendant que l'opération de dynamitage décrit dans le CFS pour St-Jean est actif.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
220 PIEDS/NM	330	440	520	590	660	740	920	1100

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 02, 06, 11, 20, 24, 29 *	1000 0 1000

CARTE D'AÉRODROME — CYJN

EFF 10 OCT 19


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

TASIUJAQ, QC

AERODROME CHART — CYTQ

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	05	23
TORA	3519	3519
TODA	3519	3519
ASDA	3519	3519
LDA	3519	3519



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 23: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYTQ


EFF 27 JAN 22

TASIUJAQ, QC

CARTE D'AÉRODROME — CYTQ

◕ APRT RADIO – **122.1**
◕ TFC – **122.1** MF*

DIST DÉCLARÉES	05	23
TORA	3519	3519
TODA	3519	3519
ASDA	3519	3519
LDA	3519	3519



MINIMUM DE DÉCOLLAGE
Pistes 05; 23: *

ÉCHELLE EN PIEDS
1000 0 1000

CARTE D'AÉRODROME — CYTQ

EFF 27 JAN 22


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

TROIS-RIVIÈRES, QC

AERODROME CHART — CYRQ

MET – **120.27** (En) **124.82** (Fr)		◕ UNICOM – **122.35**	CTR Montreal – **128.22** MF

DECL DISTS	05	23
TORA	9006	9006
TODA	9990	9990
ASDA	9006	9006
LDA	9006	9006



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05; 23: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYRQ


EFF 8 SEP 22

TROIS-RIVIÈRES, QC

CARTE D'AÉRODROME — CYRQ

MET – **124.82** (Fr) **120.27** (Ang)		UNICOM – **122.35**	CTR Montreal – **128.22** MF

DIST DÉCLARÉES	05	23
TORA	9006	9006
TODA	9990	9990
ASDA	9006	9006
LDA	9006	9006



* PROCÉDURE DE DÉPART

Piste 05 - ½ **-** AUCUN virage à GAUCHE en dessous de **1900**. Monter entre caps **286°** et **160°** sens horaire.
Note: Tour jusqu'à 264 ASL aprx 0.5 NM passé l'extrémité de la piste de départ. Tour jusqu'à 305 ASL aprx 0.8 NM passé l'extrémité de la piste de départ, 200' à GAUCHE de l'axe de piste.

Piste 23 - ½ **-** Monter entre caps **292°** et **046°** sens horaire.
Note: Arbres jusqu'à 226 ASL aprx 0.3 NM passé l'extrémité de la piste de départ.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 05; 23: *	1000 0 1000 2000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

UMIUJAQ, QC

AERODROME CHART — CYMU

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	02	20
TORA	3521	3521
TODA	3521	3521
ASDA	3521	3521
LDA	3521	3521



★ DEPARTURE PROCEDURE

Rwy 02 - ½ **-** Requires a minimum climb gradient of **460** ft/NM to **1200**. Climb hdg **025°** to **1900** BPOC.
Note: Terrain to 313 ASL abeam departure end of rwy, 500' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1600** BPOC.

Rwy 20 - ½ **-** Climb hdg **205°** to **1500** BPOC.
Note: Terrain to 392 ASL aprx 0.4 NM past departure end of rwy, LEFT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
460 FT/NM	690	920	1080	1230	1380	1540	1920	2300

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 02, 20: ★	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYMU


EFF 12 AUG 21

UMIUJAQ, QC

CARTE D'AÉRODROME — CYMU

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	02	20
TORA	3521	3521
TODA	3521	3521
ASDA	3521	3521
LDA	3521	3521



MINIMUM DE DÉCOLLAGE
Pistes 02, 20: *

ÉCHELLE EN PIEDS
1000 0 1000

CARTE D'AÉRODROME — CYMU

EFF 12 AOÛT 21


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

VAL-D'OR, QC

AERODROME CHART — CYVO

AWOS – **128.15** (En) **120.55** (Fr)		RADIO – **118.5** RADIO Rouyn – **118.5** MF
CTR Montreal – **125.9 308.3** RADIO Quebec – **122.37**		

DECL DISTS	18	36
TORA	10000	10000
TODA	10000	10000
ASDA	10000	10000
LDA	10000	10000



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300
290 FT/NM	440	580	680	780	870	970	1210	1450

★DEPARTURE PROCEDURE

Rwy 18 - ½ - Requires a minimum climb gradient of **260** ft/NM to **3300**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

Rwy 36 - ½ - Requires a minimum climb gradient of **290** ft/NM to **1600**.
Note: Trees to 1176 ASL aprx 0.2 NM past departure end of rwy, 800' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 18 : RVR 1200 RWY 36 : (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwys 18; 36:★	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYVO


EFF 23 FEB 23

VAL-D'OR, QC

CARTE D'AÉRODROME — CYVO

AWOS – **120.55** (Fr) **128.15** (Ang)		RADIO – **118.5** RADIO Rouyn – **118.5** MF
CTR Montreal – **125.9 308.3** RADIO Quebec – **122.37**		

DIST DÉCLARÉES	18	36
TORA	10000	10000
TODA	10000	10000
ASDA	10000	10000
LDA	10000	10000



TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
260 pieds/NM	390	520	610	700	780	870	1090	1300
290 pieds/NM	440	580	680	780	870	970	1210	1450

* PROCÉDURE DE DÉPART

Piste 18 - ½ - Requiert une pente de montée minimale de **260** pi/NM jusqu'à **3300**.

ou

SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **2400** ou plus haut BPOC.

Piste 36 - ½ - Requiert une pente de montée minimale de **290** pi/NM jusqu'à **1600**.
Note: Arbres jusqu'à 1176 ASL aprx 0,2 NM passé l'extrémité de la piste de départ, 800' à GAUCHE de l'axe de piste.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2400** ou plus haut BPOC.

NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
PISTE 18 : RVR 1200 PISTE 36 : (¼ sm)	NON AUTORISÉ

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 18; 36: *	1000 0 1000 2000

CARTE D'AÉRODROME — CYVO

EFF 23 FÉV 23

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

PARKING AREAS (PROCEDURES)

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
1	38.1	47.3		B757-200	Other D code aircraft
1A	25.9	22.3		DHC-8-100	B1900D B200 B100
2	35.8	39.5		B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32
2A	17.6	17.6		B1900D	B100 B200
2B	35.8	39.5		B737-800	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3	35.8	39.5		B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3A	25.9	22.3		DHC-8-100	JS32 B1900D B200 B100
4	28.4	30.5		B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
5	28.4	30.5		B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
5A	17.6	17.6		B1900D	B100 B200
5B	17.6	17.6		B1900D	B100 B200
R1	14.0	12.0		B100	smaller
R2	14.0	12.0		B100	smaller
R3	14.0	12.0		B100	smaller
R4	14.0	12.0		B100	smaller


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VAL-D'OR, QC

PARKING AREAS

CYVO

AWOS – **128.15** (En)
120.55 (Fr)



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYVO

EFF 23 FEB 23

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	480308.23N 0774710.98W	3A	480310.86N 0774712.12W
1A-1	480307.64N 0774711.31W	4	480312.63N 0774712.54W
1A-2	480306.77N 0774710.62W	5	480314.60N 0774713.11W
2-1	480307.75N 0774711.37W	5A	480314.52N 0774713.04W
2-2	480307.68N 0774711.21W	5B	480314.96N 0774712.15W
2A	480308.20N 0774710.46W	R1	480315.91N 0774713.64W
2B	480308.97N 0774711.72W	R2	480316.01N 0774712.84W
3-1	480310.35N 0774712.12W	R3	480316.12N 0774712.03W
3-2	480310.23N 0774711.85W	R4	480316.22N 0774711.23W

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros avions permis	Autres avions permis
1	38.1	47.3		B757-200	Other D code aircraft
1A	25.9	22.3		DHC-8-100	B1900D B200 B100
2	35.8	39.5		B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32
2A	17.6	17.6		B1900D	B100 B200
2B	35.8	39.5		B737-800	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3	35.8	39.5		B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3A	25.9	22.3		DHC-8-100	JS32 B1900D B200 B100
4	28.4	30.5		B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros avions permis	Autres avions permis
5	28.4	30.5		B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
5A	17.6	17.6		B1900D	B100 B200
5B	17.6	17.6		B1900D	B100 B200
R1	14.0	12.0		B100	smaller
R2	14.0	12.0		B100	smaller
R3	14.0	12.0		B100	smaller
R4	14.0	12.0		B100	smaller

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

VAL-D'OR, QC

AIRES DE STATIONNEMENT CYVO

AWOS – **120.55** (Fr)
128.15 (Ang)



Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT CYVO

EFF 23 FÉV 23

Poste de stationnement d'aéronef

Position	Coordonnées	Position	Coordonnées
1	480308.23N 0774710.98W	3A	480310.86N 0774712.12W
1A-1	480307.64N 0774711.31W	4	480312.63N 0774712.54W
1A-2	480306.77N 0774710.62W	5	480314.60N 0774713.11W
2-1	480307.75N 0774711.37W	5A	480314.52N 0774713.04W
2-2	480307.68N 0774711.21W	5B	480314.96N 0774712.15W
2A	480308.20N 0774710.46W	R1	480315.91N 0774713.64W
2B	480308.97N 0774711.72W	R2	480316.01N 0774712.84W
3-1	480310.35N 0774712.12W	R3	480316.12N 0774712.03W
3-2	480310.23N 0774711.85W	R4	480316.22N 0774711.23W


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

VICTORIAVILLE (ANDRÉ-FORTIN), QC

AERODROME CHART — CSR3

AWOS – **122.17**		UNICOM – **123.35** ATF	CTR Montreal – **132.35**

DECL DISTS	06	24
TORA	5530	5530
TODA	5530	5530
ASDA	5530	5530
LDA	5530	5530



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 06, 24: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

VICTORIAVILLE (ANDRÉ-FORTIN), QC

CARTE D'AÉRODROME CSR3

AWOS – **122.17**	UNICOM – **123.35** ATF	CTR Montreal – **132.35**

DIST DÉCLARÉES	06	24
TORA	5530	5530
TODA	5530	5530
ASDA	5530	5530
LDA	5530	5530



TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
250 pieds/NM	380	500	590	670	750	840	1050	1250

* PROCÉDURE DE DÉPART

PIste 06 - ½ **-** Requiert une pente de montée minimale de **250** pi/NM jusqu'à **5300** lorsque la montée se fait entre caps **031°** et **103°** sens horaire. AUCUN virage à DROITE en dessous de **1800**. Ne PAS monter entre caps **322°** et **240°** sens antihoraire en dessous de **8000**.
Note: Arbres jusqu'à 569 ASL par le travers de l'extrémité de la piste de départ, 470' à GAUCHE et DROITE de l'axe de piste.

ou

SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **1800** ou plus haut BPOC. Continuer à monter entre caps **322°** et **267°** sens horaire jusqu'à **8000** BPOC.

PIste 24 - ½ **-** Monter sur cap **240°** jusqu'à **1300** BPOC. Ne PAS monter entre caps **267°** et **322°** sens horaire en dessous de **8000**.
Note: Arbres jusqu'à 552 ASL par le travers de l'extrémité de la piste de départ, 390' à GAUCHE et DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Piste 06, 24: *	1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

WASKAGANISH, QC

AERODROME CHART — CYKQ

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	06	24
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



TAKE-OFF MINIMA
Rwys 06, 24: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYKQ


EFF 25 APR 19

WASKAGANISH, QC

CARTE D'AÉRODROME — CYKQ

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	06	24
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



* PROCÉDURE DE DÉPART

Piste 06 - ½
Note: Arbres jusqu'à 145 ASL passé l'extrémité de la piste de départ.

Piste 24 - ½
Note: Arbres jusqu'à 129 ASL passé l'extrémité de la piste de départ.

MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 06, 24: *	1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés


WEMINDJI ,QC

AERODROME CHART

CYNC

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DECL DISTS	10	28
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



* DEPARTURE PROCEDURE

Rwy 10 - ½ - Requires a minimum climb gradient of **380** ft/NM to **700**.
Note: Trees to 119 ASL abeam departure end of rwy, 250' LEFT and RIGHT of rwy centreline and aprx 0.2 NM past departure end of rwy, 350' LEFT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **800** BPOC.

Rwy 28 - ½
Note: Trees to 83 ASL abeam departure end of rwy, 300' LEFT and RIGHT of rwy centreline and aprx 0.2 NM past departure end of rwy.

TAKE-OFF MINIMA
Rwys 10, 28: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

WEMINDJI, QC

CARTE D'AÉRODROME — CYNC

◕ APRT RADIO – **122.1**
◕ TFC – **122.1**
MF*

DIST DÉCLARÉES	10	28
TORA	3511	3511
TODA	3511	3511
ASDA	3511	3511
LDA	3511	3511



***** PROCÉDURE DE DÉPART

PIste 10: - ½ **-** Requiert une pente de montée minimale de **380** pi/NM jusqu'à **700**.
Note: Arbres jusqu'à 119 ASL par le travers de l'extrémité de la piste de départ, 250' à GAUCHE et à DROITE de l'axe de piste et aprx 0.2 NM passé l'extrémité de la piste de départ, 350' à GAUCHE de l'axe de piste.

ou

SPEC VIS **-** Effectuer une montée à vue pour survoler l'aéroport à **800** ou plus haut BPOC.

PIste 28: - ½
Note: Arbres jusqu'à 83 ASL par le travers de l'extrémité de la piste de départ, 300' à GAUCHE et à DROITE de l'axe de piste et aprx 0.2 NM passé l'extrémité de la piste de départ.

MINIMUM DE DÉCOLLAGE
Piste 10, 28: *****

ÉCHELLE EN PIEDS
1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2023 NAV CANADA Tous droits réservés

BATHURST, NB

AERODROME CHART — CZBF

AWOS – **127.92**		UNICOM – **122.8** (AU) ATF	CTR Moncton – **134.25** RADIO Quebec – **123.47**

DECL DISTS	10	28
TORA	5613	5613
TODA	5613	5613
ASDA	5613	5613
LDA	5151	5613



* DEPARTURE PROCEDURE

Rwy 10 - ½
Note: Trees to 243 ASL aprx 0.35 NM past departure end of rwy, 900' LEFT of rwy centreline.

Rwy 28 - ½ - Requires a minimum climb gradient of **250** ft/NM to **500**.
Note: Trees to 295 ASL aprx 0.2 NM past departure end of rwy, 830' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1000** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 10; 28: *	1000 500 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

BLACK TICKLE, NL

AERODROME CHART — CCE4

TFC – **122.8** ATF*

DECL DISTS	14	32
TORA	2503	2503
TODA	2503	2503
ASDA	2503	2503
LDA	2503	2503



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 14; 32: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


CARTWRIGHT, NL

AERODROME CHART — CYCA

MET – **128.75**

TFC – **122.8** ATF*

DECL DISTS	08	26						
TORA	3937	3937						
TODA	3937	3937						
ASDA	3937	3937						
LDA	3937	3937						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 08, 26: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CHARLO, NB


AERODROME CHART — CYCL

CTR Moncton – **134.25**

TFC – **122.2**

ATF

DECL DISTS	12	30
TORA	6009	6009
TODA	6993	6993
ASDA	6009	6009
LDA	6009	6009



TAKE-OFF MINIMA
Rwys 12; 30: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


CHARLOTTETOWN, NL

AERODROME CHART — CCH4

AWOS Mary's Harbour – **122.55**

TFC – **122.8** ATF*

DECL DISTS	09	27
TORA	2502	2502
TODA	2502	2502
ASDA	2502	2502
LDA	2502	2502



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09; 27: *	1000 500 0 500

AERODROME CHART — CCH4

EFF 24 MAR 22


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CHARLOTTETOWN, PE

AERODROME CHART — CYYG

		RADIO – **118.0**	CTR Moncton – **135.65** MF

DECL DISTS	03	21	10	28				
TORA	7002	7002	7000	7000				
TODA	7986	7986	7984	7984				
ASDA	7002	7002	7000	7000				
LDA	7002	7002	7000	7000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 03: RVR 1200 RWY 10, 28: (¼sm) Day only RWY 21: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	
Rwy 03, 10: ½ Rwy 21, 28: *	SCALE IN FEET 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYG

EFF 10 AUG 23


CLARENVILLE, NL

AERODROME CHART — CCZ3

CTR Gander – **132.1 289.4**

TFC – **123.2** ATF

DECL DISTS	08	26						
TORA	3938	3938						
TODA	3938	3938						
ASDA	3938	3938						
LDA	3938	3938						



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 08, 26: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

DEBERT, NS

AERODROME CHART — CCQ3


AUTO – **122.27**

UNICOM – **123.0**

TML Halifax – **119.2**

ATF

DECL DISTS	05	09	16	23	27	34		
TORA	3144	4999	5001	3144	4999	5001		
TODA	3144	4999	5001	3144	4999	5001		
ASDA	3144	4999	5001	3144	4999	5001		
LDA	3144	4999	4504	3144	4999	5001		



*DEPARTURE PROCEDURE

Rwy 09 - ½ - Requires a minimum climb gradient of **210** ft/NM to **400**.
Climb hdg **091°** to **1100** BPOC.
Note: Trees to 188 ASL abeam departure end of rwy, 640' LEFT of rwy centerline.
Trees to 171 ASL abeam departure end of rwy, 570' RIGHT of rwy centerline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **900**.
Continue climb hdg **230°** to **1000** BPOC.

Rwy 27 - ½
Note: Trees to 171 ASL abeam departure end of rwy, 60' RIGHT
and LEFT of rwy centerline

TAKE-OFF MINIMA

Rwys 09; 27: *
Rwys 05; 16; 23; 34: NOT ASSESSED

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CCQ3

EFF 23 FEB 23


DEER LAKE, NL

AERODROME CHART — CYDF

RADIO – **122.2 239.6** **MF**

CTR Gander – **134.6**

DECL DISTS	07	25
TORA	8005	8005
TODA	8989	8989
ASDA	8005	8005
LDA	8005	8005



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07, 25: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 07, 25: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYDF

EFF 16 JUL 20

DIGBY MUNICIPAL AIRPORT, NS


AERODROME CHART — CYID

UNICOM – **122.8**

CTR Moncton – **123.9**

ATF

DECL DISTS	06	24						
TORA	3957	3957						
TODA	3957	3957						
ASDA	3957	3957						
LDA	3957	3957						



* DEPARTURE PROCEDURE

Rwy 06 - ½

Note: Trees to 535 ASL abeam departure end of rwy, 420' LEFT of rwy centerline. Trees and terrain to 535 ASL 0.1 NM past departure end of rwy, 600' LEFT of rwy centerline. Powerlines to 529 ASL abeam departure end of rwy, 530' LEFT of rwy centerline running along departure path.

Rwy 24 - ½

Note: Trees to 486 ASL abeam departure end of rwy, 360' LEFT and RIGHT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06, 24: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


EDMUNDSTON, NB

AERODROME CHART — CYES

UNICOM – **122.8**

ATF

DECL DISTS	16	34
TORA	4562	4562
TODA	4562	4562
ASDA	4562	4562
LDA	4562	4562



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 16, 34: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYES

EFF 20 APR 23

EXPLOITS VALLEY (BOTWOOD), NL


AERODROME CHART — CCP2

CTR Gander – **132.1**

TFC – **123.2**

ATF

DECL DISTS	06	24
TORA	4007	4007
TODA	4007	4007
ASDA	4007	4007
LDA	4007	4007



* DEPARTURE PROCEDURE

Rwy 06 - ½

Note: Trees to 394 ASL abeam departure end of rwy, 200' LEFT and RIGHT of rwy centreline and aprx 500' past departure end of rwy. Power line to 431 ASL aprx 0.2 NM past departure end of rwy, 800' RIGHT of rwy centreline.

Rwy 24 - ½

Note: Trees to 400 ASL abeam departure end of rwy, 200' LEFT and RIGHT of rwy centreline and aprx 400' past departure end of rwy. Power line to 418 ASL aprx 0.2 NM past departure end of rwy, 800' LEFT of rwy centreline.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06, 24: *	1000 1000

AERODROME CHART — CCP2

EFF 29 MAR 18

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FOGO, NL

AERODROME CHART — CDY3

CTR Gander – **132.1** **289.4**

TFC – **123.2** **ATF**

DECL DISTS	10	28						
TORA	3000	3000						
TODA	3000	3000						
ASDA	3000	3000						
LDA	3000	3000						

54 14.5 — 54 14

49 39.7 — 49 39.7

VAR 20° W 2013
ANNUAL RATE OF CHANGE 12' E

CDY3
N49 39.44
W54 14.25

3000 x 75

AS 283° 28

ELEV 91

AS 103° 10

ELEV 92

* DEPARTURE PROCEDURE

Rwy 10 - ½ **-** Requires a minimum climb gradient of **230** ft/NM to **400**.
Note: Trees to 206 ASL aprx 0.6 NM past departure end of rwy, both LEFT and RIGHT of runway centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **900** BPOC.
Note: Departure NOT auth when blasting area active.

Rwy 28 - ½ **-** Requires a minimum climb gradient of **330** ft/NM to **700**.
Climb hdg **283°** to **700** BPOC.
Note: Trees to 181 ASL, aprx 400' past departure end of rwy 450' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **900** BPOC.
Note: SPEC VIS NOT auth when blasting area active.

49 39.2 — 49 39.2

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
330 FT/NM	500	660	770	880	990	1100	1380	1650

54 14.5 — 54 14

TAKE-OFF MINIMA

Rwys 10; 28: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

FREDERICTON INTL, NB

AERODROME CHART — CYFC

ATIS – **127.55** AWOS – **127.55**	GND – **121.7**	TWR – **119.0** RADIO Saint John – **119.0** MF*	CTR Moncton – **124.3 270.8**

DECL DISTS	09	27	15	33				
TORA	8005	8005	6000	6000				
TODA	8399	8530	6984	6394				
ASDA	8005	8005	6000	6000				
LDA	8005	8005	6000	6000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 09: RVR 1200 RWY 15, 27, 33: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09;15;27;33: *	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYFC


EFF 27 JAN 22

GANDER INTL, NL

AERODROME CHART — CYQX

ATIS – **124.8**	GND – **121.9 275.8**	TWR – **118.1 236.6**	DEP – **132.1**

DECL DISTS	03	21	13	31				
TORA	10200	10200	8900	8900				
TODA	10607	11184	9527	9884				
ASDA	10500	10200	8900	8900				
LDA	10200	10200	8900	8900				



✱ DEPARTURE PROCEDURE

Rwy 03 - ½
Note: Trees to 518 ASL aprx 0.2 NM past departure end of rwy.

Rwy 13 - ½
Note: Trees to 506 ASL aprx 0.1 NM past departure end of rwy, 480' LEFT of rwy centreline.

Rwy 21 - ½
Note: Trees to 472 ASL aprx 0.1 NM past departure end of rwy.

Rwy 31 -½
Note: Trees to 538 ASL aprx 0.2 NM past departure end of rwy.

HOT SPOTS

HS 1 - Twy A & Twy C intxn.
Flight school and heli tfc congestion point.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 03, 13: RVR 1200 RWY 21, 31: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 03, 13, 21, 31: ✱	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQX

EFF 5 OCT 23

GANDER INTL, NL

PARKING AREAS

CYQX

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS

CYQX

EFF 1 FEB 18


GOOSE BAY, NL

AERODROME CHART (DND)

CYYR

ATIS – **128.1 340.8**	CLNC DEL – **118.1 336.5** GND – **121.9 275.8**	TWR – **119.1 236.6**	◕ TML – **119.5 267.1** ◕ CTR Gander – **120.4 267.1**

DECL DISTS	08	26	15	33				
TORA	11052	11052	9584	9584				
TODA	11052	11052	9584	9584				
ASDA	11202	12052	9724	9734				
LDA	11052	11052	9584	9584				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART (DND)


EFF 5 OCT 23

GRAND MANAN, NB

AERODROME CHART — CCN2

AUTO - **122.17**		TFC – **123.2** ATF	CTR Moncton – **124.3**

DECL DISTS	06	24
TORA	3009	3009
TODA	3009	3009
ASDA	3009	3009
LDA	3009	3009



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 24: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CCN2

EFF 3 NOV 22


GREENWOOD, NS

AERODROME CHART (DND)

CYZX

ATIS – **128.85 244.3**	CLNC DEL – **128.02 283.9** GND – **133.75 289.4**	TWR – **119.5 324.3**	TML – **120.6 335.9**

DECL DISTS	08	26	12	30				
TORA	7999	7999	7999	7999				
TODA	7999	7999	7999	7999				
ASDA	7999	7999	7999	7999				
LDA	7999	7999	7999	7999				



✱ DEPARTURE PROCEDURE

Rwys 08, 26 - ½ - Climb rwy hdg to **1200** BPOC.

Rwy 12 - ½ - Requires a minimum climb gradient of **320** ft/NM to **1200**.

Rwy 30 - ½ - Climb rwy hdg to **1200** BPOC Requires a minimum climb gradient of **290** ft/NM to **1200**.

Rwys 12, 30 - SPEC VIS - Climb in Visual Conditions to cross apr at or above **1200** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450
320 FT/NM	480	640	750	860	960	1070	1340	1600

TAKE-OFF MINIMA
All Rwys: ✱


SCALE IN FEET
2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

GREENWOOD, NS

PARKING AREAS (DND)

CYZX



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (DND)

CYZX


EFF 8 SEP 22

HALIFAX (QE II HEALTH SCIENCES CENTRE), NS

HELIPORT CHART — CHQE

ATIS Shearwater – **129.17**		ADVSY Shearwater – **126.2** TFC – **126.2** MF* CYAW	TML Halifax – **119.2**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HALIFAX/STANFIELD INTL, NS

AERODROME CHART — CYHZ

ATIS – **121.0**	CLNC DEL – **123.95** GND – **121.9 275.8**	TWR – **118.4 236.6**	TML – **119.2**

DECL DISTS	05	23	14	32				
TORA	10500	10500	7700	7700				
TODA	11189	11189	8684	8684				
ASDA	10500	10500	7700	7700				
LDA	10500	10139	7700	7700				



LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)		
FROM	TO	LDA in ft
Thld rwy 05	Short of Rwy 14-32	9544

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 14, 23: RVR 1200 RWY 05, 32: (¼sm)	RWY 23: RVR 600

TAKE-OFF MINIMA	
Rwys 05; 14: * Rwys 23; 32: ½	SCALE IN FEET 2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Low Visibility Procedures (RVR less than 1200 ft to 600 ft)

Application

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the manoeuvring area. The following message will be added to the ATIS broadcast: “LOW VISIBILITY PROCEDURES IN EFFECT”.

General

The approved taxi route from the Apron is shown on the Low Visibility Taxi Chart. Taxiway centreline lights will be illuminated in taxiway A, G, F, across Rwy 14, taxiway L to the stop bar.

Departures

When low visibility procedures are in effect, Rwy 23 is the only runway certified for low visibility operations.

Take-off roll cannot commence prior to the displaced threshold location, where the runway is served by high intensity white runway edge lights.

Sequencing of Aircraft Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-Off as described in CAP GEN Operating Minima.

Do not call for taxi clearance until the reported RVR is a minimum of 600.

Runway Level of Service	
Rwy	**Certification**
23	RVR 600

Stop Bar/Guard Light System

Each taxiway/runway entrances onto Rwy 05/23 is equipped with a stop bar consisting of red inset lights. Also, installed on either side of the stop bars located at the taxiway entrances onto Rwy 05/23 there are yellow flashing runway guard lights (Wig Wags). When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.

AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR

Arrivals

Arrivals are permitted on Rwy 23 for approved operators down to RVR 600. Twy J and Twy B are the approved exit routes. Landing aircraft traversing to Aprons I, II or III must exit Rwy 23 on Twy B or Twy J.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART
(RVR LESS THAN 1200 TO 600 FT)

HALIFAX/STANFIELD INTL, NS
CYHZ

ATIS – **121.0**	CLNC DEL – **123.95** GND – **121.9 275.8**	TWR – **118.4 236.6**

VAR 18° W 2012
ANNUAL RATE OF CHANGE 8' E

During Low Visibility Conditions	
Declared Distances	23
TORA TODA	10139 10828



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

De-icing Operations

1. Contact de-icing provider 30 min prior to dep if de-icing is required. Notify de-icing provider of any special treatments prior to pushback: ICE MAN 122.950, phone number 902-410-7748
2. De-icing provider will assign de-ice pad and advise when ready.
3. DO NOT PUSH prior to assigned de-ice pad being ready.
4. To mitigate congestion on the APN, QUEUING for de-icing is NOT ACCEPTABLE.
5. Monitor Halifax GND 121.9 for all APN movement.
6. Follow instructions to designated de-ice pad.
7. Advise ICEMAN immediately once brakes set, aircraft configured and engines at idle.
8. After de-icing, configure aircraft for taxi, however, DO NOT MOVE AIRCRAFT.
9. Once instructed, contact Halifax GND 121.9 for taxi.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HALIFAX/STANFIELD INTL, NS


PARKING AREAS (APRON I)

CYHZ

ATIS – **121.0**

CLNC DEL – **123.95**

GND – **121.9 275.8**



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

CYHZ

EFF 7 OCT 21


PARKING AREAS (APRON III)

CYHZ

ATIS – **121.0**

CLNC DEL – **123.95**

GND – **121.9 275.8**



Apron Procedures

1. All aircraft departing Positions 301, 302, 303 and 304 must be towed to the Apron III tow bar disconnect position located on the taxi line between Positions 301 and 302.

2. Aircraft departing Positions 305, 306, 307 and 308 may taxi to the hold position at Apron III/Twy J. If required to stop for any reason while taxiing on Apron III, the aircraft must be towed to the tow bar disconnect position.

3. Monitor ground frequency 121.9.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

Aircraft Parking Positions (APRON I and APRON III)

Position	Coordinates	Position	Coordinates
2A	445302.98N 0633052.10W	27	445319.65N 0633054.36W
2B	445302.13N 0633052.82W	27A	445319.47N 0633053.96W
2C	445301.48N 0633053.58W	28	445320.86N 0633056.98W
2D	445300.69N 0633053.64W	36	445321.47N 0633059.58W
2E	445300.44N 0633054.46W	38	445322.35N 0633058.83W
3	445304.04N 0633051.05W	42	445323.15N 0633057.90W
5	445304.26N 0633049.25W	42A	445322.96N 0633058.06W
6	445303.29N 0633048.01W	46	445323.92N 0633057.28W
6A	445302.94N 0633047.83W	46A	445324.31N 0633057.52W
7	445303.84N 0633047.47W	52	445315.74N 0633051.27W
7A	445303.69N 0633047.16W	53	445316.87N 0633051.95W
8	445304.51N 0633047.34W	54	445318.43N 0633051.97W
8A	445304.66N 0633046.79W	56	445319.62N 0633052.85W
9	445304.94N 0633048.25W	57	445319.65N 0633054.36W
12	445306.13N 0633049.45W	57A	445319.47N 0633053.96W
14	445307.77N 0633049.44W	58	445320.86N 0633056.98W
15	445310.18N 0633049.62W	301	445200.49N 0633155.57W
16	445311.01N 0633049.87W	302	445202.77N 0633158.95W
18	445312.29N 0633050.58W	303	445204.44N 0633201.74W
20	445313.84N 0633050.79W	304	445206.75N 0633204.61W
22	445315.74N 0633051.27W	305	445210.05N 0633204.26W
23	445316.87N 0633051.95W	306	445212.05N 0633202.77W
24	445318.43N 0633051.97W	307	445215.83N 0633200.10W
26	445319.62N 0633052.85W	308	445217.05N 0633157.79W

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HOPEDALE, NL

AERODROME CHART — CYHO

CTR Gander – **135.4**

TFC – **122.8**

ATF*

DECL DISTS	06	24
TORA	2501	2501
TODA	2501	2501
ASDA	2501	2501
LDA	2501	2501

60 14 — 60 13.3

VAR 21° W 2021

ANNUAL RATE OF CHANGE 16' E

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
310 FT/NM	470	620	730	830	930	1040	1300	1550

55 27.2

AS 14 ELEV 46

AP 4.0°

245°

CYHO
N55 26.93
W60 13.69

2501 x 75 gravel

AP 4.0°

065°

AS 06 ELEV 45

55 26.7

* DEPARTURE PROCEDURE

Rwy 06 - ½ - Requires a minimum climb gradient of **310** ft/NM to **300**. Climb hdg **065°** to **900** BPOC.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1200** BPOC.

Rwy 24 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1200** BPOC.

60 14 — 60 13.3

TAKE-OFF MINIMA
Rwys 06; 24: *

SCALE IN FEET
1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

LONG HARBOUR RIVER, NL

HELIPORT CHART — CLH7

TFC – **123.2** ATF

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

HELIPORT CHART — CLH7


EFF 30 JAN 20

LONG POND, NL

HELIPORT CHART — CCX2

ATIS St. John's – **128.0**		TFC – **123.2** ATF	CTR Gander – **133.15**

DECL DISTS								
TORA								
TODA								
ASDA								
LDA								



TAKE-OFF MINIMA	SCALE IN FEET
NOT ASSESSED	100 0 100

HELIPORT CHART — CCX2

EFF 19 MAY 22

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MAKKOVIK, NL


AERODROME CHART — CYFT

CTR Gander – **120.4** **294.5**

TFC – **122.8**

ATF*

DECL DISTS	09	27						
TORA	2592	2592						
TODA	2592	2592						
ASDA	2592	2592						
LDA	2592	2592						



* DEPARTURE PROCEDURE

Rwy 09: - ½ - Requires a minimum climb gradient of **360** ft/NM to **900**. Climb hdg **089°** to **2100** BPOC.
Note: Trees to 233 ASL abeam departure end of rwy, 200' LEFT and RIGHT of rwy centreline and aprx 350' past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

Rwy 27: - ½ - Requires a minimum climb gradient of **350** ft/NM to **1300**. Climb hdg **269°** to **2500** BPOC.
Note: Trees to 269 ASL abeam departure end of rwy, 150' LEFT and RIGHTof rwy centreline and aprx 250' past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2400** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 FT/NM	530	700	820	940	1050	1170	1460	1750
360 FT/NM	540	720	840	960	1080	1200	1500	1800

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 09, 27 *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


MARYS HARBOUR, NL

AERODROME CHART — CYMH

MET – **122.55**

TFC – **122.8** ATF*

DECL DISTS	11	29
TORA	2545	2545
TODA	2545	2545
ASDA	2545	2545
LDA	2545	2545



TAKE-OFF MINIMA

Rwys 11, 29: *

SCALE IN FEET

500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MIRAMICHI, NB


AERODROME CHART — CYCH

UNICOM – **122.7** (AU)

CTR Moncton – **123.7**

ATF

DECL DISTS	09	27
TORA	10006	10006
TODA	10990	10990
ASDA	10006	10006
LDA	10006	10006



* DEPARTURE PROCEDURE

Rwy 09 - ½

Note: Trees to 135 ASL 0.2 NM past departure end of rwy 580' RIGHT and 610' LEFT of rwy centerline.

Rwy 27 - ½

Note: Trees to 167 ASL 0.3 NM past departure end of rwy, 750' LEFT of rwy centerline. Trees to 165 ASL 0.3 NM past departure end of rwy, 130' RIGHT of rwy centerline.

TAKE-OFF MINIMA
Rwys 09; 27: *

SCALE IN FEET

1000 0 1000 2000 3000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

MONCTON/GREATER MONCTON ROMÉO LEBLANC INTL, NB

AERODROME CHART — CYQM

ATIS – **128.65**	APRON – **122.07** GND – **121.8 275.8**	TWR – **120.8 236.6**	DEP – **124.4**

DECL DISTS	06	24	11	29				
TORA	10001	10001	8000	8000				
TODA	10985	10985	8984	8984				
ASDA	10001	10001	8000	8000				
LDA	10001	10001	8000	8000				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06, 29: RVR 1200 RWY 11, 24: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 06; 11: * Rwys 24; 29: ½	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQM


EFF 5 OCT 23

PARKING AREAS (Apron VIII) CYQM

ATIS – **128.65**	APRON – **122.07** GND – **121.8 275.8**

Note:
De-icing Apron VIII - Prior to pushback, broadcast intentions and monitor all movements on Apron Advisory 122.075. Proceed to De-icing pad.

Itinerant Aircraft wishing to use Apron VIII ctc Airport Security 506-856-5429 - 2hr PNR.



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


NAIN, NL

AERODROME CHART — CYDP

TFC – **122.8** ATF*

RADIO London – **123.65**

DECL DISTS	04	22						
TORA	1986	1986						
TODA	1986	1986						
ASDA	1986	1986						
LDA	1986	1986						



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 04, 22: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYDP

EFF 7 OCT 21

NATUASHISH, NL


AERODROME CHART — CNH2

CTR Gander – **135.4**

TFC – **122.8**

ATF*

DECL DISTS	12	30
TORA	2500	2500
TODA	2500	2500
ASDA	2500	2500
LDA	2500	2500



* DEPARTURE PROCEDURE

Rwy 12 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2000** BPOC.

Rwy 30 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **2000** BPOC.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12, 30: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CNH2

EFF 27 JAN 22

POKEMOUCHE, NB


AERODROME CHART — CDA4

UNICOM – **122.35**

CTR Moncton – **134.25**

ATF

DECL DISTS	12	30						
TORA	3400	3400						
TODA	3400	3400						
ASDA	3400	3400						
LDA	3400	3400						



* DEPARTURE PROCEDURE

Rwy 12 - ½
Note: Trees to 124 ASL abeam departure end of rwy, 300' RIGHT and 350' LEFT of rwy centreline.
Note: Powerline to 99 ASL aprx 0.2NM past departure end of rwy.

Rwy 30 - ½
Note: Trees to 149 ASL aprx 0.1NM past departure end of rwy.
Note: Road to 114 ASL aprx 0.2NM past departutre end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 12, 30: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PORT HAWKESBURY, NS

AERODROME CHART — CYPD

AWOS – **128.3**		UNICOM – **122.8** ATF	RADIO London – **123.37** DRCO

DECL DISTS	11	29
TORA	5000	5000
TODA	5000	5000
ASDA	5000	5000
LDA	5000	5000



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 11; 29: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYPD


EFF 24 MAR 22

PORT HOPE SIMPSON, NL

AERODROME CHART — CCP4

AWOS Mary's Harbour – **122.55**		TFC – **122.8** ATF*	

DECL DISTS	12	30
TORA	2497	2497
TODA	2497	2497
ASDA	2497	2497
LDA	2497	2497



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

TAKE-OFF MINIMA

Rwys 12, 30: *

SCALE IN FEET

800 0 800

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

POSTVILLE, NL


AERODROME CHART — CCD4

CTR Gander – **135.4**

TFC – **122.8**

ATF*

DECL DISTS	06	24
TORA	2576	2576
TODA	2576	2576
ASDA	2576	2576
LDA	2576	2576



* DEPARTURE PROCEDURE

Rwy 06 -½- Requires a minimum climb gradient of **260** ft/NM to **600**. Climb hdg **055°** to **1600** BPOC.
Note: Trees to 248 ASL within 0.1 NM of departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.
Rwy 24 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA
Rwys 06, 24: *

SCALE IN FEET
500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

RIGOLET, NL


AERODROME CHART — CCZ2

TFC – **122.8**

ATF*

◕ TML Goose Bay – **119.5** **267.1**
◕ CTR Gander – **120.4**

DECL DISTS	11	29
TORA	2496	2496
TODA	2496	2496
ASDA	2496	2496
LDA	2496	2496



TAKE-OFF MINIMA
Rwys 11; 29: *

SCALE IN FEET
1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


SABLE ISLAND, NS

AERODROME CHART — CSB2

AWOS – **118.2**

TFC – **122.75** MF*

DECL DISTS	11	29						
TORA	1500	1500						
TODA	1500	1500						
ASDA	1500	1500						
LDA	1500	1500						



TAKE-OFF MINIMA

All Rwys: ½

SCALE IN FEET

500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

SAINT JOHN, NB


AERODROME CHART — CYSJ

RADIO – **118.5 236.6**

CTR Moncton – **124.3 270.8**

MF

DECL DISTS	05	23	14	32				
TORA	7201	7201	5100	5100				
TODA	7857	7726	5100	6084				
ASDA	7201	7201	5100	5100				
LDA	7004	7004	5100	5100				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 05, 23: RVR 1200 RWY 14, 32: (¼ sm)	RWY 05, 23: RVR 600

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05;14; 23; 32: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

REDUCED VISIBILITY PROCEDURES (RVR less than 2600 ft (1/2 sm) to 1200 ft (1/4 sm)) and LOW VISIBILITY PROCEDURES (RVR less than 1200 to 600 ft)

Application

These procedures apply to ground movements of aircraft departing under reduced and low visibility conditions.

Departures below RVR 600 are not authorized.

When weather conditions indicate visibility below RVR 2600, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the advisory: "REDUCED VISIBILITY PROCEDURES IN EFFECT" or "LOW VISIBILITY PROCEDURES IN EFFECT"

General

REDUCED VISIBILITY TAXI ROUTES

Taxi routes during reduced visibility operations are exclusive to the following routes:

1. Route 1 - Twy C, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.
2. Route 2 - Twy I, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.
3. Route 3 - Twy B, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.

Aircraft restricted to one on the maneuvering area at any time during reduced visibility operations.

LOW VISIBILITY TAXI ROUTES

Taxi routes during low visibility operations are exclusive to the following routes:

1. Route 1 - Twy C, Rwy 14/32, Twy A - to Rwy 05/23.
2. Route 2 - Twy I, Rwy 14/32, Twy A - to Rwy 05/23.
3. Route 3 - Twy B, Rwy 14/32, Twy A - to Rwy 05/23.

Aircraft restricted to one on the maneuvering area at any time during low visibility operations.

When RVR falls below 600, movement of all aircraft ceases.

Rwy 14/32 will be used for taxiing purposes only during low visibility conditions.

DEPARTURES

Rwy 14/32 and Rwy 05/23 for departures in reduced visibility conditions.

Rwy 05/23 will be used for departures in low visibility conditions.

During RVOP/LVOP departure clearance or Pre-Taxi validation will not be given to any requesting aircraft if any other aircraft has been issued an approach or departure clearance until:

- either the arriving aircraft has landed and reported off the manoeuvring area or
- a departing aircraft is in contact with the Moncton Area Control Centre.

Take-Off roll cannot commence prior to the displaced threshold location where the runway is served by high intensity white runway edge lights.

Modified Declared Distances During RVOP/LVOP

RWY 05		RWY 23	
TORA	7004	TORA	7004
TODA	7660	TODA	7529
ASDA	7004	ASDA	7004

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

REDUCED VISIBILITY PROCEDURES (RVR less than 2600 ft (1/2 sm) to 1200 ft (1/4 sm)) and LOW VISIBILITY PROCEDURES (RVR less than 1200 to 600 ft)

Sequencing of Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-Off as described in CAP GEN Operating Minima.

All aircraft are to obtain an IFR clearance or Pre-Taxi validation through the Saint John FSS prior to taxiing from any apron at Saint John Airport and are required to use the designated taxi routes.

Departing aircraft taxiing from a hangar along Twy B during RVOP or LVOP are required to taxi via Twy B to Rwy 14/32, Twy A to Rwy 05/23.

Do not request IFR clearance or Pre-Taxi validation until the RVR is greater than 600.

Guard Light System

Yellow flashing runway guard lights (Wig Wags) are installed at the Twy A entrance onto Rwy 05/23, Twy B onto Rwy 14/32, and Twy C and Twy I onto Rwy 14/32. When the twy edge lights are illuminated, the guard lights are turned on.

ARRIVALS

Arrivals are permitted on all runways for RVR 2600 ft (1/2 sm) to 1200 ft (1/4 sm). Twy A, Rwy 14/32, Twy B or Twy C and Twy A, Rwy 14/32, Twy I are the approved exit routes in RVOP.

Arrivals are not authorized in LVOP conditions.

RUNWAY LEVEL OF SERVICE

RWY	Certification	RWY	Certification
05	RVR 600	14	¼ sm
23	RVR 600	32	¼ sm

Note: Departing aircraft taxiing from a private hangar will be advised that RVOP or LVOP conditions are in effect. FSS will maintain one-in and one-out movements and will request aircraft access the designated taxi route.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. ANDREWS (CODROY VALLEY), NL


AERODROME CHART — CDA5

CTR Gander – **120.32**

TFC – **123.2**

ATF

DECL DISTS	18	36
TORA	2995	2995
TODA	2995	2995
ASDA	2995	2995
LDA	2995	2995



* DEPARTURE PROCEDURE

Rwy 18 - SPEC VIS - Restricted to CAT A & B acft only. Climb in visual conditions to cross the aprt at or above **900**. Then climb hdg **270°** to **2200** BPOC.

Rwy 36 - ½ - Restricted to CAT A & B acft only. Requires a minimum climb gradient of **310** ft/NM to **1900**. Climb hdg **359°** to **1600** BPOC.

Note: Trees to 189 ASL past departure end of rwy, 100' LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Restricted to CAT A & B acft only. Climb in visual conditions to cross the aprt at or above **900**. Then climb hdg **270°** to **2200** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
310 FT/NM	470	620	730	830	930	1040	1300	1550

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18, 36: *	500 0 500

AERODROME CHART — CDA5

EFF 17 JUN 21


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. ANTHONY, NL

AERODROME CHART — CYAY

AWOS – **118.65**		RADIO Deer Lake – **122.3** MF	CTR Gander – **133.0**

DECL DISTS	10	28
TORA	4003	4003
TODA	4987	4987
ASDA	4003	4003
LDA	4003	4003



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 10, 28: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 10: ½ Rwy 28: *	1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. JOHN'S INTL, NL

AERODROME CHART — CYYT

ATIS – **128.0**	GND – **121.9 275.8**	TWR – **120.6 236.6**	CTR Gander – **133.15 227.3**

DECL DISTS	10	28	16	34				
TORA	8502	8502	7005	7005				
TODA	9486	9486	7989	7989				
ASDA	8502	8502	7005	7005				
LDA	8502	8502	7005	7005				



* DEPARTURE PROCEDURE

Rwy 28 - ½
Note: Trees to 518 ASL aprx 450' past departure end of rwy, 500' LEFT of rwy centreline.

Rwy 34 - ½ **-** Requires a minimum climb gradient of **270** ft/NM to **1000**.
Note: Trees to 457 ASL aprx 50' past departure end of rwy, 500' RIGHT of rwy centreline. Trees to 498 ASL aprx 450' past departure end of rwy, 500' LEFT of rwy centreline.

All Aprons uncontrolled.
Taxiing acft to remain on taxilanes.
Acft shall not taxi between tml and pushed back acft.

HOT SPOTS
HS 1 - Intxn of Rwy 16/34 and Twy M experiences heavy traffic.

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 10, 16, 28: RVR 1200 RWY 34: (¼sm)	RWY 10, 28: RVR 600

TAKE-OFF MINIMA	
Rwys 10; 16: ½ Rwys 28; 34: *	SCALE IN FEET 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYYT

EFF 5 OCT 23

Low Visibility Procedures (RVR less than 1200 ft to 600 ft)

Application

These procedures apply to ground movements of aircraft departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the manoeuvring area.

General

Low Visibility Taxi Routes

Standard taxi routes are shown on the Low Visibility Taxi Chart, taxiway surfaces are painted with enhanced yellow and black centreline markings, in addition, taxiways B, C, G, H, J and Runway 16/34 are equipped with green centreline lights.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area, in the event of an ASDE failure, ATC will restrict low visibility operations to one aircraft on the manoeuvring area at a time.

Departures

When low visibility procedures are in effect, Runway 10/28 is the only runway certified for low visibility operations. Intersection takeoffs are not authorized.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push-back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off minima	Minimum RVR for start
1200 RVR	1000 RVR
600 RVR	600 RVR

Stop Bar/Guard Light System

Each taxiway/runway entrance onto runway 10/28 is equipped with a stop bar consisting of red in-set lights and red elevated lights located at the taxi holding position. Yellow flashing runway guard lights (Wig Wags) are installed at each side of the stop bar location. When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway. In the event of stop bar/guard light failure, ATC will restrict operations in low visibility operations to one aircraft on the maneuvering area at a time.

"AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR"

"Follow me" service is available via Pilot request to ATC.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


LOW VISIBILITY TAXI CHART RWY 10/28
(RVR LESS THAN 1200 TO 600 FT)

ST. JOHN'S INTL, NL
CYYT

ATIS – **128.0**	GND – **121.9 275.8**	TWR – **120.6 236.6**

LEGEND

- TAXIWAY CENTRELINE LIGHTS
- LOW VISIBILITY TAXI ROUTE
- STOP BARS



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

De-icing Procedures

1. Contact ICEMAN thirty minutes prior to push back on 129.2 MHz.
2. Contact ST JOHN'S GND after pushback for taxi to CDF.
3. Hold short of CDF on H.
4. ST JOHN'S GND will advise the flight crew to contact ICEMAN on 129.2 MHz when the aircraft has taxied to the proper entry point.
5. ICEMAN will then delegate all further manoeuvring instructions from the entry point to and on the CDF.
6. Flight crews are advised to exercise discretion at all times while on the CDF. Directional signage and taxi lines on the CDF must be followed by flight crews at all times.
7. Upon completion flight crews must advise ICEMAN that all equipment and de-icing personnel are away from the aircraft and have returned to their designated safety zones.
8. ICEMAN will instruct the aircraft to hold its position on the CDF and contact ST JOHN'S GND on 121.9 MHz.
9. Aircraft to hold its position until ST JOHN'S GND issues further taxi instructions from the CDF.

Notes:

- Aircraft intending on returning to any apron after de-icing must drip dry for 25 minutes on CDF.
- Single engine taxi not permitted from CDF.
- Engine run-ups are not permitted on CDF.
- Contact 709-753-9742 for de-icing if Icehouse unavailable.

De-icing Bay Restrictions

1. BAY 1 – Maximum wingspan for de-icing operations 35.8m (117ft).
2. BAY 2 – Maximum wingspan for de-icing operations 35.8m (117ft).
   Note: BAY 3 is closed/unusable when BAY 2 is occupied.
3. BAY 3 – Maximum wingspan for de-icing operations 79.75m (262ft).
   Note: BAYS 2 and 4 are closed/unusable when BAY 3 is occupied.
4. BAY 4 – Maximum wingspan for de-icing operations 35.8m (117ft).
   Note: BAY 3 is closed/unusable when BAY 4 is occupied.


Note: The above noted maximum wingspans are intended to protect adjacent de-icing bays, safety zones and the apron taxiway. Exceedances of these values are permitted but must be evaluated and approved by the airport authority to ensure special operating procedures are communicated and implemented.

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. JOHN'S INTL, NL

CENTRAL DE-ICING FACILITY

CYYT



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY

CYYT

EFF 10 AUG 23

ST. JOHN'S INTL, NL

PARKING AREAS

CYYT

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

PARKING AREAS
CYYT

EFF 10 AUG 23

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	473650.35N 0524440.68W	10A	473645.88N 0524426.85W
1A	473651.02N 0524441.44W	10B	473645.89N 0524426.33W
1B	473650.16N 0524441.21W	11	473644.25N 0524427.22W
2	473650.20N 0524438.40W	11A	473644.30N 0524426.35W
3	473649.46N 0524435.92W	12	473642.77N 0524426.95W
6	473648.80N 0524433.55W	12A	473642.79N 0524426.54W
7	473648.66N 0524431.53W	R1	473641.29N 0524426.75W
7A	473648.94N 0524431.61W	R2	473640.12N 0524426.35W
7B	473648.94N 0524430.84W	W2	473650.70N 0524444.16W
8	473648.17N 0524429.43W	W3	473651.43N 0524445.80W
8A	473648.38N 0524428.95W	W4	473652.63N 0524443.45W
9	473647.34N 0524427.81W	W4A	473652.57N 0524442.97W
9A	473647.29N 0524427.56W	W5	473653.57N 0524442.35W
10	473645.75N 0524427.23W		

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. LEONARD, NB


AERODROME CHART — CYSL

UNICOM – **122.7**

ATF

CTR Boston – **124.75 239.05**

DECL DISTS	18	36
TORA	5026	5026
TODA	5026	5026
ASDA	5026	5026
LDA	5026	5026



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 18; 36: *	2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSL

EFF 19 MAY 22


ST. LEWIS (FOX HARBOUR), NL

AERODROME CHART — CCK4

AWOS Mary's Harbour – **122.55**

TFC – **122.8** ATF*

DECL DISTS	05	23
TORA	2208	2208
TODA	2208	2208
ASDA	2208	2208
LDA	2208	2208



TAKE-OFF MINIMA	SCALE IN FEET
Rwys 05, 23: *	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

ST. STEPHEN, NB

AERODROME CHART


CCS3

UNICOM – **122.8**

CTR Moncton – **124.3**

ATF

DECL DISTS	13	31
TORA	2963	2963
TODA	2963	2963
ASDA	2963	2963
LDA	2963	2963



DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
300 FT/NM	450	600	700	800	900	1000	1250	1500
360 FT/NM	540	720	840	960	1080	1200	1500	1800

* DEPARTURE PROCEDURE

Rwy 13 - ½ **-** Requires a minimum climb gradient of **300** ft/NM to **700**. Climb heading **133°** to **700** BPOC.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **1100** BPOC.

Rwy 31 - ½ **-** Requires a minimum climb gradient of **360** ft/NM to **400**. Climb heading **313°** to **400** BPOC.

or

SPEC VIS **-** Climb in visual conditions to cross the aprt at or above **1100** BPOC.

TAKE-OFF MINIMA

Rwys 13, 31: *****

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


STEPHENVILLE, NL

AERODROME CHART — CYJT

CTR Gander – **120.32**

APRT RDO – **122.1** MF

DECL DISTS	09	27
TORA	10011	10011
TODA	10011	10995
ASDA	10011	10011
LDA	10011	10011



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 27: RVR 1200 RWY 09: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA
Rwys 09, 27: *

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYJT

EFF 26 MAR 20

SUMMERSIDE, PE

AERODROME CHART — CYSU


AUTO – **122.55**

UNICOM – **122.95** (AU)

ATF

CTR – **124.4 384.8**

DECL DISTS	05	23
TORA	8000	8000
TODA	8000	8000
ASDA	8000	8000
LDA	8000	8000



TAKE-OFF MINIMA
Rwys 05, 23: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYSU


EFF 7 OCT 21

SYDNEY/J.A. DOUGLAS MCCURDY, NS

AERODROME CHART — CYQY

		RADIO Charlottetown – **122.0** MF	CTR Moncton – **118.6 266.3**

DECL DISTS	06	24	18	36				
TORA	7070	7070	5997	5997				
TODA	7770	8054	6981	6981				
ASDA	7070	7070	5997	5997				
LDA	7070	7070	5997	5997				



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06: RVR 1200 RWY 18, 24, 36: (¼sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
Rwy 06: ½ Rwys 18, 24, 36: *	1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

TRENTON, NS

AERODROME CHART — CYTN

		UNICOM – **122.8** (AU) ATF	CTR Moncton – **135.3 135.65**

DECL DISTS	06	24
TORA	5377	5377
TODA	5377	5377
ASDA	5377	5377
LDA	5377	5377



***DEPARTURE PROCEDURE**

Rwy 06 - ½

Note: Trees and terrain to 286 ASL abeam departure end of rwy, 240' LEFT of rwy centerline.
Trees and terrain to 335 ASL abeam departure end of rwy, 470' RIGHT of rwy centerline.
Public roadway and vehicles to 256 ASL 0.1NM past departure end of rwy.
Powerline to 312 ASL 0.4NM past departure end of rwy, 900' RIGHT of rwy centerline.

Rwy 24 - ½

Note: Trees and terrain to 352 ASL abeam departure end of rwy, 430' RIGHT of rwy centerline.

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved


WABUSH, NL

AERODROME CHART — CYWK

ATIS – **128.12**	CLNC DEL – **122.6**	RADIO – **122.0 296.2**
MET – **128.12**		TFC – **122.0 296.2** MF

CTR Montreal – **132.25**
RADIO Quebec– **123.37**

DECL DISTS	18	36
TORA	6002	6002
TODA	6652	6986
ASDA	6002	6002
LDA	6002	6002



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 18, 36: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYWK

EFF 23 FEB 23

WINTERLAND, NL


AERODROME CHART — CCC2

CTR Gander – **134.9**

TFC – **123.2**

ATF

DECL DISTS	15	33
TORA	2998	2998
TODA	2998	2998
ASDA	2998	2998
LDA	2998	2998



★ DEPARTURE PROCEDURE

Rwy 15 - ½ **-** NO RIGHT turn below **800**.
Note: Trees to 145 ASL aprx 400' past departure end of rwy.

Rwy 33 - ½
Note: Trees to 210 ASL aprx 400' past departure end of rwy, 350' LEFT of rwy centreline and aprx 0.2NM past departure end of rwy.

TAKE-OFF MINIMA	SCALE IN FEET
Rwys 15, 33: ★	500 0 500

Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

YARMOUTH, NS


AERODROME CHART — CYQI

UNICOM – **123.0** (AU)

CTR Moncton – **123.9 368.5**

MF

DECL DISTS	06	24	15	33				
TORA	6002	6002	4999	4999				
TODA	6502	6462	5349	5249				
ASDA	6227	6002	4999	4999				
LDA	6002	6002	4999	4999				



Source of Canadian Civil Aeronautical Data: © 2023 NAV CANADA All rights reserved

AERODROME CHART — CYQI

EFF 10 AUG 23